

Package ‘CPAT’

December 25, 2018

Title Change Point Analysis Tests

Version 0.1.0

Date 2018-12-06

Maintainer Curtis Miller <cmiller@math.utah.edu>

Description Implements several statistical tests for structural change, specifically the tests featured in Horváth, Rice and Miller (in press): CUSUM (with weighted/trimmed variants), Darling-Erdős, Hidalgo-Seo, Andrews, and the new Rényi-type test.

Depends R (>= 3.2)

Suggests cointReg (>= 0.2), foreach (>= 1.4), doRNG (>= 1.7), doParallel (>= 1.0), ggplot2 (>= 2.2), dplyr (>= 0.7), tikzDevice (>= 0.12), testthat (>= 2.0)

Imports stats (>= 3.2), utils (>= 3.2), grDevices (>= 3.2), Rdpack (>= 0.9), methods (>= 3.2), Rcpp (>= 0.12), purrr (>= 0.2)

RdMacros Rdpack

SystemRequirements GNU make

License MIT + file LICENSE

Encoding UTF-8

LazyData true

LinkingTo Rcpp, RcppArmadillo

RoxygenNote 6.1.0

NeedsCompilation yes

Author Curtis Miller [aut, cre]

Repository CRAN

Date/Publication 2018-12-25 22:40:08 UTC

R topics documented:

.onAttach	2
Andrews.test	3
andrews_test	4

andrews_test_reg	4
banks	5
CPAT_startup_message	6
cpt_consistent_var	6
CUSUM.test	7
DE.test	8
dZn	9
ff	9
getLongRunWeights	10
get_lrv_vec	11
HR.test	12
HS.test	13
pdarling_erdos	14
phidalgo_seo	14
pkolmogorov	15
pZn	15
qdarling_erdos	16
qhidalgo_seo	16
qkolmogorov	17
qZn	17
rchangepoint	18
sim_de_stat	19
sim_hs_stat	20
sim_Vn	22
sim_Vn_stat	22
sim_Zn	24
sim_Zn_stat	25
stat_de	26
stat_hs	27
stat_Vn	29
stat_Zn	31
%s%	32
%s0%	33

Index **34**

.onAttach	<i>Package Attach Hook Function</i>
-----------	-------------------------------------

Description

Hook triggered when package attached

Usage

.onAttach(lib, pkg)

Arguments

`lib` a character string giving the library directory where the package defining the namespace was found

`pkg` a character string giving the name of the package

Examples

```
CPAT:::.onAttach(.libPaths()[1], "CPAT")
```

Andrews.test

Andrews' Test for End-of-Sample Structural Change

Description

Performs Andrews' test for end-of-sample structural change, as described in (Andrews 2003). This function works for both univariate and multivariate data depending on the nature of `x` and whether formula is specified. This function is thus an interface to [andrews_test](#) and [andrews_test_reg](#); see the documentation of those functions for more details.

Usage

```
Andrews.test(x, M, formula = NULL)
```

Arguments

`x` Data to test for change in mean (either a vector or `data.frame`)

`M` Numeric index of the location of the first potential change point

`formula` The regression formula, which will be passed to [lm](#)

Value

A `htest`-class object containing the results of the test

References

Andrews DWK (2003). "End-of-Sample Instability Tests." *Econometrica*, **71**(6), 1661–1694. ISSN 00129682, 14680262, <https://www.jstor.org/stable/1555535>.

Examples

```
Andrews.test(rnorm(1000), M = 900)
x <- rnorm(1000)
y <- 1 + 2 * x + rnorm(1000)
df <- data.frame(x, y)
Andrews.test(df, y ~ x, M = 900)
```

andrews_test *Univariate Andrews Test for End-of-Sample Structural Change*

Description

This implements Andrews' test for end-of-sample change, as described by Andrews (2003). This test was derived for detecting a change in univariate data. See (Andrews 2003) for a description of the test.

Usage

```
andrews_test(x, M, pval = TRUE, stat = TRUE)
```

Arguments

x	Vector of the data to test
M	Numeric index of the location of the first potential change point
pval	If TRUE, return a p-value
stat	If TRUE, return a test statistic

Value

If both pval and stat are TRUE, a list containing both; otherwise, a number for one or the other, depending on which is TRUE

References

Andrews DWK (2003). "End-of-Sample Instability Tests." *Econometrica*, **71**(6), 1661–1694. ISSN 00129682, 14680262, <https://www.jstor.org/stable/1555535>.

Examples

```
CPAT:::andrews_test(rnorm(1000), M = 900)
```

andrews_test_reg *Multivariate Andrews' Test for End-of-Sample Structural Change*

Description

This implements Andrews' test for end-of-sample change, as described by Andrews (2003). This test was derived for detecting a change in multivariate data, also originally described. See (Andrews 2003) for a description of the test.

Usage

```
andrews_test_reg(formula, data, M, pval = TRUE, stat = TRUE)
```

Arguments

<code>formula</code>	The regression formula, which will be passed to <code>lm</code>
<code>data</code>	<code>data.frame</code> containing the data
<code>M</code>	Numeric index of the location of the first potential change point
<code>pval</code>	If TRUE, return a p-value
<code>stat</code>	If TRUE, return a test statistic

Value

If both `pval` and `stat` are TRUE, a list containing both; otherwise, a number for one or the other, depending on which is TRUE

References

Andrews DWK (2003). "End-of-Sample Instability Tests." *Econometrica*, **71**(6), 1661–1694. ISSN 00129682, 14680262, <https://www.jstor.org/stable/1555535>.

Examples

```
x <- rnorm(1000)
y <- 1 + 2 * x + rnorm(1000)
df <- data.frame(x, y)
CPAT::andrews_test_reg(y ~ x, data = df, M = 900)
```

banks	<i>Bank Portfolio Returns</i>
-------	-------------------------------

Description

Data set representing the returns of an industry portfolio representing the banking industry based on company four-digit SIC codes, obtained from the data library maintained by Kenneth French. Data ranges from July 1, 1926 to October 31, 2017.

Usage

```
banks
```

Format

A data frame with 24099 rows and 1 variable:

Banks The return of a portfolio representing the banking industry

Row names are dates in YYYY-MM-DD format.

Source

http://mba.tuck.dartmouth.edu/pages/faculty/ken.french/data_library.html

CPAT_startup_message *Create Package Startup Message*

Description

Makes package startup message.

Usage

CPAT_startup_message()

Examples

CPAT:::CPAT_startup_message()

cpt_consistent_var *Variance Estimation Consistent Under Change*

Description

Estimate the variance (using the sum of squared errors) with an estimator that is consistent when the mean changes at a known point.

Usage

cpt_consistent_var(x, k)

Arguments

x A numeric vector for the data set
k The potential change point at which the data set is split

Details

This is the estimator

$$\hat{\sigma}_{T,t}^2 = T^{-1} \left(\sum_{s=1}^t (X_s - \bar{X}_t)^2 + \sum_{s=t+1}^T (X_s - \tilde{X}_{T-t})^2 \right)$$

where $\bar{X}_t = t^{-1} \sum_{s=1}^t X_s$ and $\tilde{X}_{T-t} = (T-t)^{-1} \sum_{s=t+1}^T X_s$. In this implementation, T is computed automatically as `length(x)` and k corresponds to t , a potential change point.

Value

The estimated change-consistent variance

Examples

```
CPAT::cpt_consistent_var(c(rnorm(500, mean = 0), rnorm(500, mean = 1)), k = 500)
```

CUSUM.test

*CUSUM Test***Description**

Performs the (univariate) CUSUM test for change in mean, as described in (Rice et al.). This is effectively an interface to [stat_Vn](#); see its documentation for more details. p-values are computed using [pkolmogorov](#), which represents the limiting distribution of the statistic under the null hypothesis.

Usage

```
CUSUM.test(x, use_kernel_var = FALSE, stat_plot = FALSE,
           kernel = "ba", bandwidth = "and")
```

Arguments

x	Data to test for change in mean
use_kernel_var	Set to TRUE to use kernel methods for long-run variance estimation (typically used when the data is believed to be correlated); if FALSE, then the long-run variance is estimated using $\hat{\sigma}_{T,t}^2 = T^{-1} \left(\sum_{s=1}^t (X_s - \bar{X}_t)^2 + \sum_{s=t+1}^T (X_s - \tilde{X}_{T-t})^2 \right)$, where $\bar{X}_t = t^{-1} \sum_{s=1}^t X_s$ and $\tilde{X}_{T-t} = (T-t)^{-1} \sum_{s=t+1}^T X_s$
stat_plot	Whether to create a plot of the values of the statistic at all potential change points
kernel	If character, the identifier of the kernel function as used in cointReg (see getLongRunVar); if function, the kernel function to be used for long-run variance estimation (default is the Bartlett kernel in cointReg)
bandwidth	If character, the identifier for how to compute the bandwidth as defined in cointReg (see getBandwidth); if function, a function to use for computing the bandwidth; if numeric, the bandwidth value to use (the default is to use Andrews' method, as used in cointReg)

Value

A htest-class object containing the results of the test

References

Rice G, Miller C, Horváth L (????). "A new class of change point test of Rényi type." in-press.

Examples

```
CUSUM.test(rnorm(1000))
CUSUM.test(rnorm(1000), use_kernel_var = TRUE, kernel = "bo",
           bandwidth = "nw")
```

DE.test

*Darling-Erdős Test***Description**

Performs the (univariate) Darling-Erdős test for change in mean, as described in (Rice et al.). This is effectively an interface to [stat_de](#); see its documentation for more details. p-values are computed using [pdarling_erdos](#), which represents the limiting distribution of the test statistic under the null hypothesis when a and b are chosen appropriately. (Change those parameters at your own risk!)

Usage

```
DE.test(x, a = log, b = log, use_kernel_var = FALSE,
        stat_plot = FALSE, kernel = "ba", bandwidth = "and")
```

Arguments

x	Data to test for change in mean
a	The function that will be composed with $l(x) = (2 \log x)^{1/2}$
b	The function that will be composed with $u(x) = 2 \log x + \frac{1}{2} \log \log x - \frac{1}{2} \log \pi$
use_kernel_var	Set to TRUE to use kernel methods for long-run variance estimation (typically used when the data is believed to be correlated); if FALSE, then the long-run variance is estimated using $\hat{\sigma}_{T,t}^2 = T^{-1} \left(\sum_{s=1}^t (X_s - \bar{X}_t)^2 + \sum_{s=t+1}^T (X_s - \tilde{X}_{T-t})^2 \right)$, where $\bar{X}_t = t^{-1} \sum_{s=1}^t X_s$ and $\tilde{X}_{T-t} = (T-t)^{-1} \sum_{s=t+1}^T X_s$
stat_plot	Whether to create a plot of the values of the statistic at all potential change points
kernel	If character, the identifier of the kernel function as used in cointReg (see getLongRunVar); if function, the kernel function to be used for long-run variance estimation (default is the Bartlett kernel in cointReg)
bandwidth	If character, the identifier for how to compute the bandwidth as defined in cointReg (see getBandwidth); if function, a function to use for computing the bandwidth; if numeric, the bandwidth value to use (the default is to use Andrews' method, as used in cointReg)

Value

A htest-class object containing the results of the test

References

Rice G, Miller C, Horváth L (????). "A new class of change point test of Rényi type." in-press.

Examples

```
DE.test(rnorm(1000))
DE.test(rnorm(1000), use_kernel_var = TRUE, kernel = "bo", bandwidth = "nw")
```

`dZn`*Rényi-Type Statistic Limiting Distribution Density Function*

Description

Function for computing the value of the density function of the limiting distribution of the Rényi-type statistic.

Usage

```
dZn(x, summands = NULL)
```

Arguments

<code>x</code>	Point at which to evaluate the density function (note that this parameter is not vectorized)
<code>summands</code>	Number of summands to use in summation (the default should be machine accurate)

Value

Value of the density function at x

Examples

```
CPAT:::dZn(1)
```

`ff`*Fama-French Five Factors*

Description

Data set containing the five factors described by Fama and French (2015), from the data library maintained by Kenneth French. Data ranges from July 1, 1963 to October 31, 2017.

Usage

```
ff
```

Format

A data frame with 13679 rows and 6 variables:

Mkt.RF Market excess returns

RF The risk-free rate of return

SMB The return on a diversified portfolio of small stocks minus return on a diversified portfolio of big stocks

HML The return of a portfolio of stocks with a high book-to-market (B/M) ratio minus the return of a portfolio of stocks with a low B/M ratio

RMW The return of a portfolio of stocks with robust profitability minus a portfolio of stocks with weak profitability

CMA The return of a portfolio of stocks with conservative investment minus the return of a portfolio of stocks with aggressive investment

Row names are dates in YYYYMMDD format.

Source

http://mba.tuck.dartmouth.edu/pages/faculty/ken.french/data_library.html

getLongRunWeights *Weights for Long-Run Variance*

Description

Compute some weights for long-run variance. This code comes directly from the source code of `cointReg`; see [getLongRunWeights](#).

Usage

```
getLongRunWeights(n, bandwidth, kernel = "ba")
```

Arguments

n	Length of weights' vector
bandwidth	A number for the bandwidth
kernel	The kernel function; see getLongRunVar for possible values

Value

List with components `w` containing the vector of weights and `upper`, the index of the largest non-zero entry in `w`

Examples

```
CPAT:::getLongRunWeights(10, 1)
```

Description

Computes the estimates of the long-run variance in a change point context, as described in (Rice et al.). By default it uses kernel and bandwidth selection as used in the package **cointReg**, though changing the parameters `kernel` and `bandwidth` can change this behavior. If **cointReg** is not installed, the Bartlett internal (defined internally) will be used and the bandwidth will be the square root of the sample size.

Usage

```
get_lrv_vec(dat, kernel = "ba", bandwidth = "and")
```

Arguments

<code>dat</code>	The data vector
<code>kernel</code>	If character, the identifier of the kernel function as used in cointReg (see getLongRunVar); if function, the kernel function to be used for long-run variance estimation (default is the Bartlett kernel in cointReg)
<code>bandwidth</code>	If character, the identifier for how to compute the bandwidth as defined in cointReg (see getBandwidth); if function, a function to use for computing the bandwidth; if numeric, the bandwidth value to use (the default is to use Andrews' method, as used in cointReg)

Value

A vector of estimates of the long-run variance

References

Rice G, Miller C, Horváth L (????). "A new class of change point test of Rényi type." in-press.

Examples

```
x <- rnorm(1000)
CPAT:::get_lrv_vec(x)
CPAT:::get_lrv_vec(x, kernel = "pa", bandwidth = "nw")
```

HR.test

*Rényi-Type Test***Description**

Performs the (univariate) Rényi-type test for change in mean, as described in (Rice et al.). This is effectively an interface to [stat_Zn](#); see its documentation for more details. p-values are computed using [pZn](#), which represents the limiting distribution of the test statistic under the null hypothesis, which represents the limiting distribution of the test statistic under the null hypothesis when `kn` represents a sequence t_T satisfying $t_T \rightarrow \infty$ and $t_T/T \rightarrow 0$ as $T \rightarrow \infty$. ([log](#) and [sqrt](#) should be good choices.)

Usage

```
HR.test(x, kn = log, use_kernel_var = FALSE, stat_plot = FALSE,
        kernel = "ba", bandwidth = "and")
```

Arguments

<code>x</code>	Data to test for change in mean
<code>kn</code>	A function corresponding to the trimming parameter t_T ; by default, the square root function
<code>use_kernel_var</code>	Set to TRUE to use kernel methods for long-run variance estimation (typically used when the data is believed to be correlated); if FALSE, then the long-run variance is estimated using $\hat{\sigma}_{T,t}^2 = T^{-1} \left(\sum_{s=1}^t (X_s - \bar{X}_t)^2 + \sum_{s=t+1}^T (X_s - \tilde{X}_{T-t})^2 \right)$, where $\bar{X}_t = t^{-1} \sum_{s=1}^t X_s$ and $\tilde{X}_{T-t} = (T-t)^{-1} \sum_{s=t+1}^T X_s$; if <code>custom_var</code> is not NULL, this argument is ignored
<code>stat_plot</code>	Whether to create a plot of the values of the statistic at all potential change points
<code>kernel</code>	If character, the identifier of the kernel function as used in cointReg (see getLongRunVar); if function, the kernel function to be used for long-run variance estimation (default is the Bartlett kernel in cointReg)
<code>bandwidth</code>	If character, the identifier for how to compute the bandwidth as defined in cointReg (see getBandwidth); if function, a function to use for computing the bandwidth; if numeric, the bandwidth value to use (the default is to use Andrews' method, as used in cointReg)

Value

A `htest`-class object containing the results of the test

References

Rice G, Miller C, Horváth L (????). "A new class of change point test of Rényi type." in-press.

Examples

```
HR.test(rnorm(1000))
HR.test(rnorm(1000), use_kernel_var = TRUE, kernel = "bo", bandwidth = "nw")
```

HS.test

Hidalgo-Seo Test

Description

Performs the (univariate) Hidalgo-Seo test for change in mean, as described in (Rice et al.). This is effectively an interface to [stat_hs](#); see its documentation for more details. p-values are computed using [phidalgo_seo](#), which represents the limiting distribution of the test statistic when the null hypothesis is true.

Usage

```
HS.test(x, corr = TRUE, stat_plot = FALSE)
```

Arguments

x	Data to test for change in mean
corr	If TRUE, the long-run variance will be computed under the assumption of correlated residuals; ignored if custom_var is not NULL or use_kernel_var is TRUE
stat_plot	Whether to create a plot of the values of the statistic at all potential change points

Value

A htest-class object containing the results of the test

References

Rice G, Miller C, Horváth L (????). "A new class of change point test of Rényi type." in-press.

Examples

```
HS.test(rnorm(1000))
HS.test(rnorm(1000), corr = FALSE)
```

pdarling_erdos

Darling-Erdős Statistic CDF

Description

CDF for the limiting distribution of the Darling-Erdős statistic.

Usage

pdarling_erdos(q)

Arguments

q Quantile input to CDF

Value

If Z is the random variable with this distribution, the quantity $P(Z \leq q)$

Examples

```
CPAT:::pdarling_erdos(0.1)
```

phidalgo_seo

Hidalgo-Seo Statistic CDF

Description

CDF of the limiting distribution of the Hidalgo-Seo statistic

Usage

phidalgo_seo(q)

Arguments

q Quantile input to CDF

Value

If Z is the random variable following the limiting distribution, the quantity $P(Z \leq q)$

Examples

```
CPAT:::phidalgo_seo(0.1)
```

pkolmogorov *Kolmogorov CDF*

Description

CDF of the Kolmogorov distribution.

Usage

```
pkolmogorov(q, summands = ceiling(q * sqrt(72) + 3/2))
```

Arguments

q	Quantile input to CDF
summands	Number of summands for infinite sum (the default should have machine accuracy)

Value

If Z is the random variable following the Kolmogorov distribution, the quantity $P(Z \leq q)$

Examples

```
CPAT::pkolmogorov(0.1)
```

pZn *Rényi-Type Statistic CDF*

Description

CDF for the limiting distribution of the Rényi-type statistic.

Usage

```
pZn(q, summands = NULL)
```

Arguments

q	Quantile input to CDF
summands	Number of summands for infinite sum; if NULL, automatically determined

Value

If Z is the random variable following the limiting distribution, the quantity $P(Z \leq q)$

Examples

```
CPAT::pZn(0.1)
```

qdarling_erdos *Darling-Erdős Statistic Limiting Distribution Quantile Function*

Description

Quantile function for the limiting distribution of the Darling-Erdős statistic.

Usage

```
qdarling_erdos(p)
```

Arguments

p The probability associated with the desired quantile

Value

The quantile associated with p

Examples

```
CPAT:::qdarling_erdos(0.5)
```

qhidalgo_seo *Hidalgo-Seo Statistic Limiting Distribution Quantile Function*

Description

Quantile function for the limiting distribution of the Hidalgo-Seo statistic

Usage

```
qhidalgo_seo(p)
```

Arguments

p The probability associated with the desired quantile

Value

A The quantile associated with p

Examples

```
CPAT:::qhidalgo_seo(0.5)
```

qkolmogorov

Kolmogorov Distribution Quantile Function

Description

Quantile function for the Kolmogorov distribution.

Usage

```
qkolmogorov(p, summands = 500, interval = c(0, 100),
  tol = .Machine$double.eps, ...)
```

Arguments

p	Value of the CDF at the quantile
summands	Number of summands for infinite sum
interval, tol, ...	Arguments to be passed to uniroot

Details

This function uses [uniroot](#) for finding this quantity, and many of the the accepted parameters are arguments for that function; see its documentation for more details.

Value

The quantile associated with p

Examples

```
CPAT:::qkolmogorov(0.5)
```

qZn

Rényi-Type Statistic Quantile Function

Description

Quantile function for the limiting distribution of the Rényi-type statistic.

Usage

```
qZn(p, summands = 500, interval = c(0, 100),
  tol = .Machine$double.eps, ...)
```

Arguments

p	Value of the CDF at the quantile
summands	Number of summands for infinite sum
interval, tol, ...	Arguments to be passed to <code>uniroot</code>

Details

This function uses `uniroot` for finding this quantity, and many of the the accepted parameters are arguments for that function; see its documentation for more details.

Value

The quantile associated with p

Examples

```
CPAT:::qZn(0.5)
```

```
rchangepoint
```

```
Simulate Univariate Data With a Single Change Point
```

Description

This function simulates univariate data with a structural change.

Usage

```
rchangepoint(n, changepoint = NULL, mean1 = 0, mean2 = 0,
             dist = rnorm, meanparam = "mean", ...)
```

Arguments

n	An integer for the data set's sample size
changepoint	An integer for where the change point occurs
mean1	The mean prior to the change point
mean2	The mean after the change point
dist	The function with which random data will be generated
meanparam	A string for the parameter in <code>dist</code> representing the mean
...	Other arguments to be passed to <code>dist</code>

Details

This function generates artificial change point data, where up to the specified change point the data has one mean, and after the point it has a different mean. By default, the function simulates standard Normal data with no change. If `changepoint` is `NULL`, then by default the change point will be at about the middle of the data.

Value

A vector of the simulated data

Examples

```
CPAT::rchangeoint(500)
CPAT::rchangeoint(500, changepoint = 10, mean2 = 2, sd = 2)
CPAT::rchangeoint(500, changepoint = 250, dist = rexp, meanparam = "rate",
                  mean1 = 1, mean2 = 2)
```

 sim_de_stat

Darling-Erdős Statistic Simulation

Description

Simulates multiple realizations of the Darling-Erdős statistic.

Usage

```
sim_de_stat(size, a = log, b = log, use_kernel_var = FALSE,
            kernel = "ba", bandwidth = "and", n = 500, gen_func = rnorm,
            args = NULL, parallel = FALSE)
```

Arguments

size	Number of realizations to simulate
a	The function that will be composed with $l(x) = (2 \log(x))^{1/2}$
b	The function that will be composed with $u(x) = 2 \log(x) + \frac{1}{2} \log(\log(x)) - \frac{1}{2} \log(pi)$
use_kernel_var	Set to TRUE to use kernel-based long-run variance estimation (FALSE means this is not employed)
kernel	If character, the identifier of the kernel function as used in the cointReg (see documentation for <code>cointReg::getLongRunVar</code>); if function, the kernel function to be used for long-run variance estimation (default is the Bartlett kernel in cointReg); this parameter has no effect if <code>use_kernel_var</code> is FALSE
bandwidth	If character, the identifier of how to compute the bandwidth as defined in the cointReg package (see documentation for <code>cointReg::getLongRunVar</code>); if function, a function to use for computing the bandwidth; if numeric, the bandwidth to use (the default behavior is to use the Andrews (1991) method, as used in cointReg); this parameter has no effect if <code>use_kernel_var</code> is FALSE
n	The sample size for each realization
gen_func	The function generating the random sample from which the statistic is computed
args	A list of arguments to be passed to <code>gen_func</code>
parallel	Whether to use the foreach and doParallel packages to parallelize simulation (which needs to be initialized in the global namespace before use)

Details

If `use_kernel_var` is set to `TRUE`, long-run variance estimation using kernel-based techniques will be employed; otherwise, a technique resembling standard variance estimation will be employed. Any technique employed, though, will account for the potential break points, as described in Rice et al. (). See the documentation for `stat_de` for more details.

The parameters `kernel` and `bandwidth` control parameters for long-run variance estimation using kernel methods. These parameters will be passed directly to `stat_de`.

Value

A vector of simulated realizations of the Darling-Erdős statistic

References

Andrews DWK (1991). "Heteroskedasticity and Autocorrelation Consistent Covariance Matrix Estimation." *Econometrica*, **59**(3), 817-858.

Rice G, Miller C, Horváth L (????). "A new class of change point test of Rényi type." in-press.

Examples

```
CPAT::sim_de_stat(100)
CPAT::sim_de_stat(100, use_kernel_var = TRUE,
                  gen_func = CPAT::rchangeoint,
                  args = list(changeoint = 250, mean2 = 1))
```

sim_hs_stat

Hidalgo-Seo Statistic Simulation

Description

Simulates multiple realizations of the Hidalgo-Seo statistic.

Usage

```
sim_hs_stat(size, corr = TRUE, gen_func = rnorm, args = NULL,
            n = 500, parallel = FALSE, use_kernel_var = FALSE, kernel = "ba",
            bandwidth = "and")
```

Arguments

<code>size</code>	Number of realizations to simulate
<code>corr</code>	Whether long-run variance should be computed under the assumption of correlated residuals
<code>gen_func</code>	The function generating the random sample from which the statistic is computed
<code>args</code>	A list of arguments to be passed to <code>gen_func</code>
<code>n</code>	The sample size for each realization

parallel	Whether to use the foreach and doParallel packages to parallelize simulation (which needs to be initialized in the global namespace before use)
use_kernel_var	Set to TRUE to use kernel-based long-run variance estimation (FALSE means this is not employed); <i>TODO: NOT CURRENTLY IMPLEMENTED</i>
kernel	If character, the identifier of the kernel function as used in the cointReg (see documentation for <code>cointReg::getLongRunVar</code>); if function, the kernel function to be used for long-run variance estimation (default is the Bartlett kernel in cointReg); this parameter has no effect if <code>use_kernel_var</code> is FALSE; <i>TODO: NOT CURRENTLY IMPLEMENTED</i>
bandwidth	If character, the identifier of how to compute the bandwidth as defined in the cointReg package (see documentation for <code>cointReg::getLongRunVar</code>); if function, a function to use for computing the bandwidth; if numeric, the bandwidth to use (the default behavior is to use the Andrews (1991) method, as used in cointReg); this parameter has no effect if <code>use_kernel_var</code> is FALSE; <i>TODO: NOT CURRENTLY IMPLEMENTED</i>

Details

If `corr` is TRUE, then the residuals of the data-generating process are assumed to be correlated and the test accounts for this in long-run variance estimation; see the documentation for `stat_hs` for more details. Otherwise, the sample variance is the estimate for the long-run variance, as described in Hidalgo and Seo (2013).

Value

A vector of simulated realizations of the Hidalgo-Seo statistic

References

Andrews DWK (1991). “Heteroskedasticity and Autocorrelation Consistent Covariance Matrix Estimation.” *Econometrica*, **59**(3), 817-858.

Hidalgo J, Seo MH (2013). “Testing for structural stability in the whole sample.” *Journal of Econometrics*, **175**(2), 84 - 93. ISSN 0304-4076, doi: [10.1016/j.jeconom.2013.02.008](https://doi.org/10.1016/j.jeconom.2013.02.008), <http://www.sciencedirect.com/science/article/pii/S0304407613000626>.

Examples

```
CPAT:::sim_hs_stat(100)
CPAT:::sim_hs_stat(100, gen_func = CPAT:::rchangeoint,
  args = list(changeoint = 250, mean2 = 1))
```

sim_Vn *CUSUM Statistic Simulation (Assuming Variance)*

Description

Simulates multiple realizations of the CUSUM statistic when the long-run variance of the data is known.

Usage

```
sim_Vn(size, n = 500, gen_func = rnorm, sd = 1, args = NULL)
```

Arguments

size	Number of realizations to simulate
n	The sample size for each realization
gen_func	The function generating the random sample from which the statistic is computed
sd	The square root of the second moment of the data
args	A list of arguments to be passed to gen_func

Value

A vector of simulated realizations of the CUSUM statistic

Examples

```
CPAT:::sim_Vn(100)
CPAT:::sim_Vn(100, gen_func = CPAT:::rchangeoint,
  args = list(changeoint = 250, mean2 = 1))
```

sim_Vn_stat *CUSUM Statistic Simulation*

Description

Simulates multiple realizations of the CUSUM statistic.

Usage

```
sim_Vn_stat(size, kn = function(n) { 1 }, tau = 0,
  use_kernel_var = FALSE, kernel = "ba", bandwidth = "and",
  n = 500, gen_func = rnorm, args = NULL, parallel = FALSE)
```

Arguments

size	Number of realizations to simulate
kn	A function returning a positive integer that is used in the definition of the trimmed CUSUM statistic effectively setting the bounds over which the maximum is taken
tau	The weighting parameter for the weighted CUSUM statistic (defaults to zero for no weighting)
use_kernel_var	Set to TRUE to use kernel-based long-run variance estimation (FALSE means this is not employed)
kernel	If character, the identifier of the kernel function as used in the cointReg (see documentation for <code>cointReg::getLongRunVar</code>); if function, the kernel function to be used for long-run variance estimation (default is the Bartlett kernel in cointReg); this parameter has no effect if <code>use_kernel_var</code> is FALSE
bandwidth	If character, the identifier of how to compute the bandwidth as defined in the cointReg package (see documentation for <code>cointReg::getLongRunVar</code>); if function, a function to use for computing the bandwidth; if numeric, the bandwidth to use (the default behavior is to use the method described in (Andrews 1991), as used in cointReg); this parameter has no effect if <code>use_kernel_var</code> is FALSE
n	The sample size for each realization
gen_func	The function generating the random sample from which the statistic is computed
args	A list of arguments to be passed to <code>gen_func</code>
parallel	Whether to use the foreach and doParallel packages to parallelize simulation (which needs to be initialized in the global namespace before use)

Details

This differs from `sim_Vn()` in that the long-run variance is estimated with this function, while `sim_Vn()` assumes the long-run variance is known. Estimation can be done in a variety of ways. If `use_kernel_var` is set to TRUE, long-run variance estimation using kernel-based techniques will be employed; otherwise, a technique resembling standard variance estimation will be employed. Any technique employed, though, will account for the potential break points, as described in Rice et al. (). See the documentation for [stat_Vn](#) for more details.

The parameters `kernel` and `bandwidth` control parameters for long-run variance estimation using kernel methods. These parameters will be passed directly to [stat_Vn](#).

Versions of the CUSUM statistic, such as the weighted or trimmed statistics, can be simulated with the function by passing values to `kn` and `tau`; again, see the documentation for [stat_Vn](#).

Value

A vector of simulated realizations of the CUSUM statistic

References

- Andrews DWK (1991). "Heteroskedasticity and Autocorrelation Consistent Covariance Matrix Estimation." *Econometrica*, **59**(3), 817-858.
- Rice G, Miller C, Horváth L (????). "A new class of change point test of Rényi type." in-press.

Examples

```
CPAT:::sim_Vn_stat(100)
CPAT:::sim_Vn_stat(100, kn = function(n) {floor(0.1 * n)}, tau = 1/3,
  use_kernel_var = TRUE, gen_func = CPAT:::rchangepoint,
  args = list(changepoint = 250, mean2 = 1))
```

 sim_Zn

Rènyi-Type Statistic Simulation (Assuming Variance)

Description

Simulates multiple realizations of the Rènyi-type statistic when the long-run variance of the data is known.

Usage

```
sim_Zn(size, kn, n = 500, gen_func = rnorm, args = NULL, sd = 1)
```

Arguments

size	Number of realizations to simulate
kn	A function returning a positive integer that is used in the definition of the Rènyi-type statistic effectively setting the bounds over which the maximum is taken
n	The sample size for each realization
gen_func	The function generating the random sample from which the statistic is computed
args	A list of arguments to be passed to gen_func
sd	The square root of the second moment of the data

Value

A vector of simulated realizations of the Rènyi-type statistic

Examples

```
CPAT:::sim_Zn(100, kn = function(n) {floor(log(n))})
CPAT:::sim_Zn(100, kn = function(n) {floor(log(n))},
  gen_func = CPAT:::rchangepoint, args = list(changepoint = 250,
  mean2 = 1))
```

sim_Zn_stat	<i>Rènyi-Type Statistic Simulation</i>
-------------	--

Description

Simulates multiple realizations of the Rènyi-type statistic.

Usage

```
sim_Zn_stat(size, kn = function(n) { floor(sqrt(n)) },
  use_kernel_var = FALSE, kernel = "ba", bandwidth = "and",
  n = 500, gen_func = rnorm, args = NULL, parallel = FALSE)
```

Arguments

size	Number of realizations to simulate
kn	A function returning a positive integer that is used in the definition of the Rènyi-type statistic effectively setting the bounds over which the maximum is taken
use_kernel_var	Set to TRUE to use kernel-based long-run variance estimation (FALSE means this is not employed)
kernel	If character, the identifier of the kernel function as used in the cointReg (see documentation for <code>cointReg::getLongRunVar</code>); if function, the kernel function to be used for long-run variance estimation (default is the Bartlett kernel in cointReg); this parameter has no effect if <code>use_kernel_var</code> is FALSE
bandwidth	If character, the identifier of how to compute the bandwidth as defined in the cointReg package (see documentation for <code>cointReg::getLongRunVar</code>); if function, a function to use for computing the bandwidth; if numeric, the bandwidth to use (the default behavior is to use the Andrews (1991) method, as used in cointReg); this parameter has no effect if <code>use_kernel_var</code> is FALSE
n	The sample size for each realization
gen_func	The function generating the random sample from which the statistic is computed
args	A list of arguments to be passed to <code>gen_func</code>
parallel	Whether to use the foreach and doParallel packages to parallelize simulation (which needs to be initialized in the global namespace before use)

Details

This differs from `sim_Zn()` in that the long-run variance is estimated with this function, while `sim_Zn()` assumes the long-run variance is known. Estimation can be done in a variety of ways. If `use_kernel_var` is set to TRUE, long-run variance estimation using kernel-based techniques will be employed; otherwise, a technique resembling standard variance estimation will be employed. Any technique employed, though, will account for the potential break points, as described in Rice et al. (). See the documentation for [stat_Zn](#) for more details.

The parameters `kernel` and `bandwidth` control parameters for long-run variance estimation using kernel methods. These parameters will be passed directly to [stat_Zn](#).

Value

A vector of simulated realizations of the R enyi-type statistic

References

Andrews DWK (1991). "Heteroskedasticity and Autocorrelation Consistent Covariance Matrix Estimation." *Econometrica*, **59**(3), 817-858.

Rice G, Miller C, Horv ath L (????). "A new class of change point test of R enyi type." in-press.

Examples

```
CPAT:::sim_Zn_stat(100)
CPAT:::sim_Zn_stat(100, kn = function(n) {floor(log(n))},
  use_kernel_var = TRUE, gen_func = CPAT:::rchangeoint,
  args = list(changeoint = 250, mean2 = 1))
```

stat_de

*Compute the Darling-Erd os Statistic***Description**

This function computes the Darling-Erd os statistic.

Usage

```
stat_de(dat, a = log, b = log, estimate = FALSE,
  use_kernel_var = FALSE, custom_var = NULL, kernel = "ba",
  bandwidth = "and", get_all_vals = FALSE)
```

Arguments

dat	The data vector
a	The function that will be composed with $l(x) = (2 \log x)^{1/2}$
b	The function that will be composed with $u(x) = 2 \log x + \frac{1}{2} \log \log x - \frac{1}{2} \log \pi$
estimate	Set to TRUE to return the estimated location of the change point
use_kernel_var	Set to TRUE to use kernel methods for long-run variance estimation (typically used when the data is believed to be correlated); if FALSE, then the long-run variance is estimated using $\hat{\sigma}_{T,t}^2 = T^{-1} \left(\sum_{s=1}^t (X_s - \bar{X}_t)^2 + \sum_{s=t+1}^T (X_s - \tilde{X}_{T-t})^2 \right)$, where $\bar{X}_t = t^{-1} \sum_{s=1}^t X_s$ and $\tilde{X}_{T-t} = (T-t)^{-1} \sum_{s=t+1}^T X_s$
custom_var	Can be a vector the same length as dat consisting of variance-like numbers at each potential change point (so each entry of the vector would be the "best estimate" of the long-run variance if that location were where the change point occurred) or a function taking two parameters x and k that can be used to generate this vector, with x representing the data vector and k the position of a potential change point; if NULL, this argument is ignored

kernel	If character, the identifier of the kernel function as used in cointReg (see getLongRunVar); if function, the kernel function to be used for long-run variance estimation (default is the Bartlett kernel in cointReg)
bandwidth	If character, the identifier for how to compute the bandwidth as defined in cointReg (see getBandwidth); if function, a function to use for computing the bandwidth; if numeric, the bandwidth value to use (the default is to use Andrews' method, as used in cointReg)
get_all_vals	If TRUE, return all values for the statistic at every tested point in the data set

Details

If $\bar{A}_T(\tau, t_T)$ is the weighted and trimmed CUSUM statistic with weighting parameter τ and trimming parameter t_T (see [stat_Vn](#)), then the Darling-Erdős statistic is

$$l(a_T)\bar{A}_T(1/2, 1) - u(b_T)$$

with $l(x) = \sqrt{2\log x}$ and $u(x) = 2\log x + \frac{1}{2}\log\log x - \frac{1}{2}\log\pi$ ($\log x$ is the natural logarithm of x). The parameter a corresponds to a_T and b to b_T ; these are both `log` by default.

See (Rice et al.) to learn more.

Value

If both `estimate` and `get_all_vals` are FALSE, the value of the test statistic; otherwise, a list that contains the test statistic and the other values requested (if both are TRUE, the test statistic is in the first position and the estimated changg point in the second)

References

Rice G, Miller C, Horváth L (????). "A new class of change point test of Rényi type." in-press.

Examples

```
CPAT:::stat_de(rnorm(1000))
CPAT:::stat_de(rnorm(1000), use_kernel_var = TRUE, bandwidth = "nw", kernel = "bo")
```

stat_hs	<i>Compute the Hidalgo-Seo Statistic</i>
---------	--

Description

This function computes the Hidalgo-Seo statistic for a change in mean model.

Usage

```
stat_hs(dat, estimate = FALSE, corr = TRUE, get_all_vals = FALSE,
        custom_var = NULL, use_kernel_var = FALSE, kernel = "ba",
        bandwidth = "and")
```

Arguments

dat	The data vector
estimate	Set to TRUE to return the estimated location of the change point
corr	If TRUE, the long-run variance will be computed under the assumption of correlated residuals; ignored if custom_var is not NULL or use_kernel_var is TRUE
get_all_vals	If TRUE, return all values for the statistic at every tested point in the data set
custom_var	Can be a vector the same length as dat consisting of variance-like numbers at each potential change point (so each entry of the vector would be the "best estimate" of the long-run variance if that location were where the change point occurred) or a function taking two parameters x and k that can be used to generate this vector, with x representing the data vector and k the position of a potential change point; if NULL, this argument is ignored
use_kernel_var	Set to TRUE to use kernel methods for long-run variance estimation (typically used when the data is believed to be correlated); if FALSE, then the long-run variance is estimated using $\hat{\sigma}_{T,t}^2 = T^{-1} \left(\sum_{s=1}^t (X_s - \bar{X}_t)^2 + \sum_{s=t+1}^T (X_s - \tilde{X}_{T-t})^2 \right)$, where $\bar{X}_t = t^{-1} \sum_{s=1}^t X_s$ and $\tilde{X}_{T-t} = (T-t)^{-1} \sum_{s=t+1}^T X_s$; if custom_var is not NULL, this argument is ignored
kernel	If character, the identifier of the kernel function as used in cointReg (see getLongRunVar); if function, the kernel function to be used for long-run variance estimation (default is the Bartlett kernel in cointReg)
bandwidth	If character, the identifier for how to compute the bandwidth as defined in cointReg (see getBandwidth); if function, a function to use for computing the bandwidth; if numeric, the bandwidth value to use (the default is to use Andrews' method, as used in cointReg)

Details

For a data set x_t with n observations, the test statistic is

$$\max_{1 \leq s \leq n-1} (\mathcal{LM}(s) - B_n) / A_n$$

where $\hat{u}_t = x_t - \bar{x}$ (\bar{x} is the sample mean), $a_n = (2 \log \log n)^{1/2}$, $b_n = a_n^2 - \frac{1}{2} \log \log \log n - \log \Gamma(1/2)$, $A_n = b_n / a_n^2$, $B_n = b_n^2 / a_n^2$, $\hat{\Delta} = \hat{\sigma}^2 = n^{-1} \sum_{t=1}^n \hat{u}_t^2$, and $\mathcal{LM}(s) = n(n-s)^{-1} s^{-1} \hat{\Delta}^{-1} \left(\sum_{t=1}^s \hat{u}_t \right)^2$.

If corr is FALSE, then the residuals are assumed to be uncorrelated. Otherwise, the residuals are assumed to be correlated and $\hat{\Delta} = \hat{\gamma}(0) + 2 \sum_{j=1}^{\lfloor \sqrt{n} \rfloor} \left(1 - \frac{j}{\sqrt{n}}\right) \hat{\gamma}(j)$ with $\hat{\gamma}(j) = \frac{1}{n} \sum_{t=1}^{n-j} \hat{u}_t \hat{u}_{t+j}$.

This statistic was presented in (Hidalgo and Seo 2013).

Value

If both estimate and get_all_vals are FALSE, the value of the test statistic; otherwise, a list that contains the test statistic and the other values requested (if both are TRUE, the test statistic is in the first position and the estimated change point in the second)

References

Hidalgo J, Seo MH (2013). "Testing for structural stability in the whole sample." *Journal of Econometrics*, **175**(2), 84 - 93. ISSN 0304-4076, doi: [10.1016/j.jeconom.2013.02.008](https://doi.org/10.1016/j.jeconom.2013.02.008), <http://www.sciencedirect.com/science/article/pii/S0304407613000626>.

Examples

```
CPAT:::stat_hs(rnorm(1000))
CPAT:::stat_hs(rnorm(1000), corr = FALSE)
```

stat_Vn	<i>Compute the CUSUM Statistic</i>
---------	------------------------------------

Description

This function computes the CUSUM statistic (and can compute weighted/trimmed variants, depending on the values of kn and tau).

Usage

```
stat_Vn(dat, kn = function(n) { 1 }, tau = 0, estimate = FALSE,
        use_kernel_var = FALSE, custom_var = NULL, kernel = "ba",
        bandwidth = "and", get_all_vals = FALSE)
```

Arguments

dat	The data vector
kn	A function corresponding to the trimming parameter t_T in the trimmed CUSUM variant; by default, is a function returning 1 (for no trimming)
tau	The weighting parameter τ for the weighted CUSUM statistic; by default, is 0 (for no weighting)
estimate	Set to TRUE to return the estimated location of the change point
use_kernel_var	Set to TRUE to use kernel methods for long-run variance estimation (typically used when the data is believed to be correlated); if FALSE, then the long-run variance is estimated using $\hat{\sigma}_{T,t}^2 = T^{-1} \left(\sum_{s=1}^t (X_s - \bar{X}_t)^2 + \sum_{s=t+1}^T (X_s - \tilde{X}_{T-t})^2 \right)$, where $\bar{X}_t = t^{-1} \sum_{s=1}^t X_s$ and $\tilde{X}_{T-t} = (T-t)^{-1} \sum_{s=t+1}^T X_s$
custom_var	Can be a vector the same length as dat consisting of variance-like numbers at each potential change point (so each entry of the vector would be the "best estimate" of the long-run variance if that location were where the change point occurred) or a function taking two parameters x and k that can be used to generate this vector, with x representing the data vector and k the position of a potential change point; if NULL, this argument is ignored
kernel	If character, the identifier of the kernel function as used in cointReg (see getLongRunVar); if function, the kernel function to be used for long-run variance estimation (default is the Bartlett kernel in cointReg)

bandwidth	If character, the identifier for how to compute the bandwidth as defined in cointReg (see <code>getBandwidth</code>); if function, a function to use for computing the bandwidth; if numeric, the bandwidth value to use (the default is to use Andrews' method, as used in cointReg)
get_all_vals	If TRUE, return all values for the statistic at every tested point in the data set

Details

The definition of the statistic is

$$T^{-1/2} \max_{1 \leq t \leq T} \hat{\sigma}_{t,T}^{-1} \left| \sum_{s=1}^t X_s - \frac{t}{T} \sum_{s=1}^T X_s \right|$$

A more general version is

$$T^{-1/2} \max_{t_T \leq t \leq T-t_T} \hat{\sigma}_{t,T}^{-1} \left(\frac{t}{T} \left(\frac{T-t}{T} \right) \right)^{\tau} \left| \sum_{s=1}^t X_s - \frac{t}{T} \sum_{s=1}^T X_s \right|$$

The parameter `kn` corresponds to the trimming parameter t_T and the parameter `tau` corresponds to τ .

See (Rice et al.) for more details.

Value

If both `estimate` and `get_all_vals` are FALSE, the value of the test statistic; otherwise, a list that contains the test statistic and the other values requested (if both are TRUE, the test statistic is in the first position and the estimated change point in the second)

References

Rice G, Miller C, Horváth L (????). "A new class of change point test of Rényi type." in-press.

Examples

```
CPAT:::stat_Vn(rnorm(1000))
CPAT:::stat_Vn(rnorm(1000), kn = function(n) {0.1 * n}, tau = 1/2)
CPAT:::stat_Vn(rnorm(1000), use_kernel_var = TRUE, bandwidth = "nw", kernel = "bo")
```

stat_Zn	<i>Compute the Rényi-Type Statistic</i>
---------	---

Description

This function computes the Rényi-type statistic.

Usage

```
stat_Zn(dat, kn = function(n) { floor(sqrt(n)) }, estimate = FALSE,
        use_kernel_var = FALSE, custom_var = NULL, kernel = "ba",
        bandwidth = "and", get_all_vals = FALSE)
```

Arguments

dat	The data vector
kn	A function corresponding to the trimming parameter t_T ; by default, the square root function
estimate	Set to TRUE to return the estimated location of the change point
use_kernel_var	Set to TRUE to use kernel methods for long-run variance estimation (typically used when the data is believed to be correlated); if FALSE, then the long-run variance is estimated using $\hat{\sigma}_{T,t}^2 = T^{-1} \left(\sum_{s=1}^t (X_s - \bar{X}_t)^2 + \sum_{s=t+1}^T (X_s - \tilde{X}_{T-t})^2 \right)$, where $\bar{X}_t = t^{-1} \sum_{s=1}^t X_s$ and $\tilde{X}_{T-t} = (T-t)^{-1} \sum_{s=t+1}^T X_s$; if custom_var is not NULL, this argument is ignored
custom_var	Can be a vector the same length as dat consisting of variance-like numbers at each potential change point (so each entry of the vector would be the "best estimate" of the long-run variance if that location were where the change point occurred) or a function taking two parameters x and k that can be used to generate this vector, with x representing the data vector and k the position of a potential change point; if NULL, this argument is ignored
kernel	If character, the identifier of the kernel function as used in cointReg (see getLongRunVar); if function, the kernel function to be used for long-run variance estimation (default is the Bartlett kernel in cointReg)
bandwidth	If character, the identifier for how to compute the bandwidth as defined in cointReg (see getBandwidth); if function, a function to use for computing the bandwidth; if numeric, the bandwidth value to use (the default is to use Andrews' method, as used in cointReg)
get_all_vals	If TRUE, return all values for the statistic at every tested point in the data set

Details

The definition of the statistic is

$$\max_{t_T \leq t \leq T-t_T} \hat{\sigma}_{t,T}^{-1} \left| t^{-1} \sum_{s=1}^t X_s - (T-t)^{-1} \sum_{s=t+1}^T X_s \right|$$

The parameter `kn` corresponds to the trimming parameter t_T .

Value

If both `estimate` and `get_all_vals` are `FALSE`, the value of the test statistic; otherwise, a list that contains the test statistic and the other values requested (if both are `TRUE`, the test statistic is in the first position and the estimated change point in the second)

Examples

```
CPAT:::stat_Zn(rnorm(1000))
CPAT:::stat_Zn(rnorm(1000), kn = function(n) {floor(log(n))})
CPAT:::stat_Zn(rnorm(1000), use_kernel_var = TRUE, bandwidth = "nw",
              kernel = "bo")
```

%s%

Concatenate (With Space)

Description

Concatenate and form strings (with space separation)

Usage

```
x %s% y
```

Arguments

<code>x</code>	One object
<code>y</code>	Another object

Value

A string combining `x` and `y` with a space separating them

Examples

```
`%s%` <- CPAT:::`%s%`
"Hello" %s% "world"
```

`%s0%` *Concatenate (Without Space)*

Description

Concatenate and form strings (no space separation)

Usage

`x %s0% y`

Arguments

`x` One object
`y` Another object

Value

A string combining `x` and `y`

Examples

```
`%s0%` <- CPAT:::`%s0%`  
"Hello" %s0% "world"
```

Index

*Topic **datasets**

banks, [5](#)

ff, [9](#)

.onAttach, [2](#)

%s0%, [33](#)

%s%, [32](#)

Andrews.test, [3](#)

andrews_test, [3, 4](#)

andrews_test_reg, [3, 4](#)

banks, [5](#)

CPAT_startup_message, [6](#)

cpt_consistent_var, [6](#)

CUSUM.test, [7](#)

DE.test, [8](#)

dZn, [9](#)

ff, [9](#)

get_lrv_vec, [11](#)

getBandwidth, [7, 8, 11, 12, 27, 28, 30, 31](#)

getLongRunVar, [7, 8, 10–12, 27–29, 31](#)

getLongRunWeights, [10, 10](#)

HR.test, [12](#)

HS.test, [13](#)

lm, [3, 5](#)

log, [12](#)

pdarling_erdos, [8, 14](#)

phidalgo_seo, [13, 14](#)

pkolmogorov, [7, 15](#)

pZn, [12, 15](#)

qdarling_erdos, [16](#)

qhidalgo_seo, [16](#)

qkolmogorov, [17](#)

qZn, [17](#)

rchangeoint, [18](#)

sim_de_stat, [19](#)

sim_hs_stat, [20](#)

sim_Vn, [22](#)

sim_Vn_stat, [22](#)

sim_Zn, [24](#)

sim_Zn_stat, [25](#)

sqr, [12](#)

stat_de, [8, 20, 26](#)

stat_hs, [13, 21, 27](#)

stat_Vn, [7, 23, 27, 29](#)

stat_Zn, [12, 25, 31](#)

uniroot, [17, 18](#)