

Package ‘DataGraph’

August 25, 2021

Type Package

Title Export Data from R so 'DataGraph' can Read it

Version 1.2.5

Date 2021-08-11

Author David Adalsteinsson

Maintainer David Adalsteinsson <david@visualdatatools.com>

Description Functions to save either '.dtable' or '.dtbin' files that can be read by 'DataGraph', a graphing and analysis application for mac OS. Can save a data frame, collection of data frames and sequences of data frames and individual vectors. For more information see <<https://community.visualdatatools.com/datagraph/knowledge-base/r-package/>>.

License GPL (>= 2)

Imports Rcpp (>= 0.12.10)

LinkingTo Rcpp

NeedsCompilation yes

Repository CRAN

Date/Publication 2021-08-25 12:50:29 UTC

R topics documented:

DataGraph-package	2
addDTable	3
addDTBin	3
closeDTable	4
closeDTBin	5
infoDTBin	5
openDTable	6
openDTBin	7
syncDTable	7
syncDTBin	8
writeDTable	9

Index	10
--------------	-----------

Description

Functions to save either .dtable or .dtbin files that can be read by DataGraph, a graphing and analysis application for MacOS. Can save a data frame, collection of data frames and sequences of data frames and individual vectors.

Details

There is a total of eight functions in this package One step to save a data frame into a .dtable file
writeDTable(path name,data frame)

To save multiple data frames into a single .dtable file openDTable(path name) addDTable(path name,data frame) closeDTable(path name)

To save a .dtbin file, which can contain multiple lists and data frames by name and each one can be a sequence saved by "time" openDTBin(path name) addDTBin(path name,entry name,data (frame or column),time (optional)) infoDTBin(path name) : Prints out the current content of the file closeDTBin(path name)

Author(s)

David Adalsteinsson

Maintainer: David Adalsteinsson <david@visualdatatools.com>

Examples

```
## Not run:
writeDTable("/tmp/test",mtcars)

openDTable("/tmp/test2" name)
addDTable("/tmp/test2",data frame)
... modify the table
addDTable("/tmp/test2",data frame)
closeDTable("/tmp/test2")

openDTBin("/tmp/test3")
addDTBin("/tmp/test3","Cars",mtcars)
addDTBin("/tmp/test3","Orange",Orange)
infoDTBin("/tmp/test3")
closeDTBin("/tmp/test3")

## End(Not run)
```

addDTable	<i>Save a data frame to a .dtable file</i>
-----------	--

Description

Adds a table to an already open table file. Need to open it first by using the openDTable function.

Usage

```
addDTable(path, data)
```

Arguments

path	A path name
data	A data frame

Value

Nothing returned

Examples

```
## Not run:  
openDTable("/tmp/test")  
addDTable("/tmp/test", Orange)  
closeDTable("/tmp/test")  
  
## End(Not run)
```

addDTBin	<i>Save a data frame to a .dtbin file</i>
----------	---

Description

Adds the data into a .dtbin file.

Usage

```
addDTBin(path, name, data, time)
```

Arguments

path	A path name
name	The name of the variable
data	Either a data frame or a vector
time	optional: What time value this variable is at

Value

Nothing returned

Examples

```
## Not run:  
openDTBin("/tmp/test")  
addDTBin("/tmp/test","A",Orange)  
closeDTBin("/tmp/test")  
  
## End(Not run)
```

closeDTable

Save a data frame to a .dtable file

Description

Closes a .dtable file

Usage

```
closeDTable(path)
```

Arguments

path A path name

Value

Nothing returned

Examples

```
## Not run:  
openDTBin("/tmp/test")  
addDTBin("/tmp/test","A",Orange)  
closeDTBin("/tmp/test")  
  
## End(Not run)
```

closeDTBin	<i>Close a .dtbin file</i>
------------	----------------------------

Description

Closes a .dtbin file

Usage

```
closeDTBin(path)
```

Arguments

path	A path name
------	-------------

Value

Nothing returned

Examples

```
## Not run:  
openDTBin("/tmp/test")  
addDTBin("/tmp/test","A",Orange)  
closeDTBin("/tmp/test")  
  
## End(Not run)
```

infoDTBin	<i>Save a data frame to a .dtable file</i>
-----------	--

Description

Displays the content of a .dtbin file

Usage

```
infoDTBin(path)
```

Arguments

path	A path name
------	-------------

Value

Nothing returned, but data is printed to the console. Intended as a debugging aid.

Examples

```
## Not run:
openDTBin("/tmp/test")
addDTBin("/tmp/test", "A", Orange)
infoDTBin("/tmp/test")
closeDTBin("/tmp/test")

## End(Not run)
```

openDTable*Open a .dtable file so you can write into it using addDTable*

Description

Saves the data frame to a file

Usage

```
openDTable(path)
```

Arguments

path A path name

Value

Nothing returned

Examples

```
## Not run:
openDTBin("/tmp/test")
addDTBin("/tmp/test", "A", Orange)
closeDTBin("/tmp/test")

## End(Not run)
```

openDTBin	<i>Open a new .dtbin file</i>
-----------	-------------------------------

Description

Opens a .dtbin file. Prints out an error message if the file is already open.

Usage

```
openDTBin(path)
```

Arguments

path	A path name
------	-------------

Value

Nothing returned

Examples

```
## Not run:  
openDTBin("/tmp/test")  
addDTBin("/tmp/test","A",Orange)  
infoDTBin("/tmp/test")  
closeDTBin("/tmp/test")  
  
## End(Not run)
```

syncDTable	<i>Adds a .sync file with the same name as the .dtable file.</i>
------------	--

Description

Used so that DataGraph can read up to an internal boundary inside the data file and avoids reading a partial table. DataGraph monitors this file and reloads the file when it sees a new sync file.

Usage

```
syncDTable(path)
```

Arguments

path	A path name
------	-------------

Value

Nothing returned

Examples

```
## Not run:  
openDTable("/tmp/test")  
addDTable("/tmp/test", Orange)  
syncDTable("/tmp/test")  
addDTable("/tmp/test", Orange)  
closeDTable("/tmp/test")  
  
## End(Not run)
```

syncDTBin

Adds a .sync file with the same name as the .dtbin file.

Description

Used so that DataGraph can read up to an internal boundary inside the data file and avoids reading a partial table. DataGraph monitors this file and reloads the file when it sees a new sync file.

Usage

```
syncDTBin(path)
```

Arguments

path A path name

Value

Nothing returned

Examples

```
## Not run:  
openDTBin("/tmp/test")  
addDTBin("/tmp/test", "Orange", Orange)  
syncDTBin("/tmp/test")  
addDTBin("/tmp/test", "Orange", Orange)  
closeDTBin("/tmp/test")  
  
## End(Not run)
```

writeDTable	<i>Save a data frame to a .dtable file</i>
-------------	--

Description

Saves the data frame to a file

Usage

```
writeDTable(path,data)
```

Arguments

path	A path name
data	A data frame

Value

Nothing returned

Examples

```
## Not run:  
writeDTable("/tmp/test",Orange)  
  
## End(Not run)
```

Index

* package

DataGraph-package, [2](#)

addDTable, [3](#)

addDTBin, [3](#)

closeDTable, [4](#)

closeDTBin, [5](#)

DataGraph (DataGraph-package), [2](#)

DataGraph-package, [2](#)

infoDTBin, [5](#)

openDTable, [6](#)

openDTBin, [7](#)

syncDTable, [7](#)

syncDTBin, [8](#)

writeDTable, [9](#)