

Package ‘ReDaMoR’

September 5, 2022

Type Package

Title Relational Data Modeler

Version 0.6.5

Maintainer Patrice Godard <patrice.godard@gmail.com>

Description The aim of this package is to manipulate relational data models in R.
It provides functions to create, modify and export data models in json format.
It also allows importing models created with 'MySQL Workbench' (<<https://www.mysql.com/products/workbench/>>).
These functions are accessible through a graphical user interface made with 'shiny'.
Constraints such as types, keys, uniqueness and mandatory fields are automatically checked and corrected when editing a model.
Finally, real data can be confronted to a model to check their compatibility.

URL <https://patzaw.github.io/ReDaMoR/>,
<https://github.com/patzaw/ReDaMoR/>

BugReports <https://github.com/patzaw/ReDaMoR/issues>

Depends R (>= 3.5), dplyr, magrittr, visNetwork

Imports readr, shiny, shinyjs, jsonlite, DT, colourpicker, rintrojs, markdown, rstudioapi, crayon, utils, graphics, stats, Matrix

Suggests knitr, rmarkdown, igraph, base64enc

License GPL-3

Encoding UTF-8

VignetteBuilder knitr

RoxygenNote 7.2.1

NeedsCompilation no

Author Patrice Godard [aut, cre, cph]

Repository CRAN

Date/Publication 2022-09-05 07:40:02 UTC

R topics documented:

| | |
|--------------------------------|----|
| add_field | 3 |
| add_foreign_key | 4 |
| add_index | 5 |
| add_table | 5 |
| as_type | 6 |
| auto_layout | 6 |
| c.RelDataModel | 7 |
| check_foreign_keys | 7 |
| check_types | 8 |
| clean_autosaved_RelDataModels | 8 |
| col_types | 8 |
| confront_data | 9 |
| confront_table_data | 10 |
| conv_type_ref | 11 |
| correct_constraints | 11 |
| df_to_model | 12 |
| format.RelTableModel | 13 |
| format_confrontation_report | 13 |
| format_confrontation_report_md | 14 |
| fromDBM | 15 |
| get_foreign_keys | 17 |
| get_foreign_keys.RelDataModel | 17 |
| get_foreign_keys.RelTableModel | 18 |
| identical_RelDataModel | 19 |
| identical_RelTableModel | 19 |
| index_table | 20 |
| is.MatrixModel | 20 |
| is.RelDataModel | 21 |
| is.RelTableModel | 21 |
| is_MM | 22 |
| lengths | 22 |
| list_autosaved_RelDataModel | 23 |
| list_type_ref | 23 |
| modelToVn | 23 |
| model_relational_data | 24 |
| norm_type_ref | 25 |
| order_fields | 25 |
| plot.RelDataModel | 26 |
| read_json_data_model | 26 |
| read_named_MM | 27 |
| read_named_MM_header | 28 |
| read_SQL_data_model | 28 |
| recover_RelDataModel | 29 |
| RelDataModel | 30 |
| RelTableModel | 30 |
| remove_field | 32 |

remove_foreign_key 32

remove_index 33

remove_table 33

rename_field 34

rename_table 34

set_primary_key 35

set_unique_index 35

SUPPTYPES 36

toDBM 36

update_field 37

update_foreign_key 38

update_table_display 39

view_confrontation_report 39

write_json_data_model 40

[.RelDataModel 40

Index **41**

add_field *Add a field to a table in a [RelDataModel](#)*

Description

Add a field to a table in a [RelDataModel](#)

Usage

add_field(x, tableName, name, type, nullable, unique, comment)

Arguments

- x [a RelDataModel](#)
- tableName the name of the table to modify (a single character)
- name the name of the field to add (a single character)
- type the type of the field (a single character)
- nullable if the field is nullable (a single logical)
- unique if the values are unique (a single logical)
- comment a description (a single character)

Value

A [RelDataModel](#)

| | |
|-----------------|---|
| add_foreign_key | <i>Add a foreign key between two tables</i> |
|-----------------|---|

Description

Add a foreign key between two tables

Usage

```
add_foreign_key(  
    x,  
    fromTable,  
    fromFields,  
    toTable,  
    toFields,  
    fmin = 0L,  
    fmax = -1L,  
    tmin = 1L,  
    tmax = 1L  
)
```

Arguments

| | |
|------------|--|
| x | a RelDataModel |
| fromTable | the name of the referencing table |
| fromFields | the name of the referencing fields |
| toTable | the name of the referenced table |
| toFields | the names of the referenced fields |
| fmin | from minimum cardinality (default: 0L) |
| fmax | from maximum cardinality (default: -1L ==> Infinite) |
| tmin | to minimum cardinality (default: 1L) |
| tmax | to maximum cardinality (default: 1L) |

Value

A [RelDataModel](#)

| | |
|-----------|--|
| add_index | <i>Add an index to a table in a RelDataModel</i> |
|-----------|--|

Description

Add an index to a table in a [RelDataModel](#)

Usage

```
add_index(x, tableName, fieldNames, unique)
```

Arguments

| | |
|------------|---|
| x | a RelDataModel |
| tableName | the name of the table to modify (a single character) |
| fieldNames | the names of the fields to include in the index |
| unique | a logical indicating if the indexed values are unique |

Value

A [RelDataModel](#)

| | |
|-----------|--|
| add_table | <i>Add a table to a RelDataModel</i> |
|-----------|--|

Description

Add a table to a [RelDataModel](#)

Usage

```
add_table(x, newTable)
```

Arguments

| | |
|----------|--|
| x | a RelDataModel |
| newTable | the name of the new table or a RelTableModel |

Value

A [RelDataModel](#)

| | |
|---------|---|
| as_type | <i>Convert an object into a specific type</i> |
|---------|---|

Description

Convert an object into a specific type

Usage

```
as_type(x, type)
```

Arguments

| | |
|------|----------------------|
| x | an object to convert |
| type | the targeted type |

| | |
|-------------|---|
| auto_layout | <i>Pre-compute RelDataModel layout when missing any x or y table position</i> |
|-------------|---|

Description

Pre-compute [RelDataModel](#) layout when missing any x or y table position

Usage

```
auto_layout(  
  x,  
  layout = "layout_nicely",  
  lengthMultiplier = 40 * length(x),  
  force = FALSE  
)
```

Arguments

| | |
|------------------|---|
| x | a RelDataModel |
| layout | character name of igraph layout function to use (Default: "layout_nicely"). |
| lengthMultiplier | a numeric value to scale x and y coordinate (default: 40*length(x)) |
| force | if TRUE autolayout even if all tables have coordinates (default: FALSE) |

Value

A [RelDataModel](#)

| | |
|----------------|-----------------------------------|
| c.RelDataModel | Merge <i>RelDataModel</i> objects |
|----------------|-----------------------------------|

Description

Merge *RelDataModel* objects

Usage

```
## S3 method for class 'RelDataModel'  
c(..., checkFK = TRUE)
```

Arguments

| | |
|---------|--|
| ... | <i>RelDataModel</i> objects |
| checkFK | a logical indicating if foreign keys should be checked (default: TRUE) |

Value

A *RelDataModel* objects

| | |
|--------------------|--|
| check_foreign_keys | Check the availability of foreign keys |
|--------------------|--|

Description

Check the availability of foreign keys

Usage

```
check_foreign_keys(x)
```

Arguments

| | |
|---|------------------------------|
| x | a <i>RelDataModel</i> object |
|---|------------------------------|

Value

Nothing. The function throws an error if there is an issue with foreign keys.

| | |
|-------------|---|
| check_types | <i>Check if a set of types is supported</i> |
|-------------|---|

Description

Check if a set of types is supported

Usage

```
check_types(x)
```

Arguments

x a character vector of types to be checked

| | |
|-------------------------------|--|
| clean_autosaved_RelDataModels | <i>Remove all autosaved RelDataModel</i> |
|-------------------------------|--|

Description

Remove all autosaved [RelDataModel](#)

Usage

```
clean_autosaved_RelDataModels()
```

| | |
|-----------|---|
| col_types | <i>Get the types of the columns of a RelTableModel object</i> |
|-----------|---|

Description

Get the types of the columns of a [RelTableModel](#) object

Usage

```
col_types(x)
```

Arguments

x a [RelTableModel](#) object

Value

A col_spec object with the type of each column

confront_data *Confront a [RelDataModel](#) to actual data*

Description

Confront a [RelDataModel](#) to actual data

Usage

```
confront_data(
  x,
  data = list(),
  paths = NULL,
  returnData = FALSE,
  verbose = TRUE,
  n_max = Inf,
  checks = if (n_max == Inf) {
    c("unique", "not nullable", "foreign keys")
  } else
  {
    as.character()
  },
  delim = "\t",
  ...
)
```

Arguments

| | |
|------------|---|
| x | a RelDataModel |
| data | a list of data frames to be confronted with the model. |
| paths | a character vector with file paths taken into account if the data is empty. The file basename without extension will be considered as the table name. |
| returnData | a logical indicating if the data should be returned with the report (default: FALSE). |
| verbose | a single logical value indicating if some process information should be displayed (default: TRUE) |
| n_max | maximum number of records to read (default: Inf). |
| checks | a character vector with the name of optional checks to be done (Default: if n_max==Inf ==> all of them c("unique", "not nullable", "foreign keys"), else ==> none) |
| delim | single character used to separate fields within a record (default: "\t") |
| ... | supplementary parameters for the read_delim function. |

Value

A report as a list

Examples

```
## Read the model ----
hpo_model <- read_json_data_model(
  system.file("examples/HPO-model.json", package="ReDaMoR")
)
## Confront to data ----
confrontation_report <- confront_data(
  hpo_model,
  path=list.files(
    system.file("examples/HPO-subset", package="ReDaMoR"),
    full.names=TRUE
  ),
  returnData=TRUE
)
```

confront_table_data *Confront a [RelTableModel](#) to actual data*

Description

Confront a [RelTableModel](#) to actual data

Usage

```
confront_table_data(x, d, checks = c("unique", "not nullable"))
```

Arguments

| | |
|--------|---|
| x | a RelTableModel |
| d | a data frame or a matrix for matrix model |
| checks | a character vector with the name of optional checks to be done (Default: all of them c("unique", "not nullable")) |

Value

A report as a list

| | |
|---------------|--|
| conv_type_ref | <i>Convert a set of types from or to R supported types</i> |
|---------------|--|

Description

Convert a set of types from or to R supported types

Usage

```
conv_type_ref(x, from = NULL, to = NULL, ignore.case = TRUE)
```

Arguments

| | |
|-------------|--|
| x | a character vector of types to be converted. If from is not null, x should be a set of valid types in the from reference. If to is not null, x should be a set of supported R types (SUPPTYPES). |
| from | a character vector of length one: the type reference (list_type_ref) of x |
| to | a character vector of length one: the targeted type reference (list_type_ref) |
| ignore.case | should case be ignored when converting ‘from‘ type reference (default: TRUE) |

Details

Only from XOR to should be set

| | |
|---------------------|---|
| correct_constraints | <i>Correct the constraints of a table to make them consistent</i> |
|---------------------|---|

Description

Correct the constraints of a table to make them consistent

Usage

```
correct_constraints(x)
```

Arguments

| | |
|---|--|
| x | a RelTableModel object |
|---|--|

df_to_model

*Create a RelTableModel object from column names of data frames***Description**

Create a RelTableModel object from column names of data frames

Usage

```
df_to_model(..., list = character(), pos = -1, envir = as.environment(pos))
```

Arguments

| | |
|-------|--|
| ... | the data frame objects, as names (unquoted) or character strings (quoted) |
| list | a character vector naming data frame objects |
| pos | where to get the objects. By default, uses the current environment. See ‘details’ for other possibilities. |
| envir | the environment to use. See ‘details’. |

Details

The pos argument can specify the environment from which to get the objects in any of several ways: as an integer (the position in the search list); as the character string name of an element in the search list; or as an environment. The envir argument is an alternative way to specify an environment, but is primarily there for back compatibility.

Value

A RelTableModel object.

Examples

```
## Read data files ----
to_read <- list.files(
  system.file("examples/HPO-subset", package="ReDaMoR"),
  full.names=TRUE
)
hpo_tables <- list()
for(f in to_read){
  hpo_tables[[sub("[.]txt$", "", basename(f))]] <- readr::read_tsv(f)
}
## Build the model from a list of data frames ----
new_model <- df_to_model(
  list=names(hpo_tables), envir=as.environment(hpo_tables)
)
## Plot the model ----
new_model %>%
  auto_layout(lengthMultiplier=250) %>%
  plot()
```

format.RelTableModel *Format a [RelTableModel](#) object for printing*

Description

Format a [RelTableModel](#) object for printing

Usage

```
## S3 method for class 'RelTableModel'  
format(x, ...)
```

Arguments

x a [RelTableModel](#) object
... for generics compatibility (not used)

Value

A single character

format_confrontation_report
Format confrontation report for printing in console

Description

Format confrontation report for printing in console

Usage

```
format_confrontation_report(cr, title = "Model")
```

Arguments

cr the confrontation report from [confront_data](#)
title a character with a single value corresponding to the report title (e.g. database/model name)

Examples

```
## Read the model ----
hpo_from_sql <- read_SQL_data_model(
  system.file("examples/HPO-model.sql", package="ReDaMoR")
)
## Confront to data ----
confrontation_report <- confront_data(
  hpo_from_sql,
  path=list.files(
    system.file("examples/HPO-subset", package="ReDaMoR"),
    full.names=TRUE
  ),
  verbose=FALSE,
  returnData=TRUE
)
## Show the report in console ----
format_confrontation_report(confrontation_report) %>% cat()
## Format the report using markdown ----
format_confrontation_report_md(confrontation_report) %>% cat()
```

format_confrontation_report_md

Format confrontation report in markdown format

Description

Format confrontation report in markdown format

Usage

```
format_confrontation_report_md(
  cr,
  title = "Model",
  level = 0,
  numbered = TRUE,
  bgSuccess = "green",
  txSuccess = "black",
  bgFailure = "red",
  txFailure = "white",
  bgMessage = "#FFBB33",
  txMessage = "white"
)
```

Arguments

cr the confrontation report from [confront_data](#)

title a character with a single value corresponding to the report

| | |
|-----------|---|
| level | rmarkdown level in document hierarchy (default:0 ==> highest). It should be an integer between 0 and 4. |
| numbered | a logical. If TRUE (default) the sections are part of document numbering. |
| bgSuccess | background color for SUCCESS |
| txSuccess | text color for SUCCESS |
| bgFailure | background color for FAILURE |
| txFailure | text color for FAILURE |
| bgMessage | background color for a warning message |
| txMessage | text color for a warning message |

Examples

```
## Read the model ----
hpo_from_sql <- read_SQL_data_model(
  system.file("examples/HPO-model.sql", package="ReDaMoR")
)
## Confront to data ----
confrontation_report <- confront_data(
  hpo_from_sql,
  path=list.files(
    system.file("examples/HPO-subset", package="ReDaMoR"),
    full.names=TRUE
  ),
  verbose=FALSE,
  returnData=TRUE
)
## Show the report in console ----
format_confrontation_report(confrontation_report) %>% cat()
## Format the report using markdown ----
format_confrontation_report_md(confrontation_report) %>% cat()
```

fromDBM

Convert a list of 5 normalized tibbles in a [RelDataModel](#) object

Description

Convert a list of 5 normalized tibbles in a [RelDataModel](#) object

Usage

```
fromDBM(dbm)
```

Arguments

dbm

a list with the following tibbles:

- **tables**: The tables in the model with the following information
 - **name**: the name of the table
 - **x**: the x coordinate of the table in the model drawing (NA ==> position undefined)
 - **y**: the y coordinate of the table in the model drawing (NA ==> position undefined)
 - **color**: the color of the table in the model drawing (NA ==> undefined)
 - **comment**: comment about the table
- **fields**: The fields in the model with the following information
 - **name**: the name of the field
 - **type**: the type of the field
 - **nullable**: a logical indicating if the field can be null
 - **comment**: comment about the field
 - **table**: the name of the table to which the field belongs
- **primaryKeys**: The primary keys in the model with the following information
 - **table**: the name of the relevant table
 - **field**: the name of the field participating to the primary key
- **foreignKeys**: The foreign keys in the model with the following information
 - **table**: the name of the referring table
 - **fki**: the identifier of the foreign key (by referring table)
 - **field**: the name of the referring field
 - **refTable**: the name of the referred table
 - **refField**: the name of the referred field
- **indexes**: The indexes in the model with the following information
 - **table**: the name of the relevant table
 - **idx**: the identifier of the index (by table)
 - **field**: the name of the field participating to the index
 - **unique**: a logical indicating if the field is unique

Value

A [RelDataModel](#) object

get_foreign_keys *Get a foreign key table from an object*

Description

Get a foreign key table from an object

Usage

```
get_foreign_keys(x)
```

Arguments

x a [RelTableModel](#) or a [RelDataModel](#)

Value

A tibble with the following fields:

- from: the origin of the key
- ff: the key fields in from
- to: the target of the key
- tf: the key fields in to
- fmin: minimum cardinality of from
- fmax: maximum cardinality of from
- tmin: minimum cardinality of to
- tmax: maximum cardinality of to

get_foreign_keys.RelDataModel
Get foreign keys in [RelDataModel](#)

Description

Get foreign keys in [RelDataModel](#)

Usage

```
## S3 method for class 'RelDataModel'  
get_foreign_keys(x)
```

Arguments

x a [RelDataModel](#)

Value

A tibble with the following fields:

- from: the origin of the key
- ff: the key fields in from
- to: the target of the key
- tf: the key fields in to
- fmin: minimum cardinality of from
- fmax: maximum cardinality of from
- tmin: minimum cardinality of to
- tmax: maximum cardinality of to

get_foreign_keys.RelTableModel

Get foreign keys from [RelTableModel](#)

Description

Get foreign keys from [RelTableModel](#)

Usage

```
## S3 method for class 'RelTableModel'  
get_foreign_keys(x)
```

Arguments

x a [RelTableModel](#)

Value

A tibble with the following fields:

- from: the origin of the key
- ff: the key fields in from
- to: the target of the key
- tf: the key fields in to
- fmin: minimum cardinality of from
- fmax: maximum cardinality of from
- tmin: minimum cardinality of to
- tmax: maximum cardinality of to

`identical_RelDataModel`*Check if two [RelDataModel](#) are identical*

Description

Check if two [RelDataModel](#) are identical

Usage

```
identical_RelDataModel(x, y, ...)
```

Arguments

| | |
|-----|---|
| x | a RelDataModel |
| y | a RelDataModel |
| ... | additional parameters for identical_RelTableModel() |

Value

A logical: TRUE if the 2 models are identical

`identical_RelTableModel`*Check if two [RelTableModel](#) are identical*

Description

Check if two [RelTableModel](#) are identical

Usage

```
identical_RelTableModel(x, y, includeDisplay = TRUE)
```

Arguments

| | |
|----------------|---|
| x | a RelTableModel |
| y | a RelTableModel |
| includeDisplay | a single logical (default: TRUE) indicating if the display should be included in the comparison |

Value

A logical: TRUE if the 2 models are identical

index_table *List indexes of a [RelTableModel](#) object*

Description

List indexes of a [RelTableModel](#) object

Usage

```
index_table(x)
```

Arguments

x a [RelTableModel](#) object

Value

A tibble with the following columns:

- **index**: an integer corresponding to the index number
- **field**: a character corresponding to field belonging to the index
- **unique**: a logical indicating the uniqueness of the field

is.MatrixModel *Check if the object is a [RelTableModel](#) matrix object*

Description

A matrix model is a special [RelTableModel](#) object with 3 and only 3 fields: 2 of types 'row' and 'column' and the 3rd of your choice.

Usage

```
is.MatrixModel(x)
```

Arguments

x any object

Value

A single logical: TRUE if x is a [RelTableModel](#) matrix object

is.RelDataModel *Check if the object is a [RelDataModel](#) object*

Description

Check if the object is a [RelDataModel](#) object

Usage

is.RelDataModel(x)

Arguments

x any object

Value

A single logical: TRUE if x is a [RelDataModel](#) object

is.RelTableModel *Check if the object is a [RelTableModel](#) object*

Description

Check if the object is a [RelTableModel](#) object

Usage

is.RelTableModel(x)

Arguments

x any object

Value

A single logical: TRUE if x is a [RelTableModel](#) object

| | |
|-------|--|
| is_MM | <i>Identify if a file is in MatrixMarket text format</i> |
|-------|--|

Description

Identify if a file is in MatrixMarket text format

Usage

```
is_MM(file)
```

Arguments

| | |
|------|------------------|
| file | the file to read |
|------|------------------|

Value

A logical. If FALSE, the first line of the file is returned as an attribute named "r1": attr(is_MM, "r1")

| | |
|---------|-----------------------------------|
| lengths | <i>Lengths of object elements</i> |
|---------|-----------------------------------|

Description

Lengths of object elements

Usage

```
lengths(x, use.names = TRUE)
```

Arguments

| | |
|-----------|---|
| x | an object. If there is no method implemented for this object, the base::lengths() function is used. |
| use.names | logical indicating if the result should inherit the names from x. |

Value

A non-negative integer of length length(x), except when any element has a length of more than $2^{31} - 1$ elements, when it returns a double vector. When use.names is true, the names are taken from the names on x, if any.

See Also

[base::lengths\(\)](#)

list_autosaved_RelDataModel
List autosaved [RelDataModel](#)

Description

List autosaved [RelDataModel](#)

Usage

```
list_autosaved_RelDataModel()
```

See Also

[clean_autosaved_RelDataModels\(\)](#) to clean this list.

list_type_ref *List supported types references*

Description

List supported types references

Usage

```
list_type_ref()
```

modelToVn *VisNetwork representation of a [RelDataModel](#) object*

Description

VisNetwork representation of a [RelDataModel](#) object

Usage

```
modelToVn(  
  model,  
  color = "lightgrey",  
  border = "black",  
  highlightBorder = "orange"  
)
```

Arguments

| | |
|-----------------|---------------------------------|
| model | a RelDataModel |
| color | default table background color |
| border | border color (single character) |
| highlightBorder | color of highlighted borders |
| | Internal function |

model_relational_data *Relational data modeler GUI*

Description

Relational data modeler GUI

Usage

```
model_relational_data(
  modelInput = RelDataModel(list()),
  fromR = interactive(),
  defaultColor = "#D9D9D9",
  availableColors = c("#9BC8FE", "#F67FC4", "#C6BDF1", "#DFFB86", "#F8DEC3", "#8FE6E0",
    "#FEFE8F", "#FAC6DC", "#A9ECC9"),
  example = system.file("examples/HPO-model.json", package = utils::packageName()),
  forceIntro = FALSE
)
```

Arguments

| | |
|-----------------|---|
| modelInput | the RelDataModel to start from |
| fromR | a logical indicating if the application is launched from R |
| defaultColor | a single color indicating the default table color |
| availableColors | a character of possible colors for tables |
| example | a file path to an sql or json model |
| forceIntro | if TRUE the help tour start when the application is launched (default: FALSE) |

Value

The [RelDataModel](#) designed with the GUI.

| | |
|---------------|-----------------------------|
| norm_type_ref | <i>Normalize type names</i> |
|---------------|-----------------------------|

Description

Normalize type names

Usage

```
norm_type_ref(x, typeRef, ignore.case = TRUE)
```

Arguments

| | |
|-------------|--|
| x | a character vector to normalize |
| typeRef | a character vector of length one: the type reference (list_type_ref) |
| ignore.case | should case be ignored (default: TRUE) |

| | |
|--------------|--|
| order_fields | <i>Order fields in a table in a RelDataModel</i> |
|--------------|--|

Description

Order fields in a table in a [RelDataModel](#)

Usage

```
order_fields(x, tableName, order)
```

Arguments

| | |
|-----------|--|
| x | a RelDataModel |
| tableName | the name of the table to modify (a single character) |
| order | a vector of integers all in (1:number_of_fields) |

Value

A [RelDataModel](#)

plot.RelDataModel *Plot a [RelDataModel](#) object*

Description

This function draw a visNetwork of the [RelDataModel](#).

Usage

```
## S3 method for class 'RelDataModel'  
plot(x, ...)
```

Arguments

x a [RelDataModel](#)
... additional parameters:

- **color** default table background color
- **border** border color (single character)
- **highlightBorder** color of highlighted borders

Examples

```
## Read the model ----  
hpo_model <- read_json_data_model(  
  system.file("examples/HPO-model.json", package="ReDaMoR")  
)  
## Plot the model ----  
plot(hpo_model)
```

read_json_data_model *Read a data model from JSON*

Description

Read a data model from JSON

Usage

```
read_json_data_model(txt)
```

Arguments

txt a JSON string, URL or file

Examples

```
## Read the model ----
hpo_model <- read_json_data_model(
  system.file("examples/HPO-model.json", package="ReDaMoR")
)
## Confront to data ----
confrontation_report <- confront_data(
  hpo_model,
  path=list.files(
    system.file("examples/HPO-subset", package="ReDaMoR"),
    full.names=TRUE
  ),
  returnData=TRUE
)
```

read_named_MM

Read a named sparse matrix in MatrixMarket text format

Description

Read a named sparse matrix in MatrixMarket text format

Usage

```
read_named_MM(
  file,
  skip = 0,
  n_max = Inf,
  class = c("dgCMatrix", "tibble"),
  guess_max = 20
)
```

Arguments

| | |
|-----------|---|
| file | the file to read |
| skip | the number of records to skip (default: 0) |
| n_max | the maximum number of records to read (default: Inf) |
| class | the class of object to return. By default a "dgCMatrix". If "tibble" is chosen, the sparse matrix is returned as a tibble with 3 columns: i (row index), j (column index) and x (values) and an "header" attribute containing the matrix rownames and colnames. |
| guess_max | the number of lines to read to find the header. (see read_named_MM_header()) |

Value

By default a dgCMatrix. If the "tibble" class is chosen, the sparse matrix is returned as a tibble with 3 columns: i (row index), j (column index) and x (values) and an "header" attribute containing the matrix rownames and colnames.

`read_named_MM_header` *Read the header of a named sparse matrix in MatrixMarket text format*

Description

Read the header of a named sparse matrix in MatrixMarket text format

Usage

```
read_named_MM_header(file, guess_max = 20)
```

Arguments

| | |
|------------------------|---|
| <code>file</code> | the file to read |
| <code>guess_max</code> | the number of lines to read to find the header. (4 should be sufficient. Default: 20) |

Value

A list with the following fields:

- `rownames`: a character vector with the matrix row names
- `colnames`: a character vector with the matrix column names
- `rows`: the number of matrix rows
- `columns`: the number of matrix columns
- `values`: the number of values in the matrix
- `header_length`: the number of lines in the header

`read_SQL_data_model` *Read a data model from an SQL file from the MySQL Workbench*

Description

Read a data model from an SQL file from the MySQL Workbench

Usage

```
read_SQL_data_model(f, typeRef = "MySQLWB", mysqlcomments = TRUE)

readSQLDataModel(...)
```

Arguments

| | |
|---------------|--|
| f | the SQL file to read |
| typeRef | the reference for type conversion (Default: "MySQLWB"; see list_type_ref()) |
| mysqlcomments | if MySQL comments (starting with #) should be removed (Default: TRUE) |
| ... | params for <code>read_SQL_data_model</code> |

Details

Database, table and field names should be surrounded by "".

Value

A [RelDataModel](#) object

Functions

- `readSQLDataModel()`: Deprecated version of `read_SQL_data_model`

Examples

```
## Read the model ----
hpo_from_sql <- read_SQL_data_model(
  system.file("examples/HPO-model.sql", package="ReDaMoR")
)
## Confront to data ----
confrontation_report <- confront_data(
  hpo_from_sql,
  path=list.files(
    system.file("examples/HPO-subset", package="ReDaMoR"),
    full.names=TRUE
  ),
  returnData=TRUE
)
```

`recover_RelDataModel` *Recover an autosaved [RelDataModel](#)*

Description

Recover an autosaved [RelDataModel](#)

Usage

```
recover_RelDataModel(name = NA)
```

Arguments

name The name of the autosaved [RelDataModel](#) to bring back. Available autosaved [RelDataModel](#) can be listed using the `list_autosaved_RelDataModel()`. If NA (default) the latest model is returned.

RelDataModel *Create a RelDataModel object*

Description

Create a RelDataModel object

Usage

```
RelDataModel(l, checkFK = TRUE)
```

Arguments

l the list of table models ([RelTableModel](#) objects)

checkFK a logical indicating if foreign keys should be checked (default: TRUE)

Value

A RelDataModel object.

RelTableModel *Create a RelTableModel object*

Description

Create a RelTableModel object

Usage

```
RelTableModel(l)
```

Arguments

1

the list with the following elements

- **tableName**: a character vector of length one
- **fields**: a tibble with the following columns:
 - *name*: character
 - *type*: character
 - *nullable*: logical
 - *comment*: character
- **primaryKey**: a character vector of any length. All values should be in `fields$name`
- **foreignKeys**: a list of foreign keys. Each foreign key is defined as a list with the following elements:
 - *refTable*: a character vector of length one (the referenced table)
 - *key*: a tibble with a "from" and a "to" columns
 - (*cardinality*): an optional integer vector with 4 values:
 - * *fmin*: from minimum cardinality
 - * *fmax*: from maximum cardinality
 - * *tmin*: to minimum cardinality
 - * *tmax*: to maximum cardinality
- **indexes**: a list of indexes. Each index is defined by 3 columns:
 - *field*: character (all in `fields$name`)
 - *order*: character
 - *unique*: logical
- **display**: a list gathering:
 - *x*: single numeric value for the x position of the table
 - *y*: single numeric value for the y position of the table
 - *color*: single character value corresponding to the color of the table
 - *comment*: single character value with some description of the table

Details

When defining a matrix, 3 and only 3 fields must be defined: 2 of types 'row' and 'column' and the 3rd of your choice. In this case `primaryKey` is defined automatically as the combination of row and column.

Value

A `RelTableModel` object.

| | |
|--------------|--|
| remove_field | <i>Remove a field from a table in a RelDataModel</i> |
|--------------|--|

Description

Remove a field from a table in a [RelDataModel](#)

Usage

```
remove_field(x, tableName, fieldName, rmForeignKeys = FALSE)
```

Arguments

| | |
|---------------|--|
| x | a RelDataModel |
| tableName | the name of the table to modify (a single character) |
| fieldName | the name of the field to remove (a single character) |
| rmForeignKeys | a single logical indicating if the corresponding foreign keys should be removed. If FALSE (default), the function will throw an error if it encounter a foreign key using the field. |

Value

A [RelDataModel](#)

| | |
|--------------------|--|
| remove_foreign_key | <i>Remove a foreign key between two tables</i> |
|--------------------|--|

Description

Remove a foreign key between two tables

Usage

```
remove_foreign_key(x, fromTable, fromFields, toTable, toFields)
```

Arguments

| | |
|------------|------------------------------------|
| x | a RelDataModel |
| fromTable | the name of the referencing table |
| fromFields | the name of the referencing fields |
| toTable | the name of the referenced table |
| toFields | the names of the referenced fields |

Value

A [RelDataModel](#)

| | |
|--------------|---|
| remove_index | <i>Remove an index from a table in a RelDataModel</i> |
|--------------|---|

Description

Remove an index from a table in a [RelDataModel](#)

Usage

```
remove_index(x, tableName, fieldNames)
```

Arguments

| | |
|------------|--|
| x | a RelDataModel |
| tableName | the name of the table to modify (a single character) |
| fieldNames | the names of the fields composing the index |

Value

A [RelDataModel](#)

| | |
|--------------|---|
| remove_table | <i>Remove a table from a RelDataModel</i> |
|--------------|---|

Description

Remove a table from a [RelDataModel](#)

Usage

```
remove_table(x, tableName, rmForeignKeys = FALSE)
```

Arguments

| | |
|---------------|---|
| x | a RelDataModel |
| tableName | the name of the table to remove |
| rmForeignKeys | if TRUE, remove foreign keys which are not available after extraction. If FALSE (default) the function will throw an error if any foreign keys does not exist in the extracted RelDataModel . |

Value

A [RelDataModel](#)

| | |
|--------------|---|
| rename_field | <i>Rename an existing field in a RelDataModel table</i> |
|--------------|---|

Description

Rename an existing field in a [RelDataModel](#) table

Usage

```
rename_field(x, tableName, current, new)
```

Arguments

| | |
|-----------|--|
| x | a RelDataModel |
| tableName | the name of the table to modify (a single character) |
| current | the current name of the field to modify (a single character) |
| new | the new name of the field (a single character) |

Value

A [RelDataModel](#)

| | |
|--------------|---|
| rename_table | <i>Rename a table in a RelDataModel</i> |
|--------------|---|

Description

Rename a table in a [RelDataModel](#)

Usage

```
rename_table(x, old, new)
```

Arguments

| | |
|-----|--|
| x | a RelDataModel object |
| old | a single character corresponding to the table name to change |
| new | the new table name |

Value

A [RelDataModel](#)

| | |
|-----------------|--|
| set_primary_key | <i>Set the primary key a table in a RelDataModel</i> |
|-----------------|--|

Description

Set the primary key a table in a [RelDataModel](#)

Usage

```
set_primary_key(x, tableName, fieldNames)
```

Arguments

| | |
|------------|---|
| x | a RelDataModel |
| tableName | the name of the table to modify (a single character) |
| fieldNames | the names of the fields to include in the primary key |

Value

A [RelDataModel](#)

| | |
|------------------|---|
| set_unique_index | <i>Set table index uniqueness in a RelDataModel</i> |
|------------------|---|

Description

Set table index uniqueness in a [RelDataModel](#)

Usage

```
set_unique_index(x, tableName, fieldNames, unique)
```

Arguments

| | |
|------------|--|
| x | a RelDataModel |
| tableName | the name of the table to modify (a single character) |
| fieldNames | the names of the fields composing the index |
| unique | a logical value |

Value

A [RelDataModel](#)

| | |
|-----------|--------------------------|
| SUPPTYPES | <i>Supported R types</i> |
|-----------|--------------------------|

Description

Supported R types

Usage

SUPPTYPES

Format

An object of class character of length 7.

| | |
|-------|--|
| toDBM | <i>Convert a RelDataModel object in a list of 5 normalized tibbles</i> |
|-------|--|

Description

Convert a [RelDataModel](#) object in a list of 5 normalized tibbles

Usage

toDBM(rdm)

Arguments

rdm a [RelDataModel](#) object

Value

A list with the following tibbles:

- **tables:** The tables in the model with the following information
 - **name:** the name of the table
 - **x:** the x coordinate of the table in the model drawing (NA ==> position undefined)
 - **y:** the y coordinate of the table in the model drawing (NA ==> position undefined)
 - **color:** the color of the table in the model drawing (NA ==> undefined)
 - **comment:** comment about the table
- **fields:** The fields in the model with the following information
 - **name:** the name of the field
 - **type:** the type of the field
 - **nullable:** a logical indicating if the field can be null

- **comment**: comment about the field
- **table**: the name of the table to which the field belongs
- **primaryKeys**: The primary keys in the model with the following information
 - **table**: the name of the relevant table
 - **field**: the name of the field participating to the primary key
- **foreignKeys**: The foreign keys in the model with the following information
 - **table**: the name of the referring table
 - **fki**: the identifier of the foreign key (by referring table)
 - **field**: the name of the referring field
 - **refTable**: the name of the referred table
 - **refField**: the name of the referred field
- **indexes**: The indexes in the model with the following information
 - **table**: the name of the relevant table
 - **idx**: the identifier of the index (by table)
 - **field**: the name of the field participating to the index
 - **unique**: a logical indicating if the field is unique

 update_field

 Update field information in a table of a [RelDataModel](#)

Description

Update field information in a table of a [RelDataModel](#)

Usage

```
update_field(
  x,
  tableName,
  fieldName,
  type = NULL,
  nullable = NULL,
  unique = NULL,
  comment = NULL
)
```

Arguments

| | |
|-----------|--|
| x | a RelDataModel |
| tableName | the name of the table to modify (a single character) |
| fieldName | the name of the field to modify (a single character) |
| type | the type of the field (a single character) |
| nullable | if the field is nullable (a single logical) |
| unique | if the values are unique (a single logical) |
| comment | a description (a single character) |

Value

A [RelDataModel](#)

update_foreign_key *Update a the cardinalities of a foreign key between two tables*

Description

Update a the cardinalities of a foreign key between two tables

Usage

```
update_foreign_key(  
  x,  
  fromTable,  
  fromFields,  
  toTable,  
  toFields,  
  fmin,  
  fmax,  
  tmin,  
  tmax  
)
```

Arguments

| | |
|------------|------------------------------------|
| x | a RelDataModel |
| fromTable | the name of the referencing table |
| fromFields | the name of the referencing fields |
| toTable | the name of the referenced table |
| toFields | the names of the referenced fields |
| fmin | from minimum cardinality |
| fmax | from maximum cardinality |
| tmin | to minimum cardinality |
| tmax | to maximum cardinality |

Value

A [RelDataModel](#)

update_table_display *Update the display of a table of a [RelDataModel](#)*

Description

Update the display of a table of a [RelDataModel](#)

Usage

```
update_table_display(  
  x,  
  tableName,  
  px = NULL,  
  py = NULL,  
  color = NULL,  
  comment = NULL  
)
```

Arguments

| | |
|-----------|--|
| x | a RelDataModel |
| tableName | the name of the table to modify (a single character) |
| px | the position of the table: x value |
| py | the position of the table: y value |
| color | the color of the table |
| comment | a table description/comment |

Value

A [RelDataModel](#)

view_confrontation_report
View confrontation report in rstudio viewer

Description

View confrontation report in rstudio viewer

Usage

```
view_confrontation_report(cr, ...)
```

Arguments

cr the confrontation report from [confront_data](#)
 ... additional params for the [format_confrontation_report_md\(\)](#) function

`write_json_data_model` *Write a data model in a JSON file*

Description

Write a data model in a JSON file

Usage

```
write_json_data_model(x, path)
```

Arguments

x the model to be written
 path file on disk

[.RelDataModel] *Subset a [RelDataModel](#)*

Description

Subset a [RelDataModel](#)

Usage

```
## S3 method for class 'RelDataModel'  

x[i, rmForeignKeys = FALSE, ...]
```

Arguments

x the [RelDataModel](#) object
 i the index or the names of the elements to extract
 rmForeignKeys if TRUE, remove foreign keys which are not available after extraction. If FALSE (default) the function will throw an error if any foreign keys does not exist in the extracted [RelDataModel](#).
 ... additional arguments for the [RelDataModel](#) function.

Index

- * **datasets**
 - SUPPTYPES, 36
 - [.RelDataModel, 40
- add_field, 3
- add_foreign_key, 4
- add_index, 5
- add_table, 5
- as_type, 6
- auto_layout, 6

- base::lengths(), 22
- basename, 9

- c.RelDataModel, 7
- check_foreign_keys, 7
- check_types, 8
- clean_autosaved_RelDataModels, 8
- clean_autosaved_RelDataModels(), 23
- col_types, 8
- confront_data, 9, 13, 14, 40
- confront_table_data, 10
- conv_type_ref, 11
- correct_constraints, 11

- df_to_model, 12

- format.RelTableModel, 13
- format_confrontation_report, 13
- format_confrontation_report_md, 14
- format_confrontation_report_md(), 40
- fromDBM, 15

- get_foreign_keys, 17
- get_foreign_keys.RelDataModel, 17
- get_foreign_keys.RelTableModel, 18

- identical_RelDataModel, 19
- identical_RelTableModel, 19
- identical_RelTableModel(), 19
- index_table, 20

- is.MatrixModel, 20
- is.RelDataModel, 21
- is.RelTableModel, 21
- is_MM, 22

- lengths, 22
- list_autosaved_RelDataModel, 23
- list_autosaved_RelDataModel(), 30
- list_type_ref, 11, 23, 25
- list_type_ref(), 29

- model_relational_data, 24
- modelToVn, 23

- norm_type_ref, 25

- order_fields, 25

- plot.RelDataModel, 26

- read_delim, 9
- read_json_data_model, 26
- read_named_MM, 27
- read_named_MM_header, 28
- read_named_MM_header(), 27
- read_SQL_data_model, 28
- readSQLDataModel (read_SQL_data_model), 28
- recover_RelDataModel, 29
- RelDataModel, 3–9, 15–17, 19, 21, 23–26, 29, 30, 30, 32–40
- RelTableModel, 5, 8, 10, 11, 13, 17–21, 30, 30
- remove_field, 32
- remove_foreign_key, 32
- remove_index, 33
- remove_table, 33
- rename_field, 34
- rename_table, 34

- set_primary_key, 35
- set_unique_index, 35

SUPPTYPES, [36](#)

toDBM, [36](#)

update_field, [37](#)

update_foreign_key, [38](#)

update_table_display, [39](#)

view_confrontation_report, [39](#)

write_json_data_model, [40](#)