

Package ‘SOAs’

August 6, 2022

Title Creation of Stratum Orthogonal Arrays

Version 1.2

Description Creates stratum orthogonal arrays (also known as strong orthogonal arrays). These are arrays with more levels per column than the typical orthogonal array, and whose low order projections behave like orthogonal arrays, when collapsing levels to coarser strata. Details are described in Groemping (2022) ``A unifying implementation of stratum (aka strong) orthogonal arrays" <http://www1.bht-berlin.de/FB_II/reports/Report-2022-002.pdf>.

Depends R (>= 3.6.0), DoE.base (>= 1.2)

Imports stats, combinat, FrF2, igraph, lhs (>= 1.1.3), conf.design

License GPL (>= 2)

Encoding UTF-8

URL <https://github.com/bertcarnell/SOAs>

BugReports <https://github.com/bertcarnell/SOAs/issues>

RoxygenNote 7.1.2

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

NeedsCompilation no

Author Ulrike Groemping [aut, cre],
Rob Carnell [ctb]

Maintainer Ulrike Groemping <ulrike.groemping@bht-berlin.de>

Repository CRAN

Date/Publication 2022-08-05 23:20:05 UTC

R topics documented:

SOAs-package	2
createSaturated	3
guide_SOAs	4
guide_SOAs_from_OA	6
mbound_LiuLiu	7

MDLEs	8
ocheck	10
OSOAs	12
OSOAs_hadamard	14
OSOAs_LiuLiu	16
OSOAs_regular	18
phi_optimize	20
phi_p	22
print.SOA	23
SOAs	24
SOAs2plus_regular	25
SOAs_8level	28

Index	31
--------------	-----------

SOAs-package	<i>Creation of Stratum (aka Strong) Orthogonal Arrays</i>
--------------	---

Description

Creates stratum orthogonal arrays (also known as strong orthogonal arrays).

Details

This package constructs arrays in s^{el} levels from orthogonal arrays in s levels. These are all based on equations of the type

$$D = s^{el-1}A_1 + \dots + sA_{el-1} + A_{el}, \text{ or}$$

for s^2 levels, $D = sA + B$ and

for s^3 levels, $D = s^2A + sB + C$.

The constructions differ in how they obtain the ingredient matrices, and what properties can be guaranteed for the resulting D. Where a construction function guarantees orthogonal columns for all matrices D it produces, its name starts with a OSOA, otherwise with SOA.

If optimization is requested (default TRUE), space filling properties of D are improved using a level permutation algorithm by Weng (2014). This algorithm is applied for improving the [phi_p](#) criterion, which is often a reasonable surrogate for increasing the minimum distance.

Groemping (2022) describes the constructions by He and Tang (2013, function [SOAs](#)), Liu and Liu (2015, function [OSOAs_LiuLiu](#)), He, Cheng and Tang (2018, function [SOAs2plus_regular](#)), Zhou and Tang (2019), Shi and Tang (2020, function [SOAs_8level](#)) and Li, Liu and Yang (2021) in unified notation. The constructions by Zhou and Tang (2019) and Li et al. (2021) are very close to each other and are both implemented in the three functions [OSOAs](#), [OSOAs_hadamard](#) and [OSOAs_regular](#).

Within the package, available SOA constructions for specific situations can be queried using the the guide functions [guide_SOAs](#) and [guide_SOAs_from_OA](#).

Besides the construction functions, properties of the resulting array D can be checked using the aforementioned function [phi_p](#) as well as check functions [ocheck](#), [ocheck3](#) for orthogonality and [soacheck2D](#), [soacheck3D](#) for (O)SOA stratification properties.

There is one further construction, maximin distance level expansion (XiaoXuMDLE, MDLEs), that does not yield stratum (aka strong) orthogonal arrays and is available for comparison only (Xiao and Xu 2018).

Author(s)

Author: Ulrike Groemping, BHT Berlin. Contributor: Rob Carnell.

References

- Groemping, U. (2022). A unifying implementation of stratum (aka strong) orthogonal arrays. Report 2022/02, Reports in Mathematics, Physics and Chemistry, Berliner Hochschule für Technik. http://www1.bht-berlin.de/FB_II/reports/Report-2022-002.pdf
- He, Y., Cheng, C.S. and Tang, B. (2018). Strong orthogonal arrays of strength two plus. *The Annals of Statistics* **46**, 457-468. doi: [10.1214/17AOS1555](https://doi.org/10.1214/17AOS1555)
- He, Y. and Tang, B. (2013). Strong orthogonal arrays and associated Latin hypercubes for computer experiments. *Biometrika* **100**, 254-260. doi: [10.1093/biomet/ass065](https://doi.org/10.1093/biomet/ass065)
- Li, W., Liu, M.-Q. and Yang, J.-F. (2021, in press). Construction of column-orthogonal strong orthogonal arrays. *Statistical Papers* doi: [10.1007/s0036202101249w](https://doi.org/10.1007/s0036202101249w).
- Liu, H. and Liu, M.-Q. (2015). Column-orthogonal strong orthogonal arrays and sliced strong orthogonal arrays. *Statistica Sinica* **25**, 1713-1734. doi: [10.5705/ss.2014.106](https://doi.org/10.5705/ss.2014.106)
- Shi, L. and Tang, B. (2020). Construction results for strong orthogonal arrays of strength three. *Bernoulli* **26**, 418-431. doi: [10.3150/19BEJ1130](https://doi.org/10.3150/19BEJ1130)
- Weng, J. (2014). Maximin Strong Orthogonal Arrays. *Master's thesis* at Simon Fraser University under supervision of Boxin Tang and Jiguo Cao. <https://summit.sfu.ca/item/14433>
- Xiao, Q. and Xu, H. (2018). Construction of Maximin Distance Designs via Level Permutation and Expansion. *Statistica Sinica* **28**, 1395-1414. doi: [10.5705/ss.202016.0423](https://doi.org/10.5705/ss.202016.0423)
- Zhou, Y.D. and Tang, B. (2019). Column-orthogonal strong orthogonal arrays of strength two plus and three minus. *Biometrika* **106**, 997-1004. doi: [10.1093/biomet/asz043](https://doi.org/10.1093/biomet/asz043)

See Also

Useful links:

- <https://github.com/bertcarnell/SOAs>
- Report bugs at <https://github.com/bertcarnell/SOAs/issues>

createSaturated

Function to create a regular saturated strength 2 array

Description

produces an $OA(s^k, (s^k-1)/(s-1), s, 2)$ (Rao-Hamming construction)

Usage

```
createSaturated(s, k = 2)
```

Arguments

s the prime or prime power to use
k integer; determines the run size: the resulting array will have s^k runs

Details

For many situations, the saturated fractions produced by this function are not the best choice for direct use in experimentation, because they heavily confound main effects with interactions.

If not all columns are needed, using the last m columns may yield better results than using the first m columns.

If possible, stronger OAs from other sources can be used, e.g. from package [FrF2](#) for 2-level factors or from package [DoE.base](#) for factors with more than 2 levels.

Value

createSaturated returns an s^k times $(s^k-1)/(s-1)$ matrix (saturated regular OA with s -level columns)

Examples

```
createSaturated(3, k=3) ## 27 x 13 array in 3 levels
```

guide_SOAs	<i>Utility function for inspecting available SOAs for which the user need not provide an OA</i>
------------	---

Description

Utility function for inspecting available SOAs for which the user need not provide an OA

Usage

```
guide_SOAs(s = 2, e1 = 3, m = NULL, n = NULL, ...)
```

Arguments

s required (default: 2); prime or prime power on which the SOA is based
e1 required (default: 3); the power to which s is to be taken, i.e. the SOA will have columns with s^{e1} levels
m the number of columns needed (optional)
n the maximum number of runs that are acceptable (optional); should be a multiple of s^{e1} ; must not be smaller than $m+1$, if m is specified
... currently unused

Details

The function provides the possible creation variants of an SOA that has m columns in s^e levels in up to n runs. It is permitted to specify m OR n only; in that case the function provides constructions with the smallest n or the largest m , respectively.

If both m and n are omitted, the function returns the smallest possible (O)SOA constructions for s^e levels that can be obtained without providing an OA.

Value

The function returns a data frame, each row of which contains a possibility; if no SOAs exist, the data.frame has zero rows. There is example code for constructing the SOA. Code details must be adjusted by the user (see the documentation of the respective functions). #'

Author(s)

Ulrike Groemping

References

For full detail, see [SOAs-package](#).

Groemping (2022)

He, Cheng and Tang (2018)

Li, Liu and Yang (2021)

Shi and Tang (2020)

Zhou and Tang (2019)

See Also

[guide_SOAs_from_OA](#)

Examples

```
## guide_SOAs
## There is a Zhou and Tang type SOA with 4-level columns in 8 runs
guide_SOAs(2, 2, n=8)
## There are no SOAs with 8-level columns in 8 runs
guide_SOAs(2, 3, n=8)
## What SOAs based on  $s=2$  in  $s^3$  levels with 7 columns
## can be construct without providing an OA?
guide_SOAs(2, 3, m=7)
## pick the Shi and Tang family 3 design
myST_3plus <- SOAs_8level(n=32, m=7, constr='ShiTang_alpha')
## Note that the design has orthogonal columns and strength 3+,
## i.e., very good balance properties.
```

guide_SOAs_from_OA *Utility function for inspecting SOAs obtainable from an OA*

Description

Utility function for inspecting SOAs obtainable from an OA

Usage

```
guide_SOAs_from_OA(s, nOA, mOA, tOA, e1 = tOA, ...)
```

Arguments

s	required; the unique number of levels of the columns of a given OA (need not be prime or prime power)
nOA	required; the number of runs of the OA
mOA	required; the number of columns of the OA
tOA	required; the strength of the OA; strengths larger than 5 are reduced to 5; e1 must not be larger than the (reduced) strength, except for tOA=2 with e1=3, which is supported by the LLY algorithm
e1	the power to which s is to be taken, i.e. the SOA will have columns with s^{e1} levels; default: tOA. except for tOA=2 and e1=3, e1 can be chosen smaller than tOA, but not larger. If e1 is smaller than tOA, tOA is internally reduced before working out the possibilities.
...	currently unused

Details

The function provides the possible creation variants of an SOA from a strength tOA OA with mOA s-level columns in nOA runs, for an SOA that has columns in s^{e1} levels. Note that the SOA may have nOA runs or $s \cdot nOA$ runs, depending on the construction.

Value

The function returns a data frame, each row of which contains a possibility. There is example code for constructing the SOA. The code assumes that a given OA has the name OA; this can of course be modified by the user. Further code details can also be adjusted by the user (see the documentation of the respective functions).

Author(s)

Ulrike Groemping

References

For full detail, see [SOAs-package](#).

Groemping (2022)
He and Tang (2013)
He, Cheng and Tang (2018)
Liu and Liu (2015)
Li, Liu and Yang (2021)
Shi and Tang (2020)
Zhou and Tang (2019)

See Also

[guide_SOAs](#)

Examples

```
## guide_SOAs_from_OA
## there is an OA(81, 3^10, 3) (L81.3.10 in package DoE.base)
## inspect what can be done with it:
guide_SOAs_from_OA(s=3, mOA=10, nOA=81, tOA=3)
## the output shows that a strength 3 OSOA
## with 4 columns of 27 levels each can be obtained in 81 runs
## and provides the necessary code (replace OA with L81.3.10)
## optimize=FALSE reduces example run time
OSOAs_LiuLiu(L81.3.10, t=3, optimize=FALSE)
## or that an SOA with 9 non-orthogonal columns can be obtained
## in the same number of runs
SOAs(L81.3.10, t=3)
```

mbound_LiuLiu

bound for number of columns for LiuLiu OSOAs

Description

bound for number of columns for LiuLiu OSOAs

Usage

```
mbound_LiuLiu(moa, t)
```

Arguments

moa	number of oa columns
t	strength used in the construction in function OSOAs_LiuLiu (it is assumed that the oa used has at least that strength)

Value

the maximum number of columns that can be obtained by the command `OSOAs_LiuLiu(oa, t=t)` where `oa` has at least strength `t` and consists of `moa` columns

Author(s)

Ulrike Groemping

References

#' For full detail, see [SOAs-package](#).

Liu and Liu 2015

Examples

```
## moa is the number of columns of an oa
moa <- rep(seq(4,40),3)
## t is the strength used in the construction
## the oa must have at least this strength
t <- rep(2:4, each=37)
## numbers of columns for the combination
mbounds <- mapply(mbound_LiuLiu, moa, t)
## depending on the number of levels
## the number of runs can be excessive
## for larger values of moa with larger t!
## t=3 and t=4 have the same number of columns, except for moa=4*j+3
plot(moa, mbounds, pch=t, col=t)
```

MDLEs

Function to create maximin distance level expanded arrays

Description

Maximin distance level expansion similar to Xiao and Xu is implemented, using an optimization algorithm that is less demanding than the TA algorithm of Xiao and Xu

Usage

```
MDLEs(
  oa,
  ell,
  noptim.rounds = 1,
  optimize = TRUE,
  noptim.oa = 1,
  dmethod = "manhattan",
  p = 50
)
```


Arguments

<code>oa</code>	matrix or data.frame that contains an ingoing symmetric OA. Levels must be denoted as 0 to s-1 or as 1 to s.
<code>e11</code>	the multiplier for each number of levels
<code>noptim.rounds</code>	the number of optimization rounds; optimization may take very long, therefore the default is 1, although more rounds are beneficial.
<code>optimize</code>	logical: if FALSE, suppress optimization of expansion levels
<code>noptim.oa</code>	integer: number of optimization rounds applied to initial oa itself before starting expansion
<code>dmethod</code>	distance method for <code>phi_p</code> , "manhattan" (default) or "euclidean"
<code>p</code>	p for <code>phi_p</code> (the larger, the closer to maximin distance)

Details

The ingoing oa is possibly optimized for space-filling, using function `phi_optimize` with `noptim.oa` optimization rounds. The expansions themselves are again optimized for improving `phi_p`, using an algorithm which is a variant of Weng (2014), instead of the more powerful but also much more demanding algorithm proposed by Xiao and Xu.

Value

A matrix of class MDLE with attributes

phi_p the phi_p value that was achieved

type MDLE

optimized logical: same as the input parameter

call the call that produced the matrix

permpick matrix of lists of length s with elements from 0 to e11-1; matrix element (i,j) contains the sequence of replacements used in function `DcFromDp` for constructing the level expansion of the ith level in the jth column

Author(s)

Ulrike Groemping

References

For full detail, see [SOAs-package](#).

Weng (2014)

Xiao and Xu (2018)

Examples

```
dim(aus <- MDLEs(DoE.base::L16.4.5, 2, noptim.rounds = 1))
permpicks <- attr(aus, "permpick")
## for people interested in internal workings:
## the code below produces the same matrix as MDLEs
SOAs:::DcFromDp(L16.4.5-1, 4,2, lapply(1:5, function(obj) permpicks[,obj]))
```

ocheck

*functions to evaluate low order projection properties of (O)SOAs***Description**

socheck2D and socheck3D evaluate 2D and 3D projections, ocheck and ocheck3 evaluate pairwise or 3-orthogonality of columns, and count_npairs evaluates the number of level pairs in 2D projections

Usage

```
ocheck(D, verbose = FALSE)
```

```
ocheck3(D, verbose = FALSE)
```

```
count_npairs(D, minn = 1)
```

```
count_nallpairs(ns)
```

```
socheck2D(D, s = 3, e1 = 3, t = 3, verbose = FALSE)
```

```
socheck3D(D, s = 3, e1 = 3, t = 3, verbose = FALSE)
```

Arguments

D	a matrix with factor levels or an object of class SOA; factor levels can start with 0 or with 1, and need to be consecutively numbered
verbose	logical; if TRUE, additional information is printed (confounded pair or triple projections with A2 or A3, respectively, or table of correlations)
minn	small integer number; the function counts pairs that are covered at least minn times
ns	vector of numbers of levels for each column
s	the prime or prime power according to which the array is checked
e1	the exponent so that the number of levels of the array is s^{e1} (if s is not NULL)
t	the strength for which to look (2, 3, or 4), equal to the sum of the exponents in the stratification dimensions; for example, socheck2D considers sxs 2D projections with t=2, s^2xs and sxs^2 projections with t=3, and s^3xs , s^2xs^2 and sxs^3 projections with t=4. If t=4 and e1=2, property gamma ($s^3 \times s$ and $s \times s^3$) is obviously impossible and will not be part of the checks.

Details

Functions `socheck2D` and `socheck3D` inspect 2D and 3D stratification, respectively. Each column must have s^{el} levels. `t` specifies the degree of balance the functions are asked to look for.

Function `socheck2D`,

- with `el=t=2`, looks for strength 2 conditions (s^2 levels, sxs balance),
- with `el=2, t=3`, looks for strength 2+ / 3- conditions (s^2 levels, s^2xs balance),
- with `el=t=3`, looks for strength $2^* / 3$ conditions (s^3 levels, s^2xs balance).
- with `el=2, t=4`, looks for the enhanced strength 2+ / 3- property alpha (s^2 levels, s^2xs^2 balance).
- and with `el=3, t=4`, looks for strength 3+ / 4 conditions (s^3 levels, s^3xs and s^2xs^2 balance).

Function `socheck3D`,

- with `el=2, t=3`, looks for strength 3- conditions (s^2 levels, $sxsxs$ balance),
- with `el=t=3`, looks for strength 3 conditions (s^3 levels, $sxsxs$ balance),
- and with `el=3, t=4`, looks for strength 3+ / 4 conditions (s^3 levels, s^2xsxs balance).

If `verbose=TRUE`, the functions print the pairs or triples that violate the projection requirements for 2D or 3D.

Value

Functions whose names contain "check" return a logical.

Functions `count_npairs` and `count_npairs` return a vector of counts for level combinations in factor pairs (in the order of the columns of `DoE.base::nchoosek(ncol(D), 2)`), either for the array in `D`, or for designs with numbers of levels given in `ns`.

Author(s)

Ulrike Groemping

References

For full detail, see [SOAs-package](#).

Groemping (2022)

He and Tang (2013)

Shi and Tang (2020)

Examples

```
nullcase <- matrix(0:7, nrow=8, ncol=4)
socheck2D(nullcase, s=2)
socheck3D(nullcase, s=2)
```

```
## Shi and Tang strength 3+ construction in 7 8-level factors for 32 runs
D <- SOAs_8level(32, optimize=FALSE)
```

```

## check for strength 3+ (default e1=3 is OK)
## 2D check
soacheck2D(D, s=2, t=4)
## 3D check
soacheck3D(D, s=2, t=4)
## not an OSOA
ocheck(D)

## an OSOA of strength 3 with 3-orthogonality
## 4 columns in 27 levels each
## second order model matrix

D_o <- OSOAs_LiuLiu(DoE.base::L81.3.10, optimize=FALSE)
ocheck3(D_o)

## benefit of 3-orthogonality for second order linear models
colnames(D_o) <- paste0("X", 1:4)
y <- stats::rnorm(81)
mylm <- stats::lm(y~(X1+X2+X3+X4)^2 + I(X1^2)+I(X2^2)+I(X3^2)+I(X4^2),
                  data=as.data.frame(scale(D_o, scale=FALSE)))
crossprod(stats::model.matrix(mylm))

```

OSOAs

Function to create an OSOA from an OA

Description

An OSOA in ns runs of strength 2^* (s^3 levels) or $2+$ (s^2 levels) is created from an OA($n,m,s,2$).

Usage

```

OSOAs(
  oa,
  e1 = 3,
  m = NULL,
  noptim.rounds = 1,
  noptim.repeats = 1,
  optimize = TRUE,
  dmethod = "manhattan",
  p = 50
)

```

Arguments

oa matrix or data.frame that contains an ingoing symmetric OA. Levels must be denoted as 0 to $s-1$ or as 1 to s .

e1 the exponent of the number of levels, $e1=3$ yields a strength 2^* OSOA in s^3 levels, $e1=2$ a strength $2+$ OSOA in s^2 levels

<code>m</code>	the desired number of columns of the resulting array; odd values of <code>m</code> will be reduced by one, so specify the next largest even <code>m</code> , if you need an odd number of columns (the function will do so, if possible; if <code>m=NULL</code> , the maximum possible value is used).
<code>noptim.rounds</code>	the number of optimization rounds for each independent restart
<code>noptim.repeats</code>	the number of independent restarts of optimizations with <code>noptim.rounds</code> rounds each
<code>optimize</code>	logical: should space filling be optimized by level permutations?
<code>dmethod</code>	distance method for <code>phi_p</code> , "manhattan" (default) or "euclidean"
<code>p</code>	<code>p</code> for <code>phi_p</code> (the larger, the closer to maximum distance)

Details

The function implements the algorithms proposed by Zhou and Tang 2018 (s^2 levels) or Li, Liu and Yang 2021 (s^3 levels). Both are enhanced with the modification for matrix `A` by Groemping 2022. Level permutations are optimized using an adaptation of the algorithm by Weng (2014).

Suitable OAs for argument `oa` can e.g. be constructed with OA creation functions from package **lhs** or can be obtained from arrays listed in R package **DoE.base**

Value

matrix of class `SOA` with the attributes that are listed below. All attributes can be accessed using function `attributes`, or individual attributes can be accessed using function `attr`. These are the attributes:

type the type of array (`SOA` or `OSOA`)

strength character string that gives the strength

phi_p the `phi_p` value (smaller=better)

optimized logical indicating whether optimization was applied

permpick matrix that lists the id numbers of the permutations used

perms2pickfrom optional element, when optimization was conducted: the overall permutation list to which the numbers in `permlist` refer

call the call that created the object

Author(s)

Ulrike Groemping

References

For full detail, see [SOAs-package](#).

Groemping (2022)

Li, Liu and Yang (2021)

Weng (2014)

Zhou and Tang (2019)

Examples

```

## run with optimization for actual use!

## 54 runs with seven 9-level columns
OSOAs(DoE.base::L18[,3:8], el=2, optimize=FALSE)

## 54 runs with six 27-level columns
OSOAs(DoE.base::L18[,3:8], el=3, optimize=FALSE)

## 81 runs with four 9-level columns
OSOAs(DoE.base::L27.3.4, el=2, optimize=FALSE)
## An OA with 9-level factors (L81.9.10)
## has complete balance in 2D,
## however does not achieve 3D projection for
## all four collapsed triples
## It is up to the user to decide what is more important.
## I would go for the OA.

## 81 runs with four 27-level columns
OSOAs(DoE.base::L27.3.4, el=3, optimize=FALSE)

```

OSOAs_hadamard	<i>function to create a strength 3 OSOA with 8-level columns or a strength 3- OSOA with 4-level columns from a Hadamard matrix</i>
----------------	--

Description

A Hadamard matrix in k runs is used for creating an OSOA in $n=2k$ runs for at most $m=k-2$ columns (8-level) or $m=k-1$ columns (4-level).

Usage

```

OSOAs_hadamard(
  m = NULL,
  n = NULL,
  el = 3,
  noptim.rounds = 1,
  noptim.repeats = 1,
  optimize = TRUE,
  dmethod = "manhattan",
  p = 50
)

```

Arguments

m the number of columns to be created; if n is also given, m must be compatible with it; at present, m can be at most 98.

n	the number of runs to be created; n must be a multiple of 8 and can (at present) be at most 200; if m is also given, n must be compatible with it.
e1	exponent for 2, can be 2 or 3: the OSOA will have columns with 2^{e1} (4 or 8) levels
noptim.rounds	the number of optimization rounds for each independent restart
noptim.repeats	the number of independent restarts of optimizations with noptim.rounds rounds each
optimize	logical: should space filling be optimized by level permutations?
dmethod	distance method for <code>phi_p</code> , "manhattan" (default) or "euclidean"
p	p for <code>phi_p</code> (the larger, the closer to maximin distance)

Details

At least one of m or n must be provided. For e1=2, Zhou and Tang (2019) strength 3- designs are created, for e1=3 strength 3 designs by Li, Liu and Yang (2021).

Li et al.'s creation of the matrix A has been enhanced by using a column specific fold-over, which is beneficial for the space-filling properties (see Groemping 2022).

Value

matrix of class SOA with the attributes that are listed below. All attributes can be accessed using function `attributes`, or individual attributes can be accessed using function `attr`. These are the attributes:

type the type of array (SOA or OSOA)

strength character string that gives the strength

phi_p the `phi_p` value (smaller=better)

optimized logical indicating whether optimization was applied

permpick matrix that lists the id numbers of the permutations used

perms2pickfrom optional element, when optimization was conducted: the overall permutation list to which the numbers in `permlist` refer

call the call that created the object

Author(s)

Ulrike Groemping

References

For full detail, see [SOAs-package](#).

Groemping (2022)

Li, Liu and Yang (2021)

Weng (2014)

Zhou and Tang (2019)

Examples

```

dim(OSOAs_hadamard(9, optimize=FALSE)) ## 9 8-level factors in 24 runs
dim(OSOAs_hadamard(n=16, optimize=FALSE)) ## 6 8-level factors in 16 runs
OSOAs_hadamard(n=24, m=6, optimize=FALSE) ## 6 8-level factors in 24 runs
                                         ## (though 10 would be possible)
dim(OSOAs_hadamard(m=35, optimize=FALSE)) ## 35 8-level factors in 80 runs

```

OSOAs_LiuLiu

*Function to create OSOAs of strengths 2, 3, or 4 from an OA***Description**

Creates OSOAs from an OA according to the construction by Liu and Liu (2015). Strengths 2 to 4 are covered. Strengths 3 and 4 guarantee 3-orthogonality.

Usage

```

OSOAs_LiuLiu(
  oa,
  t = NULL,
  m = NULL,
  noptim.rounds = 1,
  noptim.repeats = 1,
  optimize = TRUE,
  dmethod = "manhattan",
  p = 50
)

```

Arguments

oa	matrix or data.frame; a symmetric orthogonal array of strength at least t
t	the requested strength of the OSOA
m	the requested number of columns of the OSOA (at most <code>mbound_LiuLiu(ncol(oa), t)</code>).
noptim.rounds	the number of optimization rounds for each independent restart
noptim.repeats	the number of independent restarts of optimizations with <code>noptim.rounds</code> rounds each
optimize	logical: should space filling be optimized by level permutations?
dmethod	distance method for <code>phi_p</code> , "manhattan" (default) or "euclidean"
p	p for <code>phi_p</code> (the larger, the closer to maximin distance)

Details

The number of columns goes down dramatically with the requested strength. However, the strength 3 or 4 arrays may be worthwhile, because they guarantee 3-orthogonality, which implies that (quantitative) linear models with main effects and second order effects can be robustly estimated.

Optimization is less successful for this construction of OSOAs; for small arrays, the level permutations make (almost) no difference.

Function `mbound_LiuLiu(moa, t)` calculates the number of columns that can be obtained from a strength `t` OA with `moa` columns (if such an array exists, the function does not check that).

Ingoing arrays can be obtained from oa-generating functions of R package **lhs** like `createBoseBush`, or from OAs in R package **DoE.base**, or from 2-level designs created with R package **FrF2** (see example section).

Value

matrix of class SOA with the attributes that are listed below. All attributes can be accessed using function `attributes`, or individual attributes can be accessed using function `attr`. These are the attributes:

type the type of array (SOA or OSOA)

strength character string that gives the strength

phi_p the `phi_p` value (smaller=better)

optimized logical indicating whether optimization was applied

permpick matrix that lists the id numbers of the permutations used

perms2pickfrom optional element, when optimization was conducted: the overall permutation list to which the numbers in `permlist` refer

call the call that created the object

Author(s)

Ulrike Groemping

References

For full detail, see [SOAs-package](#).

Liu and Liu (2015)

Weng (2014)

Examples

```
## strength 2, very small (four 9-level columns in 9 runs)
OSOA9 <- OSOAs_LiuLiu(DoE.base::L9.3.4)

## strength 3, from a Plackett-Burman design of FrF2
## 10 8-level columns in 40 runs with OSOA strength 3
oa <- suppressWarnings(FrF2::pb(40)[,c(1:19,39)])
### columns 1 to 19 and 39 together are the largest possible strength 3 set
OSOA40 <- OSOAs_LiuLiu(oa, optimize=FALSE) ## strength 3, 8 levels
```

```

### optimize would improve phi_p, but suppressed for saving run time

## 9 8-level columns in 40 runs with OSOA strength 3
oa <- FrF2::pb(40,19)
### 9 columns would be obtained without the final column in oa
mbound_LiuLiu(19, t=3)    ## example for which q=3
mbound_LiuLiu(19, t=4)    ## t=3 has one more column than t=4
OSO40_2 <- OSOAs_LiuLiu(oa, optimize=FALSE) ## strength 3, 8 levels
### optimize would improve phi_p, but suppressed for saving run time

## starting from a strength 4 OA
oa <- FrF2::FrF2(64,8)
## four 16 level columns in 64 runs with OSOA strength 4
OSO64 <- OSOAs_LiuLiu(oa, optimize=FALSE) ## strength 4, 16 levels

### reducing the strength to 3 does not increase the number of columns
mbound_LiuLiu(8, t=3)
### reducing the strength to 2 doubles the number of columns
mbound_LiuLiu(8, t=2)
## eight 4-level columns in 64 runs with OSOA strength 2
OSO64_2 <- OSOAs_LiuLiu(oa, t=2, optimize=FALSE)
## fulfills the 2D strength 2 property
soacheck2D(OSO64_2, s=2, el=2, t=2)
### fulfills also the 3D strength 3 property
soacheck3D(OSO64_2, s=2, el=2, t=3)
### fulfills also the 4D strength 4 property
DoE.base::GWLP(OSO64/2)
### but not the 3D strength 4 property
soacheck3D(OSO64_2, s=2, el=2, t=4)
### and not the 2D 4x2 and 2x4 stratification balance
soacheck2D(OSO64_2, s=2, el=2, t=3)
## six 36-level columns in 72 runs with OSOA strength 2
oa <- DoE.base::L72.2.5.3.3.4.1.6.7[,10:16]
OSO72 <- OSOAs_LiuLiu(oa, t=2, optimize=FALSE)

```

OSOAs_regular

Function to create an OSOA in s^2 or s^3 levels and s^k runs from a basic number of levels s and a power k

Description

The OSOA in s^k runs accommodates at most $m=(s^k-1)/(s-1)$ columns in s^2 levels or $m'=2*\text{floor}(m/2)$ columns in s^3 levels.

Usage

```

OSOAs_regular(
  s,
  k,
  el = 3,

```

```

    m = NULL,
    noptim.rounds = 1,
    noptim.repeats = 1,
    optimize = TRUE,
    dmethod = "manhattan",
    p = 50
  )

```

Arguments

s	the prime or prime power to use (do not use for $s=2$, because other method is better); the resulting array will have pairwise orthogonal columns in s^t levels
k	integer ≥ 3 ; determines the run size: the resulting array will have s^k runs
e1	2 or 3; the exponent of the number of levels, $e1=3$ yields a strength 2^* or 3 OSOA in s^3 levels, $e1=2$ a strength 2+ or 3- OSOA in s^2 levels
m	the desired number of columns of the resulting array; for $e1=3$, odd values of m will be reduced by one, so specify the next largest even m , if you need an odd number of columns (the function will do so, if possible); if $m=NULL$, the maximum possible value is used. This is at most $(s^{(k-1)}-1)/(s-1)$, or one less if this is odd and $e1=3$.
noptim.rounds	the number of optimization rounds for each independent restart
noptim.repeats	the number of independent restarts of optimizations with <code>noptim.rounds</code> rounds each
optimize	logical: should space filling be optimized by level permutations?
dmethod	distance method for <code>phi_p</code> , "manhattan" (default) or "euclidean"
p	p for <code>phi_p</code> (the larger, the closer to maximin distance)

Details

The function implements the algorithms proposed by Zhou and Tang 2018 (s^2 levels) or Li, Liu and Yang 2021 (s^3 levels), enhanced with the modification for matrix A by Groemping (2022). Level permutations are optimized using an adaptation of the algorithm by Weng (2014).

If m is specified, the function uses the last m columns of a saturated OA produced by function `createSaturated`(s , $k-1$).

If m is small enough that a resolution IV / strength 3 OA for s levels in $s^{(k-1)}$ runs exists, function `OSOAs` should be used with such an OA (which can be obtained from package **FrF2** for $s=2$ or from package **DoE.base** for $s>2$). For $s=2$, function `OSOAs_hadamard` may also be a better choice than `OSOAs_regular` for up to 192 runs.

Value

matrix of class SOA with the attributes that are listed below. All attributes can be accessed using function `attributes`, or individual attributes can be accessed using function `attr`. These are the attributes:

type the type of array (SOA or OSOA)

strength character string that gives the strength

phi_p the phi_p value (smaller=better)

optimized logical indicating whether optimization was applied

permpick matrix that lists the id numbers of the permutations used

perms2pickfrom optional element, when optimization was conducted: the overall permutation list to which the numbers in permlist refer

call the call that created the object

Author(s)

Ulrike Groemping

References

For full detail, see [SOAs-package](#). Groemping (2022)
 Li, Liu and Yang (2021)
 Weng (2014)
 Zhou and Tang (2019)

Examples

```
## 13 columns in 9 levels each
OSOAs_regular(3, 4, el=2, optimize=FALSE) ## 13 columns, phi_p about 0.117
# optimizing level permutations typically improves phi_p a lot
# OSOAs_regular(3, 4, el=2) ## 13 columns, phi_p typically below 0.055
```

phi_optimize	<i>function to optimize the phi_p value of an array by level permutation</i>
--------------	--

Description

takes an n x m array and returns an n x m array with improved phi_p value (if possible)

Usage

```
phi_optimize(
  D,
  noptim.rounds = 1,
  noptim.repeats = 1,
  dmethod = "manhattan",
  p = 50
)
```

Arguments

D	numeric matrix or data.frame with numeric columns, n x m. A symmetric array (e.g. an OA) with n1 levels for each columns. Levels must be coded as 0 to n1 - 1 or as 1 to n1. levels from
noptim.rounds	number of rounds in the Weng algorithm
noptim.repeats	number of independent repeats of the Weng algorithm
dmethod	distance method for phi_p, "manhattan" (default) or "euclidean"
p	p for phi_p (the larger, the closer to maximin distance)

Details

The function uses the algorithm proposed by Weng (2014) for SOA optimization:

It starts with a random permutation of column levels.

Initially, individual columns are randomly permuted (m permuted matrices, called one-neighbours), and the best permutation w.r.t. the phi_p value (manhattan distance) is made the current optimum. This continues, until the current optimum is not improved by a set of randomly drawn one-neighbours.

Subsequently, pairs of columns are randomly permuted (choose(m, 2) permuted matrices, called two-neighbours). If the current optimum can be improved or the number of optimization rounds has not yet been exhausted, a new round with one-neighbours is started with the current optimum. Otherwise, the current optimum is returned, or an independent repeat is initiated (if requested).

Limited experience suggests that an increase of noptim.rounds from the default 1 is often helpful, whereas an increase of noptim.repeats did not yield as much improvement.

Value

an n x m matrix

Author(s)

Ulrike Groemping

References

For full detail, see [SOAs-package](#).

Weng (2014)

Examples

```
oa <- lhs::createBoseBush(8,16)
print(phi_p(oa, dmethod="manhattan"))
oa_optimized <- phi_optimize(oa)
print(phi_p(oa_optimized, dmethod="manhattan"))
```

phi_p

Functions to evaluate space filling of an array

Description

phi_p calculates the discrepancy

phi_p calculates the discrepancy

Usage

```
phi_p(D, dmethod = "manhattan", p = 50)
```

```
mindist(D, dmethod = "manhattan")
```

```
phi_p(D, dmethod = "manhattan", p = 50)
```

Arguments

D	an array or an object of class SOA or MDLE
dmethod	the distance to use, "manhattan" (default) or "euclidean"
p	the value for p to use in the formula for phi_p

Details

Small values of phi_p tend to be associated with good performance on the maximin distance criterion, i.e. with a larger minimum distance.

small values of phi_p are associated with good performance on the maximin distance criterion

Value

both functions return a number

a number

Author(s)

Ulrike Groemping

Ulrike Groemping

Examples

```
A <- DoE.base::L25.5.6 ## levels 1:5 for each factor
phi_p(A)
mindist(A) # 5
A2 <- phi_optimize(A)
phi_p(A2) ## improved
mindist(A2) ## 6, improved
```

```

A <- DoE.base::L16.4.5 ## levels 1:4 for each factor
phi_p(A)
phi_p(A, dmethod="euclidean")
A2 <- A
A2[,4] <- c(2,4,3,1)[A[,4]]
phi_p(A2)
## Not run:
  ## A2 has fewer minimal distances
  par(mfrow=c(2,1))
  hist(dist(A), xlim=c(2,6), ylim=c(0,40))
  hist(dist(A2), xlim=c(2,6), ylim=c(0,40))

## End(Not run)

```

print.SOA

Print Methods

Description

Print Methods

Usage

```

## S3 method for class 'SOA'
print(x, ...)

## S3 method for class 'MDLE'
print(x, ...)

```

Arguments

x object to be printed (SOA, OSOA, MDLE)
... further arguments for function print

Value

no value is returned

Examples

```

myOSOA <- OSOAs_regular(s=3, k=3, optimize=FALSE)
print(myOSOA)
str(myOSOA) ## structure for comparison

```

SOAs	<i>function to create SOAs of strength t with the GOA construction by He and Tang.</i>
------	---

Description

takes an OA(n,m,s,t) and creates an SOA(n,m',s^t,t') with $t' \leq t$.

Usage

```
SOAs(
  oa,
  t = 3,
  m = NULL,
  noptim.rounds = 1,
  noptim.repeats = 1,
  optimize = TRUE,
  dmethod = "manhattan",
  p = 50
)
```

Arguments

oa	matrix or data.frame that contains an ingoing symmetric OA. Levels must be denoted as 0 to s-1 or as 1 to s.
t	the strength the SOA should have, can be 2, 3, 4, or 5. Must not be larger than the strength of oa, but can be smaller. The resulting SOA will have s^t levels
m	the requested number of columns (see details for permitted numbers of columns)
noptim.rounds	the number of optimization rounds for each independent restart
noptim.repeats	the number of independent restarts of optimizations with noptim.rounds rounds each
optimize	logical, default TRUE; if FALSE, suppresses optimization
dmethod	method for the calculation of phi_p , "manhattan" (default) or "euclidean"
p	p for phi_p (the larger, the closer to maximin distance)

Details

The resulting SOA will have at most m' columns in s^t levels and will be of strength t . $m'(m, t)$ is a function of the number of columns of oa (denoted as m) and the strength t : $m'(m,2)=m$, $m'(m,3)=m-1$, $m'(m,4)=\text{floor}(m/2)$, $m'(m,5)=\text{floor}((m-1)/2)$.

Suitable OAs for argument oa can e.g. be constructed with OA creation functions from package **lhs** or can be obtained from arrays listed in R package **DoE.base**.

Value

matrix of class SOA with the attributes that are listed below. All attributes can be accessed using function `attributes`, or individual attributes can be accessed using function `attr`. These are the attributes:

type the type of array (SOA or OSOA)

strength character string that gives the strength

phi_p the phi_p value (smaller=better)

optimized logical indicating whether optimization was applied

permpick matrix that lists the id numbers of the permutations used

perms2pickfrom optional element, when optimization was conducted: the overall permutation list to which the numbers in permlist refer

call the call that created the object

Author(s)

Ulrike Groemping

References

For full detail, see [SOAs-package](#).

He and Tang (2013)

Weng (2014)

Examples

```
aus <- SOAs(DoE.base::L27.3.4, optimize=FALSE) ## t=3 is the default
dim(aus)
soacheck2D(aus, s=3, el=3) ## check for 2*
soacheck3D(aus, s=3, el=3) ## check for 3

aus2 <- SOAs(DoE.base::L27.3.4, t=2, optimize=FALSE)
## t can be smaller than the array strength
## --> more columns with fewer levels each
dim(aus2)
soacheck2D(aus2, s=3, el=2, t=2) # check for 2
soacheck3D(aus2, s=3, el=2)      # t=3 is the default (check for 3-)
```

SOAs2plus_regular *function to create SOAs of strength 2+ from regular s-level designs*

Description

creates an array in s^k runs with columns in s^2 levels for prime or prime power s

Usage

```
SOAs2plus_regular(
  s,
  k,
  m = NULL,
  orth = TRUE,
  old = FALSE,
  noptim.rounds = 1,
  noptim.repeats = 1,
  optimize = TRUE,
  dmethod = "manhattan",
  p = 50
)
```

Arguments

s	prime or prime power
k	array will have $n=s^k$ runs; for $s=2$, $k \geq 4$ is needed, for $s > 2$, $k \geq 3$ is sufficient
m	optional integer: number of columns requested; if NULL, the maximum possible number of columns is created, which is $(s^k-1)/(s-1) - ((s-1)^k-1)/(s-2)$ for $s > 2$ and $s^k - s^{k_1} - s^{(k-k_1)} + 2$, with $k_1 = \text{floor}(k/2)$, for $s=2$; specifying a smaller m is beneficial not only for run time but also for possibly achieving a column-orthogonal array (see Details section)
orth	logical: if FALSE, suppresses attempts for orthogonal columns and selects the first permissible column for each column of B (see Details section)
old	logical, relevant for $\text{orth}=\text{TRUE}$ only: if TRUE, limits possible columns for B to the columns not eligible for A (instead of the columns not used in A); should only be used for reproducing designs created by version 1.1 or earlier
noptim.rounds	the number of optimization rounds for each independent restart
noptim.repeats	the number of independent restarts of optimizations with noptim.rounds rounds each
optimize	logical: should optimization be applied? default TRUE
dmethod	method for the distance in <code>phi_p</code> , "manhattan" (default) or "euclidean"
p	p for <code>phi_p</code> (the larger, the closer to maximin distance)

Details

The construction is by He, Cheng and Tang (2018), Prop.1 (C2) / Theorem 2 for $s=2$ and Theorem 4 for $s > 2$.

B is chosen as an OA of strength 2, if possible, which yields orthogonal columns according to Zhou and Tang (2019). This is implemented using a matching algorithm for bipartite graphs from package **igraph**; the smaller m, the more likely that orthogonality can be achieved. However, strength 2+ SOAs are not usually advisable for m small enough that a strength 3 OA exists.

Optimization according to Weng has been added (separate level permutations in columns of A and B, noptim.rounds times). Limited tests suggest that a single round (noptim.rounds=1) often does a very good job (e.g. for $s=2$ and $k=4$), and further rounds do not yield too much improvement; there

are also cases (e.g. $s=5$ with $k=3$), for which the unoptimized array has a better ϕ_p than what can be achieved by most optimization attempts from a random start.

The search for orthogonal columns can take a long time for larger arrays, even without optimization. If this is prohibitive (or not considered valuable), `orth=FALSE` causes the function to create the matrix B for equation $D=2A+B$ with less computational effort.

The subsequent optimization, if not switched off, is of the same complexity, regardless of the value for `orth`. Its duration heavily depends on the number of optimization steps that are needed before the algorithm stops. This has not been systematically investigated; cases for which the total run time with optimization is shorter for `orth=TRUE` than for `orth=FALSE` have been observed.

With package version 1.2, the creation of SOAs has changed: Up to version 1.1, the columns of B were chosen only from those columns that were *not eligible* for A , whereas the new version chooses them from those columns that are *not used* for A . This increases the chance to achieve geometrically orthogonal columns.

Users who want to reproduce a design from an earlier version can use argument `old`.

Value

matrix of class SOA with the attributes that are listed below. All attributes can be accessed using function `attributes`, or individual attributes can be accessed using function `attr`. These are the attributes:

type the type of array (SOA or OSOA)

strength character string that gives the strength

ϕ_p the ϕ_p value (smaller=better)

optimized logical indicating whether optimization was applied

permpick matrix that lists the id numbers of the permutations used

perms2pickfrom optional element, when optimization was conducted: the overall permutation list to which the numbers in `permlist` refer

call the call that created the object

Note

Strength 2+ SOAs can accommodate a large number of factors with reasonable stratified balance behavior. Note that their use is not usually advisable for m small enough that a strength 3 OA with s^2 level factors exists.

Author(s)

Ulrike Groemping

References

For full detail, see [SOAs-package](#).

He, Cheng and Tang (2018)

Weng (2014)

Zhou and Tang (2019)

Examples

```
## unoptimized OSOA with 8 16-level columns in 64 runs
## (maximum possible number of columns)
plan64 <- SOAs2plus_regular(4, 3, optimize=FALSE)
ocheck(plan64) ## the array has orthogonal columns

## optimized SOA with 20 9-level columns in 81 runs
## (up to 25 columns are possible)
plan <- SOAs2plus_regular(3, 4, 20)
## many column pairs have only 27 level pairs covered
count_npairs(plan)
## an OA would exist for 10 9-level factors (DoE.base::L81.9.10)
## it would cover all pairs
## (SOAs are not for situations for which pair coverage
## is of primary interest)
```

SOAs_8level

Function to create 8-level SOAs according to Shi and Tang 2020

Description

creates strength 3 or 3+ SOAs with 8-level factors in 2^k runs, k at least 4. These SOAs have at least some more balance than guaranteed by strength 3.

Usage

```
SOAs_8level(
  n,
  m = NULL,
  constr = "ShiTang_alphabeta",
  noptim.rounds = 1,
  noptim.repeats = 1,
  optimize = TRUE,
  dmethod = "manhattan",
  p = 50
)
```

Arguments

<code>n</code>	run size of the SOA; power of 2, at least 16
<code>m</code>	number of colums; at most $5n/16$ for <code>constr="ShiTang_alpha"</code> (exception: only 9 for $n=32$), at most $n/4$ for <code>constr="ShiTang_alphabeta"</code> ; for <code>m=NULL</code> , defaults are $m=5n/16$ and $m=n/4-1$, respectively; the latter yields strength 3+.
<code>constr</code>	construction method. Must be one of "ShiTang_alphabeta", "ShiTang_alpha". See Details section

<code>noptim.rounds</code>	the number of optimization rounds for each independent restart
<code>noptim.repeats</code>	the number of independent restarts of optimizations with <code>noptim.rounds</code> rounds each
<code>optimize</code>	logical: should space filling be optimized by level permutations?
<code>dmethod</code>	distance method for <code>phi_p</code> , "manhattan" (default) or "euclidean"
<code>p</code>	p for <code>phi_p</code> (the larger, the closer to maximin distance)

Details

The construction is implemented as described in Groemping (2022).

The 8-level SOAs created by this construction have strength 3 and at least the additional property alpha, which means that all pairs of columns achieve perfect 4x4 balance, if consecutive level pairs (01, 23, 45, 67) are collapsed.

The "ShiTang_alpha" construction additionally yields perfect 4x2x2 balance, if one column is collapsed to 4 levels, while two further columns are collapsed to 2 levels (0123 vs 4567). with $m = n/4$ columns, the "ShiTang_alpha" construction has a single pair of correlated columns, all other columns are uncorrelated, due to a modification of Shi and Tang's column allocation that was proposed in Groemping (2022).

For $m \leq n/4 - 1$, the "ShiTang_alpha" construction also yields perfect balance for 8x2 projections in 2D (i.e. if one original column with another column collapsed to two levels). Thus, it yields all strength 4 properties in 2D and 3D, which is called strength 3+. Furthermore, Groemping (2022) proposed an improved choice of columns for matrix C that implies orthogonal columns in this case.

Value

matrix of class SOA with the attributes that are listed below. All attributes can be accessed using function `attributes`, or individual attributes can be accessed using function `attr`. These are the attributes:

type the type of array (SOA or OSOA)

strength character string that gives the strength

phi_p the `phi_p` value (smaller=better)

optimized logical indicating whether optimization was applied

permpick matrix that lists the id numbers of the permutations used

perms2pickfrom optional element, when optimization was conducted: the overall permutation list to which the numbers in `permlist` refer

call the call that created the object

Author(s)

Ulrike Groemping

References

For full detail, see [SOAs-package](#).

Groemping (2022)
Shi and Tang (2020)
Weng (2014)

Examples

```
## use with optimization for actually using such designs
##  $n/4 - 1 = 7$  columns, strength 3+
SOAs_8level(32, optimize=FALSE)

##  $n/4 = 8$  columns, strength 3 with alpha and beta
SOAs_8level(32, m=8, optimize=FALSE)

## 9 columns (special case  $n=32$ ), strength 3 with alpha
SOAs_8level(32, constr="ShiTang_alpha", optimize=FALSE)

##  $5 \cdot n/16 = 5$  columns, strength 3 with alpha
SOAs_8level(16, constr="ShiTang_alpha", optimize=FALSE)
```

Index

- * **array**
 - guide_SOAs, 4
 - guide_SOAs_from_OA, 6
- 'SOAs-package' (SOAs-package), 2
- _PACKAGE (SOAs-package), 2

- attr, 13, 15, 17, 19, 25, 27, 29
- attributes, 13, 15, 17, 19, 25, 27, 29

- count_nallpairs (ocheck), 10
- count_npairs (ocheck), 10
- createSaturated, 3, 19

- DoE.base, 4

- FrF2, 4

- guide_SOAs, 2, 4, 7
- guide_SOAs_from_OA, 2, 5, 6

- mbound_LiuLiu, 7
- MDLEs, 3, 8
- mindist (phi_p), 22

- ocheck, 2, 10
- ocheck3, 2
- ocheck3 (ocheck), 10
- OSOAs, 2, 12, 19
- OSOAs_hadamard, 2, 14, 19
- OSOAs_LiuLiu, 2, 16
- OSOAs_regular, 2, 18, 19

- phi_optimize, 9, 20
- phi_p, 2, 9, 13, 15, 16, 19, 21, 22, 24, 26, 29
- print.MDLE (print.SOA), 23
- print.SOA, 23

- soacheck2D, 2
- soacheck2D (ocheck), 10
- soacheck3D, 2
- soacheck3D (ocheck), 10

- SOAs, 2, 24
- SOAs-package, 2
- SOAs2plus_regular, 2, 25
- SOAs_8level, 2, 28

- XiaoXuMDLE, 3