

Package ‘arcpullr’

August 31, 2022

Type Package

Title Pull Data from an 'ArcGIS REST' API

Version 0.2.7

License GPL-3

Encoding UTF-8

LazyData true

Description Functions to efficiently query 'ArcGIS REST' APIs

<<https://developers.arcgis.com/rest/>>.

Both spatial and SQL queries can be used to retrieve data.

Simple Feature (sf) objects are utilized to perform spatial queries.

This package was neither produced nor is maintained by Esri.

Depends R (>= 3.6.0), sf (>= 0.9.7),

Imports httr (>= 1.4.1), jsonlite (>= 1.6.1), dplyr (>= 1.0.2),
ggplot2 (>= 3.3.0), tidyr (>= 1.0.2), rlang (>= 0.4.7), raster
(>= 3.4.5), methods, bslib, DT, rgdal

RoxygenNote 7.2.1

Suggests testthat (>= 3.0.1), knitr (>= 1.30), rmarkdown (>= 2.6),
rvest (>= 0.3.6), xml2 (>= 1.3.2), stringr (>= 1.4.0), cowplot
(>= 1.1.1), magick (>= 2.5.2)

VignetteBuilder knitr

NeedsCompilation no

Author Paul Frater [aut, cre] (<<https://orcid.org/0000-0002-7237-6563>>),
Zac Driscoll [aut] (<<https://orcid.org/0000-0002-8233-0980>>)

Maintainer Paul Frater <paul.frater@wisconsin.gov>

Repository CRAN

Date/Publication 2022-08-30 22:00:02 UTC

R topics documented:

arcpullr-package 2

| | |
|--|-----------|
| format_coords | 3 |
| get_geometry_type | 4 |
| get_image_layer | 5 |
| get_layers_by_spatial | 6 |
| get_layer_html | 7 |
| get_layer_legend | 8 |
| get_map_layer | 8 |
| get_raster_layer | 10 |
| get_service_type | 11 |
| get_sf_crs | 12 |
| get_spatial_layer | 12 |
| match_raster_colors | 13 |
| plot_layer | 14 |
| plot_layer,RasterBrick-method | 15 |
| plot_layer,RasterLayer-method | 16 |
| plot_layer,RasterStack-method | 17 |
| plot_layer,sf-method | 18 |
| raster_colors | 18 |
| raster_colors,RasterBrick-method | 19 |
| raster_colors,RasterLayer-method | 20 |
| raster_colors,RasterStack-method | 21 |
| sf_example_polys | 21 |
| sf_example_raster | 23 |
| sf_objects | 24 |
| sp_rel_lookups | 24 |
| sp_rel_xref | 25 |
| sql_where | 26 |
| valid_sp_rel | 27 |
| Index | 28 |

| | |
|------------------|-----------------|
| arcpullr-package | <i>arcpullr</i> |
|------------------|-----------------|

Description

A package for pulling spatial data from an ArcGIS REST API

Details



The role of the arcpullr package is simple...to pull spatial data from an ArcGIS REST API. These APIs are housed by various different agencies, organizations, entities, etc., but allow a consistent format for storing and retrieving spatial data

[get_spatial_layer](#)

This function makes up the core of the package. It allows users to pull spatial data given a URL of an ArcGIS REST API. There are many additional query parameters that can (and probably should) be added; however, we've simplified many of these out for you with the functions below.

[get_layer_by_spatial](#) family of functions

These functions allow you to pull layers using a spatial query. The abstract syntax is wrapped into the functions, so all you have to do is pass these functions an sf object of the spatial area, line, or point you want to query by. These functions include [get_layer_by_poly](#), [get_layer_by_point](#), [get_layer_by_line](#), [get_layer_by_multipoint](#), and [get_layer_by_envelope](#). It should be fairly obvious what type of spatial layer each function takes with the exception of [get_layer_by_envelope](#) except that it isn't particularly useful for a single point.

[get_image_layer](#)

This is one of the core functions of the package. It retrieves image service layers from an ArcGIS REST API designated by the URL

[get_map_layer](#)

This is one of the core functions of the package. It retrieves map service layers from an ArcGIS REST API designated by the URL

Helper functions

There are a few utility functions to help you along the way. The first is [plot_layer](#), which is a useful way to plot the spatial layer you've tried to pull just to make sure it works. If you want fancier maps you'd be better served with ggplot2 or tmaps, though.

Other helpers include the [sf_objects](#) functions, which allow you to easily create sf points, lines, and polygons with a few coordinates.

Lastly, there is a [sql_where](#) function to help aid in building more complex SQL WHERE clauses used to query by the where argument in the retrieval functions above.

format_coords

Convert coordinates from an 'sf' object to formatted well-known text

Description

Use this function to convert the coordinates of a sf polygon object to a string of well known text. The output can be passed to an ArcGIS REST API to perform a spatial query.

Usage

```
format_polygon_coords(sf_obj)

format_line_coords(sf_obj)

format_multipoint_coords(sf_obj)

format_point_coords(sf_obj)

format_envelope_coords(sf_obj)

format_coords(sf_obj, geom_type)
```

Arguments

| | |
|-----------|---|
| sf_obj | An sf object |
| geom_type | Either "points", "paths", or "rings". Choose wisely |

Details

Spatial queries from an ArcGIS REST API require specific text inputs formatted in a way called well-known text (WKT). ArcGIS REST APIs have their own syntax for how the text is taken. These functions will format sf objects in the correct way to be able to make spatial queries from a ArcGIS REST API

Value

String of well known text

Examples

```
mke_polygon_coords <- format_polygon_coords(mke_county)
```

| | |
|-------------------|--------------------------|
| get_geometry_type | <i>Get Geometry Type</i> |
|-------------------|--------------------------|

Description

Get Geometry Type

Usage

```
get_geometry_type(url)
```

Arguments

| | |
|-----|--|
| url | A character string of a feature services URL |
|-----|--|

Value

A character string of the layers geometry type

Examples

```
## Not run:
get_geometry_type(reykjanes_lava_flow_url)

## End(Not run)
```

| | |
|-----------------|--|
| get_image_layer | <i>Retrieve an image service layer from an ArcGIS REST API</i> |
|-----------------|--|

Description

This function retrieves image service layers from an ArcGIS REST services API and returns them as a RasterStack object

Usage

```
get_image_layer(
  url,
  sf_object = NULL,
  bbox = NULL,
  token = "",
  clip_raster = TRUE,
  format = "png",
  transparent = TRUE,
  ...
)
```

Arguments

| | |
|-------------|--|
| url | A character string of the url for the layer to pull |
| sf_object | An sf object used for the bounding box |
| bbox | Character string of the bounding box |
| token | A character string of the token (if needed) |
| clip_raster | Logical. Should the raster be clipped to contain only the pixels that reside in the sf_object? By default, ArcGIS returns some overlapping edge pixels. Setting clip_raster to TRUE (default) will remove these using mask from the raster package |
| format | The raster format desired. Default is "png" |
| transparent | Logical. Retrieve a raster with a transparent background (TRUE, default) or not (FALSE) |
| ... | Additional arguments to pass to the ArcGIS REST API |

Details

This is one of the core functions of the package. It retrieves image service layers from an ArcGIS REST API designated by the URL. These layers require a bounding box to query the map layer, which is either taken from the `sf_object` argument or optionally can be passed via the `bbox` argument. Either `sf_object` or `bbox` are optional, but one of them must be present.

All of the querying parameters are sent via a POST request to the URL, so if there are issues with passing additional parameters via `...` first determine how they fit into the POST request and make adjustments as needed. This syntax can be tricky if you're not used to it.

Value

A "RasterStack" object

Examples

```
## Not run:
wi_leaf_off_layer <- get_image_layer(wi_leaf_off_url, wis_poly)
plot_layer(wi_leaf_off_layer, outline_poly = wis_poly)

## End(Not run)
```

`get_layers_by_spatial` *Retrieve ArcGIS REST API spatial layer by spatial query*

Description

These functions are wrappers around `get_spatial_layer` that are specialized for querying by a spatial layer. They will make a POST request to the query URL which returns data (if available) based on the appropriate spatial feature (`geometry`) and relationship (`sp_rel`).

Usage

```
get_layer_by_poly(url, geometry, sp_rel = "contains", ...)

get_layer_by_line(url, geometry, sp_rel = "intersects", ...)

get_layer_by_point(url, geometry, sp_rel = "intersects", ...)

get_layer_by_multipoint(url, geometry, sp_rel = "intersects", ...)

get_layer_by_envelope(url, geometry, sp_rel = "intersects", ...)

get_layer_by_spatial(
  url,
  geometry,
  geom_type,
  sp_ref = NULL,
```

```

    sp_rel = "intersects",
    ...
  )

```

Arguments

| | |
|-----------|---|
| url | A character string of the url for the layer to pull |
| geometry | An sf object used for the spatial query |
| sp_rel | Character. The type of relationship to query by. Possible options include "intersects", "contains", and "crosses" |
| ... | Additional arguments to pass to get_spatial_layer |
| geom_type | A character of the geometry type to be used. This param is automatically specified in all get_layer_by_* functions except get_spatial_layer |
| sp_ref | The spatial reference value |

Value

An object of class "sf" of the appropriate layer

Examples

```

base_wdnr_url <- "https://dnrmaps.wi.gov/arcgis/rest/services/"
hydro_path <- "WT_SWDV/WT_Inland_Water_Resources_WTM_Ext_v2/MapServer/2"
hydro_url <- paste0(base_wdnr_url, hydro_path)
mke_waters <- get_layer_by_poly(url = hydro_url, mke_county)

```

| | |
|----------------|---|
| get_layer_html | <i>Pull the HTML body from a web page</i> |
|----------------|---|

Description

Used internally to pull HTML for a layer's web page so that the call doesn't have to be made twice in [get_geometry_type](#) if the url provided there is for a raster layer.

Usage

```
get_layer_html(url)
```

Arguments

| | |
|-----|------------------------------------|
| url | Character. The URL of the web page |
|-----|------------------------------------|

Value

A character string of the HTML body

| | |
|------------------|-------------------------------------|
| get_layer_legend | Returns a legend for a raster layer |
|------------------|-------------------------------------|

Description

Raster layers are accompanied with legends to identify what the colors mean. This function retrieves those legend values and returns them as a data.frame with the associated RGB color values. This will likely be most useful for plotting and analysis of map layers.

Usage

```
get_layer_legend(url)
```

Arguments

url A URL to a Map or Image Service layer

Value

A data.frame with two columns (color, values) and the number of rows equal to the number of values in a layer

Examples

```
## Not run:  
get_layer_legend(wi_landcover_url)  
  
## End(Not run)
```

| | |
|---------------|--|
| get_map_layer | Retrieve a map service layer from an ArcGIS REST API |
|---------------|--|

Description

This function retrieves map service layers from an ArcGIS REST services API and returns them as a RasterLayer object

Usage

```
get_map_layer(  
  url,  
  sf_object = NULL,  
  bbox = NULL,  
  token = "",  
  clip_raster = TRUE,  
  format = "png",
```



```

    transparent = TRUE,
    add_legend = TRUE,
    ...
)

```

Arguments

| | |
|-------------|--|
| url | A character string of the url for the layer to pull |
| sf_object | An sf object used for the bounding box |
| bbox | Character string of the bounding box |
| token | A character string of the token (if needed) |
| clip_raster | Logical. Should the raster be clipped to contain only the pixels that reside in the sf_object? By default, ArcGIS returns some overlapping edge pixels. Setting clip_raster to TRUE (default) will remove these using mask from the raster package |
| format | The raster format desired. Default is "png" |
| transparent | Logical. Retrieve a raster with a transparent background (TRUE, default) or not (FALSE) |
| add_legend | Logical. Pull legend and match to color values (TRUE, default) or not (FALSE) |
| ... | Additional arguments to pass to the ArcGIS REST API |

Details

This is one of the core functions of the package. It retrieves map service layers from an ArcGIS REST API designated by the URL. These layers require a bounding box to query the map layer, which is either taken from the sf_object argument or optionally can be passed via the bbox argument. Either sf_object or bbox are optional, but one of them must be present.

All of the querying parameters are sent via a POST request to the URL, so if there are issues with passing additional parameters via ... first determine how they fit into the POST request and make adjustments as needed. This syntax can be tricky if you're not used to it.

Value

A "RasterLayer" object

Examples

```

## Not run:
wi_landcover<- get_map_layer(wi_landcover_url, wis_poly)
plot_layer(wi_landcover, outline_poly = wis_poly)

## End(Not run)

```

| | |
|------------------|--|
| get_raster_layer | <i>Pull a raster layer from a map service or image service layer of an ArcGIS REST API</i> |
|------------------|--|

Description

This is an internal function to pull raster layers from either a map service or an image service of an ArcGIS REST API. This function is the engine that drives [get_map_layer](#) and [get_image_layer](#)

Usage

```
get_raster_layer(
    url,
    sf_object = NULL,
    bbox = NULL,
    token = "",
    clip_raster = TRUE,
    format = "png",
    transparent = TRUE,
    export_type = "map",
    add_legend = FALSE,
    ...
)
```

Arguments

| | |
|-------------|--|
| url | A character string of the url for the layer to pull |
| sf_object | An sf object used for the bounding box |
| bbox | Character string of the bounding box |
| token | A character string of the token (if needed) |
| clip_raster | Logical. Should the raster be clipped to contain only the pixels that reside in the sf_object? By default, ArcGIS returns some overlapping edge pixels. Setting clip_raster to TRUE (default) will remove these using mask from the raster package |
| format | The raster format desired. Default is "png" |
| transparent | Logical. Retrieve a raster with a transparent background (TRUE, default) or not (FALSE) |
| export_type | Character. Either "map" or "image" for the respective service layer desired |
| add_legend | Logical. Pull legend and match to color values (TRUE, default) or not (FALSE) |
| ... | Additional arguments to pass to the ArcGIS REST API |

Value

An object of type RasterLayer if export_type = "map" or an object of type RasterStack if export_type = "image"

| | |
|------------------|--|
| get_service_type | <i>Get elements of a Service or Layer from an ArcGIS REST endpoint</i> |
|------------------|--|

Description

This family of functions is meant to pull attributes from a particular service or layer hosted on an ArcGIS REST API. If the service is an ImageServer or MapServer, then the behavior will be slightly different than for a Feature Layer (see details).

Usage

```
get_service_type(url, ...)
```

Arguments

| | |
|-----|--|
| url | A character string of a valid layer URL |
| ... | Only used internally, but html can be passed |

Details

get_service_type will return the type of service or layer for the respective URL (or html) that is passed to the function. For a feature layer the function should return "feature_layer", for a Image or Map Server the function will return "image" or "map", respectively.

get_geometry_type will return the geometry type of feature service layers housed on an ArcGIS REST API server. If a URL is provided that points to a map or image layer the function will return an error (i.e. only feature layers have geometry types).

get_supported_operations will simply return a character vector that lists the supported operations for url.

Value

A character string defining the layer type

Examples

```
## Not run:  
get_service_type(reykjanes_lava_flow_url)  
  
## End(Not run)
```

| | |
|------------|---|
| get_sf_crs | <i>Return CRS value of an sf object</i> |
|------------|---|

Description

Return CRS value of an sf object

Usage

```
get_sf_crs(sf_obj)
```

Arguments

sf_obj An object of class sf

Value

A numeric value referring to the coordinate reference system

Examples

```
get_sf_crs(iceland_poly)
```

| | |
|-------------------|---|
| get_spatial_layer | <i>Retrieve a feature service layer from an ArcGIS REST API</i> |
|-------------------|---|

Description

This function retrieves spatial layers present in Feature Service layers of an ArcGIS REST services API and returns them as an sf object

Usage

```
get_spatial_layer(  
  url,  
  out_fields = c("*"),  
  where = "1=1",  
  token = "",  
  sf_type = NULL,  
  head = FALSE,  
  ...  
)
```

Arguments

| | |
|------------|--|
| url | A character string of the url for the layer to pull |
| out_fields | A character string of the fields to pull for each layer |
| where | A character string of the where condition. Default is 1=1 |
| token | A character string of the token (if needed) |
| sf_type | A character string specifying the layer geometry to convert to sf ("esriGeometryPolygon", "esriGeometryPoint", "esriGeometryPolyline"), if NULL (default) the server will take its best guess |
| head | Logical or numeric. Limits the number of records returned from a query. If TRUE, only the first 10 records will be returned. If numeric, then the number of records specified in head will be returned |
| ... | Additional arguments to pass to the ArcGIS REST POST request |

Details

This is one of the core functions of this package. It retrieves spatial layers from feature services of an ArcGIS REST API designated by the URL. Additional querying features can be passed such as a SQL WHERE statement (where argument) or spatial queries as well as any other types of queries that the ArcGIS REST API accepts (using ...). However, for easier spatial querying see [get_layers_by_spatial](#).

All of the querying parameters are sent via a POST request to the URL, so if there are issues with passing additional parameters via ... first determine how they fit into the POST request and make adjustments as needed. This syntax can be tricky if you're not used to it.

Value

An object of class "sf" of the appropriate layer

Examples

```
## Not run:
# lava flows on Reykjanes (pr. 'rake-yah-ness') peninsula in Iceland
lava_flows <- get_spatial_layer(reykjanes_lava_flow_url)
plot_layer(lava_flows, outline_poly = reykjanes_poly)
plot_layer(lava_flows, outline_poly = iceland_poly)

## End(Not run)
```

match_raster_colors *Match colors in RasterLayer color space to the provided legend values*

Description

Colors provided by the legend do not always correspond exactly with the colors in the colortable of a RasterLayer object. They are usually pretty close, though, so this function finds the closest colors, maps them to the appropriate colors in the Raster* object, and applies that to the legend.

Usage

```
match_raster_colors(legend, x)
```

Arguments

`legend` An object of class `raster_legend` as returned by [get_layer_legend](#)
`x` A `RasterLayer` object as returned by [get_map_layer](#)

Details

Raster colors in `x` are mapped to those in `legend` by converting the RGB hexadecimal values to a 3D vector of values for red, green and blue. The closest values are then assigned using 3D Pythagorean theorem to compute the distance among all colors. The minimum distance in three dimensional space is the color in `x` that gets mapped to the appropriate color in `legend`.

Value

A `raster_legend` object with corrected colors to match those in `x`

Examples

```
## Not run:  
wi_landcover <- get_map_layer(wi_landcover_url, wis_poly)  
legend <- get_layer_legend(wi_landcover_url)  
new_legend <- match_raster_colors(legend, wi_landcover_url)  
  
## End(Not run)
```

plot_layer

Plot a spatial layer

Description

This function plots a spatial layer as returned from [get_spatial_layer](#).

Usage

```
plot_layer(x, ...)  
  
plot_layer.sf(  
  x,  
  outline_poly = NULL,  
  outline_size = 1.2,  
  outline_color = "gray30",  
  plot_pkg = "ggplot",  
  ...  
)
```

Arguments

| | |
|---------------|---|
| x | An sf or Raster* object as returned from a get_*_layer function |
| ... | Additional arguments to plot_layer |
| outline_poly | Optional. An sf polygon to outline sf_data for context |
| outline_size | Numeric argument that controls width of parameter |
| outline_color | A character vector of a valid color |
| plot_pkg | Character. The plotting environment to use. Either "ggplot" (default) or "base" |

Value

Either a ggplot object, or simply plots x if plot_pkg = "base"

Examples

```
## Not run:
plot_layer(iceland_poly)
plot_layer(portage_county, outline_poly = wis_poly)

## End(Not run)
```

plot_layer,RasterBrick-method
Plot a RasterBrick object

Description

Plot a RasterBrick object

Usage

```
## S4 method for signature 'RasterBrick'
plot_layer(
  x,
  outline_poly = NULL,
  outline_size = 1.2,
  outline_color = "gray30",
  plot_pkg = "ggplot",
  ...
)
```

Arguments

| | |
|---------------|---|
| x | An sf or Raster* object as returned from a get_*_layer function |
| outline_poly | Optional. An sf polygon to outline sf_data for context |
| outline_size | Numeric argument that controls width of parameter |
| outline_color | A character vector of a valid color |
| plot_pkg | Character. The plotting environment to use. Either "ggplot" (default) or "base" |
| ... | Additional arguments to plot_layer |

Examples

```
## Not run:
wi_aerial <- get_map_layer(wi_leaf_off_url, wis_poly)
plot_layer(wi_aerial, outline_poly = wis_poly)

## End(Not run)
```

plot_layer,RasterLayer-method

Plot a RasterLayer object

Description

Plot a RasterLayer object

Usage

```
## S4 method for signature 'RasterLayer'
plot_layer(
  x,
  outline_poly = NULL,
  outline_size = 1.2,
  outline_color = "gray30",
  legend = TRUE,
  plot_pkg = "ggplot",
  ...
)
```

Arguments

| | |
|---------------|---|
| x | An sf or Raster* object as returned from a get_*_layer function |
| outline_poly | Optional. An sf polygon to outline sf_data for context |
| outline_size | Numeric argument that controls width of parameter |
| outline_color | A character vector of a valid color |
| legend | Logical. Only valid when plotting RasterLayers retrieved from get_map_layer where legend was also retrieved |
| plot_pkg | Character. The plotting environment to use. Either "ggplot" (default) or "base" |
| ... | Additional arguments to plot_layer |

Examples

```
## Not run:
wi_landcover <- get_map_layer(wi_landcover_url, wis_poly)
plot_layer(wi_landcover, outline_poly = wis_poly)

## End(Not run)
```

plot_layer,RasterStack-method

Plot a RasterStack object

Description

Plot a RasterStack object

Usage

```
## S4 method for signature 'RasterStack'
plot_layer(
  x,
  outline_poly = NULL,
  outline_size = 1.2,
  outline_color = "gray30",
  plot_pkg = "ggplot",
  ...
)
```

Arguments

| | |
|---------------|---|
| x | An sf or Raster* object as returned from a get_*_layer function |
| outline_poly | Optional. An sf polygon to outline sf_data for context |
| outline_size | Numeric argument that controls width of parameter |
| outline_color | A character vector of a valid color |
| plot_pkg | Character. The plotting environment to use. Either "ggplot" (default) or "base" |
| ... | Additional arguments to plot_layer |

Examples

```
## Not run:
wi_aerial <- get_map_layer(wi_leaf_off_url, wis_poly)
plot_layer(wi_aerial, outline_poly = wis_poly)

## End(Not run)
```

plot_layer, sf-method *Plot an sf object*

Description

Plot an sf object

Usage

```
## S4 method for signature 'sf'
plot_layer(
  x,
  outline_poly = NULL,
  outline_size = 1.2,
  outline_color = "gray30",
  plot_pkg = "ggplot",
  ...
)
```

Arguments

| | |
|---------------|---|
| x | An sf or Raster* object as returned from a get_*_layer function |
| outline_poly | Optional. An sf polygon to outline sf_data for context |
| outline_size | Numeric argument that controls width of parameter |
| outline_color | A character vector of a valid color |
| plot_pkg | Character. The plotting environment to use. Either "ggplot" (default) or "base" |
| ... | Additional arguments to plot_layer |

Examples

```
## Not run:
plot_layer(wis_poly)

## End(Not run)
```

| | |
|---------------|---|
| raster_colors | <i>Convert RasterLayer into data.frame of colors for each pixel that can be used for plotting</i> |
|---------------|---|

Description

This function is used internally by `plot_layer` to convert a Raster* object to a data.frame of colors for each pixel that can be used for plotting with `ggplot2`

Usage

```
raster_colors(x)
```

Arguments

x A Raster* object

Value

A data.frame with 3 columns and length(raster_object) rows. Two of these columns are the x-y coordinates of each pixel, and one is a value for color that can be used for plotting

Examples

```
## Not run:
wi_landcover <- get_map_layer(wi_landcover_url, wis_poly)
wi_landcover_data <- raster_colors(wi_landcover)
head(wi_landcover_data)

## End(Not run)
```

raster_colors,RasterBrick-method

Convert RasterBrick into data.frame of colors that can be used for plotting

Description

This function is used internally by [plot_layer](#) to convert a RasterBrick object to a data.frame of colors for each pixel that can be used for plotting with ggplot2. Note that this function assumes that the first three bands in the RasterBrick objects are the RGB values and all additional bands are ignored.

Usage

```
## S4 method for signature 'RasterBrick'
raster_colors(x)
```

Arguments

x A RasterBrick object

Value

A data.frame with 3 columns and length(raster_object) rows

Examples

```
## Not run:
wi_leaf_off_layer <- get_image_layer(wi_leaf_off_url, wis_poly)
wi_leaf_off_data <- raster_colors(wi_leaf_off_layer)

## End(Not run)
```

raster_colors,RasterLayer-method

Convert RasterLayer into data.frame of colors that can be used for plotting

Description

This function is used internally by [plot_layer](#) to convert a RasterLayer object to a data.frame of colors for each pixel that can be used for plotting with ggplot2

Usage

```
## S4 method for signature 'RasterLayer'
raster_colors(x)
```

Arguments

x A RasterLayer object

Value

A data.frame with 3 columns and length(raster_object) rows

Examples

```
## Not run:
wi_landcover <- get_map_layer(wi_landcover_url, wis_poly)
wi_landcover_data <- raster_colors(wi_landcover)

## End(Not run)
```

raster_colors,RasterStack-method

Convert RasterStack into data.frame of colors that can be used for plotting

Description

This function is used internally by [plot_layer](#) to convert a RasterStack object to a data.frame of colors for each pixel that can be used for plotting with ggplot2. Note that this function assumes that the first three bands in the RasterStack objects are the RGB values and all additional bands are ignored.

Usage

```
## S4 method for signature 'RasterStack'  
raster_colors(x)
```

Arguments

x A RasterStack object

Value

A data.frame with 3 columns and length(raster_object) rows

Examples

```
## Not run:  
wi_leaf_off_layer <- get_image_layer(wi_leaf_off_url, wis_poly)  
wi_leaf_off_data <- raster_colors(wi_leaf_off_layer)  
  
## End(Not run)
```

sf_example_polys

Various example sf polygons

Description

These are sf polygons that are used for examples throughout the package

Usage

iceland_poly
mke_county
portage_county
reykjanes_poly
wis_counties
wis_poly
cook_creek_ws
cook_creek_streams
cook_creek_env
mke_river
poly_streams_contains
poly_streams_crosses
sugar_creek
sugar_creek_env
trout_hab_project_pt
trout_hab_project_pts
example_poly
trout_hab_project_pts

Format

An object of class sf and data.frame:

An object of class sf (inherits from data.frame) with 1 rows and 3 columns.

An object of class sf (inherits from data.frame) with 1 rows and 3 columns.

An object of class sf (inherits from data.frame) with 1 rows and 2 columns.

An object of class sf (inherits from data.frame) with 72 rows and 3 columns.

An object of class sf (inherits from data.frame) with 1 rows and 2 columns.

An object of class sf (inherits from data.frame) with 1 rows and 7 columns.

An object of class sf (inherits from tbl_df, tbl, data.frame) with 5 rows and 3 columns.

An object of class sf (inherits from tbl_df, tbl, data.frame) with 10 rows and 3 columns.

An object of class sf (inherits from tbl_df, tbl, data.frame) with 5 rows and 5 columns.

An object of class sf (inherits from data.frame) with 1 rows and 28 columns.

An object of class sf (inherits from data.frame) with 4 rows and 28 columns.

An object of class sf (inherits from data.frame) with 7 rows and 28 columns.

An object of class sf (inherits from data.frame) with 15 rows and 28 columns.

An object of class sf (inherits from data.frame) with 1 rows and 11 columns.

An object of class sf (inherits from data.frame) with 4 rows and 11 columns.

An object of class sf (inherits from data.frame) with 1 rows and 1 columns.

An object of class sf (inherits from data.frame) with 4 rows and 11 columns.

Source

ggplot2's [map_data](#) and [Wisconsin DNR ArcGIS REST API](#)

| | |
|-------------------|---------------------------------------|
| sf_example_raster | <i>Various example raster objects</i> |
|-------------------|---------------------------------------|

Description

These are raster objects that are used for examples throughout the package

Usage

```
wi_landcover
```

```
wi_aerial_imagery
```

Format

An object of class RasterLayer of dimension 400 x 400 x 1.

An object of class RasterBrick of dimension 400 x 400 x 3.

Source

[Wisconsin DNR ArcGIS Image Server](#)

`sf_objects`*Create sf objects from coordinates*

Description

These are simple wrapper functions for creating sf objects from points

Usage

```
sf_line(..., crs = 4326)
sf_point(..., crs = 4326)
sf_points(..., crs = 4326)
sf_polygon(..., crs = 4326)
sf_box(xmin, ymin, xmax, ymax, crs = 4326)
```

Arguments

`...` The coordinates of the object
`crs` The coordinate reference system. Defaults to 4326
`xmin, xmax, ymin, ymax` Corners for `sf_box`

Value

An sf object of the appropriate type

Examples

```
pt_a <- c(-90, 45)
pt_b <- c(-89, 44)
pt <- sf_points(pt_a)
line <- sf_line(pt_a, pt_b)
```

`sp_rel_lookups`*Spatial relationship descriptor and lookup tables*

Description

These data.frames are used to lookup and explain which spatial relation types go with different spatial queries.

Usage

sp_rel_valid

sp_rel_lookup

Format

sp_rel_valid is a data.frame with 105 rows and 3 variables as follows:

feature_class A feature class to be queried

query_feature_class The feature class used to do a spatial query

sp_rel The spatial relationships that are valid for the feature class and query_feature_class combination

sp_rel_lookup is a data.frame with 9 rows and 2 variables as follows:

sp_rel The spatial relationship being described

description A description of the sp_rel

Details

sp_rel_lookup explains the various different types of spatial relationships available through ArcGIS REST APIs. sp_rel_valid shows which spatial relationships are valid with different geometry types being queried and used to do spatial queries

Source

sp_rel_valid—Independent tests done specifically by and for arcpullr

sp_rel_lookup—<https://help.arcgis.com/en/webapi/wpf/apiref/ESRI.ArcGIS.Client~ESRI.ArcGIS.Client.Tasks.SpatialRelationship.html>

sp_rel_xref

Lookup function for shorthand versions of spatial relation text strings

Description

After typing "esriSpatialRelIntersects" into 4 to 5 functions, you'll get pretty sick of typing that. This function serves to allow shorthand strings to be passed to the sp_rel arguments of the [get_layers_by_spatial](#) family of functions. For example, you can pass "intersects" to this function and it will return "esriSpatialRelIntersects"

Usage

sp_rel_xref(x)

Arguments

x A character string. One of "contains", "crosses", "envelopeintersects", "indexintersects", "intersects", "overlaps", "relation", "touches", "within"

Value

The appropriately named ESRI version of x. For example, an x value of "intersects" returns "esriSpatialRelIntersects"

Examples

```
sp_rel_xref("intersects")
```

sql_where

Format a SQL where clause from arguments

Description

This function will create a where statement that is compatible with [get_spatial_layer](#)). This statement can then be passed to the where argument in this function.

Usage

```
sql_where(..., rel_op = "=")
```

Arguments

... Named objects to be queried by

rel_op Character. The relational operator in the SQL clause (i.e. "=", "IN", "NOT IN", etc.). If a single rel_op is provide with multiple ... parameters then it will be recycled length(...) times.

Value

A character string that can be passed to the where argument of [get_spatial_layer](#)

Examples

```
## Not run:
wbics <- sql_where(WATERBODY_WBIC = c(805400, 804600), rel_op = "IN")
base_wdnr_url <- "https://dnrmaps.wi.gov/arcgis/rest/services/"
hydro_path <- "WT_SWDV/WT_Inland_Water_Resources_WTM_Ext_v2/MapServer/3"
hydro_url <- paste0(base_wdnr_url, hydro_path)
lakes <- get_spatial_layer(url = hydro_url, where = wbics)
plot_layer(lakes)

## End(Not run)
```

| | |
|--------------|---|
| valid_sp_rel | <i>Check to see which spatial relation types are applicable to the feature classes being queried and the sf objects use do to a spatial query</i> |
|--------------|---|

Description

Check to see which spatial relation types are applicable to the feature classes being queried and the sf objects use do to a spatial query

Usage

```
valid_sp_rel(fc1, fc2, pull = TRUE)
```

Arguments

| | |
|------|---|
| fc1 | Character. The feature class type being queried. Available options are "point", "multipoint", "line", or "area". |
| fc2 | Character. The geometry type of the sf object used to do a spatial query. Available options are "point", "multipoint", "line", or "area". |
| pull | Logical. Pull the available options (TRUE) or print all columns of the sp_rel_valid data.frame for the appropriate fc1 and fc2 |

Value

Either a vector or filtered data.frame showing the appropriate sp_rels for the given feature classes

Examples

```
valid_sp_rel("line", "line")
```

Index

- * **datasets**
 - sf_example_polys, 21
 - sf_example_raster, 23
 - sp_rel_lookups, 24
- arcpullr (arcpullr-package), 2
- arcpullr-package, 2
- cook_creek_env (sf_example_polys), 21
- cook_creek_streams (sf_example_polys), 21
- cook_creek_ws (sf_example_polys), 21
- example_poly (sf_example_polys), 21
- format_coords, 3
- format_envelope_coords (format_coords), 3
- format_line_coords (format_coords), 3
- format_multipoint_coords (format_coords), 3
- format_point_coords (format_coords), 3
- format_polygon_coords (format_coords), 3
- get_geometry_type, 4, 7
- get_image_layer, 3, 5, 10
- get_layer_by_envelope (get_layers_by_spatial), 6
- get_layer_by_line (get_layers_by_spatial), 6
- get_layer_by_multipoint (get_layers_by_spatial), 6
- get_layer_by_point (get_layers_by_spatial), 6
- get_layer_by_poly (get_layers_by_spatial), 6
- get_layer_by_spatial, 3
- get_layer_by_spatial (get_layers_by_spatial), 6
- get_layer_html, 7
- get_layer_legend, 8, 14
- get_layers_by_spatial, 6, 13, 25
- get_map_layer, 3, 8, 10, 14, 16
- get_raster_layer, 10
- get_service_type, 11
- get_sf_crs, 12
- get_spatial_layer, 3, 6, 7, 12, 14, 26
- iceland_poly (sf_example_polys), 21
- map_data, 23
- mask, 5, 9, 10
- match_raster_colors, 13
- mke_county (sf_example_polys), 21
- mke_river (sf_example_polys), 21
- plot_layer, 3, 14, 18–21
- plot_layer, RasterBrick-method, 15
- plot_layer, RasterLayer-method, 16
- plot_layer, RasterStack-method, 17
- plot_layer, sf-method, 18
- poly_streams_contains (sf_example_polys), 21
- poly_streams_crosses (sf_example_polys), 21
- portage_county (sf_example_polys), 21
- raster_colors, 18
- raster_colors, RasterBrick-method, 19
- raster_colors, RasterLayer-method, 20
- raster_colors, RasterStack-method, 21
- reykjanes_poly (sf_example_polys), 21
- sf_box (sf_objects), 24
- sf_example_polys, 21
- sf_example_raster, 23
- sf_line (sf_objects), 24
- sf_objects, 3, 24
- sf_point (sf_objects), 24
- sf_points (sf_objects), 24
- sf_polygon (sf_objects), 24
- sp_rel_lookup (sp_rel_lookups), 24

sp_rel_lookups, [24](#)
sp_rel_valid(sp_rel_lookups), [24](#)
sp_rel_xref, [25](#)
sql_where, [3](#), [26](#)
sugar_creek(sf_example_polys), [21](#)
sugar_creek_env(sf_example_polys), [21](#)

trout_hab_project_pt
 (sf_example_polys), [21](#)
trout_hab_project_pts
 (sf_example_polys), [21](#)

valid_sp_rel, [27](#)

wi_aerial_imagery(sf_example_raster),
 [23](#)
wi_landcover(sf_example_raster), [23](#)
wis_counties(sf_example_polys), [21](#)
wis_poly(sf_example_polys), [21](#)