

Package ‘comorbidity’

July 12, 2022

Type Package

Version 1.0.3

Title Computing Comorbidity Scores

Description Computing comorbidity indices and scores such as the weighted Charlson score (Charlson, 1987 <[doi:10.1016/0021-9681\(87\)90171-8](https://doi.org/10.1016/0021-9681(87)90171-8)>) and the Elixhauser comorbidity score (Elixhauser, 1998 <[doi:10.1097/00005650-199801000-00004](https://doi.org/10.1097/00005650-199801000-00004)>) using ICD-9-CM or ICD-10 codes (Quan, 2005 <[doi:10.1097/01.mlr.0000182534.19832.83](https://doi.org/10.1097/01.mlr.0000182534.19832.83)>). Australian and Swedish modifications of the Charlson Comorbidity Index are available as well (Sundararajan, 2004 <[doi:10.1016/j.jclinepi.2004.03.012](https://doi.org/10.1016/j.jclinepi.2004.03.012)> and Ludvigsson, 2021 <[doi:10.2147/CLEP.S282475](https://doi.org/10.2147/CLEP.S282475)>).

Maintainer Alessandro Gasparini <alessandro.gasparini@ki.se>

URL <https://ellessenne.github.io/comorbidity/>,
<https://github.com/ellessenne/comorbidity/>

BugReports <https://github.com/ellessenne/comorbidity/issues>

License GPL (>= 3)

Depends R (>= 2.10)

Imports checkmate, data.table, stats, stringi, utils

Suggests covr, knitr, rmarkdown, testthat

RoxygenNote 7.2.0

Encoding UTF-8

LazyData true

ByteCompile true

VignetteBuilder knitr

Language en_GB

NeedsCompilation no

Author Alessandro Gasparini [aut, cre]
(<<https://orcid.org/0000-0002-8319-7624>>),
Hojjat Salmasian [ctb] (ICD-9-CM scores),
Jonathan Williman [ctb] (<<https://orcid.org/0000-0001-5080-4435>>),
Sing Yi Chia [ctb] (<<https://orcid.org/0000-0002-7591-3141>>),
Edmund Teo [ctb] (<<https://orcid.org/0000-0003-3936-4082>>)

Repository CRAN

Date/Publication 2022-07-12 10:50:19 UTC

R topics documented:

comorbidity-package	2
australia10	2
available_algorithms	3
comorbidity	3
icd10cm_2017	7
icd10cm_2018	7
icd10cm_2022	8
icd10_2009	8
icd10_2011	9
icd9_2015	10
nhds2010	10
sample_diag	11
score	12

Index	14
--------------	-----------

comorbidity-package *Computing Comorbidity Scores*

Description

Computing comorbidity scores such as the weighted Charlson score (Charlson, 1987 doi:[10.1016/00219681\(87\)901718](https://doi.org/10.1016/00219681(87)901718)) and the Elixhauser comorbidity score (Elixhauser, 1998 doi:[10.1097/00005650-19980100000004](https://doi.org/10.1097/00005650-19980100000004)) using ICD-9-CM or ICD-10 codes (Quan, 2005 doi:[10.1097/01.mlr.0000182534.19832.83](https://doi.org/10.1097/01.mlr.0000182534.19832.83)).

Author(s)

Alessandro Gasparini (alessandro.gasparini@ki.se)

australia10 *Australian mortality data, 2010*

Description

A dataset containing Australian mortality data, obtained from Stata 17.

Usage

australia10

Format

A data frame with 3,322 rows and 3 variables:

cause ICD-10 code representing cause of death

sex Gender

deaths Number of deaths

Note

The R code used to download and process the dataset from Stata is available [here](#).

available_algorithms *Display Currently Supported Algorithms*

Description

This function prints all (currently) supported and implemented comorbidity mapping, and for each one of those, each supported scoring and weighting algorithm.

Usage

```
available_algorithms()
```

Examples

```
available_algorithms()
```

comorbidity *Comorbidity mapping.*

Description

Maps comorbidity conditions using algorithms from the Charlson and the Elixhauser comorbidity scores.

Usage

```
comorbidity(x, id, code, map, assign0, labelled = TRUE, tidy.codes = TRUE)
```

Arguments

x	A tidy <code>data.frame</code> (or a <code>data.table</code> ; tibbles are supported too) with one column containing an individual ID and a column containing all diagnostic codes. Extra columns other than ID and codes are discarded. Column names must be syntactically valid names, otherwise they are forced to be so by calling the <code>make.names()</code> function.
id	Column of x containing the individual ID.
code	Column of x containing diagnostic codes. Codes must be in upper case with no punctuation in order to be properly recognised.
map	The mapping algorithm to be used (values are case-insensitive). Possible values are the Charlson score with either ICD-10 or ICD-9-CM codes (<code>charlson_icd10_quan</code> , <code>charlson_icd9_quan</code>) and the Elixhauser score, again using either ICD-10 or ICD-9-CM (<code>elixhauser_icd10_quan</code> , <code>elixhauser_icd9_quan</code>). These mapping are based on the paper by Quan et al. (2011). It is also possible to obtain a Swedish (<code>charlson_icd10_se</code>) or Australian (<code>charlson_icd10_am</code>) modification of the Charlson score using ICD-10 codes.
assign0	Apply a hierarchy of comorbidities: should a comorbidity be present in a patient with different degrees of severity, then the milder form will be assigned a value of 0. By doing this, a type of comorbidity is not counted more than once in each patient. The comorbidities that are affected by this argument are: <ul style="list-style-type: none"> "Mild liver disease" (<code>mld</code>) and "Moderate/severe liver disease" (<code>msld</code>) for the Charlson score; "Diabetes" (<code>diab</code>) and "Diabetes with complications" (<code>diabwc</code>) for the Charlson score; "Cancer" (<code>canc</code>) and "Metastatic solid tumour" (<code>metacanc</code>) for the Charlson score; "Hypertension, uncomplicated" (<code>hypunc</code>) and "Hypertension, complicated" (<code>hypc</code>) for the Elixhauser score; "Diabetes, uncomplicated" (<code>diabunc</code>) and "Diabetes, complicated" (<code>diabc</code>) for the Elixhauser score; "Solid tumour" (<code>solidtum</code>) and "Metastatic cancer" (<code>metacanc</code>) for the Elixhauser score.
labelled	Attach labels to each comorbidity, compatible with the RStudio viewer via the <code>utils::View()</code> function. Defaults to TRUE.
tidy.codes	Tidy diagnostic codes? If TRUE, all codes are converted to upper case and all non-alphanumeric characters are removed using the regular expression <code>[^[:alnum:]]</code> . Defaults to TRUE.

Details

The ICD-10 and ICD-9-CM coding for the Charlson and Elixhauser scores is based on work by Quan *et al.* (2005). ICD-10 and ICD-9 codes must be in upper case and with alphanumeric characters only in order to be properly recognised; set `tidy.codes = TRUE` to properly tidy the codes automatically. A message is printed to the R console when non-alphanumeric characters are found.

Value

A data frame with `id`, columns relative to each comorbidity domain, comorbidity score, weighted comorbidity score, and categorisations of such scores, with one row per individual.

For the Charlson score, the following variables are included in the dataset:

- The `id` variable as defined by the user;
- `mi`, for myocardial infarction;
- `chf`, for congestive heart failure;
- `pvd`, for peripheral vascular disease;
- `cevd`, for cerebrovascular disease;
- `dementia`, for dementia;
- `cpd`, for chronic pulmonary disease;
- `rheumd`, for rheumatoid disease;
- `pud`, for peptic ulcer disease;
- `mld`, for mild liver disease;
- `diab`, for diabetes without complications;
- `diabwc`, for diabetes with complications;
- `hp`, for hemiplegia or paraplegia;
- `rend`, for renal disease;
- `canc`, for cancer (any malignancy);
- `msld`, for moderate or severe liver disease;
- `metacanc`, for metastatic solid tumour;
- `aids`, for AIDS/HIV. Please note that we combine "chronic obstructive pulmonary disease" and "chronic other pulmonary disease" for the Swedish version of the Charlson index, for comparability (and compatibility) with other definitions/implementations.

Conversely, for the Elixhauser score the dataset contains the following variables:

- The `id` variable as defined by the user;
- `chf`, for congestive heart failure;
- `carit`, for cardiac arrhythmias;
- `valv`, for valvular disease;
- `pcd`, for pulmonary circulation disorders;
- `pvd`, for peripheral vascular disorders;
- `hypunc`, for hypertension, uncomplicated;
- `hypc`, for hypertension, complicated;
- `para`, for paralysis;
- `ond`, for other neurological disorders;
- `cpd`, for chronic pulmonary disease;
- `diabunc`, for diabetes, uncomplicated;

- diabc, for diabetes, complicated;
- hypothy, for hypothyroidism;
- rf, for renal failure;
- ld, for liver disease;
- pud, for peptic ulcer disease, excluding bleeding;
- aids, for AIDS/HIV;
- lymph, for lymphoma;
- metacanc, for metastatic cancer;
- solidtum, for solid tumour, without metastasis;
- rheumd, for rheumatoid arthritis/collaged vascular disease;
- coag, for coagulopathy;
- obes, for obesity;
- wloss, for weight loss;
- fed, for fluid and electrolyte disorders;
- blane, for blood loss anaemia;
- dane, for deficiency anaemia;
- alcohol, for alcohol abuse;
- drug, for drug abuse;
- psycho, for psychoses;
- depre, for depression;

Labels are presented to the user when using the RStudio viewer (e.g. via the `utils::View()` function) for convenience.

References

- Quan H, Sundararajan V, Halfon P, Fong A, Burnand B, Luthi JC, et al. *Coding algorithms for defining comorbidities in ICD-9-CM and ICD-10 administrative data*. Medical Care 2005; 43(11):1130-1139.
- Charlson ME, Pompei P, Ales KL, et al. *A new method of classifying prognostic comorbidity in longitudinal studies: development and validation*. Journal of Chronic Diseases 1987; 40:373-383.
- Ludvigsson JF, Appelros P, Askling J et al. *Adaptation of the Charlson Comorbidity Index for register-based research in Sweden*. Clinical Epidemiology 2021; 13:21-41.
- Sundararajan V, Henderson T, Perry C, Muggivan A, Quan H, Ghali WA. *New ICD-10 version of the Charlson comorbidity index predicted in-hospital mortality*. Journal of Clinical Epidemiology 2004; 57(12):1288-1294.

Examples

```
set.seed(1)
x <- data.frame(
  id = sample(1:15, size = 200, replace = TRUE),
  code = sample_diag(200),
  stringsAsFactors = FALSE
)

# Charlson score based on ICD-10 diagnostic codes:
comorbidity(x = x, id = "id", code = "code", map = "charlson_icd10_quan", assign0 = FALSE)

# Elixhauser score based on ICD-10 diagnostic codes:
comorbidity(x = x, id = "id", code = "code", map = "elixhauser_icd10_quan", assign0 = FALSE)
```

icd10cm_2017

ICD-10-CM Diagnostic Codes, 2017 Version

Description

A dataset containing the 2017 version of the ICD10-CM coding system.

Usage

icd10cm_2017

Format

A data frame with 71,486 rows and 2 variables:

Code ICD-10-CM diagnostic code

Description Description of each code

Note

The R code used to download and process the dataset from the CDC website is available [here](#).

icd10cm_2018

ICD-10-CM Diagnostic Codes, 2018 Version

Description

A dataset containing the 2018 version of the ICD10-CM coding system.

Usage

icd10cm_2018

Format

A data frame with 71,704 rows and 2 variables:

Code ICD-10-CM diagnostic code

Description Description of each code

Note

The R code used to download and process the dataset from the CDC website is available [here](#).

icd10cm_2022

ICD-10-CM Diagnostic Codes, 2022 Version

Description

A dataset containing the 2022 version of the ICD10-CM coding system.

Usage

icd10cm_2022

Format

A data frame with 72,750 rows and 2 variables:

Code ICD-10-CM diagnostic code

Description Description of each code

Note

The R code used to download and process the dataset from the CDC website is available [here](#).

icd10_2009

ICD-10 Diagnostic Codes, 2009 Version

Description

A dataset containing the 2009 version of the ICD-10 codes.

Usage

icd10_2009

Format

A data frame with 10,817 rows and 4 variables:

Code ICD-10 diagnostic code

Code.clean ICD-10 diagnostic code, removing all punctuation

ICD.title Code description, in plain English.

Status Additional information, if available.

Note

The R code used to download and process the dataset from the CDC website is available [here](#).

Source

CDC Website: <https://goo.gl/6e2mvb>

icd10_2011

ICD-10 Diagnostic Codes, 2011 Version

Description

A dataset containing the 2011 version of the ICD-10 codes.

Usage

`icd10_2011`

Format

A data frame with 10,856 rows and 4 variables:

Code ICD-10 diagnostic code

Code.clean ICD-10 diagnostic code, removing all punctuation

ICD.title Code description, in plain English.

Status Additional information, if available.

Note

The R code used to download and process the dataset from the CDC website is available [here](#).

Source

CDC Website: <https://goo.gl/rcTJJ2>

icd9_2015

ICD-9 Diagnostic Codes, 2015 Version (v32)

Description

A dataset containing the version of the ICD-9 codes effective October 1, 2014.

Usage

icd9_2015

Format

A data frame with 14,567 rows and 3 variables:

Code ICD-9 diagnostic code

Long_description Long description of each code

Short_description Short description of each code

Note

The R code used to download and process the dataset from the CMS.gov website is available [here](#).

Source

CMS.gov Website: <https://www.cms.gov/Medicare/Coding/ICD9ProviderDiagnosticCodes/codes.html>

nhds2010

Adult same-day discharges, 2010

Description

A dataset containing adult same-day discharges from 2010, obtained from Stata 17.

Usage

nhds2010

Format

A data frame with 2,210 rows and 15 variables:

ageu Units for age
age Age
sex Sex
race Race
month Discharge month
status Discharge status
region Region
atype Type of admission
dx1 Diagnosis 1, ICD9-CM
dx2 Diagnosis 2, ICD9-CM
dx3 Diagnosis 3, ICD9-CM, imported incorrectly
dx3corr Diagnosis 3, ICD9-CM, corrected
pr1 Procedure 1
wgt Frequency weight
recid Order of record (raw data)

Note

The R code used to download and process the dataset from Stata is available [here](#).

sample_diag

Simulate ICD-10 and ICD-9 diagnostic codes

Description

A simple function to simulate ICD-10 and ICD-9 diagnostic codes at random.

Usage

```
sample_diag(n = 1, version = "ICD10_2011")
```

Arguments

n	Number of ICD codes to simulate.
version	The version of the ICD coding scheme to use. Possible choices are ICD10_2009, ICD10_2011, and ICD9_2015; defaults to ICD10_2011. See icd10_2009 , icd10_2011 , and icd9_2015 for further information on the different schemes.

Value

A vector of n ICD diagnostic codes.

Examples

```
# Simulate 10 ICD-10 codes
sample_diag(10)

# Simulate a tidy dataset with 15 individuals and 200 rows
set.seed(1)
x <- data.frame(
  id = sample(1:15, size = 200, replace = TRUE),
  code = sample_diag(n = 200),
  stringsAsFactors = FALSE
)
head(x)
```

<i>score</i>	<i>Compute (weighted) comorbidity scores</i>
--------------	--

Description

Compute (weighted) comorbidity scores

Usage

```
score(x, weights = NULL, assign0)
```

Arguments

- | | |
|----------------|---|
| <i>x</i> | An object of class <code>comorbidity</code> returned by a call to the <code>comorbidity()</code> function. |
| <i>weights</i> | The weighting system to be used. This will depend on the mapping algorithm. Possible values for the Charlson index are: <ul style="list-style-type: none"> • <code>charlson</code>, for the original weights by Charlson et al. (1987); • <code>quan</code>, for the revised weights by Quan et al. (2011). Possible values for the Elixhauser score are: • <code>vw</code>, for the weights by van Walraven et al. (2009); • <code>swiss</code>, for the Swiss Elixhauser weights by Sharma et al. (2021). Defaults to <code>NULL</code> , in which case an unweighted score will be used. |
| <i>assign0</i> | Apply a hierarchy of comorbidities: should a comorbidity be present in a patient with different degrees of severity, then the milder form will be assigned a value of 0 when calculating the score. By doing this, a type of comorbidity is not counted more than once in each patient. The comorbidities that are affected by this argument are: |

- "Mild liver disease" (`mld`) and "Moderate/severe liver disease" (`msld`) for the Charlson score;
- "Diabetes" (`diab`) and "Diabetes with complications" (`diabwc`) for the Charlson score;
- "Cancer" (`canc`) and "Metastatic solid tumour" (`metacanc`) for the Charlson score;
- "Hypertension, uncomplicated" (`hypunc`) and "Hypertension, complicated" (`hypc`) for the Elixhauser score;
- "Diabetes, uncomplicated" (`diabunc`) and "Diabetes, complicated" (`diabc`) for the Elixhauser score;
- "Solid tumour" (`solidtum`) and "Metastatic cancer" (`metacanc`) for the Elixhauser score.

Value

A numeric vector with the (weighted) comorbidity score for each subject from the input dataset.

References

Charlson ME, Pompei P, Ales KL, et al. *A new method of classifying prognostic comorbidity in longitudinal studies: development and validation*. Journal of Chronic Diseases 1987; 40:373-383.

Quan H, Li B, Couris CM, et al. *Updating and validating the Charlson Comorbidity Index and Score for risk adjustment in hospital discharge abstracts using data from 6 countries*. American Journal of Epidemiology 2011; 173(6):676-682.

van Walraven C, Austin PC, Jennings A, Quan H and Forster AJ. *A modification of the Elixhauser comorbidity measures into a point system for hospital death using administrative data*. Medical Care 2009; 47(6):626-633.

Sharma N, Schwendimann R, Endrich O, et al. *Comparing Charlson and Elixhauser comorbidity indices with different weightings to predict in-hospital mortality: an analysis of national inpatient data*. BMC Health Services Research 2021; 21(13).

Examples

```
set.seed(1)
x <- data.frame(
  id = sample(1:15, size = 200, replace = TRUE),
  code = sample_diag(200),
  stringsAsFactors = FALSE
)

# Charlson score based on ICD-10 diagnostic codes:
x1 <- comorbidity(x = x, id = "id", code = "code", map = "charlson_icd10_quan", assign0 = FALSE)
score(x = x1, weights = "charlson", assign0 = FALSE)

# Elixhauser score based on ICD-10 diagnostic codes:
x2 <- comorbidity(x = x, id = "id", code = "code", map = "elixhauser_icd10_quan", assign0 = FALSE)
score(x = x2, weights = "vw", assign0 = FALSE)
```

Index

```
* datasets
  australia10, 2
  icd10_2009, 8
  icd10_2011, 9
  icd10cm_2017, 7
  icd10cm_2018, 7
  icd10cm_2022, 8
  icd9_2015, 10
  nhds2010, 10

  australia10, 2
  available_algorithms, 3

  comorbidity, 3
  comorbidity(), 12
  comorbidity-package, 2

  icd10_2009, 8, 11
  icd10_2011, 9, 11
  icd10cm_2017, 7
  icd10cm_2018, 7
  icd10cm_2022, 8
  icd9_2015, 10, 11

  make.names(), 4

  nhds2010, 10

  sample_diag, 11
  score, 12

  utils::View(), 4, 6
```