

# Package ‘condir’

December 1, 2020

**Title** Computation of P Values and Bayes Factors for Conditioning Data

**Version** 0.1.3

**Author** Angelos-Miltiadis Kryptos <amkryptos@gmail.com>

**Maintainer** Angelos-Miltiadis Kryptos <amkryptos@gmail.com>

**Date** 2020-12-01

**Description** Set of functions for the easy analyses of conditioning data.

**Depends** R (>= 3.6.0),

**License** GPL-3

**LazyData** true

**RoxygenNote** 7.1.1

**Encoding** UTF-8

**Imports** BayesFactor (>= 0.9.12), stats (>= 3.3.2), knitr (>= 1.28),  
xtable (>= 1.8.2), psych (>= 1.9.12), graphics (>= 3.3.2),  
effsize (>= 0.7.8), shiny (>= 1.4.0)

**URL** <https://github.com/AngelosPsy/condir>

**BugReports** <https://github.com/AngelosPsy/condir/issues>

**Suggests** rmarkdown, testthat

**VignetteBuilder** knitr

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2020-12-01 12:20:05 UTC

## R topics documented:

csCompare	2
csPlot	4
csReport	5
csRobustnessPlot	6
csSensitivity	8

csShine	9
csTable	10
roundBF	10

## Index 11

---

csCompare	<i>Statistically compare CRs towards two CSs</i>
-----------	--

---

### Description

Compare CRs towards two CSs within a frequentist and a Bayesian framework.

### Usage

```
csCompare(
  cs1,
  cs2,
  group = NULL,
  data = NULL,
  alternative = "two.sided",
  conf.level = 0.95,
  mu = 0,
  rscale = 0.707,
  descriptives = TRUE,
  out.thres = 3,
  boxplot = TRUE
)
```

### Arguments

cs1	a numeric vector of values. If the data argument is defined, it can refer to either the column index or the column name of the data object. See Details for more information.
cs2	a numeric vector of values. If the data argument is defined, it can refer to either the column index or the column name of the data object. See Details for more information.
group	column index or name that contain the group data. See Details for more information.
data	numeric matrix or data frame that contains the relevant data.
alternative	a character string for the specification of the alternative hypothesis. Possible values: "two.sided" (default), "greater" or "less".
conf.level	Interval's confidence level.
mu	a numeric value for the mean value or mean difference.
rscale	the scale factor for the prior used in the Bayesian t.test.
descriptives	Returns basic descriptive statistics for cs1 and cs2.

<code>out.thres</code>	The threshold for detecting outliers (default is 3). If set to 0, no outliers analysis will be performed. See <code>Details</code> below for more information.
<code>boxplot</code>	Should a boxplot of the variables be produced (default is TRUE)?

### Details

`csCompare` performs both a student t-test (using the `stats::t.test` function) and a Bayesian t-test (using the `BayesFactor::ttest.tstat`). If `cs1` and/or `cs2` are or refer to multiple columns of a matrix or a `data.frame`, then the row means are computed before the t-tests are performed. In case group is `NULL`, paired-samples t-tests will be run. In case the group is different than `NULL`, then the `csCompare` first computes difference scores between the `cs1` and the `cs2` (i.e., `cs1 - cs2`). In case the group argument is defined but, after removal of NA's (`stats::na.omit`), only one group is present, a paired samples t-test is run. In case of independent samples t-test, the function runs a Welch's t-test.

Regarding outliers, those are detected based on the deviations from the standardized residuals of each test. For example, in case of a paired-samples t-test, the `csCompare` function will run an additional regression for detecting deviations (defined in the `out.thres` argument) from the standardized residuals. The detected outliers are removed from both the frequentists and Bayesian analyses.

### Value

The function returns (at least) 3 list objects. These are: `descriptives`, `freq.results`, and `bayes.results`. In case outliers are detected, then the outlier analyses are returned as well with the name `res.out` as prefix to all list objects. For example, the descriptive statistics of the outlier analyses, can be indexed by using `obj$res.out$descriptives`, with `obj` being the object of the `csCompare` results.

The values of the `descriptives` are described in `psych::describe`.

The values of the `freq.results` are: `method`: which test was run.

`alternative`: the alternative hypothesis.

`WG1`, `WG2`: the Shapiro test values, separately for group 1 and group 2. In case of a paired-samples t-test, the `WG2` is 0.

`WpG1`, `WpG2`: the p-values of Shapiro test, separately for group 1 and group 2. In case of a paired-samples t-test, the `WpG2` is 0.

`null.value`: The value defined by `mu` (see above).

`LCI`, `HCI`: The low (LCI) and high (HCI) bounds of the confidence intervals.

`t.statistic`: Logical.

`df`: The degrees of freedom of the t-test performed.

`p.value`: The p-value of the performed t-test.

`cohenD`: The Cohen's d for the performed t-test.

`cohenDM`: The magnitude of the resulting Cohen's d.

`hedgesG`: The Hedge's g for the performed t-test.

`hedgesGM`: The magnitude of the resulting Hedge's g.

The values of the `bayes.results` are:

LNI, HNI: The low (LNI) and high (HNI) intervals of the hypothesis to test.

rscale: The used scale (see rscale argument above).

bf10: The BF10.

bf01: The BF01.

propError: The proportional error of the computed Bayes factor.

## References

Kryptos, A. M., Klugkist, I., & Engelhard, I. M. (2017). Bayesian hypothesis testing for human threat conditioning research: An introduction and the condir R package. *European Journal of Psychotraumatology*, 8.

Rouder, J. N., Speckman, P. L., Sun, D., Morey, R. D., & Iverson, G. (2009). Bayesian t-tests for accepting and rejecting the null hypothesis. *Psychonomic Bulletin & Review*, 16, 225-237

## See Also

[t.test](#), [ttest.tstat](#)

## Examples

```
set.seed(1000)
csCompare(cs1 = rnorm(n = 100, mean = 10), cs2 = rnorm(n = 100, mean = 9))
```

---

csPlot

*Plot CRs for each CS*

---

## Description

Plot the mean of median of each CRs, for each CS

## Usage

```
csPlot(
  cs1,
  cs2,
  group = NULL,
  data = NULL,
  ylab = "CRs",
  col = c("black", "grey"),
  legend = c("cs1", "cs2")
)
```

## Arguments

cs1	a numeric vector of values. If the data argument is defined, it can refer to either the column index or the column name of the data object. See <code>Details</code> for more information.
cs2	a numeric vector of values. If the data argument is defined, it can refer to either the column index or the column name of the data object. See <code>Details</code> for more information.
group	column index or name that contain the group data. See <code>Details</code> for more information.
data	numeric matrix or data frame that contains the relevant data.
ylab	Label for the x-axis
col	The color of the error bars to be used (either given as a numeric vector or a character string). The length of the chosen colors should be equal to the length of the legend names otherwise a warning is returned.
legend	The legend names to be used. The length of the legend labels should be the same as the length of the color string, otherwise a warning is returned.

## Details

`csCompare` performs both a student t-test (using the `stats::t.test` function) and a Bayesian t-test (using the `BayesFactor::ttest.tstat`). In case `group` is not defined, paired-samples t-tests are run. In case the `group` is defined, then the `csCompare` first computes difference scores between the `cs1` and the `cs2` (i.e., `cs1 - cs2`). In case the `group` argument is defined but, after removal of NA's (`stats::na.omit`), only one group is defined, a paired samples t-test is run.

## See Also

[t.test](#), [ttest.tstat](#)

## Examples

```
set.seed(1000)
csPlot(cs1 = rnorm(n = 100, mean = 10), cs2 = rnorm(n = 100, mean = 9))
```

---

csReport

*Report results of conditioning data*

---

## Description

Report results of data analyses run with the `csCompare`.

**Usage**

```
csReport(
  csCompareObj = NULL,
  csSensitivityObj = NULL,
  save = FALSE,
  fileName = "report",
  alphaLevel = 0.05,
  interpretation = FALSE
)
```

**Arguments**

csCompareObj	a list or data frame returned from the csCompare function. The object should be of class csCompare.
csSensitivityObj	Sensitivity analysis results returned from the csSensitivity function. The object should be of class csSensitivity.
save	If code argument is set to FALSE (default), the results are printed on the screen. Otherwise, a '.txt' file with the report is generated.
fileName	The file name of the produced report. The argument is ignored if save is set to FALSE.
alphaLevel	The alpha level to be used for determining significant or non-significant results.
interpretation	Should an interpretation of the results be included? (FALSE). In case of the Bayesian results, the results are interpreted according to Lee and Wagenmakers (2013).

**Examples**

```
set.seed(1000)
tmp <- csCompare(cs1 = rnorm(n = 100, mean = 10),
  cs2 = rnorm(n = 100, mean = 9))
csReport(tmp)
```

---

csRobustnessPlot      *Plot robustness results*

---

**Description**

Plots the results of robustness test

**Usage**

```
csRobustnessPlot(
  cs1,
  cs2,
  group = NULL,
```

```

data = NULL,
alternative = "two.sided",
conf.level = 0.95,
mu = 0,
rscaleSens = c("medium", "wide", "ultrawide"),
BF01 = TRUE,
ylimz = NULL,
sensitivity = FALSE
)

```

### Arguments

cs1	a numeric vector of values. If the data argument is defined, it can refer to either the column index or the column name of the data object. See Details for more information.
cs2	a numeric vector of values. If the data argument is defined, it can refer to either the column index or the column name of the data object. See Details for more information.
group	column index or name that contain the group data. See Details for more information.
data	numeric matrix or data frame that contains the relevant data.
alternative	a character string for the specification of the alternative hypothesis. Possible values: "two.sided" (default), "greater" or "less".
conf.level	Interval's confidence level.
mu	a numeric value for the mean value or mean difference.
rscaleSens	the scale factor for the prior used in the Bayesian t.test
BF01	Should the BF01 be plotted (default is set to TRUE). If FALSE, the BF10 is plotted.
ylimz	the limits of the y-axis (default to NULL).
sensitivity	Should the sensitivity results be returned (default is set to FALSE).

### Details

This plot template is influenced by the JASP way (<https://jasp-stats.org/>) for plotting sensitivity analysis results. On the x-axis or the width of the Cauchy's Scale is plotted. On the y-axis either BF01 is plotted (if BF01 is set to TRUE) or BF10 (if BF01 is set to FALSE).

### References

- JASP Team (2019). JASP (Version 0.11.1)[Computer software].
- Kryptos, A. M., Klugkist, I., & Engelhard, I. M. (2017). Bayesian hypothesis testing for human threat conditioning research: An introduction and the condit R package. *European Journal of Psychotraumatology*, 8.

### See Also

[csCompare](#), [csSensitivity](#)

**Examples**

```
set.seed(1000)
csRobustnessPlot(cs1 = rnorm(n = 100, mean = 10),
cs2 = rnorm(n = 100, mean = 9))
```

---

csSensitivity

*Sensitivity analysis for the Bayes Factors of csCompare results*


---

**Description**

Perform a sensitivity analysis for the Bayes factors computed with the csCompare results

**Usage**

```
csSensitivity(
  cs1,
  cs2,
  group = NULL,
  data = NULL,
  alternative = "two.sided",
  conf.level = 0.95,
  mu = 0,
  rscaleSens = c(0.707, 1, 1.41),
  out.thres = 3
)
```

**Arguments**

cs1	a numeric vector of values. If the data argument is defined, it can refer to either the column index or the column name of the data object. See <code>Details</code> for more information.
cs2	a numeric vector of values. If the data argument is defined, it can refer to either the column index or the column name of the data object. See <code>Details</code> for more information.
group	column index or name that contain the group data. See <code>Details</code> for more information.
data	numeric matrix or data frame that contains the relevant data.
alternative	a character string for the specification of the alternative hypothesis. Possible values: "two.sided" (default), "greater" or "less".
conf.level	Interval's confidence level.
mu	a numeric value for the mean value or mean difference.
rscaleSens	the scale factor for the prior used in the Bayesian t.test
out.thres	The threshold for detecting outliers (default is 3). If set to 0, no outliers analysis will be performed. See <code>Details</code> below for more information.



## Details

csCompare performs both a student t-test (using the `stats::t.test` function) and a Bayesian t-test (using the `BayesFactor::ttest.tstat`). In case `group` is not defined, paired-samples t-tests are run. In case the `group` is defined, then the `csCompare` first computes difference scores between the `cs1` and the `cs2` (i.e., `cs1 - cs2`). In case the `group` argument is defined but, after removal of NA's (`stats::na.omit`), only one group is defined, a paired samples t-test is run.

## Value

The function returns a data frame with the results of the student t-test and the Bayesian t-test.

## References

Kryptos, A. M., Klugkist, I., & Engelhard, I. M. (2017). Bayesian hypothesis testing for human threat conditioning research: An introduction and the `condir` R package. *European Journal of Psychotraumatology*, 8.

## See Also

[csCompare](#), [t.test](#), [ttest.tstat](#)

## Examples

```
set.seed(1000)
csSensitivity(cs1 = rnorm(n = 100, mean = 10),
             cs2 = rnorm(n = 100, mean = 9))
```

---

csShine

*Shiny app for the condir package*

---

## Description

Launches a Shiny app for performing the core analyses included in `condir`

## Usage

```
csShine()
```

## Details

The function can be called without any arguments (i.e., `csShine()`). For the interface, we used a `css` template available at <http://getbootstrap.com>.

## References

Kryptos, A. M., Klugkist, I., & Engelhard, I. M. (2017). Bayesian hypothesis testing for human threat conditioning research: An introduction and the `condir` R package. *European Journal of Psychotraumatology*, 8.

---

csTable	<i>Produce tables of csCompare results</i>
---------	--

---

**Description**

It provides wrapper functions for generating tables of different types of computer languages.

**Usage**

```
csTable(csCompareObj, typeOfTable = "latex")
```

**Arguments**

csCompareObj    a list or data frame returned from the csCompare function  
 typeOfTable    The type of table to be generated. See details

**Details**

csCompare generates tables of different languages. The options are latex, and markdown.

**Examples**

```
tmp <- csCompare(cs1 = c(1, 2, 3, 1, 4), cs2 = c(10, 12, 12, 31, 13))
csTable(tmp)
```

---

roundBF	<i>Local function for determining how BF is reported</i>
---------	--

---

**Description**

Function used for determining the symbol, and the form, of the BF reported.

**Usage**

```
roundBF(bf, rscale, BF01 = TRUE)
```

**Arguments**

bf                    Logical. The BF.  
 rscale                The rscale that was used.  
 BF01                 Whether the BF01 (default) should be reported or not

# Index

csCompare, [2](#), [7](#), [9](#)  
csPlot, [4](#)  
csReport, [5](#)  
csRobustnessPlot, [6](#)  
csSensitivity, [7](#), [8](#)  
csShine, [9](#)  
csTable, [10](#)

roundBF, [10](#)

t.test, [4](#), [5](#), [9](#)  
ttest.tstat, [4](#), [5](#), [9](#)