

Package ‘dpcc’

June 1, 2021

Type Package

Title Dynamic Programming for Convex Clustering

Version 1.0.0

Author Bingyuan Zhang, Jie Chen, Yoshikazu Terada

Maintainer Bingyuan Zhang <zhang@sigmath.es.osaka-u.ac.jp>

Description Use dynamic programming method to solve l1 convex clustering with identical weights.

License MIT + file LICENSE

Encoding UTF-8

LazyData False

RoxygenNote 7.1.1

LinkingTo Rcpp

Imports Rcpp

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

NeedsCompilation yes

Repository CRAN

Date/Publication 2021-06-01 06:40:02 UTC

R topics documented:

cdp	2
cpaint	2
find_lambda	3

Index	4
--------------	----------

cdp

L1 convex clustering with a single lambda.

Description

L1 convex clustering with a single lambda.

Usage

```
cdp(X, lam)
```

Arguments

X a data matrix of n * p or a data vector with length n.
lam a tuning parameter.

Details

A list with length p equal to the dimension of the data matrix. Each dimension includes a vector of the estimated centroids.

Value

the estimated centroids.

Examples

```
# generate a data matrix with n = 10 and p = 2.  
X = matrix(rnorm(10*2), 10, 2)  
lam = find_lambda(X)/2  
# set a tuning parameter lambda.  
cdp(X, lam)
```

cpaint*L1 convex clustering with a lambda sequence.*

Description

L1 convex clustering with a lambda sequence.

Usage

```
cpaint(X, lam)
```

Arguments

`X` a data matrix of $n * p$ or a data vector with length n .
`lam` a sequence of lambdas.

Details

A list with length p equal to the dimension of the data matrix. Each dimension includes a sequence of vectors. Each vector includes the estimated centroids with a certain tuning parameter lambda.

Value

A sequence of estimated centroids.

Examples

```
# generate a data matrix with n = 10 and p = 2.
X = matrix(rnorm(10*2), 10, 2)
# set the biggest lambda in the sequence.
lam_max = find_lambda(X)
# set the length of the sequence.
K = 10
# equally separate the sequence with K.
Lam = sapply(1:K, function(i) i/K*lam_max)
cpaint(X,Lam)
```

find_lambda	<i>Return the lambda which causes all the points become fused into one cluster.</i>
-------------	---

Description

Return the lambda which causes all the points become fused into one cluster.

Usage

```
find_lambda(X)
```

Arguments

`X` data matrix of $n * p$

Value

the biggest lambda

Examples

```
X = matrix(rnorm(3*2), 3, 2)
find_lambda(X)
```

Index

`cdp`, 2
`cpaint`, 2
`find_lambda`, 3