

# Package ‘fauxnaif’

August 12, 2022

**Title** Convert Values to NA

**Version** 0.7.1

**Description** Provides a replacement for `dplyr::na_if()`. Allows you to specify multiple values to be replaced with NA using a single function.

**License** MIT + file LICENSE

**URL** <https://fauxnaif.rossellhayes.com/>,  
<https://github.com/rossellhayes/fauxnaif>

**BugReports** <https://github.com/rossellhayes/fauxnaif/issues>

**Depends** R (>= 3.5)

**Imports** cli, rlang (>= 1.0.0)

**Suggests** covr, dplyr, haven, knitr, magrittr, rmarkdown, testthat (>= 3.0.0), tibble, tidyr, vctrs, withr

**VignetteBuilder** knitr

**Config/testthat/edition** 3

**Encoding** UTF-8

**Language** en-US

**LazyData** true

**RoxygenNote** 7.2.1

**NeedsCompilation** no

**Author** Alexander Rossell Hayes [aut, cre, cph]  
(<https://orcid.org/0000-0001-9412-0457>)

**Maintainer** Alexander Rossell Hayes <[alexander@rossellhayes.com](mailto:alexander@rossellhayes.com)>

**Repository** CRAN

**Date/Publication** 2022-08-12 17:30:02 UTC

## R topics documented:

<code>faux_census</code> . . . . .	2
<code>na_if_in</code> . . . . .	2

**Index****5**


---

faux_census	<i>A small sample of a fabricated census-like dataset</i>
-------------	---

---

**Description**

A dataset containing fake demographic data, used in the fauxnaif vignette.

**Usage**

```
faux_census
```

**Format**

A tibble with 20 rows and 6 variables.

**Source**

Fabricated

---

na_if_in	<i>Convert values to NA</i>
----------	-----------------------------

---

**Description**

This is a replacement for `dplyr::na_if()`. It is useful if you want to convert annoying values to NA. Unlike `dplyr::na_if()`, this function allows you to specify multiple values to be replaced with NA at the same time.

- `na_if_in()` replaces values that match its arguments with NA.
- `na_if_not()` replaces values that *do not* match its arguments with NA.

**Usage**

```
na_if_in(x, ...)
```

```
na_if_not(x, ...)
```

**Arguments**

`x` Vector to modify

`...` Values to replace with NA, specified as either:

- An object, vector of objects, or list of objects.
- A function (including a [purrr-style lambda function](#)) that returns a logical vector of the same length as `x`. See section "Formulas" for more details.

**Value**

A modified version of `x` with selected values replaced with NA.

**Formulas**

These functions accept one-sided formulas that can evaluate to logical vectors of the same length as `x`. The input is represented in these conditional statements as `."`. Valid formulas take the form `~ . < 0`. See examples.

**See Also**

[dplyr::na\\_if\(\)](#) to replace a single value with NA.

[dplyr::coalesce\(\)](#) to replace missing values with a specified value.

[tidyr::replace\\_na\(\)](#) to replace NA with a value.

[dplyr::recode\(\)](#) and [dplyr::case\\_when\(\)](#) to more generally replace values.

**Examples**

```
x <- sample(c(1:5, 99))
# We can replace 99...
# ... explicitly
na_if_in(x, 99)
# ... by specifying values to keep
na_if_not(x, 1:5)
# ... or by using a formula
na_if_in(x, ~ . > 5)

messy_string <- c("abc", "", "def", "NA", "ghi", 42, "jkl", "NULL", "mno")
# We can replace unwanted values...
# ... one at a time
clean_string <- na_if_in(messy_string, "")
clean_string <- na_if_in(clean_string, "NA")
clean_string <- na_if_in(clean_string, 42)
clean_string <- na_if_in(clean_string, "NULL")
clean_string
# ... or all at once
na_if_in(messy_string, "", "NA", "NULL", 1:100)
na_if_in(messy_string, c("", "NA", "NULL", 1:100))
na_if_in(messy_string, list("", "NA", "NULL", 1:100))
# ... or using a clever formula
grepl("[a-z]{3,}", messy_string)
na_if_not(messy_string, ~ grepl("[a-z]{3,}", .))

# na_if_in() is particularly useful inside dplyr::mutate
library(dplyr)
faux_census %>%
  mutate(
    state = na_if_in(state, "Canada"),
    age   = na_if_in(age, ~ . < 18, ~ . > 120)
  )
```

```
# This function handles vector values differently than dplyr,  
# and returns a different result with vector replacement values:  
na_if_in(1:5, 5:1)  
dplyr::na_if(1:5, 5:1)
```

# Index

## \* datasets

faux\_census, 2

dplyr::case\_when(), 3

dplyr::coalesce(), 3

dplyr::na\_if(), 2, 3

dplyr::recode(), 3

faux\_census, 2

na\_if\_in, 2

na\_if\_not (na\_if\_in), 2

purrr-style lambda function, 2

tidyr::replace\_na(), 3