

Package ‘flextable’

August 9, 2022

Type Package

Title Functions for Tabular Reporting

Version 0.7.3

Description Create pretty tables for 'HTML', 'PDF', 'Microsoft Word' and 'Microsoft PowerPoint' documents from 'R Markdown'. Functions are provided to let users create tables, modify and format their content. It also extends package 'officer' that does not contain any feature for customized tabular reporting.

License GPL-3

Imports stats, utils, grDevices, graphics, officer (>= 0.4.1), rmarkdown, knitr, htmltools, xml2, data.table (>= 1.13.0), uuid (>= 0.1-4), gdtools (>= 0.1.6), rlang, base64enc

RoxygenNote 7.2.1

Suggests testthat (>= 2.1.0), doconv (>= 0.1.4), xtable, webshot, magick, ggplot2, scales, broom, broom.mixed, mgcv, cluster, lme4, nlme, bookdown, equatags, commonmark, pdftools

Encoding UTF-8

URL <https://ardata-fr.github.io/flextable-book/>,
<https://davidgohel.github.io/flextable/>

BugReports <https://github.com/davidgohel/flextable/issues>

VignetteBuilder knitr

NeedsCompilation no

Author David Gohel [aut, cre], Clementine Jager [ctb], Quentin Fazilleau [ctb], Maxim Nazarov [ctb] (rmarkdown for docx output), Titouan Robert [ctb], Michael Barrowman [ctb] (inline footnotes), Atsushi Yasumoto [ctb] (support for bookdown cross reference), Paul Julian [ctb] (support for gam objects), Sean Browning [ctb] (work on footnote positioning system)

Maintainer David Gohel <david.gohel@ardata.fr>

Repository CRAN

Date/Publication 2022-08-09 14:30:02 UTC

R topics documented:

flextable-package	5
add_body	5
add_body_row	6
add_footer	7
add_footer_lines	9
add_footer_row	10
add_header	11
add_header_lines	12
add_header_row	13
add_latex_dep	14
align	15
append_chunks	16
as_b	17
as_bracket	18
as_chunk	19
as_equation	20
as_flextable	21
as_flextable.gam	21
as_flextable.glm	22
as_flextable.grouped_data	23
as_flextable.htest	24
as_flextable.kmeans	25
as_flextable.lm	26
as_flextable.merMod	26
as_flextable.pam	27
as_flextable.tabulator	28
as_flextable.xtable	30
as_grouped_data	32
as_highlight	33
as_i	33
as_image	34
as_paragraph	35
as_raster	36
as_sub	37
as_sup	38
as_word_field	39
autofit	40
before	42
bg	43
body_add_flextable	44
bold	46

border_inner	46
border_inner_h	47
border_inner_v	48
border_outer	49
border_remove	50
colformat_char	50
colformat_date	51
colformat_datetime	52
colformat_double	53
colformat_image	55
colformat_int	56
colformat_lgl	57
colformat_num	58
color	59
colorize	61
compose	61
continuous_summary	63
delete_part	64
df_printer	64
dim.flextable	65
dim_pretty	66
empty_blanks	67
fit_to_width	68
fix_border_issues	69
flextable	69
flextable_dim	71
flextable_html_dependency	72
flextable_to_rmd	72
fmt_2stats	74
font	75
fontsize	76
footers_flextable_at_bkm	77
footnote	78
fp_border_default	79
fp_text_default	80
get_flextable_defaults	82
gg_chunk	83
headers_flextable_at_bkm	84
height	84
highlight	86
hline	87
hline_bottom	88
hline_top	89
hrule	90
htmltools_value	91
hyperlink_text	91
italic	92
knit_print.flextable	93

linerange	97
line_spacing	98
lollipop	99
merge_at	101
merge_h	102
merge_h_range	102
merge_none	103
merge_v	104
minibar	105
ncol_keys	106
nrow_part	107
padding	108
ph_with.flextable	109
plot.flextable	110
plot_chunk	111
prepend_chunks	112
print.flextable	113
proc_freq	114
rotate	115
save_as_docx	116
save_as_html	117
save_as_image	118
save_as_pptx	120
separate_header	121
set_caption	122
set_flextable_defaults	124
set_formatter	126
set_header_footer_df	128
set_header_labels	129
set_table_properties	130
shift_table	131
style	134
summarizor	135
surround	137
tabulator	138
tabulator_colnames	142
theme_alafoli	143
theme_booktabs	145
theme_box	146
theme_tron	147
theme_tron_legacy	148
theme_vader	149
theme_vanilla	150
theme_zebra	151
use_df_printer	152
use_model_printer	152
valign	153
vline	154

vline_left	155
vline_right	156
void	157
width	157
Index	159

Description

The flextable package facilitates access to and manipulation of tabular reporting elements from R.

The documentation of functions can be opened with command `help(package = "flextable")`.

To learn more about flextable, start with the vignettes: `browseVignettes(package = "flextable")`.

`flextable()` function is producing flexible tables where each cell can contain several chunks of text with their own set of formatting properties (bold, font color, etc.). Function `compose()` lets customise text of cells.

See Also

<https://davidgohel.github.io/flextable/>, `flextable()`

Description

The function adds a list of values to be inserted as new rows in the body. The values are inserted in existing columns of the input data of the flextable. Rows can be inserted at the top or the bottom of the body.

If some columns are not provided, they will be replaced by NA and displayed as empty.

Usage

```
add_body(x, top = TRUE, ..., values = NULL)
```

Arguments

<code>x</code>	a flextable object
<code>top</code>	should the rows be inserted at the top or the bottom.
<code>...</code>	named arguments (names are data colnames) of values to add. It is important to insert data of the same type as the original data, otherwise it will be transformed (probably into strings if you add a character where a double is expected). This makes possible to still format cell contents with the <code>colformat_*</code> functions, for example <code>colformat_num()</code> .
<code>values</code>	a list of name-value pairs of labels or values, names should be existing <code>col_key</code> values. This argument can be used instead of <code>...</code> for programming purpose (If <code>values</code> is supplied argument <code>...</code> is ignored).

See Also

[flextable\(\)](#)

Other functions that add lines in the table: [add_body_row\(\)](#), [add_footer_lines\(\)](#), [add_footer_row\(\)](#), [add_footer\(\)](#), [add_header_row\(\)](#), [add_header\(\)](#)

Examples

```
ft <- flextable(head(iris),
  col_keys = c(
    "Species", "Sepal.Length", "Petal.Length",
    "Sepal.Width", "Petal.Width"
  )
)

ft <- add_body(
  x = ft, Sepal.Length = 1:5,
  Sepal.Width = 1:5 * 2, Petal.Length = 1:5 * 3,
  Petal.Width = 1:5 + 10, Species = "Blah", top = FALSE
)

ft <- theme_booktabs(ft)
ft
```

`add_body_row`

Add body labels

Description

Add a row of new columns labels in body part. Labels can be spanned along multiple columns, as merged cells.

Labels are associated with a number of columns to merge that default to one if not specified. In this case, you have to make sure that the number of labels is equal to the number of columns displayed.

The function can add only one single row by call.

Usage

```
add_body_row(x, top = TRUE, values = list(), colwidths = integer(0))
```

Arguments

x	a flextable object
top	should the row be inserted at the top or the bottom.
values	values to add. It can be a list or a character() vector. If it is a list, it must be a named list using the names of the columns of the original data.frame or the colkeys; this is the recommended method because it allows to keep the original data types and therefore allows to perform conditional formatting. If a character, columns of the original data.frame stored in the flextable object are changed to character(); this is often not an issue with footer and header but can be inconvenient if adding rows into body as it will change data types to character and prevent efficient conditional formatting.
colwidths	the number of columns to merge in the row for each label

See Also

[flextable\(\)](#), [add_header_row\(\)](#)

Other functions that add lines in the table: [add_body\(\)](#), [add_footer_lines\(\)](#), [add_footer_row\(\)](#), [add_footer\(\)](#), [add_header_row\(\)](#), [add_header\(\)](#)

Examples

```
ft <- flextable(head(iris))
ft <- add_body_row(ft, values = list(1000), colwidths = 5)
ft
```

add_footer

Add column values as new lines in footer

Description

The function adds a list of values to be inserted as new rows in the footer. The values are inserted in existing columns of the input data of the flextable. Rows can be inserted at the top or the bottom of the footer.

If some columns are not provided, they will be replaced by NA and displayed as empty.

Usage

```
add_footer(x, top = TRUE, ..., values = NULL)
```

Arguments

x	a flextable object
top	should the rows be inserted at the top or the bottom.
...	named arguments (names are data colnames) of values to add. It is important to insert data of the same type as the original data, otherwise it will be transformed (probably into strings if you add a character where a double is expected). This makes possible to still format cell contents with the <code>colformat_*</code> functions, for example <code>colformat_num()</code> .
values	a list of name-value pairs of labels or values, names should be existing <code>col_key</code> values. This argument can be used instead of ... for programming purpose (If <code>values</code> is supplied argument ... is ignored).

Illustrations

See Also

Other functions that add lines in the table: `add_body_row()`, `add_body()`, `add_footer_lines()`, `add_footer_row()`, `add_header_row()`, `add_header()`

Other functions to add rows in header or footer: `add_footer_lines()`, `add_footer_row()`, `add_header_lines()`, `add_header_row()`, `add_header()`, `separate_header()`, `set_header_footer_df`, `set_header_labels()`

Examples

```

new_row <- as.list(colMeans(iris[, -5]))
new_row$Species <- "Means"

formatter <- function(x) sprintf("%.1f", x)

ft <- flextable(data = head(iris))
ft <- add_footer(ft, values = new_row)

# cosmetics
ft <- compose(
  x = ft, j = 1:4,
  value = as_paragraph(
    as_chunk(., formatter = formatter)
  ),
  part = "footer", use_dot = TRUE
)
ft <- align(ft, part = "footer", align = "right", j = 1:4)
ft

```

add_footer_lines	<i>Add labels as new rows in the footer</i>
------------------	---

Description

Add labels as new rows in the footer, where all columns are merged.

This is a sugar function to be used when you need to add labels in the footer, a footnote for example.

Usage

```
add_footer_lines(x, values = character(0), top = FALSE)
```

Arguments

x	a flextable object
values	a character vector, each element will be added as a new row.
top	should the row be inserted at the top or the bottom. Default to TRUE.

Illustrations

See Also

Other functions that add lines in the table: [add_body_row\(\)](#), [add_body\(\)](#), [add_footer_row\(\)](#), [add_footer\(\)](#), [add_header_row\(\)](#), [add_header\(\)](#)

Other functions to add rows in header or footer: [add_footer_row\(\)](#), [add_footer\(\)](#), [add_header_lines\(\)](#), [add_header_row\(\)](#), [add_header\(\)](#), [separate_header\(\)](#), [set_header_footer_df](#), [set_header_labels\(\)](#)

Examples

```
ft_1 <- flextable(head(iris))
ft_1 <- add_footer_lines(ft_1,
  values = c("blah 1", "blah 2"))
)
ft_1
```

`add_footer_row`*Add footer labels*

Description

Add a row of new columns labels in footer part. Labels can be spanned along multiple columns, as merged cells.

Labels are associated with a number of columns to merge that default to one if not specified. In this case, you have to make sure that the number of labels is equal to the number of columns displayed.

The function can add only one single row by call.

Usage

```
add_footer_row(x, top = TRUE, values = character(0), colwidths = integer(0))
```

Arguments

<code>x</code>	a flextable object
<code>top</code>	should the row be inserted at the top or the bottom.
<code>values</code>	values to add. It can be a list or a <code>character()</code> vector. If it is a list, it must be a named list using the names of the columns of the original <code>data.frame</code> or the <code>colkeys</code> ; this is the recommended method because it allows to keep the original data types and therefore allows to perform conditional formatting. If a <code>character</code> , columns of the original <code>data.frame</code> stored in the flextable object are changed to <code>character()</code> ; this is often not an issue with footer and header but can be inconvenient if adding rows into body as it will change data types to <code>character</code> and prevent efficient conditional formatting.
<code>colwidths</code>	the number of columns to merge in the row for each label

Illustrations

See Also

Other functions that add lines in the table: [add_body_row\(\)](#), [add_body\(\)](#), [add_footer_lines\(\)](#), [add_footer\(\)](#), [add_header_row\(\)](#), [add_header\(\)](#)

Other functions to add rows in header or footer: [add_footer_lines\(\)](#), [add_footer\(\)](#), [add_header_lines\(\)](#), [add_header_row\(\)](#), [add_header\(\)](#), [separate_header\(\)](#), [set_header_footer_df](#), [set_header_labels\(\)](#)

Examples

```
ft_1 <- flextable(head(iris))
ft_1 <- add_footer_row(ft_1,
  values = "blah blah", colwidths = 5
)
ft_1 <- add_footer_row(ft_1,
  values = c("blah", "blah"),
  colwidths = c(3, 2)
)
ft_1
```

add_header

Add column values as new lines in header

Description

The function adds a list of values to be inserted as new rows in the header. The values are inserted in existing columns of the input data of the flextable. Rows can be inserted at the top or the bottom of the header.

If some columns are not provided, they will be replaced by NA and displayed as empty.

Usage

```
add_header(x, top = TRUE, ..., values = NULL)
```

Arguments

x	a flextable object
top	should the rows be inserted at the top or the bottom.
...	named arguments (names are data colnames) of values to add. It is important to insert data of the same type as the original data, otherwise it will be transformed (probably into strings if you add a character where a double is expected). This makes possible to still format cell contents with the <code>colformat_*</code> functions, for example colformat_num() .
values	a list of name-value pairs of labels or values, names should be existing <code>col_key</code> values. This argument can be used instead of ... for programming purpose (If <code>values</code> is supplied argument ... is ignored).

Illustrations

Note

when repeating values, they can be merged together with function `merge_h()` and `merge_v()`.

See Also

Other functions that add lines in the table: [add_body_row\(\)](#), [add_body\(\)](#), [add_footer_lines\(\)](#), [add_footer_row\(\)](#), [add_footer\(\)](#), [add_header_row\(\)](#)
 Other functions to add rows in header or footer: [add_footer_lines\(\)](#), [add_footer_row\(\)](#), [add_footer\(\)](#), [add_header_lines\(\)](#), [add_header_row\(\)](#), [separate_header\(\)](#), [set_header_footer_df](#), [set_header_labels\(\)](#)

Examples

```
library(flextable)

fun <- function(x) {
  paste0(
    c("min: ", "max: "),
    formatC(range(x))
  )
}

new_row <- list(
  Sepal.Length = fun(iris$Sepal.Length),
  Sepal.Width = fun(iris$Sepal.Width),
  Petal.Width = fun(iris$Petal.Width),
  Petal.Length = fun(iris$Petal.Length)
)

ft_1 <- flextable(data = head(iris))
ft_1 <- add_header(ft_1, values = new_row, top = FALSE)
ft_1 <- append_chunks(ft_1, part = "header", i = 2, )
ft_1 <- theme_booktabs(ft_1, bold_header = TRUE)
ft_1 <- align(ft_1, align = "center", part = "all")
ft_1
```

add_header_lines *Add labels as new rows in the header*

Description

Add labels as new rows in the header, where all columns are merged.

This is a sugar function to be used when you need to add labels in the header, most of the time it will be used to adding titles on the top rows of the flextable.

Usage

```
add_header_lines(x, values = character(0), top = TRUE)
```

Arguments

x	a flextable object
values	a character vector, each element will be added as a new row.
top	should the row be inserted at the top or the bottom. Default to TRUE.

Illustrations

See Also

Other functions to add rows in header or footer: [add_footer_lines\(\)](#), [add_footer_row\(\)](#), [add_footer\(\)](#), [add_header_row\(\)](#), [add_header\(\)](#), [separate_header\(\)](#), [set_header_footer_df](#), [set_header_labels\(\)](#)

Examples

```
ft_1 <- flextable(head(iris))
ft_1 <- add_header_lines(ft_1, values = "blah blah")
ft_1 <- add_header_lines(ft_1, values = c("blah 1", "blah 2"))
ft_1 <- autofit(ft_1)
ft_1
```

`add_header_row`

Add header labels

Description

Add a row of new columns labels in header part. Labels can be spanned along multiple columns, as merged cells.

Labels are associated with a number of columns to merge that default to one if not specified. In this case, you have to make sure that the number of labels is equal to the number of columns displayed.

The function can add only one single row by call.

Usage

```
add_header_row(x, top = TRUE, values = character(0), colwidths = integer(0))
```

Arguments

<code>x</code>	a flextable object
<code>top</code>	should the row be inserted at the top or the bottom. Default to TRUE.
<code>values</code>	values to add, a character vector (as header rows contains only character values/columns) or a list.
<code>colwidths</code>	the number of columns used for each label

Illustrations

See Also

Other functions that add lines in the table: [add_body_row\(\)](#), [add_body\(\)](#), [add_footer_lines\(\)](#), [add_footer_row\(\)](#), [add_footer\(\)](#), [add_header\(\)](#)

Other functions to add rows in header or footer: [add_footer_lines\(\)](#), [add_footer_row\(\)](#), [add_footer\(\)](#), [add_header_lines\(\)](#), [add_header\(\)](#), [separate_header\(\)](#), [set_header_footer_df](#), [set_header_labels\(\)](#)

Examples

```
ft_1 <- flextable(head(iris))
ft_1 <- add_header_row(ft_1,
  values = "blah blah", colwidths = 5
)
ft_1 <- add_header_row(ft_1,
  values = c("blah", "blah"),
  colwidths = c(3, 2)
)
ft_1
```

add_latex_dep	<i>add latex dependencies</i>
---------------	-------------------------------

Description

Manually add flextable latex dependencies to the knitr session via [knit_meta_add\(\)](#).

When enabling caching in 'R Markdown' documents for PDF output, the flextable cached result is used directly. Call `add_latex_dep()` in a non cached chunk so that flextable latex dependencies are added to knitr metadata.

Usage

```
add_latex_dep(float = FALSE, wrapfig = FALSE)
```

Arguments

float	load package 'float'
wrapfig	load package 'wrapfig'

Examples

```
add_latex_dep()
```

align	<i>Set text alignment</i>
-------	---------------------------

Description

change text alignment of selected rows and columns of a flextable.

Usage

```
align(x, i = NULL, j = NULL, align = "left", part = "body")  
align_text_col(x, align = "left", header = TRUE, footer = TRUE)  
align_nottext_col(x, align = "right", header = TRUE, footer = TRUE)
```

Arguments

x	a flextable object
i	rows selection
j	columns selection
align	text alignment - a single character value, expected value is one of 'left', 'right', 'center', 'justify'.
part	partname of the table (one of 'all', 'body', 'header', 'footer')
header	should the header be aligned with the body
footer	should the footer be aligned with the body

Illustrations

See Also

Other sugar functions for table style: [bg\(\)](#), [bold\(\)](#), [color\(\)](#), [empty_blanks\(\)](#), [fontsize\(\)](#), [font\(\)](#), [highlight\(\)](#), [italic\(\)](#), [line_spacing\(\)](#), [padding\(\)](#), [rotate\(\)](#), [valign\(\)](#)

Examples

```
ft <- flextable(head(mtcars)[, 3:6])  
ft <- align(ft, align = "right", part = "all")  
ft <- theme_tron_legacy(ft)  
ft  
ftab <- flextable(mtcars)  
ftab <- align_text_col(ftab, align = "left")  
ftab <- align_nottext_col(ftab, align = "right")  
ftab
```

`append_chunks`*append chunks to flextable content*

Description

append chunks (for example chunk [as_chunk\(\)](#)) in a flextable.

Usage

```
append_chunks(x, ..., i = NULL, j = NULL, part = "body")
```

Arguments

x	a flextable object
...	chunks to be appended, see as_chunk() , gg_chunk() and other chunk elements for paragraph.
i	rows selection
j	column selection
part	partname of the table (one of 'body', 'header', 'footer')

Illustrations

See Also

[as_chunk\(\)](#), [as_sup\(\)](#), [as_sub\(\)](#), [colorize\(\)](#)

Other functions for mixed content paragraphs: [as_paragraph\(\)](#), [compose\(\)](#), [prepend_chunks\(\)](#)

Examples

```
library(flextable)
img.file <- file.path(R.home("doc"), "html", "logo.jpg")

ft_1 <- flextable(head(cars))

ft_1 <- append_chunks(ft_1,
  # where to append
  i = c(1, 3, 5),
  j = 1,
  # what to append
  as_chunk(" "),
  as_image(src = img.file, width = .20, height = .15)
)
ft_1 <- set_table_properties(ft_1, layout = "autofit")
ft_1
```

as_b	<i>bold chunk</i>
------	-------------------

Description

The function is producing a chunk with bold font.

It is used to add it to the content of a cell of the flextable with the functions [compose\(\)](#), [append_chunks\(\)](#) or [prepend_chunks\(\)](#).

Usage

```
as_b(x)
```

Arguments

x	value, if a chunk, the chunk will be updated
---	--

Illustrations

See Also

Other chunk elements for paragraph: [as_bracket\(\)](#), [as_chunk\(\)](#), [as_equation\(\)](#), [as_highlight\(\)](#), [as_image\(\)](#), [as_i\(\)](#), [as_sub\(\)](#), [as_sup\(\)](#), [as_word_field\(\)](#), [colorize\(\)](#), [gg_chunk\(\)](#), [hyperlink_text\(\)](#), [linerange\(\)](#), [lollipop\(\)](#), [minibar\(\)](#), [plot_chunk\(\)](#)

Examples

```
ft <- flextable( head(iris),  
                 col_keys = c("Sepal.Length", "dummy") )  
  
ft <- compose(ft, j = "dummy",  
              value = as_paragraph(  
                as_b(Sepal.Length)  
              ) )  
  
ft
```

as_bracket	<i>chunk with values in brackets</i>
------------	--------------------------------------

Description

The function is producing a chunk by pasting values and add the result in brackets.

It is used to add it to the content of a cell of the flextable with the functions [compose\(\)](#), [append_chunks\(\)](#) or [prepend_chunks\(\)](#).

Usage

```
as_bracket(..., sep = " ", p = "(", s = ")")
```

Arguments

...	text and column names
sep	separator
p	prefix, default to '('
s	suffix, default to ')'

Illustrations

See Also

Other chunk elements for paragraph: [as_b\(\)](#), [as_chunk\(\)](#), [as_equation\(\)](#), [as_highlight\(\)](#), [as_image\(\)](#), [as_i\(\)](#), [as_sub\(\)](#), [as_sup\(\)](#), [as_word_field\(\)](#), [colorize\(\)](#), [gg_chunk\(\)](#), [hyperlink_text\(\)](#), [linerange\(\)](#), [lollipop\(\)](#), [minibar\(\)](#), [plot_chunk\(\)](#)

Examples

```
ft <- flextable( head(iris),
  col_keys = c("Species", "Sepal", "Petal") )
ft <- set_header_labels(ft, Sepal="Sepal", Petal="Petal")
ft <- compose(ft, j = "Sepal",
  value = as_paragraph( as_bracket(Sepal.Length, Sepal.Width) ) )
ft <- compose(ft, j = "Petal",
  value = as_paragraph( as_bracket(Petal.Length, Petal.Width) ) )
ft
```

as_chunk	<i>chunk of text wrapper</i>
----------	------------------------------

Description

The function lets add formated text in flextable cells.

It is used to add it to the content of a cell of the flextable with the functions [compose\(\)](#), [append_chunks\(\)](#) or [prepend_chunks\(\)](#).

It should be used inside a call to [as_paragraph\(\)](#).

Usage

```
as_chunk(x, props = NULL, formatter = format_fun, ...)
```

Arguments

x	text or any element that can be formatted as text with function provided in argument <code>formatter</code> .
props	an officer::fp_text() object to be used to format the text. If not specified, it will be the default value corresponding to the cell.
formatter	a function that will format x as a character vector.
...	additional arguments for <code>formatter</code> function.

Illustrations

See Also

Other chunk elements for paragraph: [as_bracket\(\)](#), [as_b\(\)](#), [as_equation\(\)](#), [as_highlight\(\)](#), [as_image\(\)](#), [as_i\(\)](#), [as_sub\(\)](#), [as_sup\(\)](#), [as_word_field\(\)](#), [colorize\(\)](#), [gg_chunk\(\)](#), [hyperlink_text\(\)](#), [linerange\(\)](#), [lollipop\(\)](#), [minibar\(\)](#), [plot_chunk\(\)](#)

Examples

```
library(officer)

ft <- flextable( head(iris))

ft <- compose( ft, j = "Sepal.Length",
  value = as_paragraph(
    "Sepal.Length value is ",
    as_chunk(Sepal.Length, props = fp_text(color = "red")))
  ),
  part = "body")
ft <- color(ft, color = "gray40", part = "all")
ft <- autofit(ft)
ft
```

<code>as_equation</code>	<i>equation chunk</i>
--------------------------	-----------------------

Description

This function is used to insert equations into flextable.

It is used to add it to the content of a cell of the flextable with the functions [compose\(\)](#), [append_chunks\(\)](#) or [prepend_chunks\(\)](#).

To use this function, package 'equatags' is required; also `equatags::mathjax_install()` must be executed only once to install necessary dependencies.

Usage

```
as_equation(x, width = 1, height = 0.2, unit = "in")
```

Arguments

<code>x</code>	values containing the 'MathJax' equations
<code>width, height</code>	size of the resulting equation
<code>unit</code>	unit for width and height, one of "in", "cm", "mm".

See Also

Other chunk elements for paragraph: [as_bracket\(\)](#), [as_b\(\)](#), [as_chunk\(\)](#), [as_highlight\(\)](#), [as_image\(\)](#), [as_i\(\)](#), [as_sub\(\)](#), [as_sup\(\)](#), [as_word_field\(\)](#), [colorize\(\)](#), [gg_chunk\(\)](#), [hyperlink_text\(\)](#), [linerange\(\)](#), [lollipop\(\)](#), [minibar\(\)](#), [plot_chunk\(\)](#)

Examples

```
library(flextable)
if(require("equatags") && mathjax_available()){

  eqs <- c(
    "(ax^2 + bx + c = 0)",
    "a \neq 0",
    "x = {-b \pm \sqrt{b^2-4ac}} / {2a}")
  df <- data.frame(formula = eqs)
  df

  ft <- flextable(df)
  ft <- compose(
    x = ft, j = "formula",
    value = as_paragraph(as_equation(formula, width = 2, height = .5)))
  ft <- align(ft, align = "center", part = "all")
  ft <- width(ft, width = 2)
  ft

}
```

as_flextab	<i>method to convert object to flextab</i>
------------	--

Description

This is a convenient function to let users create flextab bindings from any objects. Users should consult documentation of corresponding method to understand the details and see what arguments can be used.

Usage

```
as_flextab(x, ...)
```

Arguments

- | | |
|-----|-------------------------------------|
| x | object to be transformed as flextab |
| ... | arguments for custom methods |

See Also

Other as_flextab methods: [as_flextab.gam\(\)](#), [as_flextab.glm\(\)](#), [as_flextab.grouped_data\(\)](#), [as_flextab.htest\(\)](#), [as_flextab.lm\(\)](#), [as_flextab.tabulator\(\)](#), [as_flextab.xtable\(\)](#)

as_flextab.gam	<i>tabular summary for gam object</i>
----------------	---------------------------------------

Description

produce a flextab describing a generalized additive model produced by function `mgcv::gam`.

Usage

```
## S3 method for class 'gam'  
as_flextab(x, ...)
```

Arguments

- | | |
|-----|-----------------|
| x | gam model |
| ... | unused argument |

Illustrations

See Also

Other as_flextable methods: [as_flextable.glm\(\)](#), [as_flextable.grouped_data\(\)](#), [as_flextable.htest\(\)](#), [as_flextable.lm\(\)](#), [as_flextable.tabulator\(\)](#), [as_flextable.xtable\(\)](#), [as_flextable\(\)](#)

Examples

```
if (require("mgcv")) {
  set.seed(2)

  # Simulated data
  dat <- gamSim(1, n = 400, dist = "normal", scale = 2)

  # basic GAM model
  b <- gam(y ~ s(x0) + s(x1) + s(x2) + s(x3), data = dat)

  ft <- as_flextable(b)
  ft
}
```

as_flextable.glm *tabular summary for glm object*

Description

produce a flextable describing a generalized linear model produced by function `glm`.

Usage

```
## S3 method for class 'glm'
as_flextable(x, ...)
```

Arguments

x	glm model
...	unused argument

Illustrations**See Also**

Other as_flextable methods: [as_flextable.glm\(\)](#), [as_flextable.grouped_data\(\)](#), [as_flextable.htest\(\)](#), [as_flextable.lm\(\)](#), [as_flextable.tabulator\(\)](#), [as_flextable.xtable\(\)](#), [as_flextable\(\)](#)

Examples

```
if(require("broom")){
  dat <- attitude
  dat$high.rating <- (dat$rating > 70)
  probit.model <- glm(high.rating ~ learning + critical +
    advance, data=dat, family = binomial(link = "probit"))
  ft <- as_flextable(probit.model)
  ft
}
```

`as_flextable.grouped_data`

tabular summary for grouped_data object

Description

produce a flextable from a table produced by function [as_grouped_data\(\)](#).

Usage

```
## S3 method for class 'grouped_data'
as_flextable(x, col_keys = NULL, hide_grouplabel = FALSE, ...)
```

Arguments

- `x` object to be transformed as flextable
- `col_keys` columns names/keys to display. If some column names are not in the dataset, they will be added as blank columns by default.
- `hide_grouplabel` if TRUE, group label will not be rendered, only level/value will be rendered.
- `...` unused argument

Illustrations

See Also

[as_grouped_data\(\)](#)

Other as_flextable methods: [as_flextable.gam\(\)](#), [as_flextable.glm\(\)](#), [as_flextable.htest\(\)](#), [as_flextable.lm\(\)](#), [as_flextable.tabulator\(\)](#), [as_flextable.xtable\(\)](#), [as_flextable\(\)](#)

Examples

```
library(data.table)
CO2 <- CO2
setDT(CO2)
CO2$conc <- as.integer(CO2$conc)

data_co2 <- dcast(CO2, Treatment + conc ~ Type,
                   value.var = "uptake", fun.aggregate = mean)
data_co2 <- as_grouped_data(x = data_co2, groups = c("Treatment"))

ft <- as_flextable( data_co2 )
ft <- add_footer_lines(ft, "dataset CO2 has been used for this flextable")
ft <- add_header_lines(ft, "mean of carbon dioxide uptake in grass plants")
ft <- set_header_labels(ft, conc = "Concentration")
ft <- autofit(ft)
ft <- width(ft, width = c(1, 1, 1))
ft
```

as_flextable.htest *tabular summary for htest object*

Description

produce a flextable describing an object oof class `htest`.

Usage

```
## S3 method for class 'htest'
as_flextable(x, ...)
```

Arguments

x	htest object
...	unused argument

Illustrations

See Also

Other `as_flextable` methods: [as_flextable.gam\(\)](#), [as_flextable.glm\(\)](#), [as_flextable.grouped_data\(\)](#), [as_flextable.lm\(\)](#), [as_flextable.tabulator\(\)](#), [as_flextable.xtable\(\)](#), [as_flextable\(\)](#)

Examples

```
if(require("stats")){
  M <- as.table(rbind(c(762, 327, 468), c(484, 239, 477)))
  dimnames(M) <- list(gender = c("F", "M"),
  party = c("Democrat", "Independent", "Republican"))
  ft_1 <- as_flextable(chisq.test(M))
  ft_1
}
```

`as_flextable.kmeans` *tabular summary for kmeans*

Description

produce a flextable describing a kmeans object. The function is only using package 'broom' that provides the data presented in the resulting flextable.

Usage

```
## S3 method for class 'kmeans'
as_flextable(x, digits = 4, ...)
```

Arguments

<code>x</code>	a <code>kmeans()</code> object
<code>digits</code>	number of digits for the numeric columns
<code>...</code>	unused argument

Examples

```
if(require("stats")){
  cl <- kmeans(scale(mtcars[1:7]), 5)
  ft <- as_flextable(cl)
  ft
}
```

as_flextable.lm *tabular summary for lm object*

Description

produce a flextable describing a linear model produced by function `lm`.

Usage

```
## S3 method for class 'lm'
as_flextable(x, ...)
```

Arguments

x	lm model
...	unused argument

Illustrations

See Also

Other `as_flextable` methods: `as_flextable.gam()`, `as_flextable.glm()`, `as_flextable.grouped_data()`,
`as_flextable.htest()`, `as_flextable.tabulator()`, `as_flextable.xtable()`, `as_flextable()`

Examples

```
if(require("broom")){
  lmod <- lm(rating ~ complaints + privileges +
             learning + raises + critical, data=attitude)
  ft <- as_flextable(lmod)
  ft
}
```

as_flextable.merMod *tabular summary for mixed model*

Description

produce a flextable describing a mixed model. The function is only using package `'broom.mixed'` that provides the data presented in the resulting flextable.

Usage

```
## S3 method for class 'merMod'
as_flextab(x, ...)

## S3 method for class 'lme'
as_flextab(x, ...)

## S3 method for class 'gls'
as_flextab(x, ...)

## S3 method for class 'nlme'
as_flextab(x, ...)

## S3 method for class 'brmsfit'
as_flextab(x, ...)

## S3 method for class 'glmmTMB'
as_flextab(x, ...)

## S3 method for class 'glmmadmb'
as_flextab(x, ...)
```

Arguments

x	a mixed model
...	unused argument

Examples

```
if(require("broom.mixed") && require("nlme")){
  m1 <- lme(distance ~ age, data = Orthodont)
  ft <- as_flextab(m1)
  ft
}
```

as_flextab.pam *tabular summary for pam*

Description

produce a flextab describing a pam object. The function is only using package 'broom' that provides the data presented in the resulting flextab.

Usage

```
## S3 method for class 'pam'
as_flextab(x, digits = 4, ...)
```

Arguments

x	a pam() object
digits	number of digits for the numeric columns
...	unused argument

Examples

```
if(require("cluster")){
  dat <- as.data.frame(scale(mtcars[1:7]))
  cl <- pam(dat, 3)
  ft <- as_flextab(cl)
  ft
}
```

as_flextab.tabulator
tabulator to flextab

Description

tabulator object can be transformed as a flextab with method [as_flextab\(\)](#).

Usage

```
## S3 method for class 'tabulator'
as_flextab(
  x,
  separate_with = character(0),
  big_border = fp_border_default(width = 1.5),
  small_border = fp_border_default(width = 0.75),
  rows_alignment = "left",
  columns_alignment = "center",
  label_rows = x$rows,
  sep_w = 0.05,
  unit = "in",
  ...
)
```

Arguments

x	result from tabulator()
separate_with	columns used to sepatate the groups with an horizontal line.
big_border, small_border	big and small border properties defined by a call to fp_border_default() or fp_border() .

rows_alignment, columns_alignment	alignments to apply to columns corresponding to rows and columns; see arguments <code>rows</code> and <code>columns</code> in <code>tabulator()</code> .
label_rows	labels to use for the first column names, i.e. the <code>row</code> column names. It must be a named vector, the values will be matched based on the names.
sep_w	blank column separators' width to be used. If 0, blank column separators will not be used.
unit	unit of argument <code>sep_w</code> , one of "in", "cm", "mm".
...	unused argument

See Also

[summarizor\(\)](#), [as_grouped_data\(\)](#)

Other as_flextab methods: [as_flextab.gam\(\)](#), [as_flextab.glm\(\)](#), [as_flextab.grouped_data\(\)](#), [as_flextab.htest\(\)](#), [as_flextab.lm\(\)](#), [as_flextab.xtable\(\)](#), [as_flextab\(\)](#)

Examples

```
library(flextab)

set_flextab_defaults(digits = 2, border.color = "gray")

if(require("stats")){
  dat <- aggregate(breaks ~ wool + tension,
    data = warpbreaks, mean)

  cft_1 <- tabulator(x = dat,
    rows = "wool",
    columns = "tension",
    `mean` = as_paragraph(as_chunk(breaks)),
    `(N)` = as_paragraph(
      as_chunk(length(breaks) ))
  )

  ft_1 <- as_flextab(cft_1, sep_w = .1)
  ft_1

  set_flextab_defaults(padding = 1, font.size = 9, border.color = "orange")
  ft_2 <- as_flextab(cft_1, sep_w = 0)
  ft_2

  set_flextab_defaults(padding = 6, font.size = 11,
    border.color = "white", font.color = "white",
    background.color = "#333333")
  ft_3 <- as_flextab(
    x = cft_1, sep_w = 0,
    rows_alignment = "center",
    columns_alignment = "right")
  ft_3
}
```

```
init_flextablxtable_defaults()
```

as_flextablxtable *get a flextablxtable from a xtable object*

Description

Get a flextablxtable object from a xtable object.

xtable_to_flextablxtable will be deprecated in favor of as_flextablxtable.

Usage

```
## S3 method for class 'xtable'
as_flextablxtable(
  x,
  text.properties = fp_text_default(),
  format.args = getOption("xtable.format.args", NULL),
  rowname_col = "rowname",
  hline.after = getOption("xtable.hline.after", c(-1, 0, nrow(x))),
  NA.string = getOption("xtable.NA.string", ""),
  include.rownames = TRUE,
  rotate.colnames = getOption("xtable.rotate.colnames", FALSE),
  ...
)

xtable_to_flextablxtable(
  x,
  text.properties = fp_text_default(),
  format.args = getOption("xtable.format.args", NULL),
  rowname_col = "rowname",
  hline.after = getOption("xtable.hline.after", c(-1, 0, nrow(x))),
  NA.string = getOption("xtable.NA.string", ""),
  include.rownames = TRUE,
  rotate.colnames = getOption("xtable.rotate.colnames", FALSE),
  ...
)
```

Arguments

x	xtablxtable object
text.properties	default text formatting properties
format.args	List of arguments for the formatC function. See argument format.args of print.xtable. Not yet implemented.
rowname_col	colname used for row names column

```

hline.after      see ?print.xtable.
NA.string       see ?print.xtable.
include.rownames
               see ?print.xtable.
rotate.colnames
               see ?print.xtable.
...
               unused arguments

```

Illustrations

See Also

Other as_flextable methods: [as_flextable.gam\(\)](#), [as_flextable.glm\(\)](#), [as_flextable.grouped_data\(\)](#), [as_flextable.htest\(\)](#), [as_flextable.lm\(\)](#), [as_flextable.tabulator\(\)](#), [as_flextable\(\)](#)

Examples

```

library(officer)
if( require("xtable") ){

  data(tli)
  tli.table <- xtable(tli[1:10, ])
  align(tli.table) <- rep("r", 6)
  align(tli.table) <- "|r|r|clr|r|"
  ft_1 <- as_flextable(
    tli.table,
    rotate.colnames = TRUE,
    include.rownames = FALSE)
  ft_1 <- height(ft_1, i = 1, part = "header", height = 1)
  ft_1

Grade3 <- c("A", "B", "B", "A", "B", "C", "C", "D", "A", "B",
          "C", "C", "C", "D", "B", "D", "C", "D")
Grade6 <- c("A", "A", "A", "B", "B", "B", "B", "B", "C", "C",
          "A", "C", "C", "C", "D", "D", "D", "D", "D")
Cohort <- table(Grade3, Grade6)
ft_2 <- as_flextable(xtable(Cohort))
ft_2 <- set_header_labels(ft_2, rowname = "Grade 3")
ft_2 <- autofit(ft_2)
ft_2 <- add_header(ft_2, A = "Grade 6")
ft_2 <- merge_at(ft_2, i = 1, j = seq_len( ncol(Cohort) ) + 1,
                 part = "header" )
ft_2 <- bold(ft_2, j = 1, bold = TRUE, part = "body")
ft_2 <- height_all(ft_2, part = "header", height = .4)
ft_2

temp.ts <- ts(cumsum(1 + round(rnorm(100), 0)),
              start = c(1954, 7), frequency = 12)

```

```

ft_3 <- as_flextable(x = xtable(temp.ts, digits = 0),
  NA.string = "-")
ft_3

detach("package:xtable", unload = TRUE)
}

```

as_grouped_data *grouped data transformation*

Description

Repeated consecutive values of group columns will be used to define the title of the groups and will be added as a row title.

Usage

```
as_grouped_data(x, groups, columns = NULL)
```

Arguments

x	dataset
groups	columns names to be used as row separators.
columns	columns names to keep

See Also

[as_flextable.grouped_data\(\)](#)

Examples

```

# as_grouped_data ----
library(data.table)
CO2 <- CO2
setDT(CO2)
CO2$conc <- as.integer(CO2$conc)

data_co2 <- dcast(CO2, Treatment + conc ~ Type,
  value.var = "uptake", fun.aggregate = mean)
data_co2
data_co2 <- as_grouped_data(x = data_co2, groups = c("Treatment"))
data_co2

```

<code>as_highlight</code>	<i>highlight chunk</i>
---------------------------	------------------------

Description

The function is producing a chunk with an highlight chunk.

It is used to add it to the content of a cell of the flextable with the functions `compose()`, `append_chunks()` or `prepend_chunks()`.

Usage

```
as_highlight(x, color)
```

Arguments

<code>x</code>	value, if a chunk, the chunk will be updated
<code>color</code>	color to use as text highlighting color as character vector.

See Also

Other chunk elements for paragraph: `as_bracket()`, `as_b()`, `as_chunk()`, `as_equation()`, `as_image()`, `as_i()`, `as_sub()`, `as_sup()`, `as_word_field()`, `colorize()`, `gg_chunk()`, `hyperlink_text()`, `linerange()`, `lollipop()`, `minibar()`, `plot_chunk()`

Examples

```
ft <- flextable( head(iris),
  col_keys = c("Sepal.Length", "dummy") )

ft <- compose(ft, j = "dummy",
  value = as_paragraph(as_highlight(Sepal.Length, color = "yellow")))

ft
```

<code>as_i</code>	<i>italic chunk</i>
-------------------	---------------------

Description

The function is producing a chunk with italic font.

It is used to add it to the content of a cell of the flextable with the functions `compose()`, `append_chunks()` or `prepend_chunks()`.

Usage

```
as_i(x)
```

Arguments

- x value, if a chunk, the chunk will be updated

Illustrations

See Also

Other chunk elements for paragraph: [as_bracket\(\)](#), [as_b\(\)](#), [as_chunk\(\)](#), [as_equation\(\)](#), [as_highlight\(\)](#), [as_image\(\)](#), [as_sub\(\)](#), [as_sup\(\)](#), [as_word_field\(\)](#), [colorize\(\)](#), [gg_chunk\(\)](#), [hyperlink_text\(\)](#), [linerange\(\)](#), [lollipop\(\)](#), [minibar\(\)](#), [plot_chunk\(\)](#)

Examples

```
ft <- flextable( head(iris),
  col_keys = c("Sepal.Length", "dummy") )

ft <- compose(ft, j = "dummy",
  value = as_paragraph(as_i(Sepal.Length)) )

ft
```

as_image	<i>image chunk wrapper</i>
----------	----------------------------

Description

The function lets add images within flextable objects with function [compose\(\)](#). It should be used inside a call to [as_paragraph\(\)](#).

Usage

```
as_image(src, width = NULL, height = NULL, unit = "in", guess_size = TRUE, ...)
```

Arguments

- | | |
|---------------|---|
| src | image filename |
| width, height | size of the image file. It can be ignored if parameter guess_size=TRUE, see parameter guess_size. |
| unit | unit for width and height, one of "in", "cm", "mm". |
| guess_size | If package 'magick' is installed, this option can be used (set it to TRUE and don't provide values for parameters width and height). When the flextable will be printed, the images will be read and width and height will be guessed. This should be avoided if possible as it can be an extensive task when several images. |
| ... | unused argument |

Illustrations

Note

This chunk option requires package officedown in a R Markdown context with Word output format.
PowerPoint cannot mix images and text in a paragraph, images are removed when outputting to PowerPoint format.

See Also

`compose()`, `as_paragraph()`

Other chunk elements for paragraph: `as_bracket()`, `as_b()`, `as_chunk()`, `as_equation()`, `as_highlight()`, `as_i()`, `as_sub()`, `as_sup()`, `as_word_field()`, `colorize()`, `gg_chunk()`, `hyperlink_text()`, `linerange()`, `lollipop()`, `minibar()`, `plot_chunk()`

Examples

```
img.file <- file.path( R.home("doc"),
  "html", "logo.jpg" )
if (require("magick")) {
  myft <- flextable( head(iris))
  myft <- compose( myft, i = 1:3, j = 1,
    value = as_paragraph(
      as_image(src = img.file),
      " ",
      as_chunk(Sepal.Length,
        props = fp_text_default(color = "red")))
  ),
  part = "body")
  ft <- autofit(myft)
  ft
}
```

`as_paragraph`

concatenate chunks in a flextable

Description

The function is concatenating text and images within paragraphs of a flextable object, this function is to be used with function `compose()`.

Usage

`as_paragraph(..., list_values = NULL)`

Arguments

- ... chunk elements that are defining paragraph
 list_values a list of chunk elements that are defining paragraph. If specified argument ... is unused.

Illustrations

See Also

[as_chunk\(\)](#), [minibar\(\)](#), [as_image\(\)](#), [hyperlink_text\(\)](#)

Other functions for mixed content paragraphs: [append_chunks\(\)](#), [compose\(\)](#), [prepend_chunks\(\)](#)

Examples

```
library(flextable)
ft <- flextable(airquality[sample.int(150, size = 10), ])
ft <- compose(ft,
  j = "Wind",
  value = as_paragraph(
    as_chunk(Wind, props = fp_text_default(color = "orange")),
    " ",
    minibar(value = Wind, max = max(airquality$Wind), barcol = "orange", bg = "black", height = .15),
  ),
  part = "body"
)
ft <- autofit(ft)
ft
```

as_raster *get a flextable as a raster*

Description

save a flextable as an image and return the corresponding raster. This function has been implemented to let flextable be printed on a ggplot object.

Usage

```
as_raster(x, zoom = 2, expand = 2, webshot = "webshot")
```

Arguments

- x a flextable object
 zoom, expand parameters used by webshot function.
 webshot webshot package as a scalar character, one of "webshot" or "webshot2".

Note

This function requires packages: webshot and magick.

See Also

Other flextable print function: [df_printer\(\)](#), [flextable_to_rmd\(\)](#), [htmltools_value\(\)](#), [knit_print.flextable\(\)](#), [plot.flextable\(\)](#), [print.flextable\(\)](#), [save_as_docx\(\)](#), [save_as_html\(\)](#), [save_as_image\(\)](#), [save_as_pptx\(\)](#)

Examples

```
ft <- qflextable( head( mtcars ) )
## Not run:
if( require("ggplot2") && require("webshot") ){
  print(qplot(speed, dist, data = cars, geom = "point"))
  grid::grid.raster(as_raster(ft))
}

## End(Not run)
```

as_sub

*subscript chunk***Description**

The function is producing a chunk with subscript vertical alignment.

It is used to add it to the content of a cell of the flextable with the functions [compose\(\)](#), [append_chunks\(\)](#) or [prepend_chunks\(\)](#).

Usage

```
as_sub(x)
```

Arguments

x	value, if a chunk, the chunk will be updated
---	--

Illustrations**See Also**

Other chunk elements for paragraph: [as_bracket\(\)](#), [as_b\(\)](#), [as_chunk\(\)](#), [as_equation\(\)](#), [as_highlight\(\)](#), [as_image\(\)](#), [as_i\(\)](#), [as_sup\(\)](#), [as_word_field\(\)](#), [colorize\(\)](#), [gg_chunk\(\)](#), [hyperlink_text\(\)](#), [linerange\(\)](#), [lollipop\(\)](#), [minibar\(\)](#), [plot_chunk\(\)](#)

Examples

```
ft <- flextable( head(iris), col_keys = c("dummy") )

ft <- compose(ft, i = 1, j = "dummy", part = "header",
  value = as_paragraph(
    as_sub("Sepal.Length"),
    " anything "
  )
)

ft <- autofit(ft)
ft
```

as_sup

superscript chunk

Description

The function is producing a chunk with superscript vertical alignment.

It is used to add it to the content of a cell of the flextable with the functions [compose\(\)](#), [append_chunks\(\)](#) or [prepend_chunks\(\)](#).

Usage

```
as_sup(x)
```

Arguments

x	value, if a chunk, the chunk will be updated
---	--

Illustrations

Note

This is a sugar function that ease the composition of complex labels made of different formatings.
It should be used inside a call to [as_paragraph\(\)](#).

See Also

Other chunk elements for paragraph: [as_bracket\(\)](#), [as_b\(\)](#), [as_chunk\(\)](#), [as_equation\(\)](#), [as_highlight\(\)](#), [as_image\(\)](#), [as_i\(\)](#), [as_sub\(\)](#), [as_word_field\(\)](#), [colorize\(\)](#), [gg_chunk\(\)](#), [hyperlink_text\(\)](#), [linerange\(\)](#), [lollipop\(\)](#), [minibar\(\)](#), [plot_chunk\(\)](#)

Examples

```
ft <- flextable( head(iris), col_keys = c("dummy") )

ft <- compose(ft, i = 1, j = "dummy", part = "header",
  value = as_paragraph(
    " anything ",
    as_sup("Sepal.Width")
  )
)

ft <- autofit(ft)
ft
```

as_word_field '*Word' computed field*

Description

This function is used to insert 'Word' computed field into flextable.

It is used to add it to the content of a cell of the flextable with the functions [compose\(\)](#), [append_chunks\(\)](#) or [prepend_chunks\(\)](#).

This has only effect on 'Word' output. If you want to condition its execution only for Word output, you can use it in the post processing step (see `set_flextable_defaults(post_process_docx = ...)`)

Do not forget to update the computed field in Word. Fields are defined but are not computed, this computing is an operation that has to be made by 'Microsoft Word' (select all text and hit F9 when on mac os).

Usage

```
as_word_field(x, props = NULL, width = 0.1, height = 0.15, unit = "in")
```

Arguments

x	computed field strings
props	text properties (see fp_text_default() or officer::fp_text()) object to be used to format the text. If not specified, it will use the default text properties of the cell(s).
width, height	size computed field
unit	unit for width and height, one of "in", "cm", "mm".

See Also

Other chunk elements for paragraph: [as_bracket\(\)](#), [as_b\(\)](#), [as_chunk\(\)](#), [as_equation\(\)](#), [as_highlight\(\)](#), [as_image\(\)](#), [as_i\(\)](#), [as_sub\(\)](#), [as_sup\(\)](#), [colorize\(\)](#), [gg_chunk\(\)](#), [hyperlink_text\(\)](#), [linerange\(\)](#), [lollipop\(\)](#), [minibar\(\)](#), [plot_chunk\(\)](#)

Examples

```

library(flextable)

# define some default values ----
set_flextable_defaults(font.size = 22, border.color = "gray")

# an example with append_chunks ----
pp_docx = function(x) {
  x <- add_header_lines(x, "Page ")
  x <- append_chunks(
    x = x, i = 1, part = "header", j = 1,
    as_word_field(x = "Page")
  )
  align(x, part = "header", align = "left")
}
ft_1 <- flextable(cars)
ft_1 <- autofit(ft_1)
ft_1 <- pp_docx(ft_1)

## or:
# set_flextable_defaults(post_process_docx = pp_docx)
## to prevent this line addition when output is not docx

# print(ft_1, preview = "docx")

# an example with compose ----

library(officer)
ft_2 <- flextable(head(cars))
ft_2 <- add_footer_lines(ft_2, "temp text")
ft_2 <- compose(
  x = ft_2, part = "footer", i = 1, j = 1,
  as_paragraph("p.",
    as_word_field(x = "Page", width = .05),
    " on ", as_word_field(x = "NumPages", width = .05))
)
ft_2 <- autofit(ft_2, part = c("header", "body"))

doc <- read_docx()
doc <- body_add_flextable(doc, ft_2)
doc <- body_add_break(doc)
doc <- body_add_flextable(doc, ft_2)
outfile <- print(doc, target = tempfile(fileext = ".docx"))

# reset default values ----
init_flextable_defaults()

```

Description

compute and apply optimized widths and heights (minimum estimated widths and heights for each table columns and rows in inches returned by function [dim.pretty\(\)](#)).

This function is to be used when the table widths and heights should be adjusted to fit the size of the content.

The function does not let you adjust a content that is too wide in a paginated document. It simply calculates the width of the columns so that each content has the minimum width necessary to display the content on one line.

Note that this function is not related to 'Microsoft Word' *Autofit* feature.

There is an alternative to fixed-width layouts that works well with HTML and Word output that can be set with `set_table_properties(layout = "autofit")`, see [set_table_properties\(\)](#).

Usage

```
autofit(
  x,
  add_w = 0.1,
  add_h = 0.1,
  part = c("body", "header"),
  unit = "in",
  hspans = "none"
)
```

Arguments

<code>x</code>	flextable object
<code>add_w</code>	extra width to add in inches
<code>add_h</code>	extra height to add in inches
<code>part</code>	partname of the table (one of 'all', 'body', 'header' or 'footer')
<code>unit</code>	unit for add_h and add_w, one of "in", "cm", "mm".
<code>hspans</code>	specifies how cells that are horizontally are included in the calculation. It must be one of the following values "none", "divided" or "included". If "none", widths of horizontally spanned cells is set to 0 (then do not affect the widths); if "divided", widths of horizontally spanned cells is divided by the number of spanned cells; if "included", all widths (included horizontally spanned cells) will be used in the calculation.

Illustrations

See Also

Other flextable dimensions: [dim.flextable\(\)](#), [dim.pretty\(\)](#), [fit_to_width\(\)](#), [flextable_dim\(\)](#), [height\(\)](#), [hrule\(\)](#), [ncol_keys\(\)](#), [nrow_part\(\)](#), [set_table_properties\(\)](#), [width\(\)](#)

Examples

```
ft_1 <- flextable(head(mtcars))
ft_1
ft_2 <- autofit(ft_1)
ft_2
```

before

is an element before a match with entries

Description

return a logical vector of the same length as x, indicating if elements are located before a set of entries to match or not.

Usage

```
before(x, entries)
```

Arguments

x	an atomic vector of values to be tested
entries	a sequence of items to be searched in x.

See Also

[hline\(\)](#)

Examples

```
library(flextable)
library(officer)

dat <- data.frame(
  stringsAsFactors = FALSE,
  check.names = FALSE,
  Level = c("setosa", "versicolor", "virginica", "<NA>", "Total"),
  Freq = as.integer(c(50, 50, 50, 0, 150)),
  `% Valid` = c(100/3,
               100/3, 100/3, NA, 100),
  `% Valid Cum.` = c(100/3, 100*2/3, 100, NA, 100),
  `% Total` = c(100/3,
               100/3, 100/3, 0, 100),
  `% Total Cum.` = c(100/3,
                     100*2/3, 100, 100, 100)
)

ft <- flextable(dat)
ft <- hline(ft, i = ~ before(Level, "Total"),
            border = fp_border_default(width = 2))
ft
```

bg	<i>Set background color</i>
----	-----------------------------

Description

Change background color of selected rows and columns of a flextable. A function can be used instead of fixed colors.

When bg is a function, it is possible to color cells based on values located in other columns, using hidden columns (those not used by argument colkeys) is a common use case. The argument source has to be used to define what are the columns to be used for the color definition and the argument j has to be used to define where to apply the colors and only accept values from colkeys.

Usage

```
bg(x, i = NULL, j = NULL, bg, part = "body", source = j)
```

Arguments

x	a flextable object
i	rows selection
j	columns selection
bg	color to use as background color. If a function, function need to return a character vector of colors.
part	partname of the table (one of 'all', 'body', 'header', 'footer')
source	if bg is a function, source is specifying the dataset column to be used as argument to bg. This is only useful if j is colored with values contained in other columns.

Illustrations

Note

Word does not allow you to apply transparency to table cells or paragraph shading.

See Also

Other sugar functions for table style: [align\(\)](#), [bold\(\)](#), [color\(\)](#), [empty_blanks\(\)](#), [fontsize\(\)](#), [font\(\)](#), [highlight\(\)](#), [italic\(\)](#), [line_spacing\(\)](#), [padding\(\)](#), [rotate\(\)](#), [valign\(\)](#)

Examples

```

ft_1 <- flextable(head(mtcars))
ft_1 <- bg(ft_1, bg = "wheat", part = "header")
ft_1 <- bg(ft_1, i = ~ qsec < 18, bg = "#EFEFEF", part = "body")
ft_1 <- bg(ft_1, j = "drat", bg = "#606060", part = "all")
ft_1 <- color(ft_1, j = "drat", color = "white", part = "all")
ft_1

if (require("scales")) {
  ft_2 <- flextable(head(iris))
  colourer <- col_numeric(
    palette = c("wheat", "red"),
    domain = c(0, 7)
  )
  ft_2 <- bg(ft_2,
    j = c(
      "Sepal.Length", "Sepal.Width",
      "Petal.Length", "Petal.Width"
    ),
    bg = colourer, part = "body"
  )
  ft_2
}

```

`body_add_flextable` *add flextable into a Word document*

Description

add a flextable into a Word document.

Usage

```

body_add_flextable(
  x,
  value,
  align = "center",
  pos = "after",
  split = FALSE,
  topcaption = TRUE,
  keepnext = TRUE
)

body_replace_flextable_at_bkm(
  x,
  bookmark,
  value,
  align = "center",

```

```
    split = FALSE
)
```

Arguments

x	an rdocx object
value	flextab object
align	left, center (default) or right.
pos	where to add the flextab relative to the cursor, one of "after", "before", "on" (end of line).
split	set to TRUE if you want to activate Word option 'Allow row to break across pages'.
topcaption	if TRUE caption is added before the table, if FALSE, caption is added after the table.
keepnext	default TRUE. Word option 'keep rows together' is activated when TRUE. It avoids page break within tables. This is handy for small tables, i.e. less than a page height. Be careful, if you print long tables, you should rather set its value to FALSE to avoid that the tables also generate a page break before being placed in the Word document. Since Word will try to keep it with the next paragraphs that follow the tables .
bookmark	bookmark id

body_replace_flextab_at_bkm

Use this function if you want to replace a paragraph containing a bookmark with a flextab. As a side effect, the bookmark will be lost.

Examples

```
library(officer)

# autonum for caption
autonum <- run_autonum(seq_id = "tab", bkm = "mtcars")

ftab <- flextab( head( mtcars ) )
ftab <- set_caption(ftab, caption = "mtcars data", autonum = autonum)
ftab <- autofit(ftab)
doc <- read_docx()
doc <- body_add_flextab(doc, value = ftab)
fileout <- tempfile(fileext = ".docx")
# fileout <- "test.docx" # uncomment to write in your working directory
print(doc, target = fileout)
```

bold	<i>Set bold font</i>
------	----------------------

Description

change font weight of selected rows and columns of a flextable.

Usage

```
bold(x, i = NULL, j = NULL, bold = TRUE, part = "body")
```

Arguments

x	a flextable object
i	rows selection
j	columns selection
bold	boolean value
part	partname of the table (one of 'all', 'body', 'header', 'footer')

Illustrations

See Also

Other sugar functions for table style: [align\(\)](#), [bg\(\)](#), [color\(\)](#), [empty_blanks\(\)](#), [fontsize\(\)](#), [font\(\)](#), [highlight\(\)](#), [italic\(\)](#), [line_spacing\(\)](#), [padding\(\)](#), [rotate\(\)](#), [valign\(\)](#)

Examples

```
ft <- flextable(head(iris))
ft <- bold(ft, bold = TRUE, part = "header")
```

border_inner	<i>set vertical & horizontal inner borders</i>
--------------	--

Description

The function is applying a vertical and horizontal borders to inner content of one or all parts of a flextable.

Usage

```
border_inner(x, border = NULL, part = "all")
```

Arguments

x	a flextable object
border	border properties defined by a call to fp_border()
part	partname of the table (one of 'all', 'body', 'header', 'footer')

Illustrations**See Also**

Other borders management: [border_inner_h\(\)](#), [border_inner_v\(\)](#), [border_outer\(\)](#), [border_remove\(\)](#), [hline_bottom\(\)](#), [hline_top\(\)](#), [hline\(\)](#), [surround\(\)](#), [vline_left\(\)](#), [vline_right\(\)](#), [vline\(\)](#)

Examples

```
library(officer)
std_border = fp_border(color="orange", width = 1)

dat <- iris[c(1:5, 51:55, 101:105),]
ft <- flextable(dat)
ft <- border_remove(x = ft)

# add inner vertical borders
ft <- border_inner(ft, border = std_border )
ft
```

border_inner_h *set inner borders*

Description

The function is applying a border to inner content of one or all parts of a flextable.

Usage

```
border_inner_h(x, border = NULL, part = "body")
```

Arguments

x	a flextable object
border	border properties defined by a call to fp_border()
part	partname of the table (one of 'all', 'body', 'header', 'footer')

Illustrations

See Also

Other borders management: [border_inner_v\(\)](#), [border_inner\(\)](#), [border_outer\(\)](#), [border_remove\(\)](#), [hline_bottom\(\)](#), [hline_top\(\)](#), [hline\(\)](#), [surround\(\)](#), [vline_left\(\)](#), [vline_right\(\)](#), [vline\(\)](#)

Examples

```
library(officer)
std_border = fp_border(color="orange", width = 1)

dat <- iris[c(1:5, 51:55, 101:105),]
ft <- flextable(dat)
ft <- border_remove(x = ft)

# add inner horizontal borders
ft <- border_inner_h(ft, border = std_border )
ft
```

border_inner_v *set vertical inner borders*

Description

The function is applying a vertical border to inner content of one or all parts of a flextable.

Usage

```
border_inner_v(x, border = NULL, part = "all")
```

Arguments

- | | |
|--------|--|
| x | a flextable object |
| border | border properties defined by a call to fp_border() |
| part | partname of the table (one of 'all', 'body', 'header', 'footer') |

Illustrations**See Also**

Other borders management: [border_inner_h\(\)](#), [border_inner\(\)](#), [border_outer\(\)](#), [border_remove\(\)](#), [hline_bottom\(\)](#), [hline_top\(\)](#), [hline\(\)](#), [surround\(\)](#), [vline_left\(\)](#), [vline_right\(\)](#), [vline\(\)](#)

Examples

```
library(officer)
std_border = fp_border(color="orange", width = 1)

dat <- iris[c(1:5, 51:55, 101:105),]
ft <- flextable(dat)
ft <- border_remove(x = ft)

# add inner vertical borders
ft <- border_inner_v(ft, border = std_border )
ft
```

border_outer

set outer borders

Description

The function is applying a border to outer cells of one or all parts of a flextable.

Usage

```
border_outer(x, border = NULL, part = "all")
```

Arguments

x	a flextable object
border	border properties defined by a call to fp_border()
part	partname of the table (one of 'all', 'body', 'header', 'footer')

Illustrations

See Also

Other borders management: [border_inner_h\(\)](#), [border_inner_v\(\)](#), [border_inner\(\)](#), [border_remove\(\)](#), [hline_bottom\(\)](#), [hline_top\(\)](#), [hline\(\)](#), [surround\(\)](#), [vline_left\(\)](#), [vline_right\(\)](#), [vline\(\)](#)

Examples

```
library(officer)
big_border = fp_border(color="red", width = 2)

dat <- iris[c(1:5, 51:55, 101:105),]
ft <- flextable(dat)
ft <- border_remove(x = ft)

# add outer borders
ft <- border_outer(ft, part="all", border = big_border )
ft
```

border_remove	<i>remove borders</i>
---------------	-----------------------

Description

The function is deleting all borders of the flextable object.

Usage

```
border_remove(x)
```

Arguments

x	a flextable object
---	--------------------

Illustrations

See Also

Other borders management: [border_inner_h\(\)](#), [border_inner_v\(\)](#), [border_inner\(\)](#), [border_outer\(\)](#), [hline_bottom\(\)](#), [hline_top\(\)](#), [hline\(\)](#), [surround\(\)](#), [vline_left\(\)](#), [vline_right\(\)](#), [vline\(\)](#)

Examples

```
dat <- iris[c(1:5, 51:55, 101:105),]
ft_1 <- flextable(dat)
ft_1 <- theme_box(ft_1)
ft_1

# remove all borders
ft_2 <- border_remove(x = ft_1)
ft_2
```

colformat_char	<i>format character cells</i>
----------------	-------------------------------

Description

Format character cells in a flextable.

Usage

```
colformat_char(  
  x,  
  i = NULL,  
  j = NULL,  
  na_str = get_flextab...  
  nan_str = get_flextab...  
  prefix = "",  
  suffix = ""  
)
```

Arguments

x a flextable object
i rows selection
j columns selection.
na_str, nan_str string to be used for NA and NaN values
prefix, suffix string to be used as prefix or suffix

See Also

Other cells formatters: [colformat_datetime\(\)](#), [colformat_date\(\)](#), [colformat_double\(\)](#), [colformat_image\(\)](#), [colformat_int\(\)](#), [colformat_lgl\(\)](#), [colformat_num\(\)](#), [set_formatter\(\)](#)

Examples

```
dat <- iris  
z <- flextable(head(dat))  
ft <- colformat_char(  
  x = z, j = "Species", suffix = "!"  
z <- autofit(z)  
z
```

colformat_date *format date cells*

Description

Format date cells in a flextable.

Usage

```
colformat_date(
  x,
  i = NULL,
  j = NULL,
  fmt_date = get_flextable_defaults()$fmt_date,
  na_str = get_flextable_defaults()$na_str,
  nan_str = get_flextable_defaults()$nan_str,
  prefix = "",
  suffix = ""
)
```

Arguments

<code>x</code>	a flextable object
<code>i</code>	rows selection
<code>j</code>	columns selection.
<code>fmt_date</code>	see strptime()
<code>na_str, nan_str</code>	string to be used for NA and NaN values
<code>prefix, suffix</code>	string to be used as prefix or suffix

See Also

Other cells formatters: [colformat_char\(\)](#), [colformat_datetime\(\)](#), [colformat_double\(\)](#), [colformat_image\(\)](#), [colformat_int\(\)](#), [colformat_lgl\(\)](#), [colformat_num\(\)](#), [set_formatter\(\)](#)

Examples

```
dat <- data.frame(z = Sys.Date() + 1:3,
  w = Sys.Date() - 1:3)
ft <- flextable(dat)
ft <- colformat_date(x = ft)
ft <- autofit(ft)
ft
```

`colformat_datetime` *format datetime cells*

Description

Format datetime cells in a flextable.

Usage

```
colformat_datetime(
  x,
  i = NULL,
  j = NULL,
  fmt_datetime = get_flextabler_defaults()$fmt_datetime,
  na_str = get_flextabler_defaults()$na_str,
  nan_str = get_flextabler_defaults()$nan_str,
  prefix = "",
  suffix = ""
)
```

Arguments

x	a flextabler object
i	rows selection
j	columns selection.
fmt_datetime	see strptime()
na_str, nan_str	string to be used for NA and NaN values
prefix, suffix	string to be used as prefix or suffix

See Also

Other cells formatters: [colformat_char\(\)](#), [colformat_date\(\)](#), [colformat_double\(\)](#), [colformat_image\(\)](#), [colformat_int\(\)](#), [colformat_lgl\(\)](#), [colformat_num\(\)](#), [set_formatter\(\)](#)

Examples

```
dat <- data.frame(z = Sys.time() + (1:3)*24,
  w = Sys.Date() - (1:3)*24)
ft <- flextabler(dat)
ft <- colformat_datetime(x = ft)
ft <- autofit(ft)
ft
```

colformat_double	<i>format numeric cells</i>
------------------	-----------------------------

Description

Format numeric cells in a flextabler.

Usage

```
colformat_double(
  x,
  i = NULL,
  j = NULL,
  big.mark = get_flextable_defaults()$big.mark,
  decimal.mark = get_flextable_defaults()$decimal.mark,
  digits = get_flextable_defaults()$digits,
  na_str = get_flextable_defaults()$na_str,
  nan_str = get_flextable_defaults()$nan_str,
  prefix = "",
  suffix = ""
)
```

Arguments

x	a flextable object
i	rows selection
j	columns selection.
big.mark, digits, decimal.mark	see formatC()
na_str, nan_str	string to be used for NA and NaN values
prefix, suffix	string to be used as prefix or suffix

Illustrations**See Also**

Other cells formatters: [colformat_char\(\)](#), [colformat_datetime\(\)](#), [colformat_date\(\)](#), [colformat_image\(\)](#), [colformat_int\(\)](#), [colformat_lgl\(\)](#), [colformat_num\(\)](#), [set_formatter\(\)](#)

Examples

```
dat <- mtcars
ft <- flextable(head(dat))
ft <- colformat_double(x = ft,
  big.mark =",",
  digits = 2,
  na_str = "N/A")
autofit(ft)
```

colformat_image	<i>format cells as images</i>
-----------------	-------------------------------

Description

Format image paths as images in a flextable.

Usage

```
colformat_image(  
  x,  
  i = NULL,  
  j = NULL,  
  width,  
  height,  
  na_str = get_flextable_defaults()$na_str,  
  nan_str = get_flextable_defaults()$nan_str,  
  prefix = "",  
  suffix = ""  
)
```

Arguments

x	a flextable object
i	rows selection
j	columns selection.
width, height	size of the png file in inches
na_str, nan_str	string to be used for NA and NaN values
prefix, suffix	string to be used as prefix or suffix

Illustrations

See Also

Other cells formatters: [colformat_char\(\)](#), [colformat_datetime\(\)](#), [colformat_date\(\)](#), [colformat_double\(\)](#), [colformat_int\(\)](#), [colformat_lgl\(\)](#), [colformat_num\(\)](#), [set_formatter\(\)](#)

Examples

```
img.file <- file.path( R.home("doc"), "html", "logo.jpg" )  
  
dat <- head(iris)  
dat$Species <- as.character(dat$Species)  
dat[c(1, 3, 5), "Species"] <- img.file
```

```
myft <- flextable( dat)
myft <- colformat_image(
  myft, i = c(1, 3, 5),
  j = "Species", width = .20, height = .15)
ft <- autofit(myft)
ft
```

colformat_int *format integer cells*

Description

Format integer cells in a flextable.

Usage

```
colformat_int(
  x,
  i = NULL,
  j = NULL,
  big.mark = get_flextable_defaults()$big.mark,
  na_str = get_flextable_defaults()$na_str,
  nan_str = get_flextable_defaults()$nan_str,
  prefix = "",
  suffix = ""
)
```

Arguments

x	a flextable object
i	rows selection
j	columns selection.
big.mark	see format()
na_str, nan_str	string to be used for NA and NaN values
prefix, suffix	string to be used as prefix or suffix

See Also

Other cells formatters: [colformat_char\(\)](#), [colformat_datetime\(\)](#), [colformat_date\(\)](#), [colformat_double\(\)](#), [colformat_image\(\)](#), [colformat_lgl\(\)](#), [colformat_num\(\)](#), [set_formatter\(\)](#)

Examples

```
z <- flextable(head(mtcars))
j <- c("vs", "am", "gear", "carb")
z <- colformat_int(x = z, j = j, prefix = "# ")
z
```

colformat_lgl	<i>format logical cells</i>
---------------	-----------------------------

Description

Format logical cells in a flextable.

Usage

```
colformat_lgl(  
  x,  
  i = NULL,  
  j = NULL,  
  true = "true",  
  false = "false",  
  na_str = get_flextable_defaults()$na_str,  
  nan_str = get_flextable_defaults()$nan_str,  
  prefix = "",  
  suffix = ""  
)
```

Arguments

x	a flextable object
i	rows selection
j	columns selection.
false, true	string to be used for logical
na_str, nan_str	string to be used for NA and NaN values
prefix, suffix	string to be used as prefix or suffix

See Also

Other cells formatters: [colformat_char\(\)](#), [colformat_datetime\(\)](#), [colformat_date\(\)](#), [colformat_double\(\)](#), [colformat_image\(\)](#), [colformat_int\(\)](#), [colformat_num\(\)](#), [set_formatter\(\)](#)

Examples

```
dat <- data.frame(a = c(TRUE, FALSE), b = c(FALSE, TRUE))  
  
z <- flextable(dat)  
z <- colformat_lgl(x = z, j = c("a", "b"))  
autofit(z)
```

colformat_num	<i>format numeric cells</i>
---------------	-----------------------------

Description

Format numeric cells in a flextable.

The function is different from `colformat_double()` on numeric type columns. The function uses the `format()` function of R on numeric type columns. So this is normally what you see on the R console most of the time (but scientific mode is disabled and NA are replaced).

Usage

```
colformat_num(
  x,
  i = NULL,
  j = NULL,
  big.mark = get_flextable_defaults()$big.mark,
  decimal.mark = get_flextable_defaults()$decimal.mark,
  na_str = get_flextable_defaults()$na_str,
  nan_str = get_flextable_defaults()$nan_str,
  prefix = "",
  suffix = "",
  ...
)
```

Arguments

x	a flextable object
i	rows selection
j	columns selection.
big.mark, decimal.mark	see <code>format()</code>
na_str, nan_str	string to be used for NA and NaN values
prefix, suffix	string to be used as prefix or suffix
...	additional argument for function <code>format()</code> , scientific and digits can not be used.

format call

Function `format()` is called with the following values:

- `trim` is set to TRUE,
- `scientific` is set to FALSE,
- `big.mark` is set to the value of `big.mark` argument,

- `decimal.mark` is set to the value of `decimal.mark` argument,
- other arguments are passed 'as is' to the `format` function.

argument `digits` is ignored as it is not the same `digits` that users want, this one will be used by `format()` and not `formatC()`. To change the `digit` argument use `options(digits=4)` instead.

This argument will not be changed because `colformat_num()` is supposed to format things roughly as what you see on the R console.

If these functions does not fit your needs, use `set_formatter()` that lets you use any format function.

Illustrations

See Also

Other cells formatters: `colformat_char()`, `colformat_datetime()`, `colformat_date()`, `colformat_double()`, `colformat_image()`, `colformat_int()`, `colformat_lgl()`, `set_formatter()`

Examples

```
dat <- mtcars
dat[2,1] <- NA
ft <- flextable(head(dat))
ft <- colformat_num(x = ft,
  big.mark = " ", decimal.mark = ",",
  na_str = "N/A")
ft <- autofit(ft)
ft
```

`color`

Set font color

Description

Change text color of selected rows and columns of a flextable. A function can be used instead of fixed colors.

When `color` is a function, it is possible to color cells based on values located in other columns, using hidden columns (those not used by argument `colkeys`) is a common use case. The argument `source` has to be used to define what are the columns to be used for the color definition and the argument `j` has to be used to define where to apply the colors and only accept values from `colkeys`.

Usage

```
color(x, i = NULL, j = NULL, color, part = "body", source = j)
```

Arguments

x	a flextable object
i	rows selection
j	columns selection
color	color to use as font color. If a function, function need to return a character vector of colors.
part	partname of the table (one of 'all', 'body', 'header', 'footer')
source	if color is a function, source is specifying the dataset column to be used as argument to color. This is only useful if j is colored with values contained in other columns.

Illustrations

See Also

Other sugar functions for table style: [align\(\)](#), [bg\(\)](#), [bold\(\)](#), [empty_blanks\(\)](#), [fontsize\(\)](#), [font\(\)](#), [highlight\(\)](#), [italic\(\)](#), [line_spacing\(\)](#), [padding\(\)](#), [rotate\(\)](#), [valign\(\)](#)

Examples

```

ft <- flextable(head(mtcars))
ft <- color(ft, color = "orange", part = "header")
ft <- color(ft,
            color = "red",
            i = ~ qsec < 18 & vs < 1
)
ft

if (require("scales")) {
  scale <- scales::col_numeric(domain = c(-1, 1), palette = "RdBu")
  x <- as.data.frame(cor(iris[-5]))
  x <- cbind(
    data.frame(
      colname = colnames(x),
      stringsAsFactors = FALSE
    ),
    x
  )

  ft_2 <- flextable(x)
  ft_2 <- color(ft_2, j = x$colname, color = scale)
  ft_2 <- set_formatter_type(ft_2)
  ft_2
}

```

`colorize`*colorize chunk*

Description

The function is producing a chunk with a font in color.

It is used to add it to the content of a cell of the flextable with the functions [compose\(\)](#), [append_chunks\(\)](#) or [prepend_chunks\(\)](#).

Usage

```
colorize(x, color)
```

Arguments

<code>x</code>	value, if a chunk, the chunk will be updated
<code>color</code>	color to use as text highlighting color as character vector.

See Also

Other chunk elements for paragraph: [as_bracket\(\)](#), [as_b\(\)](#), [as_chunk\(\)](#), [as_equation\(\)](#), [as_highlight\(\)](#), [as_image\(\)](#), [as_i\(\)](#), [as_sub\(\)](#), [as_sup\(\)](#), [as_word_field\(\)](#), [gg_chunk\(\)](#), [hyperlink_text\(\)](#), [linerange\(\)](#), [lollipop\(\)](#), [minibar\(\)](#), [plot_chunk\(\)](#)

Examples

```
ft <- flextable( head(iris),
  col_keys = c("Sepal.Length", "dummy") )

ft <- compose(ft, j = "dummy",
  value = as_paragraph(colorize(Sepal.Length, color = "red")))

ft
```

`compose`*Define displayed values and mixed content*

Description

Modify flextable displayed values with eventually mixed content paragraphs.

Function is handling complex formatting as image insertion with [as_image\(\)](#), superscript with [as_sup\(\)](#), formated text with [as_chunk\(\)](#) and several other *chunk* functions.

Function `mk_par` is another name for `compose` as there is an unwanted **conflict with package 'purrr'**.

If you only need to add some content at the end or the beginning of paragraphs and keep existing content as it is, functions [append_chunks\(\)](#) and [prepend_chunks\(\)](#) should be prefered.

Usage

```
compose(x, i = NULL, j = NULL, value, part = "body", use_dot = FALSE)

mk_par(x, i = NULL, j = NULL, value, part = "body", use_dot = FALSE)
```

Arguments

x	a flextable object
i	rows selection
j	column selection
value	a call to function as_paragraph() .
part	partname of the table (one of 'all', 'body', 'header', 'footer')
use_dot	by default use_dot=FALSE; if use_dot=TRUE, value is evaluated within a data.frame augmented of a column named . containing the jth column.

Illustrations**See Also**

[fp_text_default\(\)](#), [as_chunk\(\)](#), [as_b\(\)](#), [as_word_field\(\)](#)

Other functions for mixed content paragraphs: [append_chunks\(\)](#), [as_paragraph\(\)](#), [prepend_chunks\(\)](#)

Examples

```
ft_1 <- flextable(head(cars, n = 5), col_keys = c("speed", "dist", "comment"))
ft_1 <- mk_par(
  x = ft_1, j = "comment",
  i = ~ dist > 9,
  value = as_paragraph(
    colorize(as_i("speed: "), color = "gray"),
    as_sup(sprintf("%.0f", speed))
  )
)
ft_1 <- set_table_properties(ft_1, layout = "autofit")
ft_1

# using `use_dot = TRUE` ----
set.seed(8)
dat <- iris[sample.int(n = 150, size = 10),]
dat <- dat[order(dat$Species),]

ft_2 <- flextable(dat)
ft_2 <- mk_par(ft_2, j = ~ . -Species,
  value = as_paragraph(
    minibar(., barcol = "white",
    height = .1)
```

```
  ), use_dot = TRUE  
  )  
ft_2 <- theme_vader(ft_2)  
ft_2 <- autofit(ft_2)  
ft_2
```

continuous_summary *continuous columns summary*

Description

create a data.frame summary for continuous variables

Usage

```
continuous_summary(  
  dat,  
  columns = NULL,  
  by = character(0),  
  hide_grouplabel = TRUE,  
  digits = 3  
)
```

Arguments

dat	a data.frame
columns	continuous variables to be summarized. If NULL all continuous variables are summarized.
by	discrete variables to use as groups when summarizing.
hide_grouplabel	if TRUE, group label will not be rendered, only level/value will be rendered.
digits	the desired number of digits after the decimal point

Illustrations

Examples

```
ft_1 <- continuous_summary(iris, names(iris)[1:4], by = "Species",  
  hide_grouplabel = FALSE)  
ft_1
```

`delete_part` *delete flextable part*

Description

indicate to not print a part of the flextable, i.e. an header, footer or the body.

Usage

```
delete_part(x, part = "header")
```

Arguments

<code>x</code>	a flextable object
<code>part</code>	partname of the table to delete (one of 'body', 'header' or 'footer').

Illustrations

Examples

```
ft <- flextable(head(iris))
ft <- delete_part(x = ft, part = "header")
ft
```

`df_printer` *data.frame automatic printing as a flextable*

Description

Create a summary from a data.frame as a flextable. This function is to be used in an R Markdown document.

To use that function, you must declare it in the part `df_print` of the 'YAML' header of your R Markdown document:

```
---
df_print: !expr function(x) flextable::df_printer(x)
---
```

We notice an unexpected behavior with bookdown. When using bookdown it is necessary to use `use_df_printer()` instead in a setup run chunk:

```
use_df_printer()
```

Usage

```
df_printer(dat, ...)
```

Arguments

dat	the data.frame
...	unused argument

Details

'knitr' chunk options are available to customize the output:

- `ft_max_row`: The number of rows to print. Default to 10.
- `ft_split_colnames`: Should the column names be split (with non alpha-numeric characters). Default to FALSE.
- `ft_short_strings`: Should the character column be shorten. Default to FALSE.
- `ft_short_size`: Maximum length of character column if `ft_short_strings` is TRUE. Default to 35.
- `ft_short_suffix`: Suffix to add when character values are shorten. Default to "...".
- `ft_do_autofit`: Use `autofit()` before rendering the table. Default to TRUE.
- `ft_show_coltype`: Show column types. Default to TRUE.
- `ft_color_coltype`: Color to use for column types. Default to "#999999".

See Also

Other flextable print function: [as_raster\(\)](#), [flextable_to_rmd\(\)](#), [htmltools_value\(\)](#), [knit_print.flextable\(\)](#), [plot.flextable\(\)](#), [print.flextable\(\)](#), [save_as_docx\(\)](#), [save_as_html\(\)](#), [save_as_image\(\)](#), [save_as_pptx\(\)](#)

Examples

```
df_printer(head(mtcars))
```

`dim.flextable` *Get widths and heights of flextable*

Description

returns widths and heights for each table columns and rows. Values are expressed in inches.

Usage

```
## S3 method for class 'flextable'  
dim(x)
```

Arguments

x	flextable object
---	------------------

See Also

Other flextable dimensions: [autofit\(\)](#), [dim_pretty\(\)](#), [fit_to_width\(\)](#), [flextable_dim\(\)](#), [height\(\)](#), [hrule\(\)](#), [ncol_keys\(\)](#), [nrow_part\(\)](#), [set_table_properties\(\)](#), [width\(\)](#)

Examples

```
ftab <- flextable(head(iris))
dim(ftab)
```

<i>dim_pretty</i>	<i>Calculate pretty dimensions</i>
-------------------	------------------------------------

Description

return minimum estimated widths and heights for each table columns and rows in inches.

Usage

```
dim_pretty(x, part = "all", unit = "in", hspans = "none")
```

Arguments

x	flextable object
part	partname of the table (one of 'all', 'body', 'header' or 'footer')
unit	unit for returned values, one of "in", "cm", "mm".
hspans	specifies how cells that are horizontally are included in the calculation. It must be one of the following values "none", "divided" or "included". If "none", widths of horizontally spanned cells is set to 0 (then do not affect the widths); if "divided", widths of horizontally spanned cells is divided by the number of spanned cells; if "included", all widths (included horizontally spanned cells) will be used in the calculation.

See Also

Other flextable dimensions: [autofit\(\)](#), [dim.flextable\(\)](#), [fit_to_width\(\)](#), [flextable_dim\(\)](#), [height\(\)](#), [hrule\(\)](#), [ncol_keys\(\)](#), [nrow_part\(\)](#), [set_table_properties\(\)](#), [width\(\)](#)

Examples

```
ftab <- flextable(head(mtcars))
dim_pretty(ftab)
```

<code>empty_blanks</code>	<i>make blank columns as transparent</i>
---------------------------	--

Description

blank columns are set as transparent. This is a shortcut function that will delete top and bottom borders, change background color to transparent, display empty content and set blank columns' width.

Usage

```
empty_blanks(x, width = 0.05, unit = "in", part = "all")
```

Arguments

<code>x</code>	a flextable object
<code>width</code>	width of blank columns (.1 inch by default).
<code>unit</code>	unit for width, one of "in", "cm", "mm".
<code>part</code>	partname of the table (one of 'all', 'body', 'header', 'footer')

See Also

Other sugar functions for table style: [align\(\)](#), [bg\(\)](#), [bold\(\)](#), [color\(\)](#), [fontsize\(\)](#), [font\(\)](#), [highlight\(\)](#), [italic\(\)](#), [line_spacing\(\)](#), [padding\(\)](#), [rotate\(\)](#), [valign\(\)](#)

Examples

```
typology <- data.frame(
  col_keys = c(
    "Sepal.Length", "Sepal.Width", "Petal.Length",
    "Petal.Width", "Species"
  ),
  what = c("Sepal", "Sepal", "Petal", "Petal", ""),
  measure = c("Length", "Width", "Length", "Width", "Species"),
  stringsAsFactors = FALSE
)
typology

ftab <- flextable(head(iris), col_keys = c(
  "Species",
  "break1", "Sepal.Length", "Sepal.Width",
  "break2", "Petal.Length", "Petal.Width"
))
ftab <- set_header_df(ftab, mapping = typology, key = "col_keys")
ftab <- merge_h(ftab, part = "header")
ftab <- theme_vanilla(ftab)
ftab <- empty_blanks(ftab)
ftab <- width(ftab, j = c(2, 5), width = .1)
ftab
```

fit_to_width *fit a flextable to a maximum width*

Description

decrease font size for each cell incrementally until it fits a given max_width.

Usage

```
fit_to_width(x, max_width, inc = 1L, max_iter = 20, unit = "in")
```

Arguments

x	flextable object
max_width	maximum width to fit in inches
inc	the font size decrease for each step
max_iter	maximum iterations
unit	unit for max_width, one of "in", "cm", "mm".

Illustrations

See Also

Other flextable dimensions: [autofit\(\)](#), [dim.flextable\(\)](#), [dim.pretty\(\)](#), [flextable_dim\(\)](#), [height\(\)](#), [hrule\(\)](#), [ncol_keys\(\)](#), [nrow_part\(\)](#), [set_table_properties\(\)](#), [width\(\)](#)

Examples

```
ft_1 <- qflextable(head(mtcars))
ft_1 <- width(ft_1, width = 1)
ft_1

ft_2 <- fit_to_width(ft_1, max_width = 4)
ft_2
```

<code>fix_border_issues</code>	<i>fix border issues when cell are merged</i>
--------------------------------	---

Description

When cells are merged, the rendered borders will be those of the first cell. If a column is made of three merged cells, the bottom border that will be seen will be the bottom border of the first cell in the column. From a user point of view, this is wrong, the bottom should be the one defined for cell 3. This function modify the border values to avoid that effect.

Usage

```
fix_border_issues(x, part = "all")
```

Arguments

<code>x</code>	flextable object
<code>part</code>	partname of the table (one of 'all', 'body', 'header', 'footer')

Examples

```
library(officer)
dat <- data.frame(a = 1:5, b = 6:10)
ft <- flextable(dat)
ft <- theme_box(ft)
ft <- merge_at(ft, i = 4:5, j = 1, part = "body")
ft <- hline(ft, i = 5, part = "body",
            border = fp_border(color = "red", width = 5) )
print(ft)
ft <- fix_border_issues(ft)
print(ft)
```

<code>flextable</code>	<i>flextable creation</i>
------------------------	---------------------------

Description

Create a flextable object with function `flextable`.

`flextable` are designed to make tabular reporting easier for R users. Functions are available to let you format text, paragraphs and cells; table cells can be merge vertically or horizontally, row headers can easily be defined, rows heights and columns widths can be manually set or automatically computed.

If working with 'R Markdown' documents, you should read about knitr chunk options in [knit_print.flextable\(\)](#) and about setting default values with [set_flextable_defaults\(\)](#).

Usage

```
flextable(
  data,
  col_keys = names(data),
  cwidth = 0.75,
  cheight = 0.25,
  defaults = list(),
  theme_fun = theme_booktabs
)
qflextable(data)
```

Arguments

data	dataset
col_keys	columns names/keys to display. If some column names are not in the dataset, they will be added as blank columns by default.
cwidth, cheight	initial width and height to use for cell sizes in inches.
defaults, theme_fun	deprecated, use set_flextable_defaults() instead.

Reuse frequently used parameters

Some default formatting properties are automatically applied to every flextable you produce.

It is highly recommended to use this function because its use will minimize the code. For example, instead of calling the `fontsize()` function over and over again for each new flextable, set the font size default value by calling (before creating the flextables) `set_flextable_defaults(font.size = 11)`. This is also a simple way to have homogeneous arrays and make the documents containing them easier to read.

You can change these default values with function `set_flextable_defaults()`. You can reset them with function `init_flextable_defaults()`. You can access these values by calling `get_flextable_defaults()`.

new lines and tabulations

The 'flextable' package will translate for you the new lines expressed in the form `\n` and the tabs expressed in the form `\t`.

The new lines will be transformed into "soft-return", that is to say a simple carriage return and not a new paragraph.

Tabs are different depending on the output format:

- HTML is using entity *em space*
- Word - a Word 'tab' element
- PowerPoint - a PowerPoint 'tab' element
- latex - tag "`\quad`"

flextable parts

A flextable is made of 3 parts: header, body and footer.

Most functions have an argument named `part` that will be used to specify what part of the table should be modified.

qflextable

`qflextable` is a convenient tool to produce quickly a flextable for reporting where layout is fixed (see `set_table_properties()`) and columns widths are adjusted with `autofit()`.

See Also

`style()`, `autofit()`, `theme_booktabs()`, `knit_print.flextable()`, `compose()`, `footnote()`, `set_caption()`

Examples

```
ft <- flextable(head(mtcars))
ft
```

<code>flextable_dim</code>	<i>width and height of a flextable object</i>
----------------------------	---

Description

Returns the width, height and aspect ratio of a flextable in a named list. The aspect ratio is the ratio corresponding to height/width.

Names of the list are `width`, `height` and `aspect_ratio`.

Usage

```
flextable_dim(x, unit = "in")
```

Arguments

<code>x</code>	a flextable object
<code>unit</code>	unit for returned values, one of "in", "cm", "mm".

See Also

Other flextable dimensions: `autofit()`, `dim.flextable()`, `dim.pretty()`, `fit_to_width()`, `height()`, `hrule()`, `ncol_keys()`, `nrow_part()`, `set_table_properties()`, `width()`

Examples

```
ftab <- flextable(head(iris))
flextable_dim(ftab)
ftab <- autofit(ftab)
flextable_dim(ftab)
```

flextable_html_dependency*htmlDependency for flextable objects***Description**

When using loops in an R Markdown for HTML document, the `htmlDependency` object for `flextable` must also be added at least once.

Usage

```
flextable_html_dependency(htmlscroll = TRUE)
```

Arguments

`htmlscroll` add a scroll if table is too big to fit into its HTML container, default to TRUE.

Examples

```
if(require("htmltools"))
  div(flextable_html_dependency())
```

flextable_to_rmd*flextable raw code***Description**

Print openxml, latex or html code of a `flextable`. The function is particularly useful when you want to generate `flextable` in a loop from a R Markdown document.

Inside R Markdown document, chunk option `results` must be set to 'asis'.

All arguments whose name starts with `ft.` can be set in the chunk options.

See [knit_print.flextable](#) for more details.

Usage

```
flextable_to_rmd(
  x,
  ft.align = opts_current$get("ft.align"),
  ft.split = opts_current$get("ft.split"),
  ft.keepnext = opts_current$get("ft.keepnext"),
  ft.tabcolsep = opts_current$get("ft.tabcolsep"),
  ft.arraystretch = opts_current$get("ft.arraystretch"),
  ft.latex.float = opts_current$get("ft.latex.float"),
  ft.left = opts_current$get("ft.left"),
  ft.top = opts_current$get("ft.top"),
```

```

text_after = "",
webshot = opts_current$get("webshot"),
bookdown = FALSE,
pandoc2 = TRUE,
print = TRUE,
...
)

```

Arguments

x	a flextable object
ft.align	flextable alignment, supported values are 'left', 'center' and 'right'.
ft.split	Word option 'Allow row to break across pages' can be activated when TRUE.
ft.keepnext	default TRUE. Word option 'keep rows together' is activated when TRUE. It avoids page break within tables. This is handy for small tables, i.e. less than a page height. Be careful, if you print long tables, you should rather set its value to FALSE to avoid that the tables also generate a page break before being placed in the Word document. Since Word will try to keep it with the next paragraphs that follow the tables .
ft.tabcolsep	space between the text and the left/right border of its containing cell, the default value is 8 points.
ft.arraystretch	height of each row relative to its default height, the default value is 1.5.
ft.latex.float	type of floating placement in the document, one of: <ul style="list-style-type: none"> 'none' (the default value), table is placed after the preceding paragraph. 'float', table can float to a place in the text where it fits best 'wrap-r', wrap text around the table positioned to the right side of the text 'wrap-l', wrap text around the table positioned to the left side of the text 'wrap-i', wrap text around the table positioned inside edge-near the binding 'wrap-o', wrap text around the table positioned outside edge-far from the binding
ft.left, ft.top	Position should be defined with options <code>ft.left</code> and <code>ft.top</code> . These are the top left coordinates in inches of the placeholder that will contain the table. Their default values are 1 and 2 inches.
text_after	The string you put here will be added after printing the content of the flextable. For example, you can put "\pagebreak" here to have tables produced with page breaks.
webshot	webshot package as a scalar character, one of "webshot" or "webshot2".
bookdown	TRUE or FALSE (default) to support cross referencing with bookdown.
pandoc2	TRUE (default) or FALSE to get the string in a pandoc raw HTML attribute (only valid when pandoc version is >= 2).
print	print output if TRUE
...	unused arguments

See Also

Other flextable print function: [as_raster\(\)](#), [df_printer\(\)](#), [htmltools_value\(\)](#), [knit_print.flextable\(\)](#), [plot.flextable\(\)](#), [print.flextable\(\)](#), [save_as_docx\(\)](#), [save_as_html\(\)](#), [save_as_image\(\)](#), [save_as_pptx\(\)](#)

Examples

```
demo_loop <- system.file(package = "flextable", "examples/rmd", "loop_with_flextable.Rmd")
rmd_file <- tempfile(fileext = ".Rmd")
file.copy(demo_loop, to = rmd_file, overwrite = TRUE)
rmd_file # R Markdown document used for demo
if(require("rmarkdown", quietly = TRUE)){
  # render(input = rmd_file, output_format = "word_document",
  #       output_file = "loop_with_flextable.docx")
  # render(input = rmd_file, output_format = "html_document",
  #       output_file = "loop_with_flextable.html")
  # render(input = rmd_file,
  #       output_format = rmarkdown::pdf_document(latex_engine = "xelatex"),
  #       output_file = "loop_with_flextable.pdf")
}
```

fmt_2stats

format content for data generated with [summarizor\(\)](#)

Description

This function was written to allow easy demonstrations of flextable's ability to produce table summaries (with [summarizor\(\)](#)). It assumes that we have either a quantitative variable, in which case we will display the mean and the standard deviation, or a qualitative variable, in which case we will display the count and the percentage corresponding to each modality.

Usage

```
fmt_2stats(
  num1,
  num2,
  cts,
  pcts,
  num1_mask = "%.01f",
  num2_mask = "(%.01f)",
  cts_mask = "%.0f",
  pcts_mask = "(%.02f %%)"
```

Arguments

num1	a numeric statistic to display such as a mean or a median
num2	a numeric statistic to display such as a standard deviation or a median absolute deviation.
cts	a count to display
pcts	a percentage to display
num1_mask	format associated with num1, a format string used by sprintf() .
num2_mask	format associated with num2, a format string used by sprintf() .
cts_mask	format associated with cts, a format string used by sprintf() .
pcts_mask	format associated with pcts, a format string used by sprintf() .

See Also

[summarizor\(\)](#), [tabulator\(\)](#), [mk_par\(\)](#)

font	<i>Set font</i>
------	-----------------

Description

change font of selected rows and columns of a flextable.

Usage

```
font(
  x,
  i = NULL,
  j = NULL,
  fontname,
  part = "body",
  cs.family = fontname,
  hansi.family = fontname,
  eastasia.family = fontname
)
```

Arguments

x	a flextable object
i	rows selection
j	columns selection
fontname	single character value. With Word and PowerPoint output, the value specifies the font to be used to format characters in the Unicode range (U+0000-U+007F).
part	partname of the table (one of 'all', 'body', 'header', 'footer')

<code>cs.family</code>	Optional font to be used to format characters in a complex script Unicode range. For example, Arabic text might be displayed using the "Arial Unicode MS" font. Used only with Word and PowerPoint outputs. Its default value is the value of <code>fontname</code> .
<code>hansi.family</code>	optional. Specifies the font to be used to format characters in a Unicode range which does not fall into one of the other categories. Used only with Word and PowerPoint outputs. Its default value is the value of <code>fontname</code> .
<code>eastasia.family</code>	optional font to be used to format characters in an East Asian Unicode range. For example, Japanese text might be displayed using the "MS Mincho" font. Used only with Word and PowerPoint outputs. Its default value is the value of <code>fontname</code> .

Illustrations

See Also

Other sugar functions for table style: `align()`, `bg()`, `bold()`, `color()`, `empty_blanks()`, `fontsize()`, `highlight()`, `italic()`, `line_spacing()`, `padding()`, `rotate()`, `valign()`

Examples

```
require("gdtools")
fontname <- "Brush Script MT"

if (font_family_exists(fontname)) {
  ft_1 <- flextable(head(iris))
  ft_2 <- font(ft_1, fontname = fontname, part = "header")
  ft_2 <- font(ft_2, fontname = fontname, j = 5)
  ft_2
}
```

`fontsize` *Set font size*

Description

change font size of selected rows and columns of a flextable.

Usage

```
fontsize(x, i = NULL, j = NULL, size = 11, part = "body")
```

Arguments

x	a flextable object
i	rows selection
j	columns selection
size	integer value (points)
part	partname of the table (one of 'all', 'body', 'header', 'footer')

Illustrations

See Also

Other sugar functions for table style: [align\(\)](#), [bg\(\)](#), [bold\(\)](#), [color\(\)](#), [empty_blanks\(\)](#), [font\(\)](#), [highlight\(\)](#), [italic\(\)](#), [line_spacing\(\)](#), [padding\(\)](#), [rotate\(\)](#), [valign\(\)](#)

Examples

```
ft <- flextable(head(iris))
ft <- fontsize(ft, size = 14, part = "header")
ft <- fontsize(ft, size = 14, j = 2)
ft <- fontsize(ft, size = 7, j = 3)
ft
```

footers_flextable_at_bkm

add flextable at a bookmark location in document's footer

Description

replace in the footer of a document a paragraph containing a bookmark by a flextable. A bookmark will be considered as valid if enclosing words within a paragraph; i.e., a bookmark along two or more paragraphs is invalid, a bookmark set on a whole paragraph is also invalid, but bookmarking few words inside a paragraph is valid.

Usage

```
footers_flextable_at_bkm(x, bookmark, value)
```

Arguments

x	an rdocx object
bookmark	bookmark id
value	a flextable object

footnote*add footnotes to flextable*

Description

The function let add footnotes to a flextable object by adding some symbols in the flextable and associated notes in the footer of the flextable.

Symbols are added to the cells designated by the selection i and j. If you use i = c(1,3) and j = c(2,5), then you will add the symbols (or the repeated symbol) to cells [1, 2] and [3, 5].

Usage

```
footnote(
  x,
  i = NULL,
  j = NULL,
  value,
  ref_symbols = NULL,
  part = "body",
  inline = FALSE,
  sep = ";" )
```

Arguments

x	a flextable object
i, j	cellwise rows and columns selection
value	a call to function as_paragraph() .
ref_symbols	character value, symbols to append that will be used as references to notes.
part	partname of the table (one of 'body', 'header', 'footer')
inline	whether to add footnote on same line as previous footnote or not
sep	used only when inline = TRUE, character string to use as a separator between footnotes.

Illustrations

Examples

```
ft_1 <- flextable(head(iris))
ft_1 <- footnote( ft_1, i = 1, j = 1:3,
                  value = as_paragraph(
                    c("This is footnote one",
                      "This is footnote two",
                      "This is footnote three"))
```

```

),
ref_symbols = c("a", "b", "c"),
part = "header")
ft_1 <- valign(ft_1, valign = "bottom", part = "header")
ft_1 <- autofit(ft_1)

ft_2 <- flextable(head(iris))
ft_2 <- autofit(ft_2)
ft_2 <- footnote( ft_2, i = 1, j = 1:2,
                  value = as_paragraph(
                    c("This is footnote one",
                      "This is footnote two"))
),
ref_symbols = c("a", "b"),
part = "header", inline = TRUE)
ft_2 <- footnote( ft_2, i = 1, j = 3:4,
                  value = as_paragraph(
                    c("This is footnote three",
                      "This is footnote four"))
),
ref_symbols = c("c","d"),
part = "header", inline = TRUE)
ft_2

ft_3 <- flextable(head(iris))
ft_3 <- autofit(ft_3)
ft_3 <- footnote(
  x = ft_3, i = 1:3, j = 1:3,
  ref_symbols = "a",
  value = as_paragraph("This is footnote one"))
)
ft_3

```

fp_border_default *Border formatting properties*

Description

Create a `fp_border()` object that uses default values defined in flextable defaults formatting properties, i.e. default border color (see `set_flextable_defaults()`).

Usage

```

fp_border_default(
  color = flextable_global$defaults$border.color,
  style = "solid",
  width = 1
)

```

Arguments

color	border color - single character value (e.g. "#000000" or "black")
style	border style - single character value : "none" or "solid" or "dotted" or "dashed"
width	border width - an integer value : 0>= value

See Also

[hline\(\)](#), [vline\(\)](#)

Other functions for defining formatting properties: [fp_text_default\(\)](#)

Examples

```
library(flextable)

set_flextable_defaults(
  border.color = "orange")

z <- flextable(head(cars))
z <- theme_vanilla(z)
z <- vline(
  z, j = 1, part = "all",
  border = officer::fp_border())
z <- vline(
  z, j = 2, part = "all",
  border = fp_border_default())
z

init_flextable_defaults()
```

fp_text_default *Text formatting properties*

Description

Create a [fp_text\(\)](#) object that uses default values defined in the flextable it applies to.

`fp_text_default()` is a handy function that will allow you to specify certain formatting values to be applied to a piece of text, the formatting values that are not specified will simply be the existing formatting values.

For example, if you set the text in the cell to red previously, using the code `fp_text_default(bold = TRUE)`, the formatting will be 'bold' but it will also be 'red'.

On the other hand, the `fp_text()` function forces you to specify all the parameters, so we strongly recommend working with `fp_text_default()` which was created to replace the use of the former.

See also [set_flextable_defaults\(\)](#) to modify flextable defaults formatting properties.

Usage

```
fp_text_default(  
  color = flextable_global$defaults$font.color,  
  font.size = flextable_global$defaults$font.size,  
  bold = FALSE,  
  italic = FALSE,  
  underlined = FALSE,  
  font.family = flextable_global$defaults$font.family,  
  cs.family = NULL,  
  eastasia.family = NULL,  
  hansi.family = NULL,  
  vertical.align = "baseline",  
  shading.color = "transparent"  
)
```

Arguments

color	font color - a single character value specifying a valid color (e.g. "#000000" or "black").
font.size	font size (in point) - 0 or positive integer value.
bold	is bold
italic	is italic
underlined	is underlined
font.family	single character value. Specifies the font to be used to format characters in the Unicode range (U+0000-U+007F).
cs.family	optional font to be used to format characters in a complex script Unicode range. For example, Arabic text might be displayed using the "Arial Unicode MS" font.
eastasia.family	optional font to be used to format characters in an East Asian Unicode range. For example, Japanese text might be displayed using the "MS Mincho" font.
hansi.family	optional. Specifies the font to be used to format characters in a Unicode range which does not fall into one of the other categories.
vertical.align	single character value specifying font vertical alignments. Expected value is one of the following : default 'baseline' or 'subscript' or 'superscript'
shading.color	shading color - a single character value specifying a valid color (e.g. "#000000" or "black").

See Also

[as_chunk\(\)](#), [compose\(\)](#), [append_chunks\(\)](#), [prepend_chunks\(\)](#)

Other functions for defining formatting properties: [fp_border_default\(\)](#)

Examples

```
library(flextable)

set_flextable_defaults(
  font.size = 11, font.color = "#303030",
  padding = 3, table.layout = "autofit")
z <- flextable(head(cars))

z <- compose(
  x = z,
  i = ~ speed < 6,
  j = "speed",
  value = as_paragraph(
    as_chunk("slow... ", props = fp_text_default(color = "red")),
    as_chunk(speed, props = fp_text_default(italic = TRUE)))
  )
)
z

init_flextable_defaults()
```

`get_flextable_defaults`

Get flextable defaults formatting properties

Description

The current formatting properties are automatically applied to every flextable you produce. These default values are returned by this function.

Usage

```
get_flextable_defaults()
```

Value

a list containing default values.

See Also

Other functions related to themes: `set_flextable_defaults()`, `theme_alfafoli()`, `theme_booktabs()`, `theme_box()`, `theme_tron_legacy()`, `theme_tron()`, `theme_vader()`, `theme_vanilla()`, `theme_zebra()`

Examples

```
get_flextable_defaults()
```

gg_chunk	<i>gg plots chunk wrapper</i>
----------	-------------------------------

Description

This function is used to insert mini gg plots into flextable with function `compose()`. It should be used inside a call to `as_paragraph()`.

Usage

```
gg_chunk(value, width = 1, height = 0.2, unit = "in")
```

Arguments

value	gg objects, stored in a list column.
width, height	size of the resulting png file in inches
unit	unit for width and height, one of "in", "cm", "mm".

Illustrations

Note

This chunk option requires package officedown in a R Markdown context with Word output format. PowerPoint cannot mix images and text in a paragraph, images are removed when outputting to PowerPoint format.

See Also

Other chunk elements for paragraph: `as_bracket()`, `as_b()`, `as_chunk()`, `as_equation()`, `as_highlight()`, `as_image()`, `as_i()`, `as_sub()`, `as_sup()`, `as_word_field()`, `colorize()`, `hyperlink_text()`, `linerange()`, `lollipop()`, `minibar()`, `plot_chunk()`

Examples

```
library(data.table)
library(flextable)
if(require("ggplot2")){
  my_cor_plot <- function(x){
    cols <- colnames(x)[sapply(x, is.numeric)]
    x <- x[, .SD, .SDcols = cols]
    cormat <- as.data.table(cor(x))
    cormat$var1 <- colnames(cormat)
    cormat <- melt(cormat, id.vars = "var1", measure.vars = cormat$var1,
                  variable.name = "var2", value.name = "correlation")
    ggplot(data = cormat, aes(x=var1, y=var2, fill=correlation)) +
      geom_tile() + coord_equal() +
```

```

    scale_fill_gradient2(low = "blue",
                         mid = "white", high = "red", limits = c(-1, 1),
                         guide = FALSE) + theme_void()
  }
z <- as.data.table(iris)
z <- z[ , list(gg = list(my_cor_plot(.SD))), by = "Species"]
ft <- flextable(z)
ft <- mk_par(ft, j = "gg",
             value = as_paragraph(
               gg_chunk(value = gg, width = 1, height = 1)
             ))
ft
}

```

headers_flextable_at_bkm*add flextable at a bookmark location in document's header***Description**

replace in the header of a document a paragraph containing a bookmark by a flextable. A bookmark will be considered as valid if enclosing words within a paragraph; i.e., a bookmark along two or more paragraphs is invalid, a bookmark set on a whole paragraph is also invalid, but bookmarking few words inside a paragraph is valid.

Usage

```
headers_flextable_at_bkm(x, bookmark, value)
```

Arguments

x	an rdocx object
bookmark	bookmark id
value	a flextable object

height*Set flextable rows height***Description**

control rows height for a part of the flextable when the line height adjustment is "atleast" or "exact" (see [hrule\(\)](#)).

Usage

```
height(x, i = NULL, height, part = "body", unit = "in")  
  
height_all(x, height, part = "all", unit = "in")
```

Arguments

x	flextable object
i	rows selection
height	height in inches
part	partname of the table
unit	unit for height, one of "in", "cm", "mm".

Illustrations**height_all**

`height_all` is a convenient function for setting the same height to all rows (selected with argument `part`).

Note

This function has no effect when the rule for line height is set to "auto" (see `hrule()`), which is the default case, except with PowerPoint which does not support this automatic line height adjustment feature.

See Also

Other flextable dimensions: `autofit()`, `dim.flextable()`, `dim.pretty()`, `fit_to_width()`, `flextable_dim()`, `hrule()`, `ncol_keys()`, `nrow_part()`, `set_table_properties()`, `width()`

Examples

```
ft_1 <- flextable(head(iris))  
ft_1 <- height(ft_1, height = .5)  
ft_1 <- hrule(ft_1, rule = "exact")  
ft_1  
  
ft_2 <- flextable(head(iris))  
ft_2 <- height_all(ft_2, height = 1)  
ft_2 <- hrule(ft_2, rule = "exact")  
ft_2
```

<code>highlight</code>	<i>Text highlight color</i>
------------------------	-----------------------------

Description

Change text highlight color of selected rows and columns of a flextable. A function can be used instead of fixed colors.

When `color` is a function, it is possible to color cells based on values located in other columns, using hidden columns (those not used by argument `colkeys`) is a common use case. The argument `source` has to be used to define what are the columns to be used for the color definition and the argument `j` has to be used to define where to apply the colors and only accept values from `colkeys`.

Usage

```
highlight(x, i = NULL, j = NULL, color = "yellow", part = "body", source = j)
```

Arguments

<code>x</code>	a flextable object
<code>i</code>	rows selection
<code>j</code>	columns selection
<code>color</code>	color to use as text highlighting color. If a function, function need to return a character vector of colors.
<code>part</code>	partname of the table (one of 'all', 'body', 'header', 'footer')
<code>source</code>	if <code>color</code> is a function, <code>source</code> is specifying the dataset column to be used as argument to <code>color</code> . This is only useful if <code>j</code> is colored with values contained in other columns.

Illustrations

See Also

Other sugar functions for table style: `align()`, `bg()`, `bold()`, `color()`, `empty_blanks()`, `fontsize()`, `font()`, `italic()`, `line_spacing()`, `padding()`, `rotate()`, `valign()`

Examples

```
my_color_fun <- function(x) {
  out <- rep("yellow", length(x))
  out[x < quantile(x, .75)] <- "pink"
  out[x < quantile(x, .50)] <- "wheat"
  out[x < quantile(x, .25)] <- "gray90"
  out
}
```

```
ft <- flextable(head(mtcars, n = 10))
ft <- highlight(ft, j = "disp", i = ~ disp > 200, color = "yellow")
ft <- highlight(ft, j = ~ drat + wt + qsec, color = my_color_fun)
ft
```

hline*set horizontal borders*

Description

The function is applying an horizontal border to inner content of one or all parts of a flextable. The lines are the bottom borders of selected cells.

Usage

```
hline(x, i = NULL, j = NULL, border = NULL, part = "body")
```

Arguments

x	a flextable object
i	rows selection
j	columns selection
border	border properties defined by a call to fp_border()
part	partname of the table (one of 'all', 'body', 'header', 'footer')

Illustrations**See Also**

Other borders management: [border_inner_h\(\)](#), [border_inner_v\(\)](#), [border_inner\(\)](#), [border_outer\(\)](#), [border_remove\(\)](#), [hline_bottom\(\)](#), [hline_top\(\)](#), [surround\(\)](#), [vline_left\(\)](#), [vline_right\(\)](#), [vline\(\)](#)

Examples

```
library(officer)
std_border = fp_border(color="gray")

ft <- flextable(head(iris))
ft <- border_remove(x = ft)

# add horizontal borders
ft <- hline(ft, part="all", border = std_border )
ft
```

hline_bottom	<i>set bottom horizontal border</i>
--------------	-------------------------------------

Description

The function is applying an horizontal border to the bottom of one or all parts of a flextable. The line is the bottom border of selected parts.

Usage

```
hline_bottom(x, j = NULL, border = NULL, part = "body")
```

Arguments

x	a flextable object
j	columns selection
border	border properties defined by a call to fp_border()
part	partname of the table (one of 'all', 'body', 'header', 'footer')

Illustrations

See Also

Other borders management: [border_inner_h\(\)](#), [border_inner_v\(\)](#), [border_inner\(\)](#), [border_outer\(\)](#), [border_remove\(\)](#), [hline_top\(\)](#), [hline\(\)](#), [surround\(\)](#), [vline_left\(\)](#), [vline_right\(\)](#), [vline\(\)](#)

Examples

```
library(officer)
big_border = fp_border(color="orange", width = 3)

ft <- flextable(head(iris))
ft <- border_remove(x = ft)

# add/replace horizontal border on bottom
ft <- hline_bottom(ft, part="body", border = big_border )
ft
```

hline_top	<i>set top horizontal border</i>
-----------	----------------------------------

Description

The function is applying an horizontal border to the top of one or all parts of a flextable. The line is the top border of selected parts.

Usage

```
hline_top(x, j = NULL, border = NULL, part = "body")
```

Arguments

x	a flextable object
j	columns selection
border	border properties defined by a call to fp_border()
part	partname of the table (one of 'all', 'body', 'header', 'footer')

Illustrations

See Also

Other borders management: [border_inner_h\(\)](#), [border_inner_v\(\)](#), [border_inner\(\)](#), [border_outer\(\)](#), [border_remove\(\)](#), [hline_bottom\(\)](#), [hline\(\)](#), [surround\(\)](#), [vline_left\(\)](#), [vline_right\(\)](#), [vline\(\)](#)

Examples

```
library(officer)
big_border = fp_border(color="orange", width = 3)

ft <- flextable(head(iris))
ft <- border_remove(x = ft)

# add horizontal border on top
ft <- hline_top(ft, part="all", border = big_border )
ft
```

hrule*Set flextable rule for rows heights*

Description

control rules of each height for a part of the flextable, this is only for Word and PowerPoint outputs, it will not have any effect when output is HTML or PDF.

Usage

```
hrule(x, i = NULL, rule = "auto", part = "body")
```

Arguments

x	flextable object
i	rows selection
rule	specify the meaning of the height. Possible values are "atleast" (height should be at least the value specified), "exact" (height should be exactly the value specified), or the default value "auto" (height is determined based on the height of the contents, so the value is ignored).
part	partname of the table, one of "all", "header", "body", "footer"

Illustrations

See Also

Other flextable dimensions: [autofit\(\)](#), [dim.flextable\(\)](#), [dim.pretty\(\)](#), [fit_to_width\(\)](#), [flextable_dim\(\)](#), [height\(\)](#), [ncol_keys\(\)](#), [nrow_part\(\)](#), [set_table_properties\(\)](#), [width\(\)](#)

Examples

```
ft_1 <- flextable(head(iris))
ft_1 <- width(ft_1, width = 1.5)
ft_1 <- height(ft_1, height = 0.75, part = "header")
ft_1 <- hrule(ft_1, rule = "exact", part = "header")
ft_1

ft_2 <- hrule(ft_1, rule = "auto", part = "header")
ft_2
```

htmltools_value	<i>flextable as an HTML object</i>
-----------------	------------------------------------

Description

get a [div\(\)](#) from a flextable object. This can be used in a shiny application. For an output within "R Markdown" document, use [knit_print.flextable](#).

Usage

```
htmltools_value(x, ft.align = "center", ft.shadow = TRUE, ft.htmlscroll = TRUE)
```

Arguments

x	a flextable object
ft.align	flextable alignment, supported values are 'left', 'center' and 'right'.
ft.shadow	use shadow dom, this option is existing to disable shadow dom (set to FALSE) for pagedown that can not support it for now.
ft.htmlscroll	add a scroll if table is too big to fit into its HTML container, default to TRUE.

Value

an object marked as [HTML](#) ready to be used within a call to [shiny::renderUI](#) for example.

See Also

Other flextable print function: [as_raster\(\)](#), [df_printer\(\)](#), [flextable_to_rmd\(\)](#), [knit_print.flextable\(\)](#), [plot.flextable\(\)](#), [print.flextable\(\)](#), [save_as_docx\(\)](#), [save_as_html\(\)](#), [save_as_image\(\)](#), [save_as_pptx\(\)](#)

Examples

```
htmltools_value(flextable(iris[1:5,]))
```

hyperlink_text	<i>Chunk of text with hyperlink</i>
----------------	-------------------------------------

Description

The function lets add hyperlinks within flextable objects.

It is used to add it to the content of a cell of the flextable with the functions [compose\(\)](#), [append_chunks\(\)](#) or [prepend_chunks\(\)](#).

URL are not encoded, they are preserved 'as is'.

Usage

```
hyperlink_text(x, props = NULL, formatter = format_fun, url, ...)
```

Arguments

x	text or any element that can be formatted as text with function provided in argument <code>formatter</code> .
props	an <code>officer::fp_text()</code> object to be used to format the text. If not specified, it will be the default value corresponding to the cell.
formatter	a function that will format x as a character vector.
url	url to be used
...	additional arguments for <code>formatter</code> function.

Note

This chunk option requires package `officedown` in a R Markdown context with Word output format.

See Also

[compose\(\)](#)

Other chunk elements for paragraph: [as_bracket\(\)](#), [as_b\(\)](#), [as_chunk\(\)](#), [as_equation\(\)](#), [as_highlight\(\)](#), [as_image\(\)](#), [as_i\(\)](#), [as_sub\(\)](#), [as_sup\(\)](#), [as_word_field\(\)](#), [colorize\(\)](#), [gg_chunk\(\)](#), [linerange\(\)](#), [lollipop\(\)](#), [minibar\(\)](#), [plot_chunk\(\)](#)

Examples

```
dat <- data.frame(
  col = "Google it",
  href = "https://www.google.fr/search?source=hp&q=flextabale+R+package",
  stringsAsFactors = FALSE)

ftab <- flextab(dat)
ftab <- compose( x = ftab, j = "col",
  value = as_paragraph(
    "This is a link: ",
    hyperlink_text(x = col, url = href) ) )
ftab
```

Description

change font decoration of selected rows and columns of a flextabale.

Usage

```
italic(x, i = NULL, j = NULL, italic = TRUE, part = "body")
```

Arguments

x	a flextable object
i	rows selection
j	columns selection
italic	boolean value
part	partname of the table (one of 'all', 'body', 'header', 'footer')

Illustrations

See Also

Other sugar functions for table style: [align\(\)](#), [bg\(\)](#), [bold\(\)](#), [color\(\)](#), [empty_blanks\(\)](#), [fontsize\(\)](#), [font\(\)](#), [highlight\(\)](#), [line_spacing\(\)](#), [padding\(\)](#), [rotate\(\)](#), [valign\(\)](#)

Examples

```
ft <- flextable(head(mtcars))
ft <- italic(ft, italic = TRUE, part = "header")
```

`knit_print.flextable` *Render flextable in rmarkdown*

Description

Function used to render flextable in knitr/rmarkdown documents.

You should not call this method directly. This function is used by the knitr package to automatically display a flextable in an "R Markdown" document from a chunk. However, it is recommended to read its documentation in order to get familiar with the different options available.

R Markdown outputs can be :

- HTML
- 'Microsoft Word'
- 'Microsoft PowerPoint'
- PDF

Table captioning is a flextable feature compatible with R Markdown documents. The feature is available for HTML, PDF and Word documents. Compatibility with the "bookdown" package is also ensured, including the ability to produce captions so that they can be used in cross-referencing. For Word, it's recommended to work with package 'officedown' that supports all features of flextable.

Usage

```
## S3 method for class 'flextable'
knit_print(x, ...)
```

Arguments

x	a flextable object
...	arguments passed to flextable_to_rmd() .

Chunk options

Some features, often specific to an output format, are available to help you configure some global settings relative to the table output. knitr's chunk options are to be used to change the default settings:

chunk option	property
ft.align	flextable alignment, supported values are 'left', 'center' and 'right'
ft.shadow	HTML option, disable shadow dom (set to FALSE) for pagedown.
ft.htmlscroll	HTML option, add a scroll if table is too big to fit into its HTML container.
ft.split	Word option 'Allow row to break across pages' can be activated when TRUE.
ft.keepnext	Word option 'keep rows together' can be desactivated when FALSE
ft.tabcolsep	space between the text and the left/right border of its containing cell
ft.arraystretch	height of each row relative to its default height
ft.latex.float	type of floating placement in the document, one of 'none', 'float', 'wrap-r', 'wrap-l', 'wrap-i', 'wrap-o'
ft.left	left coordinates in inches
ft.top	top coordinates in inches

If some values are to be used all the time in the same document, it is recommended to set these values in a 'knitr r chunk' by using function `knitr::opts_chunk$set(ft.split=FALSE, ft.keepnext = FALSE, ...)`.

See [flextable_to_rmd\(\)](#) for more details about these options.

Table caption

Captions can be defined in two ways.

The first is with the `set_caption` function. If it is used, the other method will be ignored. The second method is by using knitr chunk option `tab.cap`.

```
set_caption(x, caption = "my caption")
```

If `set_caption` function is not used, caption identifier will be read from knitr's chunk option `tab.id`. Note that in a bookdown and when not using `officedown::rdocx_document()`, the usual numbering feature of bookdown is used.

```
tab.id='my_id'.
```

Some options are available to customise captions for any output:

label	name	value
Word stylename to use for table captions.	tab.cap.style	NULL

caption id/bookmark	tab.id	NULL
caption	tab.cap	NULL
display table caption on top of the table or not	tab.topcaption	TRUE
caption table sequence identifier.	tab.lp	"tab:"

Word output when `officedown::rdocx_document()` is used is coming with more options such as ability to choose the prefix for numbering chunk for example. The table below expose these options:

label	name	value
prefix for numbering chunk (default to "Table ")	tab.cap.pre	Table
suffix for numbering chunk (default to ": ")	tab.cap.sep	" :"
title number depth	tab.cap.tnd	0
caption prefix formatting properties	tab.cap.fp_text	fp_text_lite(bold = TRUE)
separator to use between title number and table number.	tab.cap.tns	"_"

HTML output

HTML output is using shadow dom to encapsule the table into an isolated part of the page so that no clash happens with styles. Some output may not support this feature. To our knowledge, only the pagedown output is concerned. Use knitr chunk option `ft.shadow=FALSE` to disable shadow dom.

If `ft.shadow=TRUE` some global CSS rules may change the desired output of flextables.

PDF output

Some features are not implemented in PDF due to technical infeasibility. These are the padding, line_spacing and height properties.

It is recommended to set theses values in a 'knitr r chunk' so that they are permanent all along the document: `knitr::opts_chunk$set(ft.tabcolsep=0, ft.latex.float = "none")`.

Background color and merged cells does not work well together with PDF format. Authors are hoping to fix this issue in the future.

See [add_latex_dep\(\)](#) if caching flextable results in 'R Markdown' documents.

PowerPoint output

Auto-adjust Layout is not available for PowerPoint, PowerPoint only support fixed layout. It's then often necessary to call function [autofit\(\)](#) so that the columns' widths are adjusted if user does not provide the widths.

Images cannot be integrated into tables with the PowerPoint format.

Note

Supported formats require some minimum [pandoc](#) versions:

Output format	pandoc minimal version
----------------------	-------------------------------

HTML	>= 1.12
Word (docx)	>= 2.0
PowerPoint (pptx)	>= 2.4
PDF	>= 1.12

See Also

Other flextable print function: [as_raster\(\)](#), [df_printer\(\)](#), [flextable_to_rmd\(\)](#), [htmltools_value\(\)](#), [plot.flextable\(\)](#), [print.flextable\(\)](#), [save_as_docx\(\)](#), [save_as_html\(\)](#), [save_as_image\(\)](#), [save_as_pptx\(\)](#)

Examples

```
# simple examples -----
demo_docx <- system.file(package = "flextable", "examples/rmd", "demo.Rmd")
rmd_file <- tempfile(fileext = ".Rmd")
file.copy(demo_docx, to = rmd_file, overwrite = TRUE)
rmd_file # R Markdown document used for demo
if(require("rmarkdown", quietly = TRUE)){
  # knitr::opts_chunk$set(webshot = "webshot2")
  # render(input = rmd_file, output_format = "word_document", output_file = "doc.docx")
  # render(input = rmd_file, output_format = "pdf_document", output_file = "doc.pdf")
  # render(input = rmd_file, output_format = "html_document", output_file = "doc.html")
  # render(input = rmd_file, output_format = "powerpoint_presentation", output_file = "pres.pptx")
  # render(input = rmd_file, output_format = "slidy_presentation", output_file = "slidy.html")
  # render(input = rmd_file, output_format = "beamer_presentation", output_file = "beamer.pdf")
  # render(input = rmd_file, output_format = "pagedown::html_paged", output_file = "paged.html")
}

## bookdown examples wth captions and cross ref -----
# captions_example <- system.file(
#   package = "flextable",
#   "examples/rmd", "captions_example.Rmd")
#
# dir_tmp <- tempfile(pattern = "dir")
# dir.create(dir_tmp, showWarnings = FALSE, recursive = TRUE)
# file.copy(captions_example, dir_tmp)
# rmd_file <- file.path(dir_tmp, basename(captions_example))
#
# file.copy(captions_example, to = rmd_file, overwrite = TRUE)
#
# if(require("rmarkdown", quietly = TRUE)){
  # render(input = rmd_file,
  #        output_format = word_document(),
  #        output_file = "doc.docx")
  # render(input = rmd_file,
  #        output_format = pdf_document(latex_engine = "xelatex"),
  #        output_file = "doc.pdf")
  # render(input = rmd_file,
  #        output_format = html_document(),
```

```

#           output_file = "doc.html")
#
#   # bookdown ----
#   if(require("bookdown", quietly = TRUE)){
#     render(input = rmd_file, output_format = word_document2(),
#           output_file = "book.docx")
#     render(input = rmd_file,
#           output_format = pdf_document2(latex_engine = "xelatex"),
#           output_file = "book.pdf")
#     render(input = rmd_file,
#           output_format = html_document2(),
#           output_file = "book.html")
#
#   # officedown ----
#   if(require("officedown", quietly = TRUE)){
#     render(input = rmd_file,
#           output_format = markdown_document2(base_format=rdocx_document),
#           output_file = "officedown.docx")
#   }
# }
# }

# browseURL(dirname(rmd_file))

```

linerange*mini linerange chunk wrapper***Description**

This function is used to insert lineranges into flextable with function [compose\(\)](#). It should be used inside a call to [as_paragraph\(\)](#)

Usage

```

linerange(
  value,
  min = NULL,
  max = NULL,
  rangecol = "#CCCCCC",
  stickcol = "#FF0000",
  bg = "transparent",
  width = 1,
  height = 0.2,
  raster_width = 30,
  unit = "in"
)

```

Arguments

<code>value</code>	values containing the bar size
<code>min</code>	min bar size. Default min of value
<code>max</code>	max bar size. Default max of value
<code>rangecol</code>	bar color
<code>stickcol</code>	jauge color
<code>bg</code>	background color
<code>width, height</code>	size of the resulting png file in inches
<code>raster_width</code>	number of pixels used as width when interpolating value.
<code>unit</code>	unit for width and height, one of "in", "cm", "mm".

Note

This chunk option requires package `officedown` in a R Markdown context with Word output format. PowerPoint cannot mix images and text in a paragraph, images are removed when outputting to PowerPoint format.

See Also

`compose()`, `as_paragraph()`

Other chunk elements for paragraph: `as_bracket()`, `as_b()`, `as_chunk()`, `as_equation()`, `as_highlight()`, `as_image()`, `as_i()`, `as_sub()`, `as_sup()`, `as_word_field()`, `colorize()`, `gg_chunk()`, `hyperlink_text()`, `lollipop()`, `minibar()`, `plot_chunk()`

Examples

```
myft <- flextable( head(iris, n = 10 ) )

myft <- compose( myft, j = 1,
  value = as_paragraph(
    linerange(value = Sepal.Length)
  ),
  part = "body" )

autofit(myft)
```

`line_spacing`

Set text alignment

Description

change text alignment of selected rows and columns of a `flextable`.

Usage

```
line_spacing(x, i = NULL, j = NULL, space = 1, part = "body", unit = "in")
```

Arguments

x	a flextable object
i	rows selection
j	columns selection
space	space between lines of text, 1 is single line spacing, 2 is double line spacing.
part	partname of the table (one of 'all', 'body', 'header', 'footer')
unit	unit for space, one of "in", "cm", "mm".

Illustrations

See Also

Other sugar functions for table style: [align\(\)](#), [bg\(\)](#), [bold\(\)](#), [color\(\)](#), [empty_blanks\(\)](#), [fontsize\(\)](#), [font\(\)](#), [highlight\(\)](#), [italic\(\)](#), [padding\(\)](#), [rotate\(\)](#), [valign\(\)](#)

Examples

```
ft <- flextable(head(mtcars)[, 3:6])
ft <- line_spacing(ft, space = 1.6, part = "all")
ft <- set_table_properties(ft, layout = "autofit")
ft
```

lollipop

mini lollipop chart chunk wrapper

Description

This function is used to insert lollipop charts into flextable with function [compose\(\)](#). It should be used inside a call to [as_paragraph\(\)](#)

Usage

```
lollipop(
  value,
  min = NULL,
  max = NULL,
  rangecol = "#CCCCCC",
  bg = "transparent",
  width = 1,
  height = 0.2,
```

```

    unit = "in",
    raster_width = 30,
    positivecol = "#00CC00",
    negativecol = "#CC0000",
    neutralcol = "#CCCCCC",
    neutralrange = c(0, 0),
    rectanglesize = 2
)

```

Arguments

<code>value</code>	values containing the bar size
<code>min</code>	min bar size. Default min of value
<code>max</code>	max bar size. Default max of value
<code>rangecol</code>	bar color
<code>bg</code>	background color
<code>width, height</code>	size of the resulting png file in inches
<code>unit</code>	unit for width and height, one of "in", "cm", "mm".
<code>raster_width</code>	number of pixels used as width
<code>positivecol</code>	box color of positive values
<code>negativecol</code>	box color of negative values
<code>neutralcol</code>	box color of neutral values
<code>neutralrange</code>	minimal and maximal range of neutral values (default: 0)
<code>rectanglesize</code>	size of the rectangle (default: 2, max: 5) when interpolating value.

Illustrations

Note

This chunk option requires package officedown in a R Markdown context with Word output format.
PowerPoint cannot mix images and text in a paragraph, images are removed when outputting to PowerPoint format.

See Also

`compose()`, `as_paragraph()`

Other chunk elements for paragraph: `as_bracket()`, `as_b()`, `as_chunk()`, `as_equation()`, `as_highlight()`, `as_image()`, `as_i()`, `as_sub()`, `as_sup()`, `as_word_field()`, `colorize()`, `gg_chunk()`, `hyperlink_text()`, `linerange()`, `minibar()`, `plot_chunk()`

Examples

```
iris$Sepal.Ratio <- (iris$Sepal.Length - mean(iris$Sepal.Length))/mean(iris$Sepal.Length)
ft <- flextable( tail(iris, n = 10 ))

ft <- compose( ft, j = "Sepal.Ratio",   value = as_paragraph(
  lollipop(value = Sepal.Ratio, min=-.25, max=.25)
),
part = "body")

ft <- autofit(ft)
ft
```

merge_at

Merge flextable cells into a single one

Description

Merge flextable cells into a single one. All rows and columns must be consecutive.

Usage

```
merge_at(x, i = NULL, j = NULL, part = "body")
```

Arguments

x	flextable object
i, j	columns and rows to merge
part	partname of the table where merge has to be done.

See Also

Other flextable merging function: [merge_h_range\(\)](#), [merge_h\(\)](#), [merge_none\(\)](#), [merge_v\(\)](#)

Examples

```
ft_merge <- flextable( head( mtcars ), cwidth = .5 )
ft_merge <- merge_at( ft_merge, i = 1:2, j = 1:2 )
ft_merge
```

`merge_h`*Merge flextable cells horizontally*

Description

Merge flextable cells horizontally when consecutive cells have identical values. Text of formatted values are used to compare values.

Usage

```
merge_h(x, i = NULL, part = "body")
```

Arguments

x	flextable object
i	rows where cells have to be merged.
part	partname of the table where merge has to be done.

See Also

Other flextable merging function: `merge_at()`, `merge_h_range()`, `merge_none()`, `merge_v()`

Examples

```
dummy_df <- data.frame( col1 = letters,
                        col2 = letters, stringsAsFactors = FALSE )
ft_merge <- flextable(dummy_df)
ft_merge <- merge_h(x = ft_merge)
ft_merge
```

`merge_h_range`*rowwise merge of a range of columns*

Description

Merge flextable columns into a single one for each selected rows. All columns must be consecutive.

Usage

```
merge_h_range(x, i = NULL, j1 = NULL, j2 = NULL, part = "body")
```

Arguments

x	flextable object
i	selected rows
j1, j2	selected columns that will define the range of columns to merge.
part	partname of the table where merge has to be done.

Illustrations

See Also

Other flextable merging function: [merge_at\(\)](#), [merge_h\(\)](#), [merge_none\(\)](#), [merge_v\(\)](#)

Examples

```
ft <- flextable( head( mtcars ), cwidth = .5 )
ft <- theme_box( ft )
ft <- merge_h_range( ft, i = ~ cyl == 6, j1 = "am", j2 = "carb")
ft <- flextable::align( ft, i = ~ cyl == 6, align = "center")
ft
```

merge_none

Delete flextable merging informations

Description

Delete all merging informations from a flextable.

Usage

```
merge_none(x, part = "all")
```

Arguments

x	flextable object
part	partname of the table where merge has to be done.

Illustrations

See Also

Other flextable merging function: [merge_at\(\)](#), [merge_h_range\(\)](#), [merge_h\(\)](#), [merge_v\(\)](#)

Examples

```
typology <- data.frame(
  col_keys = c( "Sepal.Length", "Sepal.Width", "Petal.Length", "Petal.Width", "Species" ),
  what = c("Sepal", "Sepal", "Petal", "Petal", "Species"),
  measure = c("Length", "Width", "Length", "Width", "Species"),
  stringsAsFactors = FALSE )

ft <- flextable( head( iris ) )
```

```
ft <- set_header_df(ft, mapping = typology, key = "col_keys" )
ft <- merge_v(ft, j = c("Species"))

ft <- theme_tron_legacy( merge_none( ft ) )
ft
```

merge_v*Merge flextable cells vertically***Description**

Merge flextable cells vertically when consecutive cells have identical values. Text of formatted values are used to compare values if available.

Two options are available, either a column-by-column algorithm or an algorithm where the combinations of these columns are used once for all target columns.

Usage

```
merge_v(x, j = NULL, target = NULL, part = "body", combine = FALSE)
```

Arguments

x	flextable object
j	column to used to find consecutive values to be merged. Columns from original dataset can also be used.
target	columns names where cells have to be merged.
part	partname of the table where merge has to be done.
combine	If the value is TRUE, the columns defined by j will be combined into a single column/value and the consecutive values of this result will be used. Otherwise, the columns are inspected one by one to perform cell merges.

Illustrations**See Also**

Other flextable merging function: [merge_at\(\)](#), [merge_h_range\(\)](#), [merge_h\(\)](#), [merge_none\(\)](#)

Examples

```
ft_merge <- flextable(mtcars)
ft_merge <- merge_v(ft_merge, j = c("gear", "carb"))
ft_merge

data_ex <- structure(list(srdr_id = c(
"175124", "175124", "172525", "172525",
```

```

"172545", "172545", "172609", "172609", "172609"
), substances = c(
  "alcohol",
  "alcohol", "alcohol", "alcohol", "cannabis",
  "cannabis", "alcohol\n cannabis\n other drugs",
  "alcohol\n cannabis\n other drugs",
  "alcohol\n cannabis\n other drugs"
), full_name = c(
  "TAU", "MI", "TAU", "MI (parent)", "TAU", "MI",
  "TAU", "MI", "MI"
), article_arm_name = c(
  "Control", "WISEteens",
  "Treatment as usual", "Brief MI (b-MI)", "Assessed control",
  "Intervention", "Control", "Computer BI", "Therapist BI"
)), row.names = c(
  NA,
  -9L
), class = c("tbl_df", "tbl", "data.frame"))

ft_1 <- flextable(data_ex)
ft_1 <- theme_box(ft_1)
ft_2 <- merge_v(ft_1, j = "srdr_id",
  target = c("srdr_id", "substances"))
ft_2

```

Description

This function is used to insert bars into flextable with function `compose()`. It should be used inside a call to `as_paragraph()`

Usage

```
minibar(
  value,
  max = NULL,
  barcol = "#CCCCCC",
  bg = "transparent",
  width = 1,
  height = 0.2,
  unit = "in"
)
```

Arguments

value	values containing the bar size
-------	--------------------------------

<code>max</code>	max bar size
<code>barcol</code>	bar color
<code>bg</code>	background color
<code>width, height</code>	size of the resulting png file in inches
<code>unit</code>	unit for width and height, one of "in", "cm", "mm".

Illustrations

Note

This chunk option requires package officedown in a R Markdown context with Word output format. PowerPoint cannot mix images and text in a paragraph, images are removed when outputting to PowerPoint format.

See Also

[compose\(\)](#), [as_paragraph\(\)](#)

Other chunk elements for paragraph: [as_bracket\(\)](#), [as_b\(\)](#), [as_chunk\(\)](#), [as_equation\(\)](#), [as_highlight\(\)](#), [as_image\(\)](#), [as_i\(\)](#), [as_sub\(\)](#), [as_sup\(\)](#), [as_word_field\(\)](#), [colorize\(\)](#), [gg_chunk\(\)](#), [hyperlink_text\(\)](#), [linerange\(\)](#), [lollipop\(\)](#), [plot_chunk\(\)](#)

Examples

```
ft <- flextable( head(iris, n = 10 ))

ft <- compose(ft, j = 1,
  value = as_paragraph(
    minibar(value = Sepal.Length, max = max(Sepal.Length))
  ),
  part = "body")

ft <- autofit(ft)
ft
```

<i>ncol_keys</i>	<i>Number of columns</i>
------------------	--------------------------

Description

returns the number of columns displayed

Usage

`ncol_keys(x)`

Arguments

x flextable object

See Also

Other flextable dimensions: [autofit\(\)](#), [dim.flextable\(\)](#), [dim.pretty\(\)](#), [fit_to_width\(\)](#), [flextable_dim\(\)](#), [height\(\)](#), [hrule\(\)](#), [nrow_part\(\)](#), [set_table_properties\(\)](#), [width\(\)](#)

Examples

```
library(flextable)
ft <- qflextable(head(cars))
ncol_keys(ft)
```

nrow_part	<i>Number of rows of a part</i>
-----------	---------------------------------

Description

returns the number of lines in a part of flextable.

Usage

```
nrow_part(x, part = "body")
```

Arguments

x flextable object
part partname of the table (one of 'body', 'header', 'footer')

See Also

Other flextable dimensions: [autofit\(\)](#), [dim.flextable\(\)](#), [dim.pretty\(\)](#), [fit_to_width\(\)](#), [flextable_dim\(\)](#), [height\(\)](#), [hrule\(\)](#), [ncol_keys\(\)](#), [set_table_properties\(\)](#), [width\(\)](#)

Examples

```
library(flextable)
ft <- qflextable(head(cars))
nrow_part(ft, part = "body")
```

padding	<i>Set paragraph paddings</i>
---------	-------------------------------

Description

change paddings of selected rows and columns of a flextable.

Usage

```
padding(
  x,
  i = NULL,
  j = NULL,
  padding = NULL,
  padding.top = NULL,
  padding.bottom = NULL,
  padding.left = NULL,
  padding.right = NULL,
  part = "body"
)
```

Arguments

x	a flextable object
i	rows selection
j	columns selection
padding	padding (shortcut for top, bottom, left and right), unit is pts (points).
padding.top	padding top, unit is pts (points).
padding.bottom	padding bottom, unit is pts (points).
padding.left	padding left, unit is pts (points).
padding.right	padding right, unit is pts (points).
part	partname of the table (one of 'all', 'body', 'header', 'footer')

Illustrations

See Also

Other sugar functions for table style: [align\(\)](#), [bg\(\)](#), [bold\(\)](#), [color\(\)](#), [empty_blanks\(\)](#), [fontsize\(\)](#), [font\(\)](#), [highlight\(\)](#), [italic\(\)](#), [line_spacing\(\)](#), [rotate\(\)](#), [valign\(\)](#)

Examples

```
ft_1 <- flextable(head(iris))
ft_1 <- theme_vader(ft_1)
ft_1 <- padding(ft_1, padding.top = 4, part = "all")
ft_1 <- padding(ft_1, j = 1, padding.right = 40)
ft_1 <- padding(ft_1, i = 3, padding.top = 40)
ft_1 <- padding(ft_1, padding.top = 10, part = "header")
ft_1 <- padding(ft_1, padding.bottom = 10, part = "header")
ft_1 <- autofit(ft_1)
ft_1
```

`ph_with.flextable` *add a flextable into a PowerPoint slide*

Description

Add a flextable in a PowerPoint document object produced by [officer::read_pptx\(\)](#).

Usage

```
## S3 method for class 'flextable'
ph_with(x, value, location, ...)
```

Arguments

<code>x</code>	a pptx device
<code>value</code>	flextable object
<code>location</code>	a location for a placeholder. See officer::ph_location_type() for example.
<code>...</code>	unused arguments.

Note

The width and height of the table can not be set with `location`. Use functions [width\(\)](#), [height\(\)](#), [autofit\(\)](#) and [dim_pretty\(\)](#) instead. The overall size is resulting from cells, paragraphs and text properties (i.e. padding, font size, border widths).

Examples

```
library(officer)

ft <- flextable(head(iris))

doc <- read_pptx()
doc <- add_slide(doc, "Title and Content", "Office Theme")
doc <- ph_with(doc, ft, location = ph_location_left())

fileout <- tempfile(fileext = ".pptx")
print(doc, target = fileout)
```

plot.flextable *plot a flextable*

Description

save a flextable as an image and display the result in a new R graphics window.

Usage

```
## S3 method for class 'flextable'
plot(x, zoom = 2, expand = 2, ...)
```

Arguments

- x a flextable object
- zoom, expand parameters used by `webshot` function.
- ... additional parameters sent to `as_raster()` function

Note

This function requires packages: `webshot` and `magick`.

See Also

Other flextable print function: `as_raster()`, `df_printer()`, `flextable_to_rmd()`, `htmltools_value()`, `knit_print.flextable()`, `print.flextable()`, `save_as_docx()`, `save_as_html()`, `save_as_image()`, `save_as_pptx()`

Examples

```
ftab <- flextable( head( mtcars ) )
ftab <- autofit(ftab)
## Not run:
if( require("webshot") ){
  plot(ftab)
}

## End(Not run)
```

plot_chunk	<i>mini plots chunk wrapper</i>
------------	---------------------------------

Description

This function is used to insert mini plots into flextable with function [compose\(\)](#). It should be used inside a call to [as_paragraph\(\)](#).

Available plots are 'box', 'line', 'points', 'density'.

Usage

```
plot_chunk(  
  value,  
  width = 1,  
  height = 0.2,  
  type = "box",  
  free_scale = FALSE,  
  unit = "in",  
  ...  
)
```

Arguments

value	a numeric vector, stored in a list column.
width, height	size of the resulting png file in inches
type	type of the plot: 'box', 'line', 'points' or 'density'.
free_scale	Should scales be free (TRUE or FALSE, the default value).
unit	unit for width and height, one of "in", "cm", "mm".
...	arguments sent to plot functions (see par())

Illustrations

Note

This chunk option requires package officedown in a R Markdown context with Word output format.

PowerPoint cannot mix images and text in a paragraph, images are removed when outputting to PowerPoint format.

See Also

Other chunk elements for paragraph: [as_bracket\(\)](#), [as_b\(\)](#), [as_chunk\(\)](#), [as_equation\(\)](#), [as_highlight\(\)](#), [as_image\(\)](#), [as_i\(\)](#), [as_sub\(\)](#), [as_sup\(\)](#), [as_word_field\(\)](#), [colorize\(\)](#), [gg_chunk\(\)](#), [hyperlink_text\(\)](#), [linerange\(\)](#), [lollipop\(\)](#), [minibar\(\)](#)

Examples

```
library(data.table)
library(flextable)

z <- as.data.table(iris)
z <- z[ , list(
  Sepal.Length = mean(Sepal.Length, na.rm = TRUE),
  z = list(.SD$Sepal.Length)
), by = "Species"]

ft <- flextable(z,
  col_keys = c("Species", "Sepal.Length", "box", "density"))
ft <- mk_par(ft, j = "box", value = as_paragraph(
  plot_chunk(value = z, type = "box",
    border = "red", col = "transparent")))
ft <- mk_par(ft, j = "density", value = as_paragraph(
  plot_chunk(value = z, type = "dens", col = "red")))
ft <- set_table_properties(ft, layout = "autofit", width = .6)
ft <- set_header_labels(ft, box = "boxplot", density= "density")
theme_vanilla(ft)
```

prepend_chunks

prepend chunks to flextable content

Description

prepend chunks (for example chunk [as_chunk\(\)](#)) in a flextable.

Usage

```
prepend_chunks(x, ..., i = NULL, j = NULL, part = "body")
```

Arguments

x	a flextable object
...	chunks to be prepended, see as_chunk() , gg_chunk() and other chunk elements for paragraph.
i	rows selection
j	column selection
part	partname of the table (one of 'body', 'header', 'footer')

See Also

Other functions for mixed content paragraphs: [append_chunks\(\)](#), [as_paragraph\(\)](#), [compose\(\)](#)

Examples

```
x <- flextable(head(iris))
x <- prepend_chunks(
  x,
  i = 1, j = 1,
  colorize(as_b("coucou "), color = "red")
)
x
```

print.flextable *flextable printing*

Description

print a flextable object to format html, docx, pptx or as text (not for display but for informative purpose). This function is to be used in an interactive context.

Usage

```
## S3 method for class 'flextable'
print(x, preview = "html", ...)
```

Arguments

x	flextable object
preview	preview type, one of c("html", "pptx", "docx", "pdf", "log"). When "log" is used, a description of the flextable is printed.
...	arguments for 'pdf_document' call when preview is "pdf".

Note

When argument preview is set to "docx" or "pptx", an external client linked to these formats (Office is installed) is used to edit a document. The document is saved in the temporary directory of the R session and will be removed when R session will be ended.

When argument preview is set to "html", an external client linked to these HTML format is used to display the table. If RStudio is used, the Viewer is used to display the table.

Note also that a print method is used when flextable are used within R markdown documents. See [knit_print.flextable\(\)](#).

See Also

Other flextable print function: [as_raster\(\)](#), [df_printer\(\)](#), [flextable_to_rmd\(\)](#), [htmltools_value\(\)](#), [knit_print.flextable\(\)](#), [plot.flextable\(\)](#), [save_as_docx\(\)](#), [save_as_html\(\)](#), [save_as_image\(\)](#), [save_as_pptx\(\)](#)

proc_freq *frequency table as flextable*

Description

This function compute a two way contingency table and make a flextable with the result.

Usage

```
proc_freq(
  x,
  row,
  col,
  main = "",
  include.row_percent = TRUE,
  include.column_percent = TRUE,
  include.table_percent = TRUE,
  include.column_total = TRUE,
  include.row_total = TRUE,
  include.header_row = TRUE,
  weight = NULL
)
```

Arguments

x	data.frame object
row	characer column names for row
col	characer column names for column
main	characer title
include.row_percent	boolean whether to include the row percents; defaults to TRUE
include.column_percent	boolean whether to include the column percents; defaults to TRUE
include.table_percent	boolean whether to include the table percents; defaults to TRUE
include.column_total	boolean whether to include the row of column totals; defaults to TRUE
include.row_total	boolean whether to include the column of row totals; defaults to TRUE
include.header_row	boolean whether to include the header row; defaults to TRUE
weight	character column name for weight

Author(s)

Titouan Robert

Examples

```
proc_freq(mtcars, "vs", "gear")
proc_freq(mtcars, "gear", "vs")
proc_freq(mtcars, "gear", "vs", weight = "wt")
proc_freq(mtcars, "gear", "vs", "My title")
```

`rotate`

rotate cell text

Description

It can be useful to be able to change the direction, when the table headers are huge for example, header labels can be rendered as "tblr" (top to bottom and right to left) corresponding to a 90 degrees rotation or "btlr" corresponding to a 270 degrees rotation. The function change cell text direction. By default, it is "lrbt" which mean from left to right and top to bottom.

'Word' and 'PowerPoint' don't handle auto height with rotated headers. So you need to set header heights (with function [height\(\)](#)) and set rule "exact" for rows heights (with function [hrule\(\)](#)) otherwise Word and PowerPoint outputs will have small height not corresponding to the necessary height to display the text.

flextable doesn't do the rotation by any angle. It only rotates by a number of right angles. This choice is made to ensure the same rendering between Word, PowerPoint (limited to angles 0, 270 and 90) HTML and PDF.

Usage

```
rotate(x, i = NULL, j = NULL, rotation, align = NULL, part = "body")
```

Arguments

<code>x</code>	a flextable object
<code>i</code>	rows selection
<code>j</code>	columns selection
<code>rotation</code>	one of "lrbt", "tblr", "btlr".
<code>align</code>	vertical alignment of paragraph within cell, one of "center" or "top" or "bottom".
<code>part</code>	partname of the table (one of 'all', 'body', 'header', 'footer')

Details

When function `autofit` is used, the rotation will be ignored. In that case, use [dim_pretty](#) and [width](#) instead of [autofit](#).

Illustrations

See Also

Other sugar functions for table style: [align\(\)](#), [bg\(\)](#), [bold\(\)](#), [color\(\)](#), [empty_blanks\(\)](#), [fontsize\(\)](#), [font\(\)](#), [highlight\(\)](#), [italic\(\)](#), [line_spacing\(\)](#), [padding\(\)](#), [valign\(\)](#)

Examples

```
library(flextable)

ft_1 <- flextable(head(iris))

ft_1 <- rotate(ft_1, j = 1:4, align = "bottom", rotation = "tbrl", part = "header")
ft_1 <- rotate(ft_1, j = 5, align = "bottom", rotation = "btlr", part = "header")

# if output is docx or pptx, think about (1) set header heights
# and (2) set rule "exact" for rows heights because Word
# and PowerPoint don't handle auto height with rotated headers
ft_1 <- height(ft_1, height = 1.2, part = "header")
ft_1 <- hrule(ft_1, i = 1, rule = "exact", part = "header")

ft_1

dat <- data.frame(
  a = c("left-top", "left-middle", "left-bottom"),
  b = c("center-top", "center-middle", "center-bottom"),
  c = c("right-top", "right-middle", "right-bottom")
)

ft_2 <- flextable(dat)
ft_2 <- theme_box(ft_2)
ft_2 <- height_all(x = ft_2, height = 1.3, part = "body")
ft_2 <- hrule(ft_2, rule = "exact")
ft_2 <- rotate(ft_2, rotation = "tbrl")
ft_2 <- width(ft_2, width = 1.3)

ft_2 <- align(ft_2, j = 1, align = "left")
ft_2 <- align(ft_2, j = 2, align = "center")
ft_2 <- align(ft_2, j = 3, align = "right")

ft_2 <- valign(ft_2, i = 1, valign = "top")
ft_2 <- valign(ft_2, i = 2, valign = "center")
ft_2 <- valign(ft_2, i = 3, valign = "bottom")

ft_2
```

Description

sugar function to save flextable objects in an Word file.

Usage

```
save_as_docx(..., values = NULL, path, pr_section = NULL)
```

Arguments

...	flextable objects, objects, possibly named. If named objects, names are used as titles.
values	a list (possibly named), each element is a flextable object. If named objects, names are used as titles. If provided, argument ... will be ignored.
path	Word file to be created
pr_section	a prop_section object that can be used to define page layout such as orientation, width and height.

See Also

Other flextable print function: [as_raster\(\)](#), [df_printer\(\)](#), [flextable_to_rmd\(\)](#), [htmltools_value\(\)](#), [knit_print.flextable\(\)](#), [plot.flextable\(\)](#), [print.flextable\(\)](#), [save_as_html\(\)](#), [save_as_image\(\)](#), [save_as_pptx\(\)](#)

Examples

```
tf <- tempfile(fileext = ".docx")

library(officer)
ft1 <- flextable( head( iris ) )
save_as_docx(ft1, path = tf)

ft2 <- flextable( head( mtcars ) )
sect_properties <- prop_section(
  page_size = page_size(orient = "landscape",
    width = 8.3, height = 11.7),
  type = "continuous",
  page_margins = page_mar()
)
save_as_docx(`iris table` = ft1, `mtcars table` = ft2,
  path = tf, pr_section = sect_properties)
```

Description

save a flextable in an HTML file. This function is useful to save the flextable in HTML file without using R Markdown (it is highly recommended to use R Markdown instead).

Usage

```
save_as_html(
  ...,
  values = NULL,
  path,
  encoding = "utf-8",
  title = deparse(sys.call())
)
```

Arguments

...	flextable objects, objects, possibly named. If named objects, names are used as titles.
values	a list (possibly named), each element is a flextable object. If named objects, names are used as titles. If provided, argument ... will be ignored.
path	HTML file to be created
encoding	encoding to be used in the HTML file
title	page title

See Also

Other flextable print function: [as_raster\(\)](#), [df_printer\(\)](#), [flextable_to_rmd\(\)](#), [htmltools_value\(\)](#), [knit_print.flextable\(\)](#), [plot.flextable\(\)](#), [print.flextable\(\)](#), [save_as_docx\(\)](#), [save_as_image\(\)](#), [save_as_pptx\(\)](#)

Examples

```
ft1 <- flextable( head( iris ) )
tf1 <- tempfile(fileext = ".html")
save_as_html(ft1, path = tf1)
# browseURL(tf1)

ft2 <- flextable( head( mtcars ) )
tf2 <- tempfile(fileext = ".html")
save_as_html(
  `iris table` = ft1,
  `mtcars table` = ft2,
  path = tf2,
  title = "rhoooo")
# browseURL(tf2)
```

Description

save a flextable as a png, pdf or jpeg image.

Image generated with package 'webshot' or package 'webshot2'. **Package 'webshot2' should be preferred** as 'webshot' can have issues with some properties (i.e. bold are not rendered for some users).

The image is coming from a screenshot of the 'HTML' output. `save_as_image()` is a tool to make life easier for users. Nevertheless, the features have some limitations that can't be solved with flextable because they are not related to flextable:

- png does support transparency,
- jpeg does not support transparency,
- webshot2 does not allow transparent background,
- webshot does allow transparent background.

Usage

```
save_as_image(x, path, zoom = 3, expand = 10, webshot = "webshot")
```

Arguments

x	a flextable object
path	image file to be created. It should end with .png, .pdf, or .jpeg.
zoom, expand	parameters used by webshot function.
webshot	webshot package as a scalar character, one of "webshot" or "webshot2".

Note

This function requires package webshot or webshot2. The screenshot process is rather slow because it is managed by an external program (see webshot or webshot2 documentation).

See Also

Other flextable print function: [as_raster\(\)](#), [df_printer\(\)](#), [flextable_to_rmd\(\)](#), [htmltools_value\(\)](#), [knit_print.flextable\(\)](#), [plot.flextable\(\)](#), [print.flextable\(\)](#), [save_as_docx\(\)](#), [save_as_html\(\)](#), [save_as_pptx\(\)](#)

Examples

```
ft <- flextable( head( mtcars ) )
ft <- autofit(ft)
tf <- tempfile(fileext = ".png")
## Not run:
if( require("webshot") ){
  save_as_image(x = ft, path = "myimage.png")
}

## End(Not run)
```

save_as_pptx*save flextable objects in an PowerPoint file*

Description

sugar function to save flextable objects in an PowerPoint file.

This feature is available to simplify the work of users by avoiding the need to use the 'officer' package. If it doesn't suit your needs, then use the API offered by 'officer' which allows simple and complicated things.

Usage

```
save_as_pptx(..., values = NULL, path)
```

Arguments

...	flextable objects, objects, possibly named. If named objects, names are used as slide titles.
values	a list (possibly named), each element is a flextable object. If named objects, names are used as slide titles. If provided, argument ... will be ignored.
path	PowerPoint file to be created

Note

The PowerPoint format ignores captions (see [set_caption\(\)](#)).

See Also

Other flextable print function: [as_raster\(\)](#), [df_printer\(\)](#), [flextable_to_rmd\(\)](#), [htmltools_value\(\)](#), [knit_print.flextable\(\)](#), [plot.flextable\(\)](#), [print.flextable\(\)](#), [save_as_docx\(\)](#), [save_as_html\(\)](#), [save_as_image\(\)](#)

Examples

```
ft1 <- flextable( head( iris ) )
tf <- tempfile(fileext = ".pptx")
save_as_pptx(ft1, path = tf)

ft2 <- flextable( head( mtcars ) )
tf <- tempfile(fileext = ".pptx")
save_as_pptx(`iris table` = ft1, `mtcars table` = ft2, path = tf)
```

separate_header	<i>Separate collapsed colnames into multiple rows</i>
-----------------	---

Description

If your variable names contain multiple delimited labels, they will be separated and placed in their own rows.

Usage

```
separate_header(  
  x,  
  opts = c("span-top", "center-hspan", "bottom-vspan", "default-theme"),  
  split = "[_\\\\.]",  
  fixed = FALSE  
)
```

Arguments

x	a flextable object
opts	optional treatments to apply to the resulting header part as a character vector with multiple supported values. The supported values are:
<ul style="list-style-type: none">• "span-top": span empty cells with the first non empty cell, this operation is made column by column.• "center-hspan": center the cells that are horizontally spanned.• "bottom-vspan": bottom align the cells treated when "span-top" is applied.• "default-theme": apply to the new header part the theme set in <code>set_flextable_defaults(theme_fu = ...)</code>.	
split	a regular expression (unless <code>fixed = TRUE</code>) to use for splitting.
fixed	logical. If <code>TRUE</code> match <code>split</code> exactly, otherwise use regular expressions.

Illustrations

See Also

Other functions to add rows in header or footer: [add_footer_lines\(\)](#), [add_footer_row\(\)](#), [add_footer\(\)](#), [add_header_lines\(\)](#), [add_header_row\(\)](#), [add_header\(\)](#), [set_header_footer_df](#), [set_header_labels\(\)](#)

Examples

```
library(flextable)

x <- data.frame(
  Species = as.factor(c("setosa", "versicolor", "virginica")),
  Sepal.Length_mean = c(5.006, 5.936, 6.588),
  Sepal.Length_sd = c(0.35249, 0.51617, 0.63588),
  Sepal.Width_mean = c(3.428, 2.77, 2.974),
  Sepal.Width_sd = c(0.37906, 0.3138, 0.3225),
  Petal.Length_mean = c(1.462, 4.26, 5.552),
  Petal.Length_sd = c(0.17366, 0.46991, 0.55189),
  Petal.Width_mean = c(0.246, 1.326, 2.026),
  Petal.Width_sd = c(0.10539, 0.19775, 0.27465)
)

ft_1 <- flextable(x)
ft_1 <- colformat_double(ft_1, digits = 2)
ft_1 <- theme_box(ft_1)
ft_1 <- separate_header(
  x = ft_1,
  opts = c("span-top", "bottom-vspan")
)
ft_1
```

set_caption

Set Caption

Description

Set caption value in a flextable.

- The caption will be associated with a paragraph style when the output is Word. It can also be numbered as a auto-numbered Word computed value.
- The PowerPoint format ignores captions. PowerPoint documents are not structured and do not behave as HTML documents and paginated documents (word, pdf), and it's not possible to know where we should create a shape to contain the caption (technically it can't be in the PowerPoint shape containing the table).

Usage

```
set_caption(
  x,
  caption,
  autonum = NULL,
  style = "Table Caption",
  html_escape = TRUE
)
```

Arguments

x	flextable object
caption	caption value
autonum	an autonum representation. See officer::run_autonum() . This has only an effect when output is Word. If used, the caption is preceded by an auto-number sequence. In this case, the caption is preceded by an auto-number sequence that can be cross referenced.
style	caption paragraph style name. These names are available with function officer::styles_info() when output is Word; if HTML, the value is set as class value in the caption tag.
html_escape	should HTML entities be escaped so that it can be safely included as text or an attribute value within an HTML document.

R Markdown

flextable captions can be defined from R Markdown documents by using `knitr::opts_chunk$set()`. The following options are available with `officedown::rdocx_document` and/or bookdown:

label	name	value
Word stylename to use for table captions.	tab.cap.style	NULL
caption id/bookmark	tab.id	NULL
caption	tab.cap	NULL
display table caption on top of the table or not	tab.topcaption	TRUE
caption table sequence identifier.	tab.lp	"tab:"

The following options are only available when used with `officedown::rdocx_document`:

label	name	value
prefix for numbering chunk (default to "Table ").	tab.cap.pre	Table
suffix for numbering chunk (default to ":").	tab.cap.sep	" :"
title number depth	tab.cap.tnd	0
separator to use between title number and table number.	tab.cap.tns	"_"
caption prefix formatting properties	tab.cap.fp_text	fp_text_lite(bold = TRUE)

See [knit_print.flextable](#) for more details.

See Also

[flextable\(\)](#)

Examples

```
ftab <- flextable( head( iris ) )
ftab <- set_caption(ftab, "my caption")
ftab
```

```
library(officer)
autonum <- run_autonum(seq_id = "tab", bkm = "mtcars")
ftab <- flextable( head( mtcars ) )
ftab <- set_caption(ftab, caption = "mtcars data", autonum = autonum)
ftab
```

set_flextable_defaults*Modify flextable defaults formatting properties***Description**

The current formatting properties (see [get_flextable_defaults\(\)](#)) are automatically applied to every flextable you produce. Use `set_flextable_defaults()` to override them. Use `init_flextable_defaults()` to re-init all values with the package defaults.

Usage

```
set_flextable_defaults(
  font.family = NULL,
  font.size = NULL,
  font.color = NULL,
  text.align = NULL,
  padding = NULL,
  padding.bottom = NULL,
  padding.top = NULL,
  padding.left = NULL,
  padding.right = NULL,
  border.color = NULL,
  background.color = NULL,
  line_spacing = NULL,
  table.layout = NULL,
  cs.family = NULL,
  eastasia.family = NULL,
  hansi.family = NULL,
  decimal.mark = NULL,
  big.mark = NULL,
  digits = NULL,
  na_str = NULL,
  nan_str = NULL,
  fmt_date = NULL,
  fmt_datetime = NULL,
  extra_css = NULL,
  fonts_ignore = NULL,
  theme_fun = NULL,
  post_process_pdf = NULL,
```

```

    post_process_docx = NULL,
    post_process_html = NULL,
    post_process_pptx = NULL
  )

  init_flextable_defaults()

```

Arguments

<code>font.family</code>	single character value. When format is Word, it specifies the font to be used to format characters in the Unicode range (U+0000-U+007F).
<code>font.size</code>	font size (in point) - 0 or positive integer value.
<code>font.color</code>	font color - a single character value specifying a valid color (e.g. "#000000" or "black").
<code>text.align</code>	text alignment - a single character value, expected value is one of 'left', 'right', 'center', 'justify'.
<code>padding</code>	padding (shortcut for top, bottom, left and right padding)
<code>padding.bottom</code> , <code>padding.top</code> , <code>padding.left</code> , <code>padding.right</code>	paragraph paddings - 0 or positive integer value.
<code>border.color</code>	border color - single character value (e.g. "#000000" or "black").
<code>background.color</code>	cell background color - a single character value specifying a valid color (e.g. "#000000" or "black").
<code>line_spacing</code>	space between lines of text, 1 is single line spacing, 2 is double line spacing.
<code>table.layout</code>	'autofit' or 'fixed' algorithm. Default to 'autofit'.
<code>cs.family</code>	optional and only for Word. Font to be used to format characters in a complex script Unicode range. For example, Arabic text might be displayed using the "Arial Unicode MS" font.
<code>eastasia.family</code>	optional and only for Word. Font to be used to format characters in an East Asian Unicode range. For example, Japanese text might be displayed using the "MS Mincho" font.
<code>hansi.family</code>	optional and only for Word. Font to be used to format characters in a Unicode range which does not fall into one of the other categories.
<code>decimal.mark</code> , <code>big.mark</code> , <code>na_str</code> , <code>nan_str</code>	<code>formatC</code> arguments used by <code>colformat_num()</code> , <code>colformat_double()</code> , and <code>colformat_int()</code> .
<code>digits</code>	<code>formatC</code> argument used by <code>colformat_double()</code> .
<code>fmt_date</code> , <code>fmt_datetime</code>	formats for date and datetime columns as documented in <code>strptime()</code> . Default to '%Y-%m-%d' and '%Y-%m-%d %H:%M:%S'.
<code>extra_css</code>	css instructions to be integrated with the table.
<code>fonts_ignore</code>	if TRUE, pdf-engine pdflatex can be used instead of xelatex or lualatex. If pdflatex is used, fonts will be ignored because they are not supported by pdflatex, whereas with the xelatex and lualatex engines they are.

`theme_fun` a single character value (the name of the theme function to be applied) or a theme function (input is a flextable, output is a flextable).
`post_process_pdf`, `post_process_docx`, `post_process_html`, `post_process_pptx`
Post-processing functions that will allow you to customize the display by output type (pdf, html, docx, pptx). They are executed just before printing the table.

Value

a list containing previous default values.

Illustrations

See Also

Other functions related to themes: `get_flextable_defaults()`, `theme_alafoli()`, `theme_booktabs()`, `theme_box()`, `theme_tron_legacy()`, `theme_tron()`, `theme_vader()`, `theme_vanilla()`, `theme_zebra()`

Examples

```
ft_1 <- qflextable(head(airquality))
ft_1

old <- set_flextable_defaults(
  font.color = "#AA8855",
  border.color = "#8855AA")
ft_2 <- qflextable(head(airquality))
ft_2

do.call(set_flextable_defaults, old)
```

`set_formatter` *set column formatter functions*

Description

Define formatter functions associated to each column key. Functions have a single argument (the vector) and are returning the formatted values as a character vector.

Usage

```
set_formatter(x, ..., values = NULL, part = "body")

set_formatter_type(
  x,
  fmt_double = "%.03f",
  fmt_integer = "%.0f",
```

```

  fmt_date = "%Y-%m-%d",
  fmt_datetime = "%Y-%m-%d %H:%M:%S",
  true = "true",
  false = "false",
  na_str = ""
)

```

Arguments

x	a flextable object
...	Name-value pairs of functions, names should be existing col_key values
values	a list of name-value pairs of functions, names should be existing col_key values. If values is supplied argument ... is ignored.
part	partname of the table (one of 'body' or 'header' or 'footer')
fmt_double, fmt_integer	arguments used by sprintf to format double and integer columns.
fmt_date, fmt_datetime	arguments used by format to format date and date time columns.
false, true	string to be used for logical columns
na_str	string for NA values

set_formatter_type

set_formatter_type is an helper function to quickly define formatter functions regarding to column types.

This function will be deprecated in favor of the colformat_* functions, for example [colformat_double\(\)](#).

See Also

Other cells formatters: [colformat_char\(\)](#), [colformat_datetime\(\)](#), [colformat_date\(\)](#), [colformat_double\(\)](#), [colformat_image\(\)](#), [colformat_int\(\)](#), [colformat_lgl\(\)](#), [colformat_num\(\)](#)

Other cells formatters: [colformat_char\(\)](#), [colformat_datetime\(\)](#), [colformat_date\(\)](#), [colformat_double\(\)](#), [colformat_image\(\)](#), [colformat_int\(\)](#), [colformat_lgl\(\)](#), [colformat_num\(\)](#)

Examples

```

ft <- flextable( head( iris ) )
ft <- set_formatter( x = ft,
  Sepal.Length = function(x) sprintf("%.02f", x),
  Sepal.Width = function(x) sprintf("%.04f", x)
)
ft <- theme_vanilla( ft )
ft

```

`set_header_footer_df` *Set flextable's header or footer rows*

Description

Use a data.frame to specify flextable's header or footer rows.

The data.frame must contain a column whose values match flextable col_keys argument, this column will be used as join key. The other columns will be displayed as header or footer rows. The leftmost column is used as the top header/footer row and the rightmost column is used as the bottom header/footer row.

Usage

```
set_header_df(x, mapping = NULL, key = "col_keys")
```

```
set_footer_df(x, mapping = NULL, key = "col_keys")
```

Arguments

<code>x</code>	a flextable object
<code>mapping</code>	a data.frame specifying for each colname content of the column.
<code>key</code>	column to use as key when joining data_mapping.

Illustrations

See Also

Other functions to add rows in header or footer: [add_footer_lines\(\)](#), [add_footer_row\(\)](#), [add_footer\(\)](#), [add_header_lines\(\)](#), [add_header_row\(\)](#), [add_header\(\)](#), [separate_header\(\)](#), [set_header_labels\(\)](#)

Examples

```
typology <- data.frame(
  col_keys = c(
    "Sepal.Length", "Sepal.Width", "Petal.Length",
    "Petal.Width", "Species"
  ),
  what = c("Sepal", "Sepal", "Petal", "Petal", "Species"),
  measure = c("Length", "Width", "Length", "Width", "Species"),
  stringsAsFactors = FALSE
)

ft_1 <- flextable(head(iris))
ft_1 <- set_header_df(ft_1, mapping = typology, key = "col_keys")
ft_1 <- merge_h(ft_1, part = "header")
ft_1 <- merge_v(ft_1, j = "Species", part = "header")
```

```
ft_1 <- theme_vanilla(ft_1)
ft_1 <- fix_border_issues(ft_1)
ft_1

typology <- data.frame(
  col_keys = c(
    "Sepal.Length", "Sepal.Width", "Petal.Length",
    "Petal.Width", "Species"
  ),
  unit = c("(cm)", "(cm)", "(cm)", "(cm)", ""),
  stringsAsFactors = FALSE
)
ft_2 <- set_footer_df(ft_1, mapping = typology, key = "col_keys")
ft_2 <- italic(ft_2, italic = TRUE, part = "footer")
ft_2 <- theme_booktabs(ft_2)
ft_2 <- fix_border_issues(ft_2)
ft_2
```

set_header_labels *Change headers labels*

Description

This function set labels for specified columns in the bottom row header of a flextable.

Usage

```
set_header_labels(x, ..., values = NULL)
```

Arguments

- | | |
|--------|--|
| x | a flextable object |
| ... | named arguments (names are data colnames), each element is a single character value specifying label to use. |
| values | a named list (names are data colnames), each element is a single character value specifying label to use. If provided, argument ... will be ignored. |

Illustrations

See Also

Other functions to add rows in header or footer: [add_footer_lines\(\)](#), [add_footer_row\(\)](#), [add_footer\(\)](#), [add_header_lines\(\)](#), [add_header_row\(\)](#), [add_header\(\)](#), [separate_header\(\)](#), [set_header_footer_df](#)

Examples

```
ft <- flextable(head(iris))
ft <- set_header_labels(ft,
  Sepal.Length = "Sepal length",
  Sepal.Width = "Sepal width", Petal.Length = "Petal length",
  Petal.Width = "Petal width"
)

ft <- flextable(head(iris))
ft <- set_header_labels(ft,
  values = list(
    Sepal.Length = "Sepal length",
    Sepal.Width = "Sepal width",
    Petal.Length = "Petal length",
    Petal.Width = "Petal width"
  )
)
ft
```

set_table_properties *Global table properties*

Description

Set table layout and table width. Default to fixed algorithm.

If layout is fixed, column widths will be used to display the table; width is ignored.

If layout is autofit, column widths will not be used; table width is used (as a percentage).

Usage

```
set_table_properties(x, layout = "fixed", width = 0)
```

Arguments

x	flextable object
layout	'autofit' or 'fixed' algorithm. Default to 'autofit'.
width	The parameter has a different effect depending on the output format. Users should consider it as a minimum width. In HTML, it is the minimum width of the space that the table should occupy. In Word, it is a preferred size and Word may decide not to strictly stick to it. It has no effect on PowerPoint and PDF output. Its default value is 0, as an effect, it only use necessary width to display all content. It is not used by the PDF output.

Illustrations

Note

PowerPoint output ignore 'autofit layout'.

See Also

Other flextable dimensions: [autofit\(\)](#), [dim_flextable\(\)](#), [dim_pretty\(\)](#), [fit_to_width\(\)](#), [flextable_dim\(\)](#), [height\(\)](#), [hrule\(\)](#), [ncol_keys\(\)](#), [nrow_part\(\)](#), [width\(\)](#)

Examples

```
library(flextable)
ft_1 <- qflextable(head(cars))
ft_2 <- set_table_properties(ft_1, width = .5, layout = "autofit")
ft_2
```

shift_table

Create a shift table

Description

Create a shift table ready to be used with `tabulator()`.

The function is transforming a dataset representing some 'Laboratory Tests Results' structured as *CDISC clinical trial data sets* format to a dataset representing the shift table.

Shift tables are tables used in clinical trial analysis. They show the progression of change from the baseline, with the progression often being along time; the number of subjects is displayed in different range (e.g. low, normal, or high) at baseline and at selected time points or intervals.

Usage

```
shift_table(
  x,
  cn_visit = "VISIT",
  cn_visit_num = "VISITNUM",
  cn_grade = "LBNRIND",
  cn_usubjid = "USUBJID",
  cn_lab_cat = NA_character_,
  cn_is_baseline = "LBLFL",
  baseline_identifier = "Y",
  cn_treatment = NA_character_,
  grade_levels = c("LOW", "NORMAL", "HIGH"),
  grade_labels = c("Low", "Normal", "High")
)
```

Arguments

x	Laboratory Tests Results data frame.
cn_visit	column name containing visit names, default to "VISIT".
cn_visit_num	column name containing visit numbers, default to "VISITNUM".
cn_grade	column name containing reference range indicators, default to "LBNRIND".
cn_usubjid	column name containing unique subject identifiers, default to "USUBJID".
cn_lab_cat	column name containing lab tests or examination names, default to "LBTEST".
cn_is_baseline	column name containing baseline flags, default to "LBLFL".
baseline_identifier	baseline flag value to use for baseline identification. Its default is "Y".
cn_treatment	column name containing treatment names, default to NA.
grade_levels	levels to use for reference range indicators
grade_labels	labels to use for reference range indicators

Value

the shift table as a data.frame. Additionnal elements are provided in attributes:

- "VISIT_N": count of unique subject id per visits, labs and eventually treatments. This element is supposed to be used as value for argument `hidden_data` of function `tabulator()`.
- "FUN_VISIT": a utility function to easily turn `visit` column as a factor column. It should be applied after the shift table creation.
- "FUN_GRADE": a utility function to easily turn `grade` column as a factor column. It adds "MISSING/Missing" and "SUM/Sum" at the end of the set of values specified in arguments `grade_levels` and `grade_labels`. It should be applied after the shift table creation.

Examples

```
library(data.table)
library(flextable)

# data simulation ----
USUBJID <- sprintf("01-ABC-%04.0f", 1:200)
VISITS <- c("SCREENING 1", "WEEK 2", "MONTH 3")
LBTEST <- c("Albumin", "Sodium")

VISITNUM <- seq_along(VISITS)
LBLFL <- rep(NA_character_, length(VISITNUM))
LBLFL[1] <- "Y"

VISIT <- data.frame(VISIT = VISITS, VISITNUM = VISITNUM,
                     LBLFL = LBLFL, stringsAsFactors = FALSE)
labdata <- expand.grid(USUBJID = USUBJID, LBTEST = LBTEST,
                      VISITNUM = VISITNUM,
                      stringsAsFactors = FALSE)
setDT(labdata)
```

```

labdata <- merge(labdata, VISIT, by = "VISITNUM")

subject_elts <- unique(labdata[, .SD, .SDcols = "USUBJID"])
subject_elts <- unique(subject_elts)
subject_elts[, c("TREAT") := list(
  sample(x = c("Treatment", "Placebo"), size = .N, replace = TRUE))]
subject_elts[, c("TREAT"):= list(
  factor(.SD$TREAT, levels = c("Treatment", "Placebo")))]
setDF(subject_elts)

labdata <- merge(labdata, subject_elts,
  by = "USUBJID", all.x = TRUE, all.y = FALSE)
labdata[, c("LBNRIND"):= list(
  sample(x = c("LOW", "NORMAL", "HIGH"), size = .N,
  replace = TRUE, prob = c(.03, .9, .07)))]
setDF(labdata)

# shift table calculation ----

SHIFT_TABLE <- shift_table(
  x = labdata, cn_visit = "VISIT",
  cn_grade = "LBNRIND",
  cn_usubjid = "USUBJID",
  cn_lab_cat = "LBTEST",
  cn_treatment = "TREAT",
  cn_is_baseline = "LBLFL",
  baseline_identifier = "Y",
  grade_levels = c("LOW", "NORMAL", "HIGH"))

# get attrs for post treatment ----
SHIFT_TABLE_VISIT <- attr(SHIFT_TABLE, "VISIT_N")
visit_as_factor <- attr(SHIFT_TABLE, "FUN_VISIT")
range_as_factor <- attr(SHIFT_TABLE, "FUN_GRADE")

# post treatments ----
SHIFT_TABLE$VISIT = visit_as_factor(SHIFT_TABLE$VISIT)
SHIFT_TABLE$BASELINE = range_as_factor(SHIFT_TABLE$BASELINE)
SHIFT_TABLE$LBNRIND = range_as_factor(SHIFT_TABLE$LBNRIND)

SHIFT_TABLE_VISIT$VISIT = visit_as_factor(SHIFT_TABLE_VISIT$VISIT)

# tabulator ----

my_format <- function(z) {
  formatC(z * 100, digits = 1, format = "f",
          flag = "0", width = 4)
}

tab <- tabulator(
  x = SHIFT_TABLE,

```

```

hidden_data = SHIFT_TABLE_VISIT,
row_compose = list(
  VISIT = as_paragraph(VISIT, "\n(N=", N_VISIT, ")")
),
rows = c("LBTEST", "VISIT", "BASELINE"),
columns = c("TREAT", "LBNRIND"),
`n` = as_paragraph(N),
`%` = as_paragraph(as_chunk(PCT, formatter = my_format))
)

# as_flextable ----

ft_1 <- as_flextable(
  x = tab, separate_with = "VISIT",
  label_rows = c(LBTEST = "Lab Test", VISIT = "Visit",
    BASELINE = "Reference Range Indicator"))

ft_1

```

style*Set flextable style***Description**

Modify flextable text, paragraphs and cells formatting properties. It allows to specify a set of formatting properties for a selection instead of using multiple functions (.i.e bold, italic, bg) that should all be applied to the same selection of rows and columns.

Usage

```

style(
  x,
  i = NULL,
  j = NULL,
  pr_t = NULL,
  pr_p = NULL,
  pr_c = NULL,
  part = "body"
)

```

Arguments

x	a flextable object
i	rows selection
j	columns selection
pr_t	object(s) of class fp_text
pr_p	object(s) of class fp_par
pr_c	object(s) of class fp_cell
part	partname of the table (one of 'all', 'body', 'header' or 'footer')

Illustrations

Examples

```
library(officer)
def_cell <- fp_cell(border = fp_border(color = "wheat"))

def_par <- fp_par(text.align = "center")

ft <- flextable(head(mtcars))

ft <- style(ft, pr_c = def_cell, pr_p = def_par, part = "all")
ft <- style(ft, ~ drat > 3.5, ~ vs + am + gear + carb,
            pr_t = fp_text(color = "red", italic = TRUE)
)
ft
```

summarizor

data summary preparation

Description

It performs a univariate statistical analysis of a dataset by group and formats the results so that they can be used with the [tabulator\(\)](#) function.

Usage

```
summarizor(x, by = character(), overall_label = NULL)
```

Arguments

x	dataset
by	columns names to be used as grouping columns
overall_label	label to use as overall label

Illustrations

ft_1 appears as:

ft_2 appears as:

Note

This is very first version of the function; be aware it can evolve or change.

See Also

[fmt_2stats\(\)](#)

Examples

```

z <- summarizor(CO2[-c(1, 4)],
  by = "Treatment",
  overall_label = "Overall"
)

# version 1 ----
tab_1 <- tabulator(
  x = z,
  rows = c("variable", "stat"),
  columns = "Treatment",
  blah = as_paragraph(
    as_chunk(
      fmt_2stats(
        num1 = stat, num2 = value, cts = cts, pcts = percent
      )
    )
  )
)

ft_1 <- as_flextable(tab_1, separate_with = "variable")
ft_1

# version 2 ----
n_format <- function(n, percent) {
  z <- character(length = length(n))
  wcts <- !is.na(n)
  z[wcts] <- sprintf("%.0f (%.01f %%)", n[wcts], percent[wcts] * 100)
  z
}
stat_format <- function(value) {
  z <- character(length = length(value))
  wnum <- !is.na(value)
  z[wnum] <- sprintf("%.01f", value[wnum])
  z
}

tab_2 <- tabulator(z,
  rows = c("variable", "stat"),
  columns = "Treatment",
  `Est.` = as_paragraph(as_chunk(value)),
  `N` = as_paragraph(as_chunk(n_format(cts, percent)))
)

ft_2 <- as_flextable(tab_2, separate_with = "variable")
ft_2

```

surround	<i>Set borders for a selection of cells</i>
----------	---

Description

Highlight specific cells with borders.

To set borders for the whole table, use [border_outer\(\)](#), [border_inner_h\(\)](#) and [border_inner_v\(\)](#).

All the following functions also support the row and column selector i and j:

- [hline\(\)](#): set bottom borders (inner horizontal)
- [vline\(\)](#): set right borders (inner vertical)
- [hline_top\(\)](#): set the top border (outer horizontal)
- [vline_left\(\)](#): set the left border (outer vertical)

Usage

```
surround(  
  x,  
  i = NULL,  
  j = NULL,  
  border = NULL,  
  border.top = NULL,  
  border.bottom = NULL,  
  border.left = NULL,  
  border.right = NULL,  
  part = "body"  
)
```

Arguments

x	a flextable object
i	rows selection
j	columns selection
border	border (shortcut for top, bottom, left and right)
border.top	border top
border.bottom	border bottom
border.left	border left
border.right	border right
part	partname of the table (one of 'all', 'body', 'header', 'footer')

See Also

Other borders management: [border_inner_h\(\)](#), [border_inner_v\(\)](#), [border_inner\(\)](#), [border_outer\(\)](#), [border_remove\(\)](#), [hline_bottom\(\)](#), [hline_top\(\)](#), [hline\(\)](#), [vline_left\(\)](#), [vline_right\(\)](#), [vline\(\)](#)

Examples

```

library(officer)
library(flextable)

# cell to highlight
vary_i <- 1:3
vary_j <- 1:3

std_border <- fp_border(color = "orange")

ft <- flextable(head(iris))
ft <- border_remove(x = ft)
ft <- border_outer(x = ft, border = std_border)

for (id in seq_along(vary_i)) {
  ft <- bg(
    x = ft,
    i = vary_i[id],
    j = vary_j[id], bg = "yellow"
  )
  ft <- surround(
    x = ft,
    i = vary_i[id],
    j = vary_j[id],
    border.left = std_border,
    border.right = std_border,
    part = "body"
  )
}

ft <- autofit(ft)
ft
# # render
# print(ft, preview = "pptx")
# print(ft, preview = "docx")
# print(ft, preview = "pdf")
# print(ft, preview = "html")

```

Description

It tabulates a data.frame representing an aggregation which is then transformed as a flextable. The function allows to define any display with the syntax of flextable in a table whose layout is showing dimensions of the aggregation across rows and columns.

Usage

```
tabulator(
  x,
  rows,
  columns,
  datasup_first = NULL,
  datasup_last = NULL,
  hidden_data = NULL,
  row_compose = list(),
  ...
)

## S3 method for class 'tabulator'
summary(object, ...)
```

Arguments

x	an aggregated data.frame
rows	column names to use in rows dimensions
columns	column names to use in columns dimensions
datasup_first	additional data that will be merged with table and placed after the columns presenting the row dimensions.
datasup_last	additional data that will be merged with table and placed at the end of the table.
hidden_data	additional data that will be merged with table, the columns are not presented but can be used with compose() or mk_par() function.
row_compose	a list of call to as_paragraph() - these calls will be applied to the row dimensions (the name is used to target the displayed column).
...	named arguments calling function as_paragraph() . The names are used as labels and the values are evaluated when the flextable is created.
object	an object returned by function tabulator() .

Value

an object of class [tabulator](#).

Methods (by generic)

- [summary\(tabulator\)](#): call [summary\(\)](#) to get a data.frame describing mappings between variables and their names in the flextable. This data.frame contains a column named `col_keys` where are stored the names that can be used for further selections.

Illustrations

ft_1 appears as:

ft_2 appears as:

Note

This is very first version of the function; be aware it can evolve or change.

See Also

[as_flextable.tabulator\(\)](#), [summarizor\(\)](#), [as_grouped_data\(\)](#), [tabulator_colnames\(\)](#)

Examples

```
n_format <- function(z){
  x <- sprintf("%.0f", z)
  x[is.na(z)] <- "-"
  x
}

set_flextable_defaults(digits = 2, border.color = "gray")

if(require("stats")){
  dat <- aggregate(breaks ~ wool + tension,
    data = warpbreaks, mean)

  cft_1 <- tabulator(
    x = dat, rows = "wool",
    columns = "tension",
    `mean` = as_paragraph(as_chunk(breaks)),
    `(N)` = as_paragraph(
      as_chunk(length(breaks), formatter = n_format ))
  )

  ft_1 <- as_flextable(cft_1)
  ft_1
}

if(require("data.table") && require("ggplot2")){

  multi_fun <- function(x) {
    list(mean = mean(x),
        sd = sd(x))
  }
  myformat <- function(z){
    x <- sprintf("%.1f", z)
    x[is.na(z)] <- ""
    x
  }

  grey_txt <- fp_text_default(color = "gray")

  dat <- as.data.table(ggplot2::diamonds)
  dat <- dat[cut %in% c("Fair", "Good", "Very Good")]
  dat <- dat[clarity %in% c("I1", "SI1", "VS2")]

  dat <- dat[, unlist(lapply(.SD, multi_fun),
    
```

```
    recursive = FALSE),
  .SDcols = c("z", "y"),
  by = c("cut", "color", "clarity")]

tab_2 <- tabulator(
  x = dat, rows = c("cut", "color"),
  columns = "clarity",
  `z stats` = as_paragraph(
    as_chunk(z.mean, formatter = myformat)),
  `y stats` = as_paragraph(
    as_chunk(y.mean, formatter = myformat),
    as_chunk("\u2022", props = grey_txt),
    as_chunk(y.sd, formatter = myformat, props = grey_txt),
    as_chunk(")", props = grey_txt)
  )
)
ft_2 <- as_flextable(tab_2)
ft_2 <- autofit(x = ft_2, add_w = .05)
ft_2
}

if(require("data.table")){
#' # data.table version
dat <- melt(as.data.table(iris),
            id.vars = "Species",
            variable.name = "name", value.name = "value")[,  

  list(avg = mean(value, na.rm = TRUE),
       sd = sd(value, na.rm = TRUE)),
            by = c("Species", "name")]
]
# dplyr version
# library(dplyr)
# dat <- iris %>%
#   pivot_longer(cols = -c(Species)) %>%
#   group_by(Species, name) %>%
#   summarise(avg = mean(value, na.rm = TRUE),
#             sd = sd(value, na.rm = TRUE),
#             .groups = "drop")

tab_3 <- tabulator(
  x = dat, rows = c("Species"),
  columns = "name",
  `mean (sd)` = as_paragraph( as_chunk(avg),
    " (\u2022, as_chunk(sd), \u2022)")
)
ft_3 <- as_flextable(tab_3, separate_with = character(0))
ft_3
}

init_flextable_defaults()
```

tabulator_colnames *column keys of tabulator objects*

Description

The function provides a way to get column keys associated with the flextable corresponding to a [tabulator\(\)](#) object. It helps in customizing or programing with tabulator.

The function is using column names from the original dataset, eventually filters and returns the names corresponding to the selection.

Usage

```
tabulator_colnames(x, columns, type = NULL, ...)
```

Arguments

x	a tabulator() object
columns	column names to look for
type	the type of column to look for, it can be: <ul style="list-style-type: none"> • 'columns': visible columns, corresponding to names provided in the '...' arguments of your call to 'tabulator()'. • 'hidden': unvisible columns, corresponding to names of the original dataset columns. • 'rows': visible columns used as 'row' content • 'rows_supp': visible columns used as 'rows_supp' content • NULL: any type of column
...	any filter conditions that use variables names, the same than the argument <code>columns</code> of function tabulator() (<code>tabulator(columns = c("col1", "col2"))</code>).

See Also

[tabulator\(\)](#), [as_flextable.tabulator\(\)](#)

Examples

```
library(flextable)

cancer_dat <- data.frame(
  count = c(
    9L, 5L, 1L, 2L, 2L, 1L, 9L, 3L, 1L, 10L, 2L, 1L, 1L, 2L, 0L, 3L,
    2L, 1L, 1L, 2L, 0L, 12L, 4L, 1L, 7L, 3L, 1L, 5L, 5L, 3L, 10L,
    4L, 1L, 4L, 2L, 0L, 3L, 1L, 0L, 4L, 4L, 2L, 42L, 28L, 19L, 26L,
    19L, 11L, 12L, 10L, 7L, 10L, 5L, 6L, 5L, 0L, 3L, 4L, 3L, 3L,
    1L, 2L, 3L
  ),
  risktime = c(
```

```
157L, 77L, 21L, 139L, 68L, 17L, 126L, 63L, 14L, 102L, 55L,
12L, 88L, 50L, 10L, 82L, 45L, 8L, 76L, 42L, 6L, 134L, 71L,
22L, 110L, 63L, 18L, 96L, 58L, 14L, 86L, 42L, 10L, 66L,
35L, 8L, 59L, 32L, 8L, 51L, 28L, 6L, 212L, 130L, 101L,
136L, 72L, 63L, 90L, 42L, 43L, 64L, 21L, 32L, 47L, 14L,
21L, 39L, 13L, 14L, 29L, 7L, 10L
),
time = rep(as.character(1:7), 3),
histology = rep(as.character(1:3), 21),
stage = rep(as.character(1:3), each = 21)
)

datasup_first <- data.frame(
  time = factor(1:7, levels = 1:7),
  zzz = runif(7)
)

z <- tabulator(cancer_dat,
  rows = "time",
  columns = c("histology", "stage"),
  datasup_first = datasup_first,
  n = as_paragraph(as_chunk(count))
)

j <- tabulator_colnames(
  x = z, type = "columns",
  columns = c("n"),
  stage %in% 1
)

src <- tabulator_colnames(
  x = z, type = "hidden",
  columns = c("count"),
  stage %in% 1
)

if (require("scales")) {
  colourer <- col_numeric(
    palette = c("wheat", "red"),
    domain = c(0, 45)
  )
  ft_1 <- as_flextable(z)
  ft_1 <- bg(
    ft_1,
    bg = colourer, part = "body",
    j = j, source = src
  )
  ft_1
}
```

`theme_alafo` *Apply alafoli theme*

Description

Apply alafoli theme

Usage

`theme_alafo(x)`

Arguments

`x` a flextable object

Illustrations

behavior

Theme functions are not like 'ggplot2' themes. They are applied to the existing table **immediately**. If you add a row in the footer, the new row is not formatted with the theme. The theme function applies the theme only to existing elements when the function is called.

That is why theme functions should be applied after all elements of the table have been added (mainly additionnal header or footer rows).

If you want to automatically apply a theme function to each flextable, you can use the `theme_fun` argument of `set_flextable_defaults()`; be aware that this theme function is applied as the last instruction when calling `flextable()` - so if you add headers or footers to the array, they will not be formatted with the theme.

You can also use the `post_process_html` argument of `set_flextable_defaults()` (or `post_process_pdf`, `post_process_docx`, `post_process_pptx`) to specify a theme to be applied systematically before the `flextable()` is printed; in this case, don't forget to take care that the theme doesn't override any formatting done before the print statement.

See Also

Other functions related to themes: `get_flextable_defaults()`, `set_flextable_defaults()`, `theme_booktabs()`, `theme_box()`, `theme_tron_legacy()`, `theme_tron()`, `theme_vader()`, `theme_vanilla()`, `theme_zebra()`

Examples

```
ft <- flextable(head(airquality))
ft <- theme_alafo(ft)
ft
```

theme_booktabs	<i>Apply booktabs theme</i>
----------------	-----------------------------

Description

Apply theme booktabs to a flextable

Usage

```
theme_booktabs(x, bold_header = FALSE, ...)
```

Arguments

x	a flextable object
bold_header	header will be bold if TRUE.
...	unused

Illustrations

behavior

Theme functions are not like 'ggplot2' themes. They are applied to the existing table **immediately**. If you add a row in the footer, the new row is not formatted with the theme. The theme function applies the theme only to existing elements when the function is called.

That is why theme functions should be applied after all elements of the table have been added (mainly additionnal header or footer rows).

If you want to automatically apply a theme function to each flextable, you can use the `theme_fun` argument of `set_flextable_defaults()`; be aware that this theme function is applied as the last instruction when calling `flextable()` - so if you add headers or footers to the array, they will not be formatted with the theme.

You can also use the `post_process_html` argument of `set_flextable_defaults()` (or `post_process_pdf`, `post_process_docx`, `post_process_pptx`) to specify a theme to be applied systematically before the `flextable()` is printed; in this case, don't forget to take care that the theme doesn't override any formatting done before the print statement.

See Also

Other functions related to themes: `get_flextable_defaults()`, `set_flextable_defaults()`, `theme_alafofi()`, `theme_box()`, `theme_tron_legacy()`, `theme_tron()`, `theme_vader()`, `theme_vanilla()`, `theme_zebra()`

Examples

```
ft <- flextable(head(airquality))
ft <- theme_booktabs(ft)
ft
```

theme_box

Apply box theme

Description

Apply theme box to a flextable

Usage

```
theme_box(x)
```

Arguments

x	a flextable object
---	--------------------

Illustrations

behavior

Theme functions are not like 'ggplot2' themes. They are applied to the existing table **immediately**. If you add a row in the footer, the new row is not formatted with the theme. The theme function applies the theme only to existing elements when the function is called.

That is why theme functions should be applied after all elements of the table have been added (mainly additionnal header or footer rows).

If you want to automatically apply a theme function to each flextable, you can use the `theme_fun` argument of `set_flextable_defaults()`; be aware that this theme function is applied as the last instruction when calling `flextable()` - so if you add headers or footers to the array, they will not be formatted with the theme.

You can also use the `post_process_html` argument of `set_flextable_defaults()` (or `post_process_pdf`, `post_process_docx`, `post_process_pptx`) to specify a theme to be applied systematically before the `flextable()` is printed; in this case, don't forget to take care that the theme doesn't override any formatting done before the print statement.

See Also

Other functions related to themes: `get_flextable_defaults()`, `set_flextable_defaults()`, `theme_alafoli()`, `theme_booktabs()`, `theme_tron_legacy()`, `theme_tron()`, `theme_vader()`, `theme_vanilla()`, `theme_zebra()`

Examples

```
ft <- flextable(head(airquality))
ft <- theme_box(ft)
ft
```

theme_tron

Apply tron theme

Description

Apply theme tron to a flextable

Usage

```
theme_tron(x)
```

Arguments

x	a flextable object
---	--------------------

Illustrations

behavior

Theme functions are not like 'ggplot2' themes. They are applied to the existing table **immediately**. If you add a row in the footer, the new row is not formatted with the theme. The theme function applies the theme only to existing elements when the function is called.

That is why theme functions should be applied after all elements of the table have been added (mainly additionnal header or footer rows).

If you want to automatically apply a theme function to each flextable, you can use the `theme_fun` argument of `set_flextable_defaults()`; be aware that this theme function is applied as the last instruction when calling `flextable()` - so if you add headers or footers to the array, they will not be formatted with the theme.

You can also use the `post_process_html` argument of `set_flextable_defaults()` (or `post_process_pdf`, `post_process_docx`, `post_process_pptx`) to specify a theme to be applied systematically before the `flextable()` is printed; in this case, don't forget to take care that the theme doesn't override any formatting done before the print statement.

See Also

Other functions related to themes: `get_flextable_defaults()`, `set_flextable_defaults()`, `theme_alafofi()`, `theme_booktabs()`, `theme_box()`, `theme_tron_legacy()`, `theme_vader()`, `theme_vanilla()`, `theme_zebra()`

Examples

```
ft <- flextable(head(airquality))
ft <- theme_tron(ft)
ft
```

theme_tron_legacy *Apply tron legacy theme*

Description

Apply theme tron legacy to a flextable

Usage

```
theme_tron_legacy(x)
```

Arguments

x	a flextable object
---	--------------------

Illustrations

behavior

Theme functions are not like 'ggplot2' themes. They are applied to the existing table **immediately**. If you add a row in the footer, the new row is not formatted with the theme. The theme function applies the theme only to existing elements when the function is called.

That is why theme functions should be applied after all elements of the table have been added (mainly additionnal header or footer rows).

If you want to automatically apply a theme function to each flextable, you can use the `theme_fun` argument of `set_flextable_defaults()`; be aware that this theme function is applied as the last instruction when calling `flextable()` - so if you add headers or footers to the array, they will not be formatted with the theme.

You can also use the `post_process_html` argument of `set_flextable_defaults()` (or `post_process_pdf`, `post_process_docx`, `post_process_pptx`) to specify a theme to be applied systematically before the `flextable()` is printed; in this case, don't forget to take care that the theme doesn't override any formatting done before the print statement.

See Also

Other functions related to themes: `get_flextable_defaults()`, `set_flextable_defaults()`, `theme_alafofi()`, `theme_booktabs()`, `theme_box()`, `theme_tron()`, `theme_vader()`, `theme_vanilla()`, `theme_zebra()`

Examples

```
ft <- flextable(head(airquality))
ft <- theme_tron_legacy(ft)
ft
```

theme_vader

Apply Sith Lord Darth Vader theme

Description

Apply Sith Lord Darth Vader theme to a flextable

Usage

```
theme_vader(x, ...)
```

Arguments

x	a flextable object
...	unused

Illustrations

behavior

Theme functions are not like 'ggplot2' themes. They are applied to the existing table **immediately**. If you add a row in the footer, the new row is not formatted with the theme. The theme function applies the theme only to existing elements when the function is called.

That is why theme functions should be applied after all elements of the table have been added (mainly additionnal header or footer rows).

If you want to automatically apply a theme function to each flextable, you can use the `theme_fun` argument of `set_flextable_defaults()`; be aware that this theme function is applied as the last instruction when calling `flextable()` - so if you add headers or footers to the array, they will not be formatted with the theme.

You can also use the `post_process_html` argument of `set_flextable_defaults()` (or `post_process_pdf`, `post_process_docx`, `post_process_pptx`) to specify a theme to be applied systematically before the `flextable()` is printed; in this case, don't forget to take care that the theme doesn't override any formatting done before the print statement.

See Also

Other functions related to themes: [get_flextable_defaults\(\)](#), [set_flextable_defaults\(\)](#), [theme_alafoli\(\)](#), [theme_booktabs\(\)](#), [theme_box\(\)](#), [theme_tron_legacy\(\)](#), [theme_tron\(\)](#), [theme_vanilla\(\)](#), [theme_zebra\(\)](#)

Examples

```
ft <- flextable(head(airquality))
ft <- theme_vader(ft)
ft
```

`theme_vanilla`

Apply vanilla theme

Description

Apply theme vanilla to a flextable: The external horizontal lines of the different parts of the table (body, header, footer) are black 2 points thick, the external horizontal lines of the different parts are black 0.5 point thick. Header text is bold, text columns are left aligned, other columns are right aligned.

Usage

```
theme_vanilla(x)
```

Arguments

x	a flextable object
---	--------------------

behavior

Theme functions are not like 'ggplot2' themes. They are applied to the existing table **immediately**. If you add a row in the footer, the new row is not formatted with the theme. The theme function applies the theme only to existing elements when the function is called.

That is why theme functions should be applied after all elements of the table have been added (mainly additionnal header or footer rows).

If you want to automatically apply a theme function to each flextable, you can use the `theme_fun` argument of `set_flextable_defaults()`; be aware that this theme function is applied as the last instruction when calling `flextable()` - so if you add headers or footers to the array, they will not be formatted with the theme.

You can also use the `post_process_html` argument of `set_flextable_defaults()` (or `post_process_pdf`, `post_process_docx`, `post_process_pptx`) to specify a theme to be applied systematically before the `flextable()` is printed; in this case, don't forget to take care that the theme doesn't override any formatting done before the print statement.

Illustrations

See Also

Other functions related to themes: [get_flextable_defaults\(\)](#), [set_flextable_defaults\(\)](#), [theme_alfafoli\(\)](#), [theme_booktabs\(\)](#), [theme_box\(\)](#), [theme_tron_legacy\(\)](#), [theme_tron\(\)](#), [theme_vader\(\)](#), [theme_zebra\(\)](#)

Examples

```
ft <- flextable(head(airquality))
ft <- theme_vanilla(ft)
ft
```

theme_zebra

Apply zebra theme

Description

Apply theme zebra to a flextable

Usage

```
theme_zebra(
  x,
  odd_header = "#CFCFCF",
  odd_body = "#EFEFEF",
  even_header = "transparent",
  even_body = "transparent"
)
```

Arguments

x	a flextable object
odd_header, odd_body, even_header, even_body	odd/even colors for table header and body

Illustrations

behavior

Theme functions are not like 'ggplot2' themes. They are applied to the existing table **immediately**. If you add a row in the footer, the new row is not formatted with the theme. The theme function applies the theme only to existing elements when the function is called.

That is why theme functions should be applied after all elements of the table have been added (mainly additionnal header or footer rows).

If you want to automatically apply a theme function to each flextable, you can use the `theme_fun` argument of `set_flextable_defaults()`; be aware that this theme function is applied as the last instruction when calling `flextable()` - so if you add headers or footers to the array, they will not be formatted with the theme.

You can also use the `post_process_html` argument of `set_flextable_defaults()` (or `post_process_pdf`, `post_process_docx`, `post_process_pptx`) to specify a theme to be applied systematically before the `flextable()` is printed; in this case, don't forget to take care that the theme doesn't override any formatting done before the print statement.

See Also

Other functions related to themes: [get_flextable_defaults\(\)](#), [set_flextable_defaults\(\)](#), [theme_alafooli\(\)](#), [theme_booktabs\(\)](#), [theme_box\(\)](#), [theme_tron_legacy\(\)](#), [theme_tron\(\)](#), [theme_vader\(\)](#), [theme_vanilla\(\)](#)

Examples

```
ft <- flextable(head(airquality))
ft <- theme_zebra(ft)
ft
```

<code>use_df_printer</code>	<i>set data.frame automatic printing as a flextable</i>
-----------------------------	---

Description

Define [df_printer\(\)](#) as data.frame print method in an R Markdown document.

In a setup run chunk:

```
flextable::use_df_printer()
```

Usage

```
use_df_printer()
```

See Also

[df_printer\(\)](#), [flextable\(\)](#)

<code>use_model_printer</code>	<i>set model automatic printing as a flextable</i>
--------------------------------	--

Description

Define [as_flextable\(\)](#) as print method in an R Markdown document for models of class:

- lm
- glm
- models from package 'lme' and 'lme4'
- htest (t.test, chisq.test, ...)
- gam
- kmeans and pam

In a setup run chunk:

```
flextable::use_model_printer()
```

Usage

```
use_model_printer()
```

See Also

[use_df_printer\(\)](#), [flextable\(\)](#)

valign	<i>Set vertical alignment</i>
--------	-------------------------------

Description

change vertical alignment of selected rows and columns of a flextable.

Usage

```
valign(x, i = NULL, j = NULL, valign = "center", part = "body")
```

Arguments

x	a flextable object
i	rows selection
j	columns selection
valign	vertical alignment of paragraph within cell, one of "center" or "top" or "bottom".
part	partname of the table (one of 'all', 'body', 'header', 'footer')

Illustrations**See Also**

Other sugar functions for table style: [align\(\)](#), [bg\(\)](#), [bold\(\)](#), [color\(\)](#), [empty_blanks\(\)](#), [fontsize\(\)](#), [font\(\)](#), [highlight\(\)](#), [italic\(\)](#), [line_spacing\(\)](#), [padding\(\)](#), [rotate\(\)](#)

Examples

```
ft_1 <- flextable(iris[c(1:3, 51:53, 101:103), ])
ft_1 <- theme_box(ft_1)
ft_1 <- merge_v(ft_1, j = 5)
ft_1

ft_2 <- valign(ft_1, j = 5, valign = "top", part = "all")
ft_2
```

vline*set vertical borders*

Description

The function is applying vertical borders to inner content of one or all parts of a flextable. The lines are the right borders of selected cells.

Usage

```
vline(x, i = NULL, j = NULL, border = NULL, part = "all")
```

Arguments

x	a flextable object
i	rows selection
j	columns selection
border	border properties defined by a call to fp_border()
part	partname of the table (one of 'all', 'body', 'header', 'footer')

Illustrations

See Also

Other borders management: [border_inner_h\(\)](#), [border_inner_v\(\)](#), [border_inner\(\)](#), [border_outer\(\)](#), [border_remove\(\)](#), [hline_bottom\(\)](#), [hline_top\(\)](#), [hline\(\)](#), [surround\(\)](#), [vline_left\(\)](#), [vline_right\(\)](#)

Examples

```
library(officer)
std_border = fp_border(color="orange")

ft <- flextable(head(iris))
ft <- border_remove(x = ft)

# add vertical borders
ft <- vline(ft, border = std_border )
ft
```

vline_left *set flextable left vertical borders*

Description

The function is applying vertical borders to the left side of one or all parts of a flextable. The line is the left border of selected cells of the first column.

Usage

```
vline_left(x, i = NULL, border = NULL, part = "all")
```

Arguments

x	a flextable object
i	rows selection
border	border properties defined by a call to fp_border()
part	partname of the table (one of 'all', 'body', 'header', 'footer')

Illustrations

See Also

Other borders management: [border_inner_h\(\)](#), [border_inner_v\(\)](#), [border_inner\(\)](#), [border_outer\(\)](#), [border_remove\(\)](#), [hline_bottom\(\)](#), [hline_top\(\)](#), [hline\(\)](#), [surround\(\)](#), [vline_right\(\)](#), [vline\(\)](#)

Examples

```
library(officer)
std_border = fp_border(color="orange")

ft <- flextable(head(iris))
ft <- border_remove(x = ft)

# add vertical border on the left side of the table
ft <- vline_left(ft, border = std_border )
ft
```

<code>vline_right</code>	<i>set flextable right vertical borders</i>
--------------------------	---

Description

The function is applying vertical borders to the right side of one or all parts of a flextable. The line is the right border of selected cells of the last column.

Usage

```
vline_right(x, i = NULL, border = NULL, part = "all")
```

Arguments

<code>x</code>	a flextable object
<code>i</code>	rows selection
<code>border</code>	border properties defined by a call to fp_border()
<code>part</code>	partname of the table (one of 'all', 'body', 'header', 'footer')

Illustrations

See Also

Other borders management: [border_inner_h\(\)](#), [border_inner_v\(\)](#), [border_inner\(\)](#), [border_outer\(\)](#), [border_remove\(\)](#), [hline_bottom\(\)](#), [hline_top\(\)](#), [hline\(\)](#), [surround\(\)](#), [vline_left\(\)](#), [vline\(\)](#)

Examples

```
library(officer)
std_border = fp_border(color="orange")

ft <- flextable(head(iris))
ft <- border_remove(x = ft)

# add vertical border on the left side of the table
ft <- vline_right(ft, border = std_border )
ft
```

void	<i>Delete flextable content</i>
------	---------------------------------

Description

Set content display as a blank " ".

Usage

```
void(x, j = NULL, part = "body")
```

Arguments

x	flextable object
j	columns selection
part	partname of the table

Examples

```
ftab <- flextable(head(mtcars))
ftab <- void(ftab, ~ vs + am + gear + carb )
ftab
```

width	<i>Set columns width</i>
-------	--------------------------

Description

Defines the widths of one or more columns in the table. This function will have no effect if you have used `set_table_properties(layout = "autofit")`.

`set_table_properties()` can provide an alternative to fixed-width layouts that is supported with HTML and Word output that can be set with `set_table_properties(layout = "autofit")`.

Usage

```
width(x, j = NULL, width, unit = "in")
```

Arguments

x	a <code>flextable()</code> object
j	columns selection
width	width in inches
unit	unit for width, one of "in", "cm", "mm".

Details

Heights are not used when flextable is been rendered into HTML.

Illustrations

See Also

Other flextable dimensions: [autofit\(\)](#), [dim.flextable\(\)](#), [dim.pretty\(\)](#), [fit_to_width\(\)](#), [flextable_dim\(\)](#), [height\(\)](#), [hrule\(\)](#), [ncol_keys\(\)](#), [nrow_part\(\)](#), [set_table_properties\(\)](#)

Examples

```
ft <- flextable(head(iris))
ft <- width(ft, width = 1.5)
ft
```

Index

- * **as_flextab methods**
 - as_flextab, 21
 - as_flextab.gam, 21
 - as_flextab.glm, 22
 - as_flextab.grouped_data, 23
 - as_flextab.htest, 24
 - as_flextab.lm, 26
 - as_flextab.tabulator, 28
 - as_flextab.xtable, 30
- * **borders management**
 - border_inner, 46
 - border_inner_h, 47
 - border_inner_v, 48
 - border_outer, 49
 - border_remove, 50
 - hline, 87
 - hline_bottom, 88
 - hline_top, 89
 - surround, 137
 - vline, 154
 - vline_left, 155
 - vline_right, 156
- * **cells formatters**
 - colformat_char, 50
 - colformat_date, 51
 - colformat_datetime, 52
 - colformat_double, 53
 - colformat_image, 55
 - colformat_int, 56
 - colformat_lgl, 57
 - colformat_num, 58
 - set_formatter, 126
- * **chunk elements for paragraph**
 - as_b, 17
 - as_bracket, 18
 - as_chunk, 19
 - as_equation, 20
 - as_highlight, 33
 - as_i, 33
- as_image, 34
- as_sub, 37
- as_sup, 38
- as_word_field, 39
- colorize, 61
- gg_chunk, 83
- hyperlink_text, 91
- linerange, 97
- lollipop, 99
- minibar, 105
- plot_chunk, 111
- * **flextab dimensions**
 - autofit, 40
 - dim.flextab, 65
 - dim.pretty, 66
 - fit_to_width, 68
 - flextab_dim, 71
 - height, 84
 - hrule, 90
 - ncol_keys, 106
 - nrow_part, 107
 - set_table_properties, 130
 - width, 157
- * **flextab merging function**
 - merge_at, 101
 - merge_h, 102
 - merge_h_range, 102
 - merge_none, 103
 - merge_v, 104
- * **flextab print function**
 - as_raster, 36
 - df_printer, 64
 - flextab_to_rmd, 72
 - htmltools_value, 91
 - knit_print.flextab, 93
 - plot.flextab, 110
 - print.flextab, 113
 - save_as_docx, 116
 - save_as_html, 117

save_as_image, 118
 save_as_pptx, 120
*** functions for defining formatting properties**
 fp_border_default, 79
 fp_text_default, 80
*** functions for mixed content paragraphs**
 append_chunks, 16
 as_paragraph, 35
 compose, 61
 prepend_chunks, 112
*** functions related to themes**
 get_flextabler_defaults, 82
 set_flextabler_defaults, 124
 theme_alafooli, 144
 theme_booktabs, 145
 theme_box, 146
 theme_tron, 147
 theme_tron_legacy, 148
 theme_vader, 149
 theme_vanilla, 150
 theme_zebra, 151
*** functions that add lines in the table**
 add_body, 5
 add_body_row, 6
 add_footer, 7
 add_footer_lines, 9
 add_footer_row, 10
 add_header, 11
 add_header_row, 13
*** functions that add rows in the table**
 add_header_lines, 12
*** functions to add rows in header or footer**
 add_footer, 7
 add_footer_lines, 9
 add_footer_row, 10
 add_header, 11
 add_header_lines, 12
 add_header_row, 13
 separate_header, 121
 set_header_footer_df, 128
 set_header_labels, 129
*** sugar functions for table style**
 align, 15
 bg, 43
 bold, 46
 color, 59
 empty_blanks, 67
 font, 75
 fontsize, 76
 highlight, 86
 italic, 92
 line_spacing, 98
 padding, 108
 rotate, 115
 valign, 153
*** tools for clinical reporting**
 shift_table, 131

 add_body, 5, 7–10, 12, 14
 add_body_row, 6, 6, 8–10, 12, 14
 add_footer, 6, 7, 7, 9, 10, 12–14, 121, 128, 129
 add_footer_lines, 6–8, 9, 10, 12–14, 121, 128, 129
 add_footer_row, 6–9, 10, 12–14, 121, 128, 129
 add_header, 6–10, 11, 13, 14, 121, 128, 129
 add_header_lines, 8–10, 12, 12, 14, 121, 128, 129
 add_header_row, 6–10, 12, 13, 13, 121, 128, 129
 add_header_row(), 7
 add_latex_dep, 14
 add_latex_dep(), 95
 align, 15, 43, 46, 60, 67, 76, 77, 86, 93, 99, 108, 116, 153
 align_nottext_col(align), 15
 align_text_col(align), 15
 append_chunks, 16, 36, 62, 112
 append_chunks(), 17–20, 33, 37–39, 61, 81, 91
 as_b, 17, 18–20, 33–35, 37–39, 61, 83, 92, 98, 100, 106, 111
 as_b(), 62
 as_bracket, 17, 18, 19, 20, 33–35, 37–39, 61, 83, 92, 98, 100, 106, 111
 as_chunk, 17, 18, 19, 20, 33–35, 37–39, 61, 83, 92, 98, 100, 106, 111
 as_chunk(), 16, 36, 61, 62, 81, 112
 as_equation, 17–19, 20, 33–35, 37–39, 61, 83, 92, 98, 100, 106, 111
 as_flextabler, 21, 22–24, 26, 29, 31
 as_flextabler(), 28, 152
 as_flextabler.brmsfit
 (as_flextabler.merMod), 26
 as_flextabler.gam, 21, 21, 22–24, 26, 29, 31

as_flextable.glm, 21, 22, 22, 23, 24, 26, 29, 31
as_flextable.glmmadmb
(as_flextable.merMod), 26
as_flextable.glmmTMB
(as_flextable.merMod), 26
as_flextable.gls (as_flextable.merMod), 26
as_flextable.grouped_data, 21, 22, 23, 24, 26, 29, 31
as_flextable.grouped_data(), 32
as_flextable.htest, 21–23, 24, 26, 29, 31
as_flextable.kmeans, 25
as_flextable.lm, 21–24, 26, 29, 31
as_flextable.lme (as_flextable.merMod), 26
as_flextable.merMod, 26
as_flextable.nlme
(as_flextable.merMod), 26
as_flextable.pam, 27
as_flextable.tabulator, 21–24, 26, 28, 31
as_flextable.tabulator(), 140, 142
as_flextable.xtable, 21–24, 26, 29, 30
as_grouped_data, 32
as_grouped_data(), 23, 29, 140
as_highlight, 17–20, 33, 34, 35, 37–39, 61, 83, 92, 98, 100, 106, 111
as_i, 17–20, 33, 33, 35, 37–39, 61, 83, 92, 98, 100, 106, 111
as_image, 17–20, 33, 34, 34, 37–39, 61, 83, 92, 98, 100, 106, 111
as_image(), 36, 61
as_paragraph, 16, 35, 62, 112
as_paragraph(), 19, 34, 35, 38, 62, 78, 83, 97–100, 105, 106, 111, 139
as_raster, 36, 65, 74, 91, 96, 110, 113, 117–120
as_raster(), 110
as_sub, 17–20, 33–35, 37, 38, 39, 61, 83, 92, 98, 100, 106, 111
as_sub(), 16
as_sup, 17–20, 33–35, 37, 38, 39, 61, 83, 92, 98, 100, 106, 111
as_sup(), 16, 61
as_word_field, 17–20, 33–35, 37, 38, 39, 61, 83, 92, 98, 100, 106, 111
as_word_field(), 62
autofit, 40, 66, 68, 71, 85, 90, 107, 115, 131, 158
autofit(), 71, 95, 109
before, 42
bg, 15, 43, 46, 60, 67, 76, 77, 86, 93, 99, 108, 116, 153
body_add_flextable, 44
body_replace_flextable_at_bkm
(body_add_flextable), 44
bold, 15, 43, 46, 60, 67, 76, 77, 86, 93, 99, 108, 116, 153
border_inner, 46, 48–50, 87–89, 137, 154–156
border_inner_h, 47, 47, 48–50, 87–89, 137, 154–156
border_inner_h(), 137
border_inner_v, 47, 48, 48, 49, 50, 87–89, 137, 154–156
border_inner_v(), 137
border_outer, 47, 48, 49, 50, 87–89, 137, 154–156
border_outer(), 137
border_remove, 47–49, 50, 87–89, 137, 154–156
colformat_char, 50, 52–57, 59, 127
colformat_date, 51, 51, 53–57, 59, 127
colformat_datetime, 51, 52, 52, 54–57, 59, 127
colformat_double, 51–53, 53, 55–57, 59, 127
colformat_double(), 58, 125, 127
colformat_image, 51–54, 55, 56, 57, 59, 127
colformat_int, 51–55, 56, 57, 59, 127
colformat_int(), 125
colformat_lgl, 51–56, 57, 59, 127
colformat_num, 51–57, 58, 127
colformat_num(), 6, 8, 11, 125
color, 15, 43, 46, 59, 67, 76, 77, 86, 93, 99, 108, 116, 153
colorize, 17–20, 33–35, 37–39, 61, 83, 92, 98, 100, 106, 111
colorize(), 16
compose, 16, 36, 61, 112
compose(), 5, 17–20, 33–35, 37–39, 61, 71, 81, 83, 91, 92, 97–100, 105, 106, 111, 139
continuous_summary, 63

delete_part, 64
 df_printer, 37, 64, 74, 91, 96, 110, 113, 117–120
 df_printer(), 152
 dim_flextab, 41, 65, 66, 68, 71, 85, 90, 107, 131, 158
 dim_pretty, 41, 66, 66, 68, 71, 85, 90, 107, 115, 131, 158
 dim_pretty(), 41, 109
 div(), 91
 empty_blanks, 15, 43, 46, 60, 67, 76, 77, 86, 93, 99, 108, 116, 153
 fit_to_width, 41, 66, 68, 71, 85, 90, 107, 131, 158
 fix_border_issues, 69
 flextab, 69
 flextab(), 5–7, 123, 152, 153, 157
 flextab-package, 5
 flextab_dim, 41, 66, 68, 71, 85, 90, 107, 131, 158
 flextab_html_dependency, 72
 flextab_to_rmd, 37, 65, 72, 91, 96, 110, 113, 117–120
 flextab_to_rmd(), 94
 fmt_2stats, 74
 fmt_2stats(), 136
 font, 15, 43, 46, 60, 67, 75, 77, 86, 93, 99, 108, 116, 153
 fontsize, 15, 43, 46, 60, 67, 76, 76, 86, 93, 99, 108, 116, 153
 footers_flextab_at_bkm, 77
 footnote, 78
 footnote(), 71
 format(), 56, 58, 59
 formatC, 125
 formatC(), 54, 59
 fp_border(), 28, 47–49, 79, 87–89, 154–156
 fp_border_default, 79, 81
 fp_border_default(), 28
 fp_text(), 80
 fp_text_default, 80, 80
 fp_text_default(), 39, 62
 get_flextab_defaults, 82, 126, 144–150, 152
 get_flextab_defaults(), 70, 124
 gg_chunk, 17–20, 33–35, 37–39, 61, 83, 92, 98, 100, 106, 111
 gg_chunk(), 16, 112
 headers_flextab_at_bkm, 84
 height, 41, 66, 68, 71, 84, 90, 107, 131, 158
 height(), 109, 115
 height_all(height), 84
 highlight, 15, 43, 46, 60, 67, 76, 77, 86, 93, 99, 108, 116, 153
 hline, 47–50, 87, 88, 89, 137, 154–156
 hline(), 42, 80, 137
 hline_bottom, 47–50, 87, 88, 89, 137, 154–156
 hline_top, 47–50, 87, 88, 89, 137, 154–156
 hline_top(), 137
 hrule, 41, 66, 68, 71, 85, 90, 107, 131, 158
 hrule(), 84, 85, 115
 HTML, 91
 htmltools_value, 37, 65, 74, 91, 96, 110, 113, 117–120
 hyperlink_text, 17–20, 33–35, 37–39, 61, 83, 91, 98, 100, 106, 111
 hyperlink_text(), 36
 init_flextab_defaults
 (set_flextab_defaults), 124
 init_flextab_defaults(), 70
 italic, 15, 43, 46, 60, 67, 76, 77, 86, 92, 99, 108, 116, 153
 kmeans(), 25
 knit_meta_add(), 14
 knit_print.flextab, 37, 65, 72, 74, 91, 93, 110, 113, 117–120, 123
 knit_print.flextab(), 69, 71, 113
 line_spacing, 15, 43, 46, 60, 67, 76, 77, 86, 93, 98, 108, 116, 153
 linerange, 17–20, 33–35, 37–39, 61, 83, 92, 97, 100, 106, 111
 lollipop, 17–20, 33–35, 37–39, 61, 83, 92, 98, 99, 106, 111
 merge_at, 101, 102–104
 merge_h, 101, 102, 103, 104
 merge_h(), 11
 merge_h_range, 101, 102, 102, 103, 104
 merge_none, 101–103, 103, 104

merge_v, 101–103, 104
merge_v(), 11
minibar, 17–20, 33–35, 37–39, 61, 83, 92, 98, 100, 105, 111
minibar(), 36
mk_par (compose), 61
mk_par(), 75, 139

ncol_keys, 41, 66, 68, 71, 85, 90, 106, 107, 131, 158
nrow_part, 41, 66, 68, 71, 85, 90, 107, 107, 131, 158

officer::fp_text(), 19, 39, 92
officer::ph_location_type(), 109
officer::read_pptx(), 109
officer::run_automum(), 123
officer::styles_info(), 123

padding, 15, 43, 46, 60, 67, 76, 77, 86, 93, 99, 108, 116, 153
pam(), 28
par(), 111
ph_with.flextable, 109
plot.flextable, 37, 65, 74, 91, 96, 110, 113, 117–120
plot_chunk, 17–20, 33–35, 37–39, 61, 83, 92, 98, 100, 106, 111
prepend_chunks, 16, 36, 62, 112
prepend_chunks(), 17–20, 33, 37–39, 61, 81, 91
print.flextable, 37, 65, 74, 91, 96, 110, 113, 117–120
proc_freq, 114
prop_section, 117

qflextable (flextable), 69

rotate, 15, 43, 46, 60, 67, 76, 77, 86, 93, 99, 108, 115, 153

save_as_docx, 37, 65, 74, 91, 96, 110, 113, 116, 118–120
save_as_html, 37, 65, 74, 91, 96, 110, 113, 117, 118, 119, 120
save_as_image, 37, 65, 74, 91, 96, 110, 113, 117, 118, 119, 120
save_as_pptx, 37, 65, 74, 91, 96, 110, 113, 117–119, 120

separate_header, 8–10, 12–14, 121, 128, 129
set_caption, 122
set_caption(), 71, 120
set_flextable_defaults, 82, 124, 144–150, 152
set_flextable_defaults(), 69, 70, 79, 80, 144–151
set_footer_df (set_header_footer_df), 128
set_formatter, 51–57, 59, 126
set_formatter(), 59
set_formatter_type (set_formatter), 126
set_header_df (set_header_footer_df), 128
set_header_footer_df, 8–10, 12–14, 121, 128, 129
set_header_labels, 8–10, 12–14, 121, 128, 129
set_table_properties, 41, 66, 68, 71, 85, 90, 107, 130, 158
set_table_properties(), 41, 71, 157
shift_table, 131
sprintf(), 75
strptime(), 52, 53, 125
style, 134
style(), 71
summarizor, 135
summarizor(), 29, 74, 75, 140
summary.tabulator (tabulator), 138
surround, 47–50, 87–89, 137, 154–156

tabulator, 138
tabulator(), 28, 29, 75, 135, 142
tabulator_colnames, 142
tabulator_colnames(), 140
theme_alafoli, 82, 126, 143, 145–150, 152
theme_booktabs, 82, 126, 144, 145, 146–150, 152
theme_booktabs(), 71
theme_box, 82, 126, 144, 145, 146, 147–150, 152
theme_tron, 82, 126, 144–146, 147, 148–150, 152
theme_tron_legacy, 82, 126, 144–147, 148, 149, 150, 152
theme_vader, 82, 126, 144–148, 149, 150, 152
theme_vanilla, 82, 126, 144–149, 150, 152
theme_zebra, 82, 126, 144–150, 151

use_df_printer, 152
use_df_printer(), 64, 153
use_model_printer, 152

valign, 15, 43, 46, 60, 67, 76, 77, 86, 93, 99,
 108, 116, 153
vline, 47–50, 87–89, 137, 154, 155, 156
vline(), 80, 137
vline_left, 47–50, 87–89, 137, 154, 155, 156
vline_left(), 137
vline_right, 47–50, 87–89, 137, 154, 155,
 156
void, 157

width, 41, 66, 68, 71, 85, 90, 107, 115, 131,
 157
width(), 109

xtable_to_flextable
 (as_flextable.xtable), 30