

Package ‘fundiversity’

August 25, 2022

Title Easy Computation of Alpha Functional Diversity Indices

Version 1.0.0

Description Computes 5 alpha-functional diversity indices: Functional Divergence (FDiv), Function Evenness (FEve), Functional Richness (FRic), Functional Dispersion (FDis) and Rao's entropy (Q) (reviewed in Villéger et al. 2008 <[doi:10.1890/07-1206.1](https://doi.org/10.1890/07-1206.1)>). Provides efficient, modular, and parallel functions to compute functional diversity indices.

License GPL-3

Encoding UTF-8

LazyData true

RoxygenNote 7.2.1

Depends R (>= 2.10)

Imports future.apply, geometry, Matrix, vegan

Suggests testthat (>= 3.0.0), knitr, rmarkdown, memoise

URL <https://hugogruson.fr/fundiversity/>,
<https://github.com/bisaloo/fundiversity>

BugReports <https://github.com/Bisaloo/fundiversity/issues>

Config/testthat/edition 3

VignetteBuilder knitr

NeedsCompilation no

Author Matthias Grenié [aut, cre] (<<https://orcid.org/0000-0002-4659-7522>>),
Hugo Gruson [aut] (<<https://orcid.org/0000-0002-4094-1476>>)

Maintainer Matthias Grenié <matthias.grenie@gmail.com>

Repository CRAN

Date/Publication 2022-08-25 10:32:35 UTC

R topics documented:

fd_fdis	2
fd_fdiv	3
fd_feve	4
fd_fric	5
fd_fric_intersect	6
fd_raoq	8
site_sp_birds	9
site_sp_plants	9
traits_birds	10
traits_plants	11
Index	12

fd_fdis	<i>Compute Functional Dispersion (FDis)</i>
---------	---

Description

Compute Functional Dispersion (FDis)

Usage

```
fd_fdis(traits, sp_com)
```

Arguments

traits	Trait matrix with species as rows and traits as columns. It has to contain exclusively numerical values. This can be either a <code>matrix</code> , a <code>data.frame</code> , or a <code>Matrix::Matrix()</code> object.
sp_com	Site-species matrix with sites as rows and species as columns if not provided, the function considers all species with equal abundance in a single site. This can be either a <code>matrix</code> , a <code>data.frame</code> , or a <code>Matrix::Matrix()</code> object.

Value

a `data.frame` with two columns:

- `site` the names of the sites as the row names of the input `sp_com`,
- `FDis` the values of functional dispersion at each site.

NB: when a site contains no species `FDis` is equal to 0.

Parallelization

The computation of this function can be parallelized thanks to `future::plan()`. To get more information on how to parallelize your computation please refer to the parallelization vignette with: `vignette("parallel", package = "fundiversity")`

References

Laliberté, E., & Legendre, P. (2010). A distance-based framework for measuring functional diversity from multiple traits. *Ecology*, 91(1), 299–305. doi:10.1890/082244.1

Examples

```
data(traits_birds)
data(site_sp_birds)
fd_fdis(traits_birds, site_sp_birds)
```

fd_fdiv	<i>Compute Functional Divergence (FDiv)</i>
---------	---

Description

Compute Functional Divergence (FDiv)

Usage

```
fd_fdiv(traits, sp_com)
```

Arguments

traits	Trait matrix with species as rows and traits as columns. It has to contain exclusively numerical values. This can be either a matrix, a data.frame, or a <code>Matrix::Matrix()</code> object.
sp_com	Site-species matrix with sites as rows and species as columns if not provided, the function considers all species with equal abundance in a single site. This can be either a matrix, a data.frame, or a <code>Matrix::Matrix()</code> object.

Details

By default, when loading **fundiversity**, the functions to compute convex hulls are **memoised** through the `memoise` package if it is installed. To deactivate this behavior you can set the option `fundiversity.memoise` to `FALSE` by running the following line: `options(fundiversity.memoise = FALSE)`. If you use it interactively it will only affect your current session. Add it to your script(s) or `.Rprofile` file to avoid toggling it each time.

Value

a data.frame with two columns:

- `site` the names of the sites as the row names of the input `sp_com`,
- `FDiv` the values of functional divergence at each site.

NB: when a site contains no species FDiv is equal to 0.

Parallelization

The computation of this function can be parallelized thanks to `future::plan()`. To get more information on how to parallelize your computation please refer to the parallelization vignette with: `vignette("parallel", package = "fundiversity")`

References

Villéger S., Mason N. W. H., Mouillot D. (2008), New multidimensional functional diversity indices for a multifaceted framework in functional ecology, *Ecology* 89(8), doi:[10.1890/071206.1](https://doi.org/10.1890/071206.1)

Examples

```
data(traits_birds)
fd_fdiv(traits_birds)
```

fd_feve	<i>Compute Functional Evenness (FEve)</i>
---------	---

Description

Compute Functional Evenness (FEve)

Usage

```
fd_feve(traits = NULL, sp_com, dist_matrix = NULL)
```

Arguments

traits	Trait matrix with species as rows and traits as columns. It has to contain exclusively numerical values. This can be either a matrix, a data.frame, or a <code>Matrix::Matrix()</code> object.
sp_com	Site-species matrix with sites as rows and species as columns if not provided, the function considers all species with equal abundance in a single site. This can be either a matrix, a data.frame, or a <code>Matrix::Matrix()</code> object.
dist_matrix	A dissimilarity matrix that can be provided instead of a trait data.frame (default: NULL). This can be either a matrix, a data.frame, or a <code>Matrix::Matrix()</code> object.

Value

a data.frame with two columns:

- site character column that contains site names based on input sp_com row names,
- FEve numeric column that contains FEve values corresponding to each site.

NB: By definition FEve is equal to NA when the number of species per site is strictly lower than 3.

Parallelization

The computation of this function can be parallelized thanks to `future::plan()`. To get more information on how to parallelize your computation please refer to the parallelization vignette with: `vignette("parallel", package = "fundiversity")`

References

Villéger, S., Mason, N.W.H., Mouillot, D., 2008. New Multidimensional Functional Diversity Indices for a Multifaceted Framework in Functional Ecology. *Ecology* 89, 2290–2301. doi:10.1890/071206.1

Examples

```
data(traits_birds)
fd_fve(traits_birds)
```

fd_fric	<i>Compute Functional Richness (FRic)</i>
---------	---

Description

Functional Richness is computed as the volume of the convex hull from all included traits.

Usage

```
fd_fric(traits, sp_com, stand = FALSE)
```

Arguments

traits	Trait matrix with species as rows and traits as columns. It has to contain exclusively numerical values. This can be either a <code>matrix</code> , a <code>data.frame</code> , or a <code>Matrix::Matrix()</code> object.
sp_com	Site-species matrix with sites as rows and species as columns if not provided, the function considers all species with equal abundance in a single site. This can be either a <code>matrix</code> , a <code>data.frame</code> , or a <code>Matrix::Matrix()</code> object.
stand	a boolean indicating whether to standardize FRic values over the observed maximum over all species (default: <code>FALSE</code>). This scales FRic between 0 and 1. NB: The maximum FRic values only considers species that are present in both site-species and trait matrices. If you want to consider species that are absent in the site-species matrix, add corresponding columns of 0s.

Details

By default, when loading **fundiversity**, the functions to compute convex hulls are **memoised** through the `memoise` package if it is installed. To deactivate this behavior you can set the option `fundiversity.memoise` to `FALSE` by running the following line: `options(fundiversity.memoise = FALSE)`. If you use it interactively it will only affect your current session. Add it to your script(s) or `.Rprofile` file to avoid toggling it each time.

Value

a data.frame with two columns:

- site the names of the sites as the row names of the input sp_com,
- FRic the values of functional richness at each site.

NB: FRic is equal to NA when there are strictly less species in a site than the number of provided traits.

Parallelization

The computation of this function can be parallelized thanks to `future::plan()`. To get more information on how to parallelize your computation please refer to the parallelization vignette with: `vignette("parallel", package = "fundiversity")`

References

Cornwell W. K., Schwilk D. W., Ackerly D. D. (2006), A trait-based test for habitat filtering: convex hull volume, *Ecology* 84(6), doi:[10.1890/00129658\(2006\)87\[1465:ATTFHF\]2.0.CO;2](https://doi.org/10.1890/00129658(2006)87[1465:ATTFHF]2.0.CO;2)

Examples

```
data(traits_birds)
fd_fric(traits_birds)
```

fd_fric_intersect	<i>Intersection between convex hulls of pairs of sites</i>
-------------------	--

Description

Compute volume of the intersection of the convex hulls of all pairs of sites (including self-intersection, which corresponds to their convex hull). Note that when standardizing convex hulls of intersections, this function uses the convex hull of all provided traits, thus standardized volume of self-intersection hulls can be lower than one.

Usage

```
fd_fric_intersect(traits, sp_com, stand = FALSE)
```

Arguments

traits	Trait matrix with species as rows and traits as columns. It has to contain exclusively numerical values. This can be either a matrix, a data.frame, or a <code>Matrix::Matrix()</code> object.
sp_com	Site-species matrix with sites as rows and species as columns if not provided, the function considers all species with equal abundance in a single site. This can be either a matrix, a data.frame, or a <code>Matrix::Matrix()</code> object.

stand a boolean indicating whether to standardize FRic values over the observed maximum over all species (default: FALSE). This scales FRic between 0 and 1. **NB:** The maximum FRic values only considers species that are present in **both** site-species and trait matrices. If you want to consider species that are absent in the site-species matrix, add corresponding columns of 0s.

Details

By default, when loading **fundiversity**, the functions to compute convex hulls are **memoised** through the `memoise` package if it is installed. To deactivate this behavior you can set the option `fundiversity.memoise` to FALSE by running the following line: `options(fundiversity.memoise = FALSE)`. If you use it interactively it will only affect your current session. Add it to your script(s) or `.Rprofile` file to avoid toggling it each time.

Value

a data.frame with three columns:

- `first_site` the names of the first site used in the pair `sp_com`,
- `second_site` the names of the first site used in the pair,
- `FRic_intersect` the volume of the convex hulls intersection of each pair of site.

NB: `FRic_intersect` is equal to NA when there are strictly less species in one of the sites than the number of provided traits.

Parallelization

The computation of this function can be parallelized thanks to `future::plan()`. To get more information on how to parallelize your computation please refer to the parallelization vignette with: `vignette("parallel", package = "fundiversity")`

See Also

`fd_fric()`, `geometry::intersectn()`, `geometry::convhulln()`

Examples

```
data(traits_birds)
fd_fric_intersect(traits_birds)
```

fd_raoq	<i>Compute Rao's entropy index (Rao's Q)</i>
---------	--

Description

Compute Rao's entropy index (Rao's Q)

Usage

```
fd_raoq(traits = NULL, sp_com, dist_matrix = NULL)
```

Arguments

traits	Trait matrix with species as rows and traits as columns. It has to contain exclusively numerical values. This can be either a matrix, a data.frame, or a <code>Matrix::Matrix()</code> object.
sp_com	Site-species matrix with sites as rows and species as columns if not provided, the function considers all species with equal abundance in a single site. This can be either a matrix, a data.frame, or a <code>Matrix::Matrix()</code> object.
dist_matrix	A dissimilarity matrix that can be provided instead of a trait data.frame (default: NULL). This can be either a matrix, a data.frame, or a <code>Matrix::Matrix()</code> object.

Value

a data.frame with two columns:

- site the names of the sites as the row names of the input sp_com,
- Q the values of Rao's quadratic entropy at each site.

NB: Rao's quadratic entropy is 0 when there are no species in the site.

References

Pavoine S., Dolédec S. (2005). The apportionment of quadratic entropy: a useful alternative for partitioning diversity in ecological data. *Environmental and Ecological Statistics*, 12(2), 125–138. doi:10.1007/s1065100510372

Examples

```
data(traits_birds)
fd_raoq(traits_birds)
```

site_sp_birds

Site-species matrix of birds along a Tropical Gradient

Description

Presences and absences of birds at different elevations along a tropical gradient. Species names are indicated as column names.

Usage

site_sp_birds

Format

A matrix with 217 columns (1 per species) and 8 rows:

elev_250 is species present at 250 m elevation? 0=No, 1=Yes

elev_500 is species present at 500 m elevation? 0=No, 1=Yes

elev_1000 is species present at 1000 m elevation? 0=No, 1=Yes

elev_1500 is species present at 1500 m elevation? 0=No, 1=Yes

elev_2000 is species present at 2000 m elevation? 0=No, 1=Yes

elev_2500 is species present at 2500 m elevation? 0=No, 1=Yes

elev_3000 is species present at 3000 m elevation? 0=No, 1=Yes

elev_3500 is species present at 3500 m elevation? 0=No, 1=Yes

Source

Nowak, Larissa et al. (2019), Data from: Projecting consequences of global warming for the functional diversity of fleshy-fruited plants and frugivorous birds along a tropical elevational gradient, Dryad, Dataset, [doi:10.5061/dryad.c0n737b](https://doi.org/10.5061/dryad.c0n737b)

site_sp_plants

Site-species matrix of plants along a Tropical Gradient

Description

Presences and absences of plants at different elevations along a tropical gradient. Species names are indicated as column names.

Usage

site_sp_plants

Format

A matrix with 392 columns (1 per species) and 10 rows:

elev_250 is species present at 250 m elevation? 0=No, 1=Yes

elev_500 is species present at 500 m elevation? 0=No, 1=Yes

elev_1000 is species present at 1000 m elevation? 0=No, 1=Yes

elev_1500 is species present at 1500 m elevation? 0=No, 1=Yes

elev_2000 is species present at 2000 m elevation? 0=No, 1=Yes

elev_2500 is species present at 2500 m elevation? 0=No, 1=Yes

elev_3000 is species present at 3000 m elevation? 0=No, 1=Yes

elev_3500 is species present at 3500 m elevation? 0=No, 1=Yes

elev_3750 is species present at 3750 m elevation? 0=No, 1=Yes

elev_4000 is species present at 4000 m elevation? 0=No, 1=Yes

Source

Nowak, Larissa et al. (2019), Data from: Projecting consequences of global warming for the functional diversity of fleshy-fruited plants and frugivorous birds along a tropical elevational gradient, Dryad, Dataset, [doi:10.5061/dryad.c0n737b](https://doi.org/10.5061/dryad.c0n737b)

traits_birds

Functional Traits of Frugivorous Birds along a Tropical Gradient

Description

A dataset containing some functional traits of frugivorous birds in the Manú biosphere reserve, southeast Peru. Given are species mean trait values. The row names of the dataset give species names. Morphological traits have been measured on museum specimen following Eck et al.(2011). Traits have been measured only for adult and, if possible, for a minimum of two female and two male specimens. Body mass was taken from Dunning et al. (2007).

Usage

traits_birds

Format

A data frame with 217 rows and 4 variables:

Bill.width..mm. bill width, in mm

Bill.length..mm. bill length, in mm

Kipp.s.index Kipp's index indicating wing Pointedness

Bodymass..g. adult's bodymass, in g

Source

Nowak, Larissa et al. (2019), Data from: Projecting consequences of global warming for the functional diversity of fleshy-fruited plants and frugivorous birds along a tropical elevational gradient, Dryad, Dataset, [doi:10.5061/dryad.c0n737b](https://doi.org/10.5061/dryad.c0n737b)

traits_plants

Functional Traits of Fleshy-fruit plants along a Tropical Gradient

Description

Taxonomy and functional traits of 392 fleshy-fruited plant species from the Manu National Park in south-east Peru. Given are fruit length and width (mm), plant height (m) and crop mass (g). Fruit traits have been measured on fresh fruit samples. Number of fruits per plant (used to determine the crop mass) and plant height have been estimated in the field. Species names are indicated as row names.

Usage

```
traits_plants
```

Format

A data frame with 392 rows and 4 variables:

Fruit.length..mm. fruit length, in mm

Fruit.width..mm. fruit width, in mm

Plant.height..m. plant height, in m

Crop.mass..g. seed mass, in g

Source

Nowak, Larissa et al. (2019), Data from: Projecting consequences of global warming for the functional diversity of fleshy-fruited plants and frugivorous birds along a tropical elevational gradient, Dryad, Dataset, [doi:10.5061/dryad.c0n737b](https://doi.org/10.5061/dryad.c0n737b)

Index

* datasets

- site_sp_birds, 9
- site_sp_plants, 9
- traits_birds, 10
- traits_plants, 11

- fd_fdis, 2
- fd_fdiv, 3
- fd_feve, 4
- fd_fric, 5
- fd_fric(), 7
- fd_fric_intersect, 6
- fd_raoq, 8
- future::plan(), 2, 4–7

- geometry::convhulln(), 7
- geometry::intersectn(), 7

- Matrix::Matrix(), 2–6, 8

- site_sp_birds, 9
- site_sp_plants, 9

- traits_birds, 10
- traits_plants, 11