

Package ‘fxTWAPLS’

June 7, 2022

Title An Improved Version of WA-PLS

Version 0.1.1

Description The goal of this package is to provide an improved version of WA-PLS (Weighted Averaging Partial Least Squares) by including the tolerances of taxa and the frequency of the sampled climate variable. This package also provides a way of leave-out cross-validation that removes both the test site and sites that are both geographically close and climatically close for each cycle, to avoid the risk of pseudo-replication.

License GPL-3

Encoding UTF-8

URL <https://github.com/special-uor/fxTWAPLS/>,
<https://special-uor.github.io/fxTWAPLS/>,
<https://research.reading.ac.uk/palaeoclimate/>

BugReports <https://github.com/special-uor/fxTWAPLS/issues>

Imports doFuture, foreach, future, geosphere, ggplot2, JOPS, MASS, parallel, progressr

Suggests magrittr, progress, scales, tictoc

Depends R (>= 3.6)

RoxygenNote 7.1.2

Language en-GB

NeedsCompilation no

Author Mengmeng Liu [aut] (<<https://orcid.org/0000-0001-6250-0148>>),
Iain Colin Prentice [aut] (<<https://orcid.org/0000-0002-1296-6764>>),
Cajo J. F. ter Braak [aut] (<<https://orcid.org/0000-0002-0414-8745>>),
Sandy P. Harrison [aut] (<<https://orcid.org/0000-0001-5687-1903>>),
Roberto Villegas-Diaz [aut, cre]
(<<https://orcid.org/0000-0001-5036-8661>>),
SPECIAL Research Group @ University of Reading [cph]

Maintainer Roberto Villegas-Diaz <r.villegas-diaz@outlook.com>

Repository CRAN

Date/Publication 2022-06-06 23:30:06 UTC

R topics documented:

cv.pr.w	2
cv.w	5
fx	7
fx_pspline	8
get_distance	9
get_pseudo	10
pb	11
plot_residuals	12
plot_train	13
rand.t.test.w	14
sse.sample	16
TWAPLS.predict.w	19
TWAPLS.w	20
TWAPLS.w2	22
WAPLS.predict.w	24
WAPLS.w	25
WAPLS.w2	27

Index	29
--------------	-----------

cv.pr.w

Pseudo-removed leave-out cross-validation

Description

Pseudo-removed leave-out cross-validation

Usage

```
cv.pr.w(
  modern_taxa,
  modern_climate,
  nPLS = 5,
  trainfun,
  predictfun,
  pseudo,
  usefx = FALSE,
  fx_method = "bin",
  bin = NA,
  cpus = 4,
  test_mode = TRUE,
  test_it = 5
)
```

Arguments

<code>modern_taxa</code>	The modern taxa abundance data, each row represents a sampling site, each column represents a taxon.
<code>modern_climate</code>	The modern climate value at each sampling site.
<code>nPLS</code>	The number of components to be extracted.
<code>trainfun</code>	Training function you want to use, either <code>WAPLS.w</code> or <code>TWAPLS.w</code> .
<code>predictfun</code>	Predict function you want to use: if <code>trainfun</code> is <code>WAPLS.w</code> , then this should be <code>WAPLS.predict.w</code> ; if <code>trainfun</code> is <code>TWAPLS.w</code> , then this should be <code>TWAPLS.predict.w</code> .
<code>pseudo</code>	The geographically and climatically close sites to each test site, obtained from <code>get_pseudo</code> function.
<code>usefx</code>	Boolean flag on whether or not use fx correction.
<code>fx_method</code>	Binned or p-spline smoothed fx correction: if <code>usefx</code> = FALSE, this should be NA; otherwise, <code>fx</code> function will be used when choosing "bin"; <code>fx_pspline</code> function will be used when choosing "pspline".
<code>bin</code>	Binwidth to get fx, needed for both binned and p-splined method. if <code>usefx</code> = FALSE, this should be NA;
<code>cpus</code>	Number of CPUs for simultaneous iterations to execute, check <code>parallel::detectCores()</code> for available CPUs on your machine.
<code>test_mode</code>	Boolean flag to execute the function with a limited number of iterations, <code>test_it</code> , for testing purposes only.
<code>test_it</code>	Number of iterations to use in the test mode.

Value

Leave-one-out cross validation results.

See Also

`fx`, `TWAPLS.w`, `TWAPLS.predict.w`, `WAPLS.w`, and `WAPLS.predict.w`

Examples

```

pseudo_Tmin <- fxTWAPLS::get_pseudo(dist,
                                      modern_pollen$Tmin,
                                      cpus = 2, # Remove the following line
                                      test_mode = test_mode)

cv_pr_t_Tmin <- fxTWAPLS::cv.pr.w(taxa,
                                      modern_pollen$Tmin,
                                      nPLS = 5,
                                      fxTWAPLS::TWAPLS.w,
                                      fxTWAPLS::TWAPLS.predict.w,
                                      pseudo_Tmin,
                                      cpus = 2, # Remove the following line
                                      test_mode = test_mode)

cv_pr_tf_Tmin <- fxTWAPLS::cv.pr.w(taxa,
                                      modern_pollen$Tmin,
                                      nPLS = 5,
                                      fxTWAPLS::TWAPLS.w,
                                      fxTWAPLS::TWAPLS.predict.w,
                                      pseudo_Tmin,
                                      usefx = TRUE,
                                      fx_method = "bin",
                                      bin = 0.02,
                                      cpus = 2, # Remove the following line
                                      test_mode = test_mode)

# Run with progress bar
`%>%` <- magrittr::`%>%
cv_pr_t_Tmin <- fxTWAPLS::cv.pr.w(taxa,
                                      modern_pollen$Tmin,
                                      nPLS = 5,
                                      fxTWAPLS::TWAPLS.w,
                                      fxTWAPLS::TWAPLS.predict.w,
                                      pseudo_Tmin,
                                      cpus = 2, # Remove the following line
                                      test_mode = test_mode) %>% fxTWAPLS::pb()

cv_pr_tf_Tmin <- fxTWAPLS::cv.pr.w(taxa,
                                      modern_pollen$Tmin,
                                      nPLS = 5,
                                      fxTWAPLS::TWAPLS.w,
                                      fxTWAPLS::TWAPLS.predict.w,
                                      pseudo_Tmin,
                                      usefx = TRUE,
                                      fx_method = "bin",
                                      bin = 0.02,
                                      cpus = 2, # Remove the following line
                                      test_mode = test_mode) %>% fxTWAPLS::pb()

## End(Not run)

```

cv.w*Leave-one-out cross-validation*

Description

Leave-one-out cross-validation as rioja (<https://cran.r-project.org/package=rioja>).

Usage

```
cv.w(
  modern_taxa,
  modern_climate,
  nPLS = 5,
  trainfun,
  predictfun,
  usefx = FALSE,
  fx_method = "bin",
  bin = NA,
  cpus = 4,
  test_mode = FALSE,
  test_it = 5
)
```

Arguments

modern_taxa	The modern taxa abundance data, each row represents a sampling site, each column represents a taxon.
modern_climate	The modern climate value at each sampling site.
nPLS	The number of components to be extracted.
trainfun	Training function you want to use, either WAPLS.w or TWAPLS.w .
predictfun	Predict function you want to use: if trainfun is WAPLS.w , then this should be WAPLS.predict.w ; if trainfun is TWAPLS.w , then this should be TWAPLS.predict.w .
usefx	Boolean flag on whether or not use fx correction.
fx_method	Binned or p-spline smoothed fx correction: if usefx = FALSE, this should be NA; otherwise, fx function will be used when choosing "bin"; fx_pspline function will be used when choosing "pspline".
bin	Binwidth to get fx, needed for both binned and p-splined method. if usefx = FALSE, this should be NA;
cpus	Number of CPUs for simultaneous iterations to execute, check parallel::detectCores() for available CPUs on your machine.
test_mode	boolean flag to execute the function with a limited number of iterations, test_it , for testing purposes only.
test_it	number of iterations to use in the test mode.

Value

leave-one-out cross validation results

See Also

[fx](#), [TWAPLS.w](#), [TWAPLS.predict.w](#), [WAPLS.w](#), and [WAPLS.predict.w](#)

Examples

```
## Not run:
# Load modern pollen data
modern_pollen <- read.csv("/path/to/modern_pollen.csv")

# Extract taxa
taxaColMin <- which(colnames(modern_pollen) == "taxa0")
taxaColMax <- which(colnames(modern_pollen) == "taxaN")
taxa <- modern_pollen[, taxaColMin:taxaColMax]

## LOOCV
test_mode <- TRUE # It should be set to FALSE before running
### without fx
cv_t_Tmin <- fxTWAPLS::cv.w(taxa,
                               modern_pollen$Tmin,
                               nPLS = 5,
                               fxTWAPLS::TWAPLS.w,
                               fxTWAPLS::TWAPLS.predict.w,
                               cpus = 2, # Remove the following line
                               test_mode = test_mode)

### with fx
cv_tf_Tmin <- fxTWAPLS::cv.w(taxa,
                               modern_pollen$Tmin,
                               nPLS = 5,
                               fxTWAPLS::TWAPLS.w,
                               fxTWAPLS::TWAPLS.predict.w,
                               usefx = TRUE,
                               fx_method = "bin",
                               bin = 0.02,
                               cpus = 2, # Remove the following line
                               test_mode = test_mode)

# Run with progress bar
`%>%` <- magrittr::`%>%`
### without fx
cv_t_Tmin <- fxTWAPLS::cv.w(taxa,
                               modern_pollen$Tmin,
                               nPLS = 5,
                               fxTWAPLS::TWAPLS.w,
                               fxTWAPLS::TWAPLS.predict.w,
                               cpus = 2, # Remove the following line
                               test_mode = test_mode) %>% fxTWAPLS::pb()

### with fx
cv_tf_Tmin <- fxTWAPLS::cv.w(taxa,
```

```

modern_pollen$Tmin,
nPLS = 5,
fxTWAPLS::TWAPLS.w,
fxTWAPLS::TWAPLS.predict.w,
usefx = TRUE,
fx_method = "bin",
bin = 0.02,
cpus = 2, # Remove the following line
test_mode = test_mode) %>% fxTWAPLS::pb()

## End(Not run)

```

fx*Get frequency of the climate value*

Description

Function to get the frequency of the climate value, which will be used to provide fx correction for WA-PLS and TWA-PLS.

Usage

```
fx(x, bin, show_plot = FALSE)
```

Arguments

<code>x</code>	Numeric vector with the modern climate values.
<code>bin</code>	Binwidth to get the frequency of the modern climate values.
<code>show_plot</code>	Boolean flag to show a plot of <code>fx ~ x</code> .

Value

Numeric vector with the frequency of the modern climate values.

See Also

[cv.w](#), [cv.pr.w](#), and [sse.sample](#)

Examples

```

## Not run:
# Load modern pollen data
modern_pollen <- read.csv("/path/to/modern_pollen.csv")

# Get the frequency of each climate variable fx
fx_Tmin <- fxTWAPLS::fx(modern_pollen$Tmin, bin = 0.02, show_plot = TRUE)
fx_gdd <- fxTWAPLS::fx(modern_pollen$gdd, bin = 20, show_plot = TRUE)
fx_alpha <- fxTWAPLS::fx(modern_pollen$alpha, bin = 0.002, show_plot = TRUE)

```

```
## End(Not run)
```

fx_pspline

Get frequency of the climate value with p-spline smoothing

Description

Function to get the frequency of the climate value, which will be used to provide fx correction for WA-PLS and TWA-PLS.

Usage

```
fx_pspline(x, bin, show_plot = FALSE)
```

Arguments

<code>x</code>	Numeric vector with the modern climate values.
<code>bin</code>	Binwidth to get the frequency of the modern climate values, the curve will be p-spline smoothed later
<code>show_plot</code>	Boolean flag to show a plot of $f(x) \sim x$.

Value

Numeric vector with the frequency of the modern climate values.

See Also

`cv.w`, `cv.pr.w`, and `sse.sample`

Examples

get_distance	<i>Get the distance between points</i>
--------------	--

Description

Get the distance between points, the output will be used in [get_pseudo](#).

Usage

```
get_distance(point, cpus = 4, test_mode = FALSE, test_it = 5)
```

Arguments

point	Each row represents a sampling site, the first column is longitude and the second column is latitude, both in decimal format.
cpus	Number of CPUs for simultaneous iterations to execute, check <code>parallel::detectCores()</code> for available CPUs on your machine.
test_mode	Boolean flag to execute the function with a limited number of iterations, <code>test_it</code> , for testing purposes only.
test_it	Number of iterations to use in the test mode.

Value

Distance matrix, the value at the *i*-th row, means the distance between the *i*-th sampling site and the whole sampling sites.

See Also

[get_pseudo](#)

Examples

```
## Not run:
# Load modern pollen data
modern_pollen <- read.csv("/path/to/modern_pollen.csv")

point <- modern_pollen[, c("Long", "Lat")]
test_mode <- TRUE # It should be set to FALSE before running
dist <- fxTWAPLS::get_distance(point,
                                cpus = 2, # Remove the following line
                                test_mode = test_mode)
# Run with progress bar
`%>%` <- magrittr::`%>%`
dist <- fxTWAPLS::get_distance(point,
                                cpus = 2, # Remove the following line
                                test_mode = test_mode) %>% fxTWAPLS::pb()

## End(Not run)
```

get_pseudo*Get geographically and climatically close sites***Description**

Get the sites which are both geographically and climatically close to the test site, which could result in pseudo-replication and inflate the cross-validation statistics. The output will be used in [cv.pr.w](#).

Usage

```
get_pseudo(dist, x, cpus = 4, test_mode = FALSE, test_it = 5)
```

Arguments

<code>dist</code>	Distance matrix which contains the distance from other sites.
<code>x</code>	The modern climate values.
<code>cpus</code>	Number of CPUs for simultaneous iterations to execute, check <code>parallel::detectCores()</code> for available CPUs on your machine.
<code>test_mode</code>	Boolean flag to execute the function with a limited number of iterations, <code>test_it</code> , for testing purposes only.
<code>test_it</code>	Number of iterations to use in the test mode.

Value

The geographically and climatically close sites to each test site.

See Also

[get_distance](#)

Examples

```
## Not run:
# Load modern pollen data
modern_pollen <- read.csv("/path/to/modern_pollen.csv")

point <- modern_pollen[, c("Long", "Lat")]
test_mode <- TRUE # It should be set to FALSE before running
dist <- fxTWAPLS::get_distance(point,
                                cpus = 2, # Remove the following line
                                test_mode = test_mode)
pseudo_Tmin <- fxTWAPLS::get_pseudo(dist,
                                         modern_pollen$Tmin,
                                         cpus = 2, # Remove the following line
                                         test_mode = test_mode)

# Run with progress bar
`%>%` <- magrittr::`%>%`
pseudo_Tmin <- fxTWAPLS::get_pseudo(dist,
```

```
modern_pollen$Tmin,  
cpus = 2, # Remove the following line  
test_mode = test_mode) %>% fxtWAPLS::pb()  
  
## End(Not run)
```

pb	<i>Show progress bar</i>
----	--------------------------

Description

Show progress bar

Usage

```
pb(expr, ...)
```

Arguments

expr	R expression.
...	Arguments passed on to progressr::with_progress
cleanup	If TRUE, all progression handlers will be shutdown at the end regardless of the progression is complete or not.
delay_terminal	If TRUE, output and conditions that may end up in the terminal will delayed.
delay_stdout	If TRUE, standard output is captured and relayed at the end just before any captured conditions are relayed.
delay_conditions	A character vector specifying base::condition classes to be captured and relayed at the end after any captured standard output is relayed.
interrupts	Controls whether interrupts should be detected or not. If TRUE and a interrupt is signaled, progress handlers are asked to report on the current amount progress when the evaluation was terminated by the interrupt, e.g. when a user pressed Ctrl-C in an interactive session, or a batch process was interrupted because it ran out of time.
interval (numeric)	The minimum time (in seconds) between successive progression updates from handlers.
enable (logical)	If FALSE, then progress is not reported. The default is to report progress in interactive mode but not batch mode. See below for more details.

Value

Return data from the function called.

`plot_residuals` *Plot the residuals*

Description

Plot the residuals, the black line is 0 line, the red line is the locally estimated scatterplot smoothing, which shows the degree of local compression.

Usage

```
plot_residuals(train_output, col)
```

Arguments

- | | |
|---------------------------|---|
| <code>train_output</code> | Training output, can be the output of WA-PLS, WA-PLS with fx correction, TWA-PLS, or TWA-PLS with fx correction |
| <code>col</code> | Choose which column of the fitted value to plot, in other words, how many number of components you want to use. |

Value

Plotting status.

See Also

[TWAPLS.w](#) and [WAPLS.w](#)

Examples

```
## Not run:
# Load modern pollen data
modern_pollen <- read.csv("/path/to/modern_pollen.csv")

# Extract taxa
taxaColMin <- which(colnames(modern_pollen) == "taxa0")
taxaColMax <- which(colnames(modern_pollen) == "taxaN")
taxa <- modern_pollen[, taxaColMin:taxaColMax]

# MTCO
## WAPLS and fxWAPLS
fit_Tmin <- fxTWAPLS::WAPLS.w(taxa, modern_pollen$Tmin, nPLS = 5)
fit_f_Tmin <- fxTWAPLS::WAPLS.w(taxa,
                                  modern_pollen$Tmin,
                                  nPLS = 5,
                                  usefx = TRUE,
                                  fx_method = "bin",
                                  bin = 0.02)

## TWAPLS and fxTWAPLS
fit_t_Tmin <- fxTWAPLS::TWAPLS.w(taxa, modern_pollen$Tmin, nPLS = 5)
```

```

fit_tf_Tmin <- fxtWAPLS::TWAPLS.w(taxa,
                                     modern_pollen$Tmin,
                                     nPLS = 5,
                                     usefx = TRUE,
                                     fx_method = "bin",
                                     bin = 0.02)
fxtWAPLS::plot_residuals(fit_Tmin, 3)
fxtWAPLS::plot_residuals(fit_f_Tmin, 3)
fxtWAPLS::plot_residuals(fit_t_Tmin, 3)
fxtWAPLS::plot_residuals(fit_tf_Tmin, 3)

## End(Not run)

```

plot_train*Plot the training results***Description**

Plot the training results, the black line is the 1:1 line, the red line is the linear regression line to fitted and x, which shows the degree of overall compression.

Usage

```
plot_train(train_output, col)
```

Arguments

- | | |
|--------------|--|
| train_output | Training output, can be the output of WA-PLS, WA-PLS with fx correction, TWA-PLS, or TWA-PLS with fx correction. |
| col | Choose which column of the fitted value to plot, in other words, how many number of components you want to use. |

Value

Plotting status.

See Also

[TWAPLS.w](#) and [WAPLS.w](#)

Examples

```

## Not run:
# Load modern pollen data
modern_pollen <- read.csv("/path/to/modern_pollen.csv")

# Extract taxa
taxaColMin <- which(colnames(modern_pollen) == "taxa0")

```

```

taxaColMax <- which(colnames(modern_pollen) == "taxaN")
taxa <- modern_pollen[, taxaColMin:taxaColMax]

# MTCO
## WAPLS and fxWAPLS
fit_Tmin <- fxTWAPLS::WAPLS.w(taxa, modern_pollen$Tmin, nPLS = 5)
fit_f_Tmin <- fxTWAPLS::WAPLS.w(taxa,
                                   modern_pollen$Tmin,
                                   nPLS = 5,
                                   usefx = TRUE,
                                   fx_method = "bin",
                                   bin = 0.02)
## TWAPLS and fxTWAPLS
fit_t_Tmin <- fxTWAPLS::TWAPLS.w(taxa, modern_pollen$Tmin, nPLS = 5)
fit_tf_Tmin <- fxTWAPLS::TWAPLS.w(taxa,
                                   modern_pollen$Tmin,
                                   nPLS = 5,
                                   usefx = TRUE,
                                   fx_method = "bin",
                                   bin = 0.02)
fxTWAPLS::plot_train(fit_Tmin, 3)
fxTWAPLS::plot_train(fit_f_Tmin, 3)
fxTWAPLS::plot_train(fit_t_Tmin, 3)
fxTWAPLS::plot_train(fit_tf_Tmin, 3)

## End(Not run)

```

rand.t.test.w*Random t-test***Description**

Do a random t-test to the cross-validation results.

Usage

```
rand.t.test.w(cvoutput, n.perm = 999)
```

Arguments

<code>cvoutput</code>	Cross-validation output either from <code>cv.w</code> or <code>cv.pr.w</code> .
<code>n.perm</code>	The number of permutation times to get the p value, which assesses whether using the current number of components is significantly different from using one less.

Value

A matrix of the statistics of the cross-validation results. Each component is described below:

- R2 the coefficient of determination (the larger, the better the fit).
- Avg.Bias average bias.
- Max.Bias maximum bias.
- Min.Bias minimum bias.
- RMSEP root-mean-square error of prediction (the smaller, the better the fit).
- delta.RMSEP the percent change of RMSEP using the current number of components than using one component less.
- p assesses whether using the current number of components is significantly different from using one component less, which is used to choose the last significant number of components to avoid over-fitting.
- The degree of overall compression is assessed by doing linear regression to the cross-validation result and the observed climate values.
 - Compre.b0: the intercept.
 - Compre.b1: the slope (the closer to 1, the less the overall compression).
 - Compre.b0.se: the standard error of the intercept.
 - Compre.b1.se: the standard error of the slope.

See Also

[cv.w](#) and [cv.pr.w](#)

Examples

```
## Not run:
# Load modern pollen data
modern_pollen <- read.csv("/path/to/modern_pollen.csv")

# Extract taxa
taxaColMin <- which(colnames(modern_pollen) == "taxa0")
taxaColMax <- which(colnames(modern_pollen) == "taxaN")
taxa <- modern_pollen[, taxaColMin:taxaColMax]

## LOOCV
test_mode <- TRUE # It should be set to FALSE before running
### without fx
cv_t_Tmin <- fxtWAPLS::cv.w(taxa,
                               modern_pollen$Tmin,
                               nPLS = 5,
                               fxtWAPLS::TWAPLS.w,
                               fxtWAPLS::TWAPLS.predict.w,
                               cpus = 2, # Remove the following line
                               test_mode = test_mode) %>% fxtWAPLS::pb()

### with fx
cv_tf_Tmin <- fxtWAPLS::cv.w(taxa,
                               modern_pollen$Tmin,
```

```

nPLS = 5,
fxTWAPLS::TWAPLS.w,
fxTWAPLS::TWAPLS.predict.w,
usefx = TRUE,
fx_method = "bin",
bin = 0.02,
cpus = 2, # Remove the following line
test_mode = test_mode) %>% fxTWAPLS::pb()

## Random t-test
rand_t_Tmin <- fxTWAPLS::rand.t.test.w(cv_t_Tmin, n.perm = 999)
rand_tf_Tmin <- fxTWAPLS::rand.t.test.w(cv_tf_Tmin, n.perm = 999)

## End(Not run)

```

sse.sample*Calculate Sample Specific Errors***Description**

Calculate Sample Specific Errors

Usage

```

sse.sample(
  modern_taxa,
  modern_climate,
  fossil_taxa,
  trainfun,
  predictfun,
  nboot,
  nPLS,
  nsig,
  usefx = FALSE,
  fx_method = "bin",
  bin = NA,
  cpus = 4,
  seed = NULL,
  test_mode = FALSE,
  test_it = 5
)

```

Arguments

- | | |
|-----------------------------|--|
| <code>modern_taxa</code> | The modern taxa abundance data, each row represents a sampling site, each column represents a taxon. |
| <code>modern_climate</code> | The modern climate value at each sampling site |

fossil_taxa	Fossil taxa abundance data to reconstruct past climates, each row represents a site to be reconstructed, each column represents a taxon.
trainfun	Training function you want to use, either WAPLS.w or TWAPLS.w .
predictfun	Predict function you want to use: if trainfun is WAPLS.w , then this should be WAPLS.predict.w ; if trainfun is TWAPLS.w , then this should be TWAPLS.predict.w .
nboot	The number of bootstrap cycles you want to use.
nPLS	The number of components to be extracted.
nsig	The significant number of components to use to reconstruct past climates, this can be obtained from the cross-validation results.
usefx	Boolean flag on whether or not use fx correction.
fx_method	Binned or p-spline smoothed fx correction: if usefx = FALSE, this should be NA; otherwise, fx function will be used when choosing "bin"; fx_pspline function will be used when choosing "pspline".
bin	Binwidth to get fx, needed for both binned and p-splined method. if usefx = FALSE, this should be NA;
cpus	Number of CPUs for simultaneous iterations to execute, check parallel::detectCores() for available CPUs on your machine.
seed	Seed for reproducibility.
test_mode	Boolean flag to execute the function with a limited number of iterations, test_it , for testing purposes only.
test_it	Number of iterations to use in the test mode.

Value

The bootstrapped standard error for each site.

See Also

[fx](#), [TWAPLS.w](#), [TWAPLS.predict.w](#), [WAPLS.w](#), and [WAPLS.predict.w](#)

Examples

```
## Not run:
# Load modern pollen data
modern_pollen <- read.csv("/path/to/modern_pollen.csv")

# Extract taxa
taxaColMin <- which(colnames(modern_pollen) == "taxa0")
taxaColMax <- which(colnames(modern_pollen) == "taxaN")
taxa <- modern_pollen[, taxaColMin:taxaColMax]

# Load reconstruction data
Holocene <- read.csv("/path/to/Holocene.csv")
taxaColMin <- which(colnames(Holocene) == "taxa0")
taxaColMax <- which(colnames(Holocene) == "taxaN")
core <- Holocene[, taxaColMin:taxaColMax]
```



```

predictfun =
  fxTWAPLS::TWAPLS.predict.w,
nboot = nboot,
nPLS = 5,
nsig = 3,
usefx = TRUE,
fx_method = "bin",
bin = 0.02,
cpus = 2,
seed = 1) %>% fxTWAPLS::pb()

## End(Not run)

```

TWAPLS.predict.w *TWA-PLS predict function*

Description

TWA-PLS predict function

Usage

```
TWAPLS.predict.w(TWAPLSSoutput, fossil_taxa)
```

Arguments

- | | |
|---------------|--|
| TWAPLSSoutput | The output of the TWAPLS.w training function, either with or without fx correction. |
| fossil_taxa | Fossil taxa abundance data to reconstruct past climates, each row represents a site to be reconstructed, each column represents a taxon. |

Value

A list of the reconstruction results. Each element in the list is described below:

- `fit` the fitted values using each number of components.
- `nPLS` the total number of components extracted.

See Also

[TWAPLS.w](#)

Examples

```

## Not run:
# Load modern pollen data
modern_pollen <- read.csv("/path/to/modern_pollen.csv")

# Extract taxa
taxaColMin <- which(colnames(modern_pollen) == "taxa0")
taxaColMax <- which(colnames(modern_pollen) == "taxaN")
taxa <- modern_pollen[, taxaColMin:taxaColMax]

# Load reconstruction data
Holocene <- read.csv("/path/to/Holocene.csv")
taxaColMin <- which(colnames(Holocene) == "taxa0")
taxaColMax <- which(colnames(Holocene) == "taxaN")
core <- Holocene[, taxaColMin:taxaColMax]

# MTCO
## Train
fit_t_Tmin <- fxTWAPLS::TWAPLS.w(taxa, modern_pollen$Tmin, nPLS = 5)
fit_tf_Tmin <- fxTWAPLS::TWAPLS.w(taxa,
                                    modern_pollen$Tmin,
                                    nPLS = 5,
                                    usefx = TRUE,
                                    fx_method = "bin",
                                    bin = 0.02)

## Predict
fossil_t_Tmin <- fxTWAPLS::TWAPLS.predict.w(fit_t_Tmin, core)
fossil_tf_Tmin <- fxTWAPLS::TWAPLS.predict.w(fit_tf_Tmin, core)

## End(Not run)

```

TWAPLS.w

TWA-PLS training function

Description

TWA-PLS training function, which can perform fx correction. $1/fx^2$ correction will be applied at step 7.

Usage

```

TWAPLS.w(
  modern_taxa,
  modern_climate,
  nPLS = 5,
  usefx = FALSE,
  fx_method = "bin",

```

```
bin = NA
)
```

Arguments

<code>modern_taxa</code>	The modern taxa abundance data, each row represents a sampling site, each column represents a taxon.
<code>modern_climate</code>	The modern climate value at each sampling site.
<code>nPLS</code>	The number of components to be extracted.
<code>usefx</code>	Boolean flag on whether or not use fx correction.
<code>fx_method</code>	Binned or p-spline smoothed fx correction: if <code>usefx</code> = FALSE, this should be NA; otherwise, <code>fx</code> function will be used when choosing "bin"; <code>fx_pspline</code> function will be used when choosing "pspline".
<code>bin</code>	Binwidth to get fx, needed for both binned and p-splined method. if <code>usefx</code> = FALSE, this should be NA;

Value

A list of the training results, which will be used by the predict function. Each element in the list is described below:

- `fit` the fitted values using each number of components.
- `x` the observed modern climate values.
- `taxon_name` the name of each taxon.
- `optimum` the updated taxon optimum
- `comp` each component extracted (will be used in step 7 regression).
- `u` taxon optimum for each component (step 2).
- `t` taxon tolerance for each component (step 2).
- `z` a parameter used in standardization for each component (step 5).
- `s` a parameter used in standardization for each component (step 5).
- `orth` a list that stores orthogonalization parameters (step 4).
- `alpha` a list that stores regression coefficients (step 7).
- `meanx` mean value of the observed modern climate values.
- `nPLS` the total number of components extracted.

See Also

`fx`, `TWAPLS.predict.w`, and `WAPLS.w`

Examples

```

## Not run:
# Load modern pollen data
modern_pollen <- read.csv("/path/to/modern_pollen.csv")

# Extract taxa
taxaColMin <- which(colnames(modern_pollen) == "taxa0")
taxaColMax <- which(colnames(modern_pollen) == "taxaN")
taxa <- modern_pollen[, taxaColMin:taxaColMax]

# MTCO
fit_t_Tmin <- fxTWAPLS::TWAPLS.w(taxa, modern_pollen$Tmin, nPLS = 5)
fit_tf_Tmin <- fxTWAPLS::TWAPLS.w(taxa,
                                    modern_pollen$Tmin,
                                    nPLS = 5,
                                    usefx = TRUE,
                                    fx_method = "bin",
                                    bin = 0.02)

## End(Not run)

```

TWAPLS.w2

TWA-PLS training function v2

Description

TWA-PLS training function, which can perform fx correction. 1/fx correction will be applied at step 2 and step 7.

Usage

```

TWAPLS.w2(
  modern_taxa,
  modern_climate,
  nPLS = 5,
  usefx = FALSE,
  fx_method = "bin",
  bin = NA
)

```

Arguments

- | | |
|-----------------------------|--|
| <code>modern_taxa</code> | The modern taxa abundance data, each row represents a sampling site, each column represents a taxon. |
| <code>modern_climate</code> | The modern climate value at each sampling site. |
| <code>nPLS</code> | The number of components to be extracted. |

<code>usefx</code>	Boolean flag on whether or not use <code>fx</code> correction.
<code>fx_method</code>	Binned or p-spline smoothed <code>fx</code> correction: if <code>usefx</code> = FALSE, this should be NA; otherwise, <code>fx</code> function will be used when choosing "bin"; <code>fx_pspline</code> function will be used when choosing "pspline".
<code>bin</code>	Binwidth to get <code>fx</code> , needed for both binned and p-splined method. if <code>usefx</code> = FALSE, this should be NA;

Value

A list of the training results, which will be used by the predict function. Each element in the list is described below:

- `fit` the fitted values using each number of components.
- `x` the observed modern climate values.
- `taxon_name` the name of each taxon.
- `optimum` the updated taxon optimum
- `comp` each component extracted (will be used in step 7 regression).
- `u` taxon optimum for each component (step 2).
- `t` taxon tolerance for each component (step 2).
- `z` a parameter used in standardization for each component (step 5).
- `s` a parameter used in standardization for each component (step 5).
- `orth` a list that stores orthogonalization parameters (step 4).
- `alpha` a list that stores regression coefficients (step 7).
- `meanx` mean value of the observed modern climate values.
- `nPLS` the total number of components extracted.

See Also

`fx`, `TWAPLS.predict.w`, and `WAPLS.w`

Examples

```
## Not run:
# Load modern pollen data
modern_pollen <- read.csv("/path/to/modern_pollen.csv")

# Extract taxa
taxaColMin <- which(colnames(modern_pollen) == "taxa0")
taxaColMax <- which(colnames(modern_pollen) == "taxaN")
taxa <- modern_pollen[, taxaColMin:taxaColMax]

# Get the frequency of each climate variable fx
fx_Tmin <- fxTWAPLS::fx(modern_pollen$Tmin, bin = 0.02)

# MTCO
fit_t_Tmin2 <- fxTWAPLS::TWAPLS.w2(taxa, modern_pollen$Tmin, nPLS = 5)
```

```

fit_tf_Tmin2 <- fxTWAPLS::TWAPLS.w2(taxa,
                                      modern_pollen$Tmin,
                                      nPLS = 5,
                                      usefx = TRUE,
                                      fx_method = "bin",
                                      bin = 0.02)

## End(Not run)

```

WAPLS.predict.w*WA-PLS predict function***Description**

WA-PLS predict function

Usage

```
WAPLS.predict.w(WAPLSSoutput, fossil_taxa)
```

Arguments

<code>WAPLSSoutput</code>	The output of the WAPLS.w training function, either with or without fx correction.
<code>fossil_taxa</code>	Fossil taxa abundance data to reconstruct past climates, each row represents a site to be reconstructed, each column represents a taxon.

Value

A list of the reconstruction results. Each element in the list is described below:

- `fit` The fitted values using each number of components.
- `nPLS` The total number of components extracted.

See Also

[WAPLS.w](#)

Examples

```

## Not run:
# Load modern pollen data
modern_pollen <- read.csv("/path/to/modern_pollen.csv")

# Extract taxa
taxaColMin <- which(colnames(modern_pollen) == "taxa0")
taxaColMax <- which(colnames(modern_pollen) == "taxaN")
taxa <- modern_pollen[, taxaColMin:taxaColMax]

```

```

# Load reconstruction data
Holocene <- read.csv("/path/to/Holocene.csv")
taxaColMin <- which(colnames(Holocene) == "taxa0")
taxaColMax <- which(colnames(Holocene) == "taxaN")
core <- Holocene[, taxaColMin:taxaColMax]

# MTCO
## Train
fit_Tmin <- fxTWAPLS::WAPLS.w(taxa, modern_pollen$Tmin, nPLS = 5)
fit_f_Tmin <- fxTWAPLS::WAPLS.w(taxa,
                                  modern_pollen$Tmin,
                                  nPLS = 5,
                                  usefx = TRUE,
                                  fx_method = "bin",
                                  bin = 0.02)
## Predict
fossil_Tmin <- fxTWAPLS::WAPLS.predict.w(fit_Tmin, core)
fossil_f_Tmin <- fxTWAPLS::WAPLS.predict.w(fit_f_Tmin, core)

## End(Not run)

```

WAPLS.w*WA-PLS training function***Description**

WA-PLS training function, which can perform fx correction. $1/fx^2$ correction will be applied at step 7.

Usage

```

WAPLS.w(
  modern_taxa,
  modern_climate,
  nPLS = 5,
  usefx = FALSE,
  fx_method = "bin",
  bin = NA
)

```

Arguments

- | | |
|-----------------------------|--|
| <code>modern_taxa</code> | The modern taxa abundance data, each row represents a sampling site, each column represents a taxon. |
| <code>modern_climate</code> | The modern climate value at each sampling site. |
| <code>nPLS</code> | The number of components to be extracted. |

usefx	Boolean flag on whether or not use fx correction.
fx_method	Binned or p-spline smoothed fx correction: if usefx = FALSE, this should be NA; otherwise, fx function will be used when choosing "bin"; fx_pspline function will be used when choosing "pspline".
bin	Binwidth to get fx, needed for both binned and p-splined method. if usefx = FALSE, this should be NA;

Value

A list of the training results, which will be used by the predict function. Each element in the list is described below:

- fit the fitted values using each number of components.
- x the observed modern climate values.
- taxon_name the name of each taxon.
- optimum the updated taxon optimum (u^* in the WA-PLS paper).
- comp each component extracted (will be used in step 7 regression).
- u taxon optimum for each component (step 2).
- z a parameter used in standardization for each component (step 5).
- s a parameter used in standardization for each component (step 5).
- orth a list that stores orthogonalization parameters (step 4).
- alpha a list that stores regression coefficients (step 7).
- meanx mean value of the observed modern climate values.
- nPLS the total number of components extracted.

See Also

[fx](#), [TWAPLS.w](#), and [WAPLS.predict.w](#)

Examples

```
## Not run:
# Load modern pollen data
modern_pollen <- read.csv("/path/to/modern_pollen.csv")

# Extract taxa
taxaColMin <- which(colnames(modern_pollen) == "taxa0")
taxaColMax <- which(colnames(modern_pollen) == "taxaN")
taxa <- modern_pollen[, taxaColMin:taxaColMax]

# MTCO
fit_Tmin <- fxTWAPLS::WAPLS.w(taxa, modern_pollen$Tmin, nPLS = 5)
fit_f_Tmin <- fxTWAPLS::WAPLS.w(taxa,
                                  modern_pollen$Tmin,
                                  nPLS = 5,
                                  usefx = TRUE,
                                  fx_method = "bin",
```

```
    bin = 0.02)

## End(Not run)
```

WAPLS.w2

WA-PLS training function v2

Description

WA-PLS training function, which can perform fx correction. 1/fx correction will be applied at step 2 and step 7.

Usage

```
WAPLS.w2(
  modern_taxa,
  modern_climate,
  nPLS = 5,
  usefx = FALSE,
  fx_method = "bin",
  bin = NA
)
```

Arguments

<code>modern_taxa</code>	The modern taxa abundance data, each row represents a sampling site, each column represents a taxon.
<code>modern_climate</code>	The modern climate value at each sampling site.
<code>nPLS</code>	The number of components to be extracted.
<code>usefx</code>	Boolean flag on whether or not use fx correction.
<code>fx_method</code>	Binned or p-spline smoothed fx correction: if <code>usefx</code> = FALSE, this should be NA; otherwise, <code>fx</code> function will be used when choosing "bin"; <code>fx_pspline</code> function will be used when choosing "pspline".
<code>bin</code>	Binwidth to get fx, needed for both binned and p-splined method. if <code>usefx</code> = FALSE, this should be NA;

Value

A list of the training results, which will be used by the predict function. Each element in the list is described below:

- `fit` the fitted values using each number of components.
- `x` the observed modern climate values.
- `taxon_name` the name of each taxon.

optimum the updated taxon optimum (u^* in the WA-PLS paper).
comp each component extracted (will be used in step 7 regression).
u taxon optimum for each component (step 2).
z a parameter used in standardization for each component (step 5).
s a parameter used in standardization for each component (step 5).
orth a list that stores orthogonalization parameters (step 4).
alpha a list that stores regression coefficients (step 7).
meanx mean value of the observed modern climate values.
nPPLS the total number of components extracted.

See Also

`fx`, `TWAPLS.w`, and `WAPLS.predict.w`

Examples

Index

base::condition, [11](#)
cv.pr.w, [2](#), [7](#), [8](#), [10](#), [14](#), [15](#)
cv.w, [5](#), [7](#), [8](#), [14](#), [15](#)
fx, [3](#), [5](#), [6](#), [7](#), [17](#), [21](#), [23](#), [26–28](#)
fx_pspline, [3](#), [5](#), [8](#), [17](#), [21](#), [23](#), [26](#), [27](#)
get_distance, [9](#), [10](#)
get_pseudo, [3](#), [9](#), [10](#)
pb, [11](#)
plot_residuals, [12](#)
plot_train, [13](#)
progressr::with_progress, [11](#)
rand.t.test.w, [14](#)
sse.sample, [7](#), [8](#), [16](#)
TWAPLS.predict.w, [3](#), [5](#), [6](#), [17](#), [19](#), [21](#), [23](#)
TWAPLS.w, [3](#), [5](#), [6](#), [12](#), [13](#), [17](#), [19](#), [20](#), [26](#), [28](#)
TWAPLS.w2, [22](#)
WAPLS.predict.w, [3](#), [5](#), [6](#), [17](#), [24](#), [26](#), [28](#)
WAPLS.w, [3](#), [5](#), [6](#), [12](#), [13](#), [17](#), [21](#), [23](#), [24](#), [25](#)
WAPLS.w2, [27](#)