

Package ‘gglm’

October 8, 2020

Type Package

Title Grammar of Graphics for Linear Model Diagnostic Plots

Version 0.1.0

Description

Allows for easy creation of diagnostic plots for linear models using the Grammar of Graphics. Provides functionality for both individual diagnostic plots and an array of four standard diagnostic plots.

License CC0

Encoding UTF-8

LazyData true

Imports ggplot2, patchwork, rlang

URL <https://github.com/graysonwhite/gglm>

BugReports <https://github.com/graysonwhite/gglm/issues>

RoxygenNote 7.1.0

NeedsCompilation no

Author Grayson White [cre, aut]

Maintainer Grayson White <graysonwhite13@gmail.com>

Repository CRAN

Date/Publication 2020-10-08 12:20:02 UTC

R topics documented:

gglm	2
stat_cooks_leverage	2
stat_cooks_obs	3
stat_fitted_resid	4
stat_normal_qq	4
stat_resid_hist	5
stat_resid_leverage	5
stat_scale_location	6
Index	8

*gglm**gglm*

Description

Provides four standard visual model diagnostic plots with ‘ggplot2’.

Usage

```
gglm(data, theme = ggplot2::theme_gray(), ...)
```

Arguments

<code>data</code>	A model object of type ‘lm’ or ‘glm’.
<code>theme</code>	The theme of the ‘ggplot’s to be produced.
<code>...</code>	Currently ignored. For extendability.

Value

A a ‘ggplot2’ object for visual diagnostic of model validity.

Examples

```
data(mtcars)
m1 <- lm(mpg ~ cyl + disp + hp, data = mtcars)
gglm(m1)
```

*stat_cooks_leverage**stat_cooks_leverage*

Description

Cook’s Distance vs. Leverage

Usage

```
stat_cooks_leverage(  
  alpha = 0.5,  
  method = "loess",  
  color = "steelblue",  
  se = FALSE,  
  ...  
)
```

Arguments

alpha	Adjust transparency of points.
method	Method for fitting the line to the points.
color	Color of the line.
se	Keep standard error bands around line?
...	Currently ignored. For extendability.

Value

A 'ggplot2' layer for plotting Cook's Distance vs. Leverage.

Examples

```
data(mtcars)
model <- lm(mpg ~ cyl + disp + hp, data = mtcars)
ggplot2::ggplot(data = model) + stat_cooks_leverage()
```

stat_cooks_obs	<i>stat_cooks_obs</i>
----------------	-----------------------

Description

'ggplot2' layer for plotting cook's distance by observation number.

Usage

```
stat_cooks_obs(...)
```

Arguments

... Currently ignored. For extendability.

Value

A 'ggplot2' layer for plotting cook's distance by observation number.

Examples

```
data(mtcars)
model <- lm(mpg ~ cyl + disp + hp, data = mtcars)
ggplot2::ggplot(data = model) + stat_cooks_obs()
```

stat_fitted_resid	<i>stat_fitted_resid</i>
-------------------	--------------------------

Description

‘ggplot2‘ layer for plotting a fitted vs. residual scatter plot.

Usage

```
stat_fitted_resid(alpha = 0.5, ...)
```

Arguments

alpha	Adjust transparency of points.
...	Currently ignored. For extendability.

Value

A ‘ggplot2‘ layer for plotting a fitted vs. residual scatter plot.

Examples

```
data(mtcars)
model <- lm(mpg ~ cyl + disp + hp, data = mtcars)
ggplot2::ggplot(data = model) + stat_fitted_resid()
```

stat_normal_qq	<i>stat_normal_qq</i>
----------------	-----------------------

Description

Normal QQ plot.

Usage

```
stat_normal_qq(alpha = 0.5, ...)
```

Arguments

alpha	Adjust transparency of points.
...	Currently ignored. For extendability.

Value

A ‘ggplot2‘ layer for plotting a Normal Q-Q plot.

Examples

```
data(mtcars)
model <- lm(mpg ~ cyl + disp + hp, data = mtcars)
ggplot2::ggplot(data = model) + stat_normal_qq()
```

stat_resid_hist *stat_resid_hist*

Description

Visualize the distribution of the residuals of a model.

Usage

```
stat_resid_hist(bins = 30, ...)
```

Arguments

bins	Adjust the number of bins.
...	Currently ignored. For extendability.

Value

A ‘ggplot2’ layer for plotting a histogram of residuals.

Examples

```
data(mtcars)
model <- lm(mpg ~ cyl + disp + hp, data = mtcars)
ggplot2::ggplot(data = model) + stat_resid_hist()
```

stat_resid_leverage *stat_resid_leverage*

Description

Residual vs. leverage plot.

Usage

```
stat_resid_leverage(
  alpha = 0.5,
  method = "loess",
  se = FALSE,
  color = "steelblue",
  ...
)
```

Arguments

alpha	Adjust transparency of points.
method	Method for fitting the line to the points.
se	Keep standard error bands around line?
color	Color of the line.
...	Currently ignored. For extendability.

Value

A 'ggplot2' layer for plotting a fitted vs. residual scatter plot.

Examples

```
data(mtcars)
model <- lm(mpg ~ cyl + disp + hp, data = mtcars)
ggplot2::ggplot(data = model) + stat_resid_leverage()
```

stat_scale_location *stat_scale_location*

Description

Scale location diagnostic plot.

Usage

```
stat_scale_location(
  alpha = 0.5,
  na.rm = TRUE,
  se = FALSE,
  method = "loess",
  color = "steelblue",
  ...
)
```

Arguments

alpha	Adjust the transparency of points.
na.rm	Remove points with value NA?
se	Keep standard error bands around line?
method	Method for fitting the line to the points.
color	Color of the line.
...	Currently ignored. For extendability.

Value

A 'ggplot2' layer for plotting the scale location diagnostic plot.

Examples

```
data(mtcars)
model <- lm(mpg ~ cyl + disp + hp, data = mtcars)
ggplot2::ggplot(data = model) + stat_scale_location()
```

Index

`ggglm`, 2

`stat_cooks_leverage`, 2

`stat_cooks_obs`, 3

`stat_fitted_resid`, 4

`stat_normal_qq`, 4

`stat_resid_hist`, 5

`stat_resid_leverage`, 5

`stat_scale_location`, 6