

Package ‘nextGenShinyApps’

July 21, 2022

Type Package

Title Advanced Tools for Building the Next Generation of 'Shiny'
Applications and Dashboards

Version 1.5

Author Obinna Obianom

Maintainer Obinna Obianom <idonshayo@gmail.com>

Description Responsive tools for designing and developing 'Shiny' dashboards and applications. The scripts and style sheets are based on 'jQuery' <<https://jquery.com/>> and 'Bootstrap' <<https://getbootstrap.com/>>.

License MIT + file LICENSE

URL <https://github.com/oobianom/nextGenShinyApps>

BugReports <https://github.com/oobianom/nextGenShinyApps>

Depends R (>= 3.4)

Imports utils, shiny, htmltools

Suggests rmarkdown, knitr, qpdf

Encoding UTF-8

VignetteBuilder knitr

Language en-US

LazyData false

RoxygenNote 7.1.1

NeedsCompilation no

Repository CRAN

Date/Publication 2022-07-21 12:00:02 UTC

R topics documented:

accordion	2
accordionItem	3
actionButton	4

alert	5
card	6
checkboxInput	8
cssjsinclude	9
dashboardBody	9
fluidPage	10
load.example	11
masterButton	12
modal.header	13
modalDialog	14
nav	16
rand.num	16
row	17
setup.toolbar.buttons	17
setup.toolbar.menu	18
sidebarLayout	18
sidebarPanel	19
sortablegrid	20
spinner	21
submitButton	22
tabPanel	23
tabsetPanel	24
template.loc	25
textAreaInput	26
textInput	27
titlePanel	29

Index **30**

accordion *Generate an accordion*

Description

Wrap one or more accordion items into a container

Usage

```
accordion(..., id, style = c("default", "1", "2", "3", "4"), uncollapsed = 1)
```

Arguments

...	The accordionItem elements to include within the body of the particular accordion
id	The identification of the accordion
style	Style of the accordion, use "default", "1", "2", "3", "4"
uncollapsed	Indicate by number which accordionItem should not be collapsed

Value

HTML of a container with a class called accordion

Examples

```
if (interactive()) {
  library(shiny)
  library(nextGenShinyApps)

  shiny::shinyApp(
    ui = fluidPage(
      style = "8",
      custom.bg.color = "white",
      sidebar = NULL,
      header = NULL,
      accordion(
        id = "accordion5",
        style = "2",
        accordionItem(
          title = "Accordion 1",
          icon = shiny::icon("edit"),
          "Massa sed elementum sus"
        ),
        accordionItem(
          title = "Accordion 2",
          icon = shiny::icon("cog"),
          "Auctor neque etiam non."
        )
      )
    ),
    server = function(input, output) {
    }
  )
}
```

accordionItem

Generate an accordion item

Description

Embed an accordion item within an accordion

Usage

```
accordionItem(
  ...,
```

```

  title = "A title",
  status = c("default", "primary", "secondary", "info", "success", "danger", "warning"),
  icon = NULL
)

```

Arguments

...	The elements to include within the body of the particular accordion
title	The title of the accordion item
status	Set the header background using either of "default", "primary", "secondary", "info", "success", "danger", "warning"
icon	Include an icon to the left of the title for the accordion item

Value

A list of properties for an accordion item

Examples

```

if (interactive()) {
  accordionItem(
    title = "Accordion 2",
    icon = shiny::icon("cog"),
    "Auctor neque etiam non."
  )
}

```

actionButton

Create a button

Description

Upgrade to the actionButton in 'Shiny' package

Usage

```

actionButton(
  inputId,
  label,
  icon = NULL,
  width = NULL,
  ...,
  size = c("m", "xs", "s", "l", "xl"),
  style = c("default", "pill", "round", "clean"),
  bg.type = c("default", "primary", "secondary", "info", "success", "danger",
    "warning"),
  outline = FALSE
)

```

Arguments

inputId	Input identification
label	Input label
icon	Choice of button icon
width	Width of the bottom
...	other elements or attributes for the button
size	Size of the button, choices include "m","xs", "s", "l", "xl"
style	Style of the button, choices include "default", "pill", "round", "clean"
bg.type	Color of the button, choices include "default", "primary", "secondary", "info", "success", "danger", "warning"
outline	Use an outline styling, TRUE or FALSE

Value

HTML of the buttons to insert into a page

Examples

```
if (interactive()) {
  shiny::div(actionButton("button",
    "Action button with primary color",
    icon = shiny::icon("folder"), bg.type = "primary"
  ))
  shiny::div(actionButton("button",
    "Action button with primary color",
    icon = shiny::icon("file"),
    bg.type = "danger", outline = TRUE
  ))
}
```

alert

Create an alert

Description

Create an alert with various styles

Usage

```
alert(
  ...,
  type = c("default", "standard"),
  close = FALSE,
  color = c("none", "primary", "secondary", "info", "success", "danger", "warning"),
  outline = FALSE,
  icon = NULL
)
```

Arguments

...	Content of the alert
type	Choose a style for the alert, choices include "default", "standard"
close	Allow alert to be closable, TRUE or FALSE
color	Color of the alert, choose between "none", "primary", "secondary", "info", "success", "danger", "warning"
outline	Include an outline and exclude background, TRUE or FALSE
icon	Include an icon to the left of the content

Value

HTML of an alert box to be inserted within a page

Examples

```
if (interactive()) {
  card(
    header = FALSE,
    shiny::h2("Standard alert (closeable)"),
    alert("EX1", type = "standard",
          color = "primary"),
    alert("EX2", type = "standard",
          color = "secondary"),
    alert("EX3", type = "standard",
          color = "secondary", outline = TRUE),
    alert("EX4", type = "standard",
          color = "danger", outline = TRUE, close = TRUE),
    alert("EX5", type = "standard",
          close = TRUE),
    alert("EX6", type = "standard",
          color = "primary", icon = shiny::icon("info"))
  )
}
```

card

Generate a flexible and extensible content container

Description

Widely used Bootstrap feature with improvements to allow collapse, minimize and closing

Usage

```

card(
  ...,
  title = "Standard Card",
  collapsed = FALSE,
  bg.fade = TRUE,
  width = 12,
  alert.text = NULL,
  alert.bg = c("primary", "warning", "secondary", "info", "success", "danger"),
  toolbar = NULL,
  header = TRUE,
  draggable = TRUE
)

```

Arguments

...	The elements to include within the body of the card
title	The text to display in the header title
collapsed	If TRUE, the card is collapsed. The default is FALSE
bg.fade	If TRUE, the background will be faded if a background exists
width	Select a width from 1 to 12 to indicate the size of the card
alert.text	Enter text for the alert portion. Leave as NULL to exclude the alert
alert.bg	Indicate the type of alert to include, choices are "primary", "warning", "secondary", "info", "success", "danger"
toolbar	The default is NULL, which means all toolbar will be displayed use this to set what toolbar to show.
header	If FALSE, the header will be excluded
draggable	If FALSE, the card will not be draggable

Value

HTML code of the container with a class called card that holds the items

Note

For more information on the features of the card, visit the examples section of the help documentation

Examples

```

if (interactive()) {
  card(
    title = "Standard card",
    collapsed = TRUE,
    alert.text = "An alert for the content",
    alert.bg = "warning",
    toolbar = list(collapse = TRUE,

```

```
    maximize = TRUE, close = FALSE, menu = TRUE),
    shiny::h3("Sample text"),
    "Lorem ipsum dolor sit a"
  )
}
```

checkboxInput

Create an advanced checkbox input

Description

Modifications to checkboxinput to allow added styles

Usage

```
checkboxInput(inputId, label, value = FALSE, width = NULL, inline = FALSE)
```

Arguments

inputId	The identification name
label	The label for the input
value	The current value of the input
width	width of the text input
inline	make inline or block format

Value

HTML elements of a checkbox

Note

For more information on the features of the form, visit the examples section of the help documentation

Examples

```
checkboxInput("somevalue", "Some value", FALSE)
checkboxInput("somevalue", "Some value", FALSE)
checkboxInput("somevalue", "Some value", FALSE)
```

cssjsinclude	<i>Include stylesheets and scripts</i>
--------------	--

Description

Use the package scripts and stylesheets in a page

Usage

```
cssjsinclude(template, color)
```

Arguments

template	The template type
color	The numeric style of template

Value

A list of files to be inserted in the header of a page

Examples

```
cssjsinclude('color', '1')
```

dashboardBody	<i>Create the body section of the application</i>
---------------	---

Description

Create a simple body containing a header and a content for the main body

Usage

```
dashboardBody(header, ...)
```

Arguments

header	OPTIONAL. Items to display in the header section (use the titlePanel() function to set this property).
...	The elements to include within the body of the modal

Value

An HTML of the body of the page

Note

Endeavor to use as standalone and not within the fluidPage, as this function it already called within fluidPage

Examples

```
if (interactive()) {
  dashboardBody(
    header = titlePanel(
      left = "Sample nextGenShinyApps Title",
      right = shiny::icon("user")
    ),
    "sample text for main body"
  )
}
```

fluidPage

Generate a container for the application

Description

An upgrade to the fluidPage function available in the 'Shiny' package

Usage

```
fluidPage(
  ...,
  id = NULL,
  header = NULL,
  sidebar = NULL,
  class = NULL,
  style = rand.sc13,
  custom.bg.color = NULL,
  modal.header.links = NULL
)
```

Arguments

...	The elements to include within the body of the page
id	OPTIONAL. Identification tag of the container
header	OPTIONAL. Items to display in the header section (use the titlePanel() function to set this property).
sidebar	OPTIONAL. Items to display in the sidebay section (use the sidebarPanel() function to set this property).
class	OPTIONAL. Class name for the container

style OPTIONAL. Various unique styles choices from 1 - 12
custom.bg.color OPTIONAL. Choice to change the background color of the container. Use HEX values such as #FFFFFF or RGB code such as rgb(255,255,255) or simple color name such as 'lightblue'
modal.header.links OPTIONAL. One or more list containing links that appear when the app title is clicked. To remove, set to NULL

Value

A rendered HTML of the container holder of the application items

Note

This global layout can be applied to a variety of shiny app and dashboard, with or without a sidebar. See the example below.

Examples

```

if (interactive()) {
  library(shiny)
  library(nextGenShinyApps)

  shiny::shinyApp(
    ui = fluidPage(
      style = "6",
      header = titlePanel(left = "Sample App Title",
        right = "Image/logo"),
      sidebar = sidebarPanel(
        title = "myApp",
        "Sample sidebar content"
      ),
      "Sample body content"
    ),
    server = function(input, output) {}
  )
}

```

load.example

Load examples for the package

Description

Example shiny applications spanning aspects of the package

Usage

```
load.example(  
  example = c("Plain", "noSideBar", "Card", "Tab", "Modal", "Form", "Button",  
    "Spinner", "Alert", "Accordion")  
)
```

Arguments

example choose the example to show - "Plain","noSideBar","Card","Tab","Modal","Form","Button","Spinner","Alert","Accordion"

Value

A rendered HTML of the user specified example file

Examples

```
if (interactive()) {  
  load.example(example = "Card")  
}
```

masterButton

Create a master button

Description

A master button creator

Usage

```
masterButton(  
  text = "Text",  
  icon = NULL,  
  width = NULL,  
  size = c("m", "xs", "s", "l", "xl"),  
  style = c("default", "pill", "round", "clean"),  
  bg.type = c("default", "primary", "secondary", "info", "success", "danger",  
    "warning"),  
  outline = FALSE,  
  extraClass = NULL,  
  ...  
)
```

Arguments

text	Button text
icon	Choice of button icon
width	Width of the bottom
size	Size of the button, choices include "m", "xs", "s", "l", "xl"
style	Style of the button, choices include "default", "pill", "round", "clean"
bg.type	Color of the button, choices include "default", "primary", "secondary", "info", "success", "danger", "warning"
outline	Use an outline styling, TRUE or FALSE
extraClass	other class names to add to the button attribute
...	Other elements to add to the button

Value

HTML of the buttons to insert into a page

Examples

```
if (interactive()) {
  card(
    shiny::h2("Master buttons with various styles"),
    header = FALSE,
    shiny::div(masterButton("Submit button with primary color",
      icon = shiny::icon("file"), size = "s", bg.type = "primary"
    ))
  )
}
```

modal.header	<i>Create hyperlink modal section that appears ONLY when the sidebar logo is clicked</i>
--------------	--

Description

Additional tab section for additional links

Usage

```
modal.header(...)
```

Arguments

... The list of tabs to include

Value

An HTML containing elements of links to be inserted in the header of a page

Examples

```
if (interactive()) {
  list1 <- list(
    title = "Home", icon = shiny::icon("home"),
    link = "https://google.com"
  )
  list2 <- list(
    title = "Docs", icon = shiny::icon("folder"),
    link = "https://obi.obianom.com"
  )

  modal.header(list(list1, list2))
}
```

 modalDialog

Generate a modal box

Description

Advanced modal dialog that allows various positioning and transparency

Usage

```
modalDialog(
  ...,
  title = NULL,
  footer = modalButton("Dismiss"),
  size = c("m", "s", "l", "xl"),
  easyClose = FALSE,
  fade = TRUE,
  position = c("centered", "left", "right", "top", "bottom"),
  transparent = FALSE
)
```

Arguments

...	The elements to include within the body of the modal
title	The text to display in the header title
footer	Footer list of buttons or text
size	The size of the modal, "m", "s", "l", "xl"
easyClose	Allow simple closing, FALSE or TRUE

fade	Allow fading away or fading in, FALSE or TRUE
position	Set the position of the modal. Choices include "centered", "left", "right", "top", "bottom"
transparent	Allow background transparency, FALSE or TRUE

Value

An HTML containing elements of a modal box that remains hidden until a button is clicked

Note

For more information on the features of the card, visit the examples section of the help documentation

Examples

```

if (interactive()) {
  library(shiny)
  library(nextGenShinyApps)
  shiny::shinyApp(
    ui = fluidPage(
      style = "8",
      custom.bg.color = "white",
      sidebar = NULL,
      header = NULL,
      shiny::h3("Modal EXAMPLES"),
      shiny::div(actionButton("obianom1", "Show BIG shiny modal on the RIGHT")),
      shiny::br(),
      shiny::div(actionButton("obianom2", "Show SMALL shiny modal on the RIGHT"))
    ),
    server = function(input, output) {
      shiny::observeEvent(input$obianom1, {
        shiny::showModal(modalDialog(
          textInput("dataset", "Enter a data set"),
          shiny::div("Id leo in vitae"),
          size = "1",
          position = "bottom",
        ))
      })
      shiny::observeEvent(input$obianom2, {
        shiny::showModal(modalDialog(
          textInput("dataset", "Enter a data set"),
          shiny::div("Lorem donec massa"),
          size = "1",
          position = "right",
        ))
      })
    }
  )
}

```

nav

Nav tag

Description

A nav tag for creating HTML navigations

Usage

```
nav(class, id = NULL, role = NULL, ...)
```

Arguments

class	The class of the navigation container
id	The identification of the navigation container
role	The character role of the container on the page
...	The content of the container

Value

HTML content of a container with type nav

Examples

```
nav('sample','id1','sample','some content')
```

rand.num

Random number between 1 and 10000

Description

One or more random numbers

Usage

```
rand.num(num)
```

Arguments

num	The number of numbers to return
-----	---------------------------------

Value

One or more numbers

Examples

```
rand.num(10)
```

row	<i>Generate a row div</i>
-----	---------------------------

Description

A simple row div

Usage

```
row(...)
```

Arguments

... The elements to include within the body of the row

Value

An HTML containing elements of a container with class row to be embedded in a page

Examples

```
row(shiny::div(width=12,"Hello nextGenShinyApps"))
```

setup.toolbar.buttons	<i>Generate toolbar buttons</i>
-----------------------	---------------------------------

Description

Use within a card to display toolbar

Usage

```
setup.toolbar.buttons(...)
```

Arguments

... The list of buttons to display

Value

HTML code of a container containing items to be inserted in the toolbar

Note

For more information on the features of a toolbar within a card, visit the examples section of the help documentation

Examples

```
setup.toolbar.buttons(list(maximize=TRUE, collapse=TRUE, close=TRUE))
```

```
setup.toolbar.menu      Generate toolbar menu
```

Description

Use within a card to display menu

Usage

```
setup.toolbar.menu(...)
```

Arguments

... The list declaring whether to show menu

Value

HTML code of a container containing menu to be inserted in the toolbar if declared TRUE

Note

For more information on the features of a toolbar within a card, visit the examples section of the help documentation

Examples

```
setup.toolbar.menu(list(menu=TRUE))
```

```
sidebarLayout            Sidebar layout
```

Description

Container for sidebar, optional

Usage

```
sidebarLayout(...)
```

Arguments

... content of the sidebar layout

Value

An HTML containing elements in a container

Examples

```
sidebarLayout("sample text")
```

sidebarPanel	<i>Create the sidebar panel</i>
--------------	---------------------------------

Description

Creates an advanced sidebar panel with colors corresponding to a chosen theme style

Usage

```
sidebarPanel(..., title = "TitleApp", footer = FALSE)
```

Arguments

... The elements to include within the body of the sidebar
 title Title of the sidebar content
 footer Whether or not to enable the footer content

Value

An HTML containing elements of a sidebar to be embedded in a page

Note

This global layout can be applied to a variety of shiny app and dashboard, with or without a sidebar. See the example below.

Examples

```
if (interactive()) {
  library(shiny)
  library(nextGenShinyApps)

  shiny::shinyApp(
    ui = fluidPage(
      style = "7",
      header = NULL,
```

```
        sidebar = sidebarPanel(  
          title = "myApp",  
          "Sample sidebar contents",  
          footer = FALSE  
        ),  
        "Plain content"  
      ),  
      server = function(input, output) {}  
    )  
  }
```

sortablegrid

Generate a sortable grid

Description

A grid that holds draggable items

Usage

```
sortablegrid(..., width = 6)
```

Arguments

...	The elements to include within the body of the grid
width	The width of the grid

Value

HTML code of a container that allows items within it to be draggable

Note

For more information on the features of a sortable grid, visit the examples section of the help documentation

Examples

```
sortablegrid("item1",width=12)
```

spinner	<i>Create a spinner</i>
---------	-------------------------

Description

Create a loading spinner for customization of outputs

Usage

```
spinner(  
  type = c("ring", "grow", "square", "rect"),  
  size = c("l", "s"),  
  color = c("default", "primary", "secondary", "info", "success", "danger", "warning")  
)
```

Arguments

type	Choose a style for the spinner using "ring","grow","square","rect"
size	Size of the spinner, "l" for large and "s" for small
color	Color of the spinner, choose between "default", "primary", "secondary", "info", "success", "danger", "warning"

Value

An HTML containing elements of a spinner to be embedded in a page during loading

Examples

```
if (interactive()) {  
  library(shiny)  
  library(nextGenShinyApps)  
  
  shiny::shinyApp(  
    ui = fluidPage(  
      style = "3",  
      custom.bg.color = "cyan",  
      sidebar = NULL,  
      header = NULL,  
      card(  
        header = FALSE,  
        shiny::h2("loading spinner"),  
        spinner(type = "rect", size = "s"),  
        spinner(type = "rect", color = "primary"),  
        spinner(type = "grow", color = "secondary"),  
        spinner(type = "ring", color = "success"),  
        spinner(type = "rect", color = "warning"),  
        spinner(type = "square", color = "danger"),
```

```

        spinner(type = "rect", color = "info")
      )
    },
    server = function(input, output) {
    }
  )
}

```

 submitButton

Create a submit button

Description

Upgrade to the submitButton in 'Shiny' package

Usage

```

submitButton(
  text = "Apply Changes",
  icon = NULL,
  width = NULL,
  size = c("m", "xs", "s", "l", "xl"),
  style = c("default", "pill", "round", "clean"),
  bg.type = c("default", "primary", "secondary", "info", "success", "danger",
             "warning"),
  outline = FALSE
)

```

Arguments

text	Button text
icon	Choice of button icon
width	Width of the bottom
size	Size of the button, choices include "m","xs", "s", "l", "xl"
style	Style of the button, choices include "default", "pill", "round", "clean"
bg.type	Color of the button, choices include "default", "primary", "secondary", "info", "success", "danger", "warning"
outline	Use an outline styling, TRUE or FALSE

Value

HTML of the submit buttons to insert into a page

Examples

```
if (interactive()) {
  card(
    shiny::h2("Submit buttons with various styles"),
    header = FALSE,
    shiny::div(submitButton("Submit button with primary color",
      icon = shiny::icon("file"), size = "s", bg.type = "primary"
    )),
    shiny::div(submitButton("Secondary color",
      icon = shiny::icon("folder"), bg.type = "secondary"
    )),
    shiny::div(submitButton("Success color",
      icon = shiny::icon("filter"), bg.type = "success"
    )),
    shiny::div(submitButton("Warning color",
      icon = shiny::icon("grid"), bg.type = "warning"
    )),
    shiny::div(submitButton("Danger color",
      icon = shiny::icon("check"), bg.type = "danger"
    )),
    shiny::div(submitButton("Info color",
      icon = shiny::icon("trash"), bg.type = "info"
    ))
  )
}
```

tabPanel

Create a tab panel item

Description

Create a tab panel item that is enclosed by a `tabsetPanel`

Usage

```
tabPanel(title, ...)
```

Arguments

<code>title</code>	title of the tab
<code>...</code>	content of the tab

Value

An list containing the title and content of a tab

Examples

```

if (interactive()) {
  tabPanel("Summary", "Convallis aesus.")
  tabPanel("Summary", "nextGenShinyAppss.")
}

```

tabsetPanel

Create an advanced tabset

Description

Advanced tabset panel with styles and functionalities

Usage

```

tabsetPanel(
  ...,
  type = c("default", "pills", "clean", "jPills", "justified"),
  border = TRUE,
  justified = FALSE,
  position = c("left", "end", "center")
)

```

Arguments

...	Content of the tabset, created using the tabPanel for each individual item
type	Type of tabset to create, choices include "default", "pills", "clean", "jPills", "justified"
border	Include a board for the tabset, TRUE or FALSE
justified	Justify tab headers, TRUE or FALSE
position	position of the tabs, choices include "left", "end", "center"

Value

An HTML containing elements of a tabset to be embedded in a page

Note

Many examples exist for the tabset, fid them using the package load.example function

Examples

```
if (interactive()) {
  library(shiny)
  library(nextGenShinyApps)
  tab2 <- tabPanel("Summary", "SAMPLE nunc.")
  tab3 <- tabPanel("Tab 3", "aoreet sit amet.")
  tab4 <- tabPanel("Tab 4", "Vulputate pulvinar")

  shiny::shinyApp(
    ui = fluidPage(
      style = "8",
      custom.bg.color = "rgb(110,134,032)",
      sidebar = NULL,
      header = NULL,
      tabsetPanel(
        tab2,
        tab3,
        type = "pills",
        justified = TRUE
      )
    ),
    server = function(input, output) {
    }
  )
}
```

template.loc

Template location full text

Description

Fetch the location of the scripts

Usage

```
template.loc(template = "core")
```

Arguments

template The type of template to fetch

Value

A path for the location of the package

Examples

```
template.loc('core')
```

 textAreaInput

Create an advanced text area input

Description

Modifications to 'textAreaInput' to allow added styles

Usage

```
textAreaInput(
  inputId,
  label,
  value = "",
  width = NULL,
  height = NULL,
  cols = NULL,
  rows = NULL,
  placeholder = NULL,
  resize = c("both", "none", "vertical", "horizontal"),
  style = c("default", "pill", "round", "clean"),
  border.type = c("none", "primary", "info", "success", "danger", "warning")
)
```

Arguments

inputId	The identification name
label	The label for the input
value	The current value of the input
width	width of the text input
height	height of the text input
cols	col of text to display
rows	row of text to display
placeholder	A placeholder text
resize	Make inout resizable, with choices "both", "none", "vertical", "horizontal"
style	Style to adapt, options include "default", "pill", "round", "clean"
border.type	Add a border coloring using either of "none", "primary", "info", "success", "danger", "warning"

Value

HTML element of a textAreaInput

Note

For more information on the features of the form, visit the examples section of the help documentation

Examples

```
textInput("caption",
  "Sample Text area input",
  "Data Summary",
  width = "1000px", border.type = "success"
)
```

textInput

Create an advanced text input

Description

Modifications to textInput to allow added functionality and styles

Usage

```
textInput(
  inputId,
  label,
  value = "",
  width = NULL,
  placeholder = NULL,
  size = c("m", "s", "l", "xl"),
  style = c("default", "pill", "round", "clean"),
  border.type = c("none", "primary", "info", "success", "danger", "warning"),
  prepend = NULL,
  append = NULL
)
```

Arguments

inputId	The identification name
label	The label for the input
value	The current value of the input
width	width of the text input
placeholder	A placeholder text
size	The size of the input, "m", "s", "l", "xl"
style	Style to adapt, options include "default", "pill", "round", "clean"

<code>border.type</code>	Add a border coloring using either of "none", "primary", "info", "success", "danger", "warning"
<code>prepend</code>	Add a prepended text or icon
<code>append</code>	Add an appended text or icon

Value

A HTML with modifications to the style information

Note

For more information on the features of the form, visit the examples section of the help documentation

Examples

```
if (interactive()) {
  library(shiny)
  library(nextGenShinyApps)

  shiny::shinyApp(
    ui = fluidPage(
      style = "8",
      custom.bg.color = "white",
      sidebar = NULL,
      header = NULL,
      card(
        header = FALSE,
        tags$h3("Text input"),
        textInput("caption", "Basic"),
        textInput("caption", "Basic", style = "clean"),
        textInput("caption", "Border - primary",
          "Enter sample text",
          prepend = "@", border.type = "info"
        ),
        textInput("caption", "Border - primary",
          "Enter sample text",
          prepend = shiny::icon("lock")
        ),
        textInput("caption", "Border - primary",
          "Enter sample text",
          append = "%"
        ),
        textInput("caption", "Border - primary",
          "Enter sample text",
          prepend = shiny::icon("chart"),
          append = ".00"
        )
      )
    ),
    server = function(input, output) {
```

```
    }  
  )  
}
```

titlePanel

Title panel for the header of the application

Description

Used to embed the header within the body of the application

Usage

```
titlePanel(left = "Sample Title", right = NULL, link = "#")
```

Arguments

left	The title text for the header
right	Content to include on the top right corner
link	Hyperlink to navigate when clicked

Value

An HTML containing elements to insert in a title

Examples

```
if (interactive()) {  
  titlePanel(  
    left = "Sample App Title",  
    right = shiny::div("Image/logo", shiny::icon("trash"))  
  )  
}
```

Index

[accordion](#), 2
[accordionItem](#), 3
[actionButton](#), 4
[alert](#), 5

[card](#), 6
[checkboxInput](#), 8
[cssjsinclude](#), 9

[dashboardBody](#), 9

[fluidPage](#), 10

[load.example](#), 11

[masterButton](#), 12
[modal.header](#), 13
[modalDialog](#), 14

[nav](#), 16

[rand.num](#), 16
[row](#), 17

[setup.toolbar.buttons](#), 17
[setup.toolbar.menu](#), 18
[sidebarLayout](#), 18
[sidebarPanel](#), 19
[sortablegrid](#), 20
[spinner](#), 21
[submitButton](#), 22

[tabPanel](#), 23
[tabsetPanel](#), 24
[template.loc](#), 25
[textAreaInput](#), 26
[textInput](#), 27
[titlePanel](#), 29