

Package ‘nlmeVPC’

September 7, 2022

Title Visual Model Checking for Nonlinear Mixed Effect Model

Version 2.3

Date 2022-09-07

Description Various visual and numerical diagnosis methods for the nonlinear mixed effect model, including visual predictive checks, numerical predictive checks, and coverage plot (Karls-son and Holford, 2008, <<https://www.page-meeting.org/?abstract=1434>>).

Depends R (>= 3.5.0),Hmisc

Imports quantreg, optimx, ggplot2, Rcpp, timeDate

Suggests testit

LinkingTo Rcpp, RcppArmadillo

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.2.1

NeedsCompilation yes

Author Eun-Kyung Lee [aut, cre],
Eun-Hwa Kang [aut]

Maintainer Eun-Kyung Lee <lee.eunk@gmail.com>

Repository CRAN

Date/Publication 2022-09-07 07:50:05 UTC

R topics documented:

aqrVPC	2
asVPC	3
bootVPC	5
coverageDetailplot	7
coverageplot	8
FindBestCut	10
findQuantile	11
findSIMQ	11
findSIMQuantile	12

makeCOVbin	13
NumericalCheck	14
optK	16
origdata	17
quantVPC	17
simdata	19
VPCgraph	19

Index	22
--------------	-----------

aqrVPC	<i>The visual predictive checks using the additive quantile regression (aqrVPC)</i>
--------	---

Description

This function draws the visual predictive check (VPC) plot using additive quantile regression. The quantile regression methods are used to calculate quantiles.

Usage

```
aqrVPC(orig_data,
        sim_data,
        probs = c(0.1,0.5,0.9),
        conf.level = 0.95,
        X_name = "TIME",
        Y_name = "DV",
        MissingDV = NULL,
        plot_caption = TRUE,
        DV_point = TRUE,
        plot_flag = TRUE,
        linesize = 0.7,
        pointsize = 0.7,
        captionsize = 10,
        qss_lambda = NULL, ...)
```

Arguments

orig_data	A data frame of original data with X and Y variable.
sim_data	A matrix of simulated data with only Y values collected.
probs	A numeric vector of probabilities.
conf.level	Confidence level of the interval.
X_name	Name of X variable in orig_data (usually "TIME" in pharmacokinetic data).
Y_name	Name of Y variable in orig_data (usually "DV" in pharmacokinetic data).
MissingDV	Name of missing indicator variable in orig_data, which have value 1 if missing, value 0 otherwise. (usually "MDV" in pharmacokinetic data).

plot_caption	Put caption with additional information if TRUE; omit if FALSE.
DV_point	Draw point (X, Y) in the plot if TRUE; omit if FALSE.
plot_flag	Draw plot if TRUE; generate data for drawing plot if FALSE.
linesize	Size of line in the plot.
pointsize	Size of point in the plot.
captionsize	Size of caption.
qss_lambda	Smoothing parameter in <code>quantreg::qss</code> function. Larger lambda produces a smoother fit.
...	Arguments to be passed to methods.

Value

aqrVPC plot or the values to draw aqrVPC plot.

References

Koenker, Roger, and Kevin F. Hallock. "Quantile regression." *Journal of economic perspectives* 15.4 (2001): 143-156.

Jansen, K. M., Patel, K., Nieforth, K., & Kirkpatrick, C. M. (2018). A regression approach to visual predictive checks for population pharmacometric models. *CPT: pharmacometrics & systems pharmacology*, 7(10), 678-686.

Examples

```
data(origdata)
data(simdata)
aqrVPC(origdata, simdata)
```

asVPC

the average shifted visual predictive checks (asVPC)

Description

This function draws the average shifted visual predictive check (asVPC) plot. It calculates percentiles of original data and simulated data using bin-related weights. Draw the VPC type plot.

Usage

```
asVPC(orig_data,
      sim_data,
      type = "CI",
      weight_method = "bin",
      N_xbin = NULL,
      N_hist = NULL,
```

```

probs = c(0.1,0.5,0.9),
conf.level = 0.95,
X_name = "TIME",
Y_name = "DV",
MissingDV = NULL,
DV_point = TRUE,
CIvpc_type = "line",
bin_grid = TRUE,
plot_caption = TRUE,
plot_flag = TRUE,
linesize = 0.7,
pointsize = 0.7,
captionsize = 10,
Kmethod = "cluster",
maxK = NULL,
beta = 0.2,
lambda = 0.3,
R = 4,
C1 = 2.5,
C2 = 7.8,...)

```

Arguments

<code>orig_data</code>	A data frame of original data with X and Y variable.
<code>sim_data</code>	A matrix of simulated data with only Y values collected.
<code>type</code>	Type of VPC graph; "CI", "percentile", or "scatter".
<code>weight_method</code>	The way to put weight when the average shifted values are calculated. "bin" or "distance".
<code>N_xbin</code>	Number of bins in X variable. If NULL, optimal number of bins are automatically calculated using <code>optK</code> function.
<code>N_hist</code>	The number of shifted histograms.
<code>probs</code>	A numeric vector of probabilities.
<code>conf.level</code>	Confidence level of the interval.
<code>X_name</code>	Name of X variable in <code>orig_data</code> (usually "TIME" in pharmacokinetic data).
<code>Y_name</code>	Name of Y variable in <code>orig_data</code> (usually "DV" in pharmacokinetic data).
<code>MissingDV</code>	Name of missing indicator variable in <code>orig_data</code> , which have value 1 if missing, value 0 otherwise. (usually "MDV" in pharmacokinetic data).
<code>DV_point</code>	Draw point (X, Y) in the plot if TRUE; omit if FALSE.
<code>CIvpc_type</code>	Type of CI area in VPC graph; "line" or "segment".
<code>bin_grid</code>	Draw grid lines for binning in X variable if TRUE; omit if FALSE.
<code>plot_caption</code>	Put caption with additional information if TRUE; omit if FALSE.
<code>plot_flag</code>	Draw plot if TRUE; generate data for drawing plot if FALSE.
<code>linesize</code>	Size of line in the plot.
<code>pointsize</code>	Size of point in the plot.

captionsize	Size of caption.
Kmethod	The way to calculate the penalty in automatic binning. "cluster" or "kernel".
maxK	The maximum number of bins.
beta	Additional parameter for automatic binning, used in optK function.
lambda	Additional parameter for automatic binning, used in optK function.
R	Additional parameter for automatic binning, used in optK function.
C1	Additional parameter for automatic binning, used in optK function.
C2	Additional parameter for automatic binning, used in optK function.
...	Arguments to be passed to methods.

Value

asVPC plot or the values to draw asVPC plot.

Examples

```
data(origdata)
data(simdata)
asVPC(origdata, simdata, type="CI", N_hist=3, weight_method="distance", N_xbin=8)
asVPC(origdata, simdata, type="CI", N_hist=3, weight_method="bin", N_xbin=8)
```

bootVPC

the bootstrap visual predicrive checks.

Description

This function draws the visual predictive check plot with bootstrapped data. It compares the distribution of quantiles obtained from the bootstrapped data to the distribution of quantiles from simulated data drawn from the fitted model.

Usage

```
bootVPC(orig_data,
        sim_data,
        B = 1000,
        N_xbin = NULL,
        conf.level = 0.95,
        X_name = "TIME",
        Y_name = "DV",
        subject_name = "ID",
        MissingDV = NULL,
        DV_point = TRUE,
```

```

plot_caption = TRUE,
plot_flag = TRUE,
linesize = 0.7,
pointsize = 0.7,
Kmethod = "cluster",
maxK = NULL,
beta = 0.2,
lambda = 0.3,
R = 4,
C1 = 2.5,
C2 = 7.8, ...)

```

Arguments

<code>orig_data</code>	A data frame of original data with X and Y variable.
<code>sim_data</code>	A matrix of simulated data with only Y values collected.
<code>B</code>	Number of bootstrap samples.
<code>N_xbin</code>	Number of bins in X variable. If NULL, optimal number of bins are automatically calculated using <code>optK</code> function.
<code>conf.level</code>	Confidence level of the interval.
<code>X_name</code>	Name of X variable in <code>orig_data</code> (usually "TIME" in pharmacokinetic data).
<code>Y_name</code>	Name of Y variable in <code>orig_data</code> (usually "DV" in pharmacokinetic data).
<code>subject_name</code>	Name of subject variable in <code>orig_data</code> (usually "ID" in pharmacokinetic data).
<code>MissingDV</code>	Name of missing indicator variable in <code>orig_data</code> , which have value 1 if missing, value 0 otherwise. (usually "MDV" in pharmacokinetic data).
<code>DV_point</code>	Draw point (X, Y) in the plot if TRUE; omit if FALSE.
<code>plot_caption</code>	Put caption with additional information if TRUE; omit if FALSE.
<code>plot_flag</code>	Draw plot if TRUE; generate data for drawing plot if FALSE.
<code>linesize</code>	Size of line in the plot.
<code>pointsize</code>	Size of point in the plot.
<code>Kmethod</code>	The way to calculate the penalty in automatic binning. "cluster" or "kernel".
<code>maxK</code>	The maximum number of bins.
<code>beta</code>	Additional parameter for automatic binning, used in <code>optK</code> function.
<code>lambda</code>	Additional parameter for automatic binning, used in <code>optK</code> function.
<code>R</code>	Additional parameter for automatic binning, used in <code>optK</code> function.
<code>C1</code>	Additional parameter for automatic binning, used in <code>optK</code> function.
<code>C2</code>	Additional parameter for automatic binning, used in <code>optK</code> function.
<code>...</code>	Arguments to be passed to methods.

Value

bootVPC plot or the values to draw bootVPC plot.

References

Post, T. M., et al. (2008) Extensions to the visual predictive check for facilitate model performance evaluation, Journal of pharmacokinetics and pharmacodynamics, 35(2), 185-202

Examples

```
data(origdata)
data(simdata)
bootVPC(origdata,simdata,N_xbin=8)
```

coverageDetailplot *draw the detailed coverage plot*

Description

This function draws the detailed coverage plot for the specific prediction level to check over or under estimate regions in each prediction level.

Usage

```
coverageDetailplot(orig_data,
                   sim_data,
                   N_xbin = NULL,
                   predL = 0.5,
                   conf.level = 0.95,
                   X_name = "TIME",
                   Y_name = "DV",
                   MissingDV = NULL,
                   Kmethod = "cluster",
                   maxK = NULL,
                   beta = 0.2,
                   lambda = 0.3,
                   R = 4,
                   C1 = 2.5,
                   C2 = 7.8, ...)
```

Arguments

orig_data	A data frame of original data with X and Y variable.
sim_data	A matrix of simulated data with only Y values collected.
N_xbin	Number of bins in X variable. If NULL, optimal number of bins are automatically calculated using optK function.
predL	Scalar of probability
conf.level	Confidence level of the interval.

X_name	Name of X variable in orig_data (usually "TIME" in pharmacokinetic data).
Y_name	Name of Y variable in orig_data (usually "DV" in pharmacokinetic data)
MissingDV	Name of missing indicator variable in orig_data, which have value 1 if missing, value 0 otherwise. (usually "MDV" in pharmacokinetic data).
Kmethod	The way to calculate the penalty in automatic binning."cluster" or "kernel".
maxK	The maximum number of bins
beta	Additional parameter for automatic binning, used in optK function.
lambda	Additional parameter for automatic binning, used in optK function.
R	Additional parameter for automatic binning, used in optK function.
C1	Additional parameter for automatic binning, used in optK function.
C2	Additional parameter for automatic binning, used in optK function.
...	Arguments to be passed to methods.

Value

the detailed coverage plot

References

Post, T. M., et al. (2008) Extensions to the visual predictive check for facilitate model performance evaluation, *Journal of pharmacokinetics and pharmacodynamics*, 35(2), 185-202

Examples

```
data(origdata)
data(simdata)
coverageDetailplot(origdata,simdata,predL=0.5,N_xbin=8)
```

coverageplot

coverage plot

Description

Draw the coverage plot that visualizes the result of the numerical predictive checks.

Usage

```
coverageplot(orig_data,
             sim_data,
             N_xbin = NULL,
             pred.level = c(0,0.1,0.2,0.3,0.4,0.5,0.6,0.7,0.8,0.9),
             conf.level = 0.95,
             X_name = "TIME",
```



```

Y_name = "DV",
MissingDV = NULL,
plot_flag = TRUE,
linesize = 0.7,
pointsize = 1.5,
Kmethod = "cluster",
maxK = NULL,
beta = 0.2,
lambda = 0.3,
R = 4,
C1 = 2.5,
C2 = 7.8, ...)

```

Arguments

orig_data	A data frame of original data with X and Y variable.
sim_data	A matrix of simulated data with only Y values collected.
N_xbin	Number of bins in X variable. If NULL, optimal number of bins are automatically calculated using optK function.
pred.level	Numeric vector of probabilities.
conf.level	Confidence level of the interval.
X_name	Name of X variable in orig_data (usually "TIME" in pharmacokinetic data).
Y_name	Name of Y variable in orig_data (usually "DV" in pharmacokinetic data).
MissingDV	Name of missing indicator variable in orig_data, which have value 1 if missing, value 0 otherwise. (usually "MDV" in pharmacokinetic data).
plot_flag	Draw plot if TRUE; generate data for drawing plot if FALSE.
linesize	Size of line in the plot.
pointsize	Size of point in the plot.
Kmethod	The way to calculate the penalty in automatic binning."cluster" or "kernel".
maxK	The maximum number of bins.
beta	Additional parameter for automatic binning, used in optK function.
lambda	Additional parameter for automatic binning, used in optK function.
R	Additional parameter for automatic binning, used in optK function.
C1	Additional parameter for automatic binning, used in optK function.
C2	Additional parameter for automatic binning, used in optK function.
...	arguments to be passed to methods

Value

coverage plot

References

Holford N, & Karlsson M. (2008). "A tutorial on visual predictive checks, abstr 1434." Annual Meeting of the Populations Approach Group in Europe. www.page-meeting.org. 2008.

Examples

```
data(origdata)
data(simdata)
coverageplot(origdata,simdata,N_xbin=8)
```

FindBestCut

Find the best cutoff values of binning for the visual predictive checks.

Description

Find the best cutoff values for a given number of bins by various rules.

Usage

```
FindBestCut(X,
            K,
            beta = 0.2, ...)
```

Arguments

X	A numeric vector to divide into K bins.
K	Number of bins.
beta	Additional parameter in the penalty. For more detailed explanation, see reference.
...	Arguments to be passed to methods.

Value

The best cutoff values to make K bins using X and the minimum within sums of square values for the binning

References

Lavielle, M. and Bleakley, K. (2011). Automatic data binning for improved visual diagnosis of pharmacometric models. *Journal of pharmacokinetics and pharmacodynamics*, 38(6), 861-871.
VPC automatic binning algorithm in PsN 5.0.0 manual.

Examples

```
data(origdata)
FindBestCut(origdata$TIME,K=10)
```

findQuantile	<i>Find quantiles of the original data.</i>
--------------	---

Description

Find quantiles of the original data.

Usage

```
findQuantile(Y,
             X,
             X_bin,
             probs=c(0.1,0.5,0.9),...)
```

Arguments

Y	A numeric vector whose sample quantiles are wanted.
X	A numeric vector corresponding to Y.
X_bin	Binning result from makeCOVbin function.
probs	A numeric vector of probabilities.
...	Arguments to be passed to methods.

Value

quantiles of Y using X_bin

Examples

```
data(origdata)
CUT = FindBestCut(origdata$TIME,8)$cutoffs
time_bin = makeCOVbin(origdata$TIME,K=8,cutoffs = CUT)
findQuantile(origdata$DV,origdata$TIME,X_bin=time_bin)
```

findSIMQ	<i>find quantiles of the simulated data using Rcpp</i>
----------	--

Description

find quantiles of the simulated data using Rcpp

Usage

```
findSIMQ(SIM,
         X,
         Xbin,
         probs,
         confLevel,
         approx)
```

Arguments

SIM	A matrix of simulated data with only Y values collected.
X	A numeric vector corresponding to Y
Xbin	Binning result from makeCOVbin function
probs	A numeric vector of probabilities
confLevel	Confidence level of the interval.
approx	Arguments to be passed to methods

Value

quantiles of SIM using xbin

Examples

```
data(origdata)
data(simdata)
CUT = FindBestCut(origdata$TIME,8)$cutoffs
time_bin = makeCOVbin(origdata$TIME,K=8,cutoffs = CUT)
findSIMQ(simdata,origdata$TIME,Xbin=time_bin,probs=c(0.1,0.5,0.9),
confLevel=0.95,approx=FALSE)
```

findSIMQuantile	<i>Find quantiles of the simulated data.</i>
-----------------	--

Description

Find quantiles of the simulated data.

Usage

```
findSIMQuantile(sim_data,
                X,
                X_bin,
                probs = c(0.1,0.5,0.9),
                conf.level = 0.95,
                approx = FALSE, ...)
```

Arguments

sim_data	A matrix of simulated data with only Y values collected.
X	A numeric vector corresponding to Y.
X_bin	Binning result from makeCOVbin function.
probs	A numeric vector of probabilities.
conf.level	Confidence level of the interval.
approx	Arguments to be passed to methods
...	Arguments to be passed to methods

Value

quantiles of sim_data using X_bin

Examples

```
data(origdata)
data(simdata)
CUT = FindBestCut(origdata$TIME,8)$cutoffs
time_bin = makeCOVbin(origdata$TIME,K=8,cutoffs = CUT)
findSIMQuantile(simdata,origdata$TIME,X_bin=time_bin)
```

makeCOVbin	<i>Discretise numeric data into categorical variable</i>
------------	--

Description

Discretise numeric value into a categorical variable using the user-defined breaks. If cutoffs and the number of bins (K) are NULL, find the best number of bins using optK function and find the best cutoff values using FindBestCut function.

Usage

```
makeCOVbin(X,
           K,
           cutoffs,
           adjust0bin = TRUE, ...)
```

Arguments

X	A numeric vector corresponding to Y.
K	Number of bins.
cutoffs	A numeric vector of two or more unique cut points.
adjust0bin	Adjust bin with 0 observation if TRUE.
...	Arguments to be passed to methods.

Value

The result of binning and the summary of the binning results

References

Lavielle, M. and Bleakley, K. (2011). Automatic data binning for improved visual diagnosis of pharmacometric models. *Journal of pharmacokinetics and pharmacodynamics*, 38(6), 861-871.

Examples

```
data(origdata)
CUT = FindBestCut(origdata$TIME,8)$cutoffs
makeCOVbin(origdata$TIME,K=8,cutoffs=CUT)
```

NumericalCheck

The numerical predictive checks

Description

This function calculates the numerical predictive checks for each prediction level. For a given level of prediction, the predicted interval is calculated using the simulated data, and the number of observed data below the predicted interval is counted. The expected number of points below the predicted interval is also calculated and compared to the observed number.

Usage

```
NumericalCheck(orig_data,
               sim_data,
               N_xbin = NULL,
               pred.level = c(0,0.1,0.2,0.3,0.4,0.5,0.6,0.7,0.8,0.9),
               conf.level = 0.95,
               X_name = "TIME",
               Y_name = "DV",
               MissingDV = NULL,
               Kmethod = "cluster",
               maxK = NULL,
               beta = 0.2,
               lambda = 0.3,
               R = 4,
               C1 = 2.5,
               C2 = 7.8, ...)
```

Arguments

orig_data	A data frame of original data with X and Y variable.
sim_data	A matrix of simulated data with only Y values collected.

N_xbin	Number of bins in X variable. If NULL, optimal number of bins are automatically calculated using optK function.
pred.level	Numeric vector of probabilities.
conf.level	Confidence level of the interval.
X_name	Name of X variable in orig_data (usually "TIME" in pharmacokinetic data).
Y_name	Name of Y variable in orig_data (usually "DV" in pharmacokinetic data).
MissingDV	Name of missing indicator variable in orig_data, which have value 1 if missing, value 0 otherwise. (usually "MDV" in pharmacokinetic data).
Kmethod	The way to calculate the penalty in automatic binning. "cluster" or "kernel".
maxK	The maximum number of bins.
beta	Additional parameter for automatic binning, used in optK function.
lambda	Additional parameter for automatic binning, used in optK function.
R	Additional parameter for automatic binning, used in optK function.
C1	Additional parameter for automatic binning, used in optK function.
C2	Additional parameter for automatic binning, used in optK function.
...	Arguments to be passed to methods.

Value

The result of numerical predictive check

References

Holford N, & Karlsson M. (2008). "A tutorial on visual predictive checks, abstr 1434." Annual Meeting of the Populations Approach Group in Europe. www.page-meeting.org. 2008.

Harling, Uekert, K. 2018. VPC and NPC User Guide. ICON plc.

https://github.com/UUPharmacometrics/PsN/releases/download/4.9.0/vpc_npc_userguide.pdf.

Examples

```
data(origdata)
data(simdata)
NumericalCheck(origdata,simdata,N_xbin=8)$NPC
```

`optK`*Find the optimal number of bins*

Description

This function automatically finds the optimal number of bins using dynamic programming.

Usage

```
optK(X,  
      Kmethod = "cluster",  
      maxK = 10,  
      beta = 0.2,  
      lambda = 0.3,  
      R = 4,  
      C1 = 2.5,  
      C2 = 7.8, ...)
```

Arguments

X	Numeric vector corresponding to Y.
Kmethod	The way to calculate the penalty in automatic binning. "cluster" or "kernel".
maxK	The maximum number of bins.
beta	Additional parameter for automatic binning. For more detailed explanation, see reference.
lambda	Additional parameter for automatic binning. For more detailed explanation, see reference.
R	Additional parameter for automatic binning. For more detailed explanation, see reference.
C1	Additional parameter for automatic binning. For more detailed explanation, see reference.
C2	Additional parameter for automatic binning. For more detailed explanation, see reference.
...	Arguments to be passed to methods.

Value

The optimal number of bins, the result of binning, and the summary of binning including the penalty values up to the maximum number of bins are returned.

References

Lavielle, M. and Bleakley, K. (2011). Automatic data binning for improved visual diagnosis of pharmacometric models. *Journal of pharmacokinetics and pharmacodynamics*, 38(6), 861-871.

Examples

```
data(origdata)
optK(origdata$TIME)
```

origdata	<i>Pharmacokinetics of Theophylline with different time schedule</i>
----------	--

Description

The simulated Theoph data frame has 132 rows and 3 columns of data from an experiment on the pharmacokinetics of theophylline.

Arguments

ID	an ordered factor with levels 1, ..., 12 identifying the subject on whom the observation was made. The ordering is by increasing maximum concentration of theophylline observed.
TIME	time since drug administration when the sample was drawn (hr).
DV	theophylline concentration in the sample (mg/L)

Examples

```
data(origdata)
dim(origdata)
```

quantVPC	<i>the quantified visual predictive check plot (QVPC)</i>
----------	---

Description

The quantified visual predictive check visually represents actual and unavailable observations around predicted medians, regardless of the density or shape of the observed data distribution, through the form of a percent.

Usage

```
quantVPC(orig_data,
          sim_data,
          N_xbin = NULL,
          prob = 0.5,
          X_name = "TIME",
          Y_name = "DV",
          MissingDV = NULL,
```

```

Kmethod = "cluster",
maxK = NULL,
beta = 0.2,
lambda = 0.3,
R = 4,
C1 = 2.5,
C2 = 7.8, ...)

```

Arguments

<code>orig_data</code>	A data frame of original data with X and Y variable.
<code>sim_data</code>	A matrix of simulated data with only Y values collected.
<code>N_xbin</code>	Number of bins in X variable. If NULL, optimal number of bins are automatically calculated using <code>optK</code> function.
<code>prob</code>	Scalar of probability.
<code>X_name</code>	Name of X variable in <code>orig_data</code> (usually "TIME" in pharmacokinetic data).
<code>Y_name</code>	Name of Y variable in <code>orig_data</code> (usually "DV" in pharmacokinetic data).
<code>MissingDV</code>	Name of missing indicator variable in <code>orig_data</code> , which have value 1 if missing, value 0 otherwise. (usually "MDV" in pharmacokinetic data).
<code>Kmethod</code>	The way to calculate the penalty in automatic binning. "cluster" or "kernel".
<code>maxK</code>	The maximum number of bins.
<code>beta</code>	Additional parameter for automatic binning, used in <code>optK</code> function.
<code>lambda</code>	Additional parameter for automatic binning, used in <code>optK</code> function.
<code>R</code>	Additional parameter for automatic binning, used in <code>optK</code> function.
<code>C1</code>	Additional parameter for automatic binning, used in <code>optK</code> function.
<code>C2</code>	Additional parameter for automatic binning, used in <code>optK</code> function.
<code>...</code>	Arguments to be passed to methods.

Value

`quantVPC` plot

References

Post, T.M., et al. (2008) Extensions to the visual predictive check for facilitate model performance evaluation, *Journal of pharmacokinetics and pharmacodynamics*, 35(2), 185-202

Examples

```

data(origdata)
data(simdata)
quantVPC(origdata, simdata, prob=0.5, N_xbin=8)

```

simdata	<i>simulation data</i>
---------	------------------------

Description

simulation data from the fitted model of the origdata

Examples

```
data(simdata)
dim(simdata)
```

VPCgraph	<i>the original visual predictive check plot (VPC)</i>
----------	--

Description

This function draws the original visual predictive check plot proposed by Holford & Karlsson (2008). The visual predictive check plot is a graphical comparison of observations and simulated predictions. It compares the distribution of quantiles obtained from the observed data to the distribution of quantiles from simulated data drawn from the fitted model.

Usage

```
VPCgraph(orig_data,
  sim_data,
  type = "CI",
  N_xbin = NULL,
  probs = c(0.1,0.5,0.9),
  conf.level = 0.95,
  X_name = "TIME",
  Y_name = "DV",
  MissingDV = NULL,
  DV_point = TRUE,
  CIvpc_type = "line",
  bin_grid = TRUE,
  plot_caption = TRUE,
  plot_flag = TRUE,
  linesize = 0.7,
  pointsize = 0.7,
  captionsize = 10,
  Kmethod = "cluster",
  maxK = NULL,
  beta = 0.2,
  lambda = 0.3,
```

```
R = 4,
C1 = 2.5,
C2 = 7.8, ...)
```

Arguments

orig_data	A data frame of original data with X and Y variable.
sim_data	A matrix of simulated data with only Y values collected.
type	Type of VPC graph; "CI", "percentile", or "scatter".
N_xbin	Number of bins in X variable. If NULL, optimal number of bins are automatically calculated using optK function.
probs	A numeric vector of probabilities.
conf.level	Confidence level of the interval.
X_name	Name of X variable in orig_data (usually "TIME" in pharmacokinetic data).
Y_name	Name of Y variable in orig_data (usually "DV" in pharmacokinetic data).
MissingDV	Name of missing indicator variable in orig_data, which have value 1 if missing, value 0 otherwise. (usually "MDV" in pharmacokinetic data).
DV_point	Draw point (X, Y) in the plot if TRUE; omit if FALSE.
CIvpc_type	Type of CI area in VPC graph; "line" or "segment".
bin_grid	Draw grid lines for binning in X variable if TRUE; omit if FALSE.
plot_caption	Put caption with additional information if TRUE; omit if FALSE.
plot_flag	Draw plot if TRUE; generate data for drawing plot if FALSE.
linesize	Size of line in the plot.
pointsize	Size of point in the plot.
captionsize	Size of caption .
Kmethod	The way to calculate the penalty in automatic binning. "cluster" or "kernel".
maxK	The maximum number of bins.
beta	Additional parameter for automatic binning, used in optK function.
lambda	Additional parameter for automatic binning, used in optK function.
R	Additional parameter for automatic binning, used in optK function.
C1	Additional parameter for automatic binning, used in optK function.
C2	Additional parameter for automatic binning, used in optK function.
...	Arguments to be passed to methods.

Value

Visual predictive check plot or the values to draw VPC plot.

References

- Holford N, & Karlsson M. (2008). "A tutorial on visual predictive checks, abstr 1434." Annual Meeting of the Populations Approach Group in Europe. www.page-meeting.org. 2008.
- Harling, Uekcert, K. 2018. VPC and NPC User Guide. ICON plc.
https://github.com/UUPharmacometrics/PsN/releases/download/4.9.0/vpc_npc_userguide.pdf.

Examples

```
data(origdata)
data(simdata)
VPCgraph(origdata,simdata,type="CI",X_name="TIME",Y_name="DV",N_xbin=8)
```

Index

* datasets

origdata, [17](#)

simdata, [19](#)

aqrVPC, [2](#)

asVPC, [3](#)

bootVPC, [5](#)

coverageDetailplot, [7](#)

coverageplot, [8](#)

FindBestCut, [10](#)

findQuantile, [11](#)

findSIMQ, [11](#)

findSIMQuantile, [12](#)

makeCOVbin, [13](#)

NumericalCheck, [14](#)

optK, [16](#)

origdata, [17](#)

quantVPC, [17](#)

simdata, [19](#)

VPCgraph, [19](#)