

Package ‘onion’

February 11, 2021

Version 1.5-0

Title Octonions and Quaternions

LazyData TRUE

Description Quaternions and Octonions are four- and eight- dimensional extensions of the complex numbers. They are normed division algebras over the real numbers and find applications in spatial rotations (quaternions), and string theory and relativity (octonions). The quaternions are noncommutative and the octonions nonassociative. See the package vignette for more details.

Maintainer Robin K. S. Hankin <hankin.robin@gmail.com>

License GPL-2

Depends methods, R (>= 3.5.0)

Suggests testthat,knitr,rmarkdown

VignetteBuilder knitr

Imports emulator

URL <https://github.com/RobinHankin/onion>

BugReports <https://github.com/RobinHankin/onion/issues>

NeedsCompilation yes

Author Robin K. S. Hankin [aut, cre] (<<https://orcid.org/0000-0001-5982-0415>>)

Repository CRAN

Date/Publication 2021-02-11 07:00:02 UTC

R topics documented:

onion-package	2
Arith	4
biggest	6
bind	6
bunny	7
c	8

Compare-methods	9
Complex	9
condense	11
cumsum	12
Extract	13
length	14
Logic	15
Math	16
names	17
O1	18
onion	19
onion-class	21
onionmat	22
orthogonal	25
p3d	26
plot	27
prods	27
rep	29
roct	30
rotate	31
seq	32
show	32
sum	33
threeform	34
zapsmall	35

Index**37**

onion-package

*Octonions and Quaternions***Description**

Quaternions and Octonions are four- and eight- dimensional extensions of the complex numbers. They are normed division algebras over the real numbers and find applications in spatial rotations (quaternions), and string theory and relativity (octonions). The quaternions are noncommutative and the octonions nonassociative. See the package vignette for more details.

Details

Package:	onion
Version:	1.5-0
Title:	Octonions and Quaternions
LazyData:	TRUE
Authors@R:	person(given=c("Robin", "K. S."), family="Hankin", role = c("aut", "cre"), email="hankin.robin@gmail.com")
Description:	Quaternions and Octonions are four- and eight- dimensional extensions of the complex numbers. They are
Maintainer:	Robin K. S. Hankin <hankin.robin@gmail.com>

License: GPL-2
 Depends: methods, R (>= 3.5.0)
 Suggests: testthat, knitr, rmarkdown
 VignetteBuilder: knitr
 Imports: emulator
 URL: <https://github.com/RobinHankin/onion>
 BugReports: <https://github.com/RobinHankin/onion/issues>
 Author: Robin K. S. Hankin [aut, cre] (<<https://orcid.org/0000-0001-5982-0415>>)

Index of help topics:

Arith	Methods for Function Arith in package Onion
Compare-methods	Methods for compare S4 group
01	Unit onions
Re	Complex functionality for onions
biggest	Returns the biggest type of a set of onions
bind	Binding of onionmats
bunny	The Stanford Bunny
c	Concatenation
condense	Condense an onionic vector into a short form
cumsum	Cumulative sums and products of onions
i	Extract or Replace Parts of onions or glubs
length	Length of an octonionic vector
log	Various logarithmic and circular functions for onions
logic.onion	Logical operations on onions
names.onion	Names of an onionic vector
onion	Basic onion functions
onion-class	Class "onion"
onion-package	Octonions and Quaternions
onionmat	Onionic matrices
orthogonal	Orthogonal matrix equivalents
p3d	Three dimensional plotting
plot	Plot onions
prods	Various products of two onions
rep	Replicate elements of onionic vectors
roct	Random onionic vector
rotate	Rotates 3D vectors using quaternions
seq	seq method for onions
show	Print method for onions
sum	Various summary statistics for onions
threeform	Various non-field diagnostics
zapsmall	Concatenation

There are precisely four normed division algebras over the reals: the reals themselves, the complex numbers, the quaternions, and the octonions. The R system is well equipped to deal with the first two: the **onion** package provides some functionality for the third and fourth.

Author(s)

NA

Maintainer: Robin K. S. Hankin <hankin.robin@gmail.com>

References

R. K. S. Hankin 2006. “Normed division algebras in R: introducing the onion package”. *R News*, Volume 6, number 2

Examples

```
rquat(10)    # random quaternions

0k + (0i + 0jl)/(0j-0il)  # basic octonions

x <- roct(10)
y <- roct(10)
z <- roct(10)

x*(y*z) - (x*y)*z  # nonassociative!
```

Description

Methods for Arithmetic functions for onions: +, -, *, /, ^

Usage

```
onion_negative(z)
onion_inverse(z)
onion_arith_onion(e1,e2)
onion_arith_numeric(e1,e2)
numeric_arith_onion(e1,e2)
harmonize_oo(a,b)
harmonize_on(a,b)
onion_plus_onion(a,b)
onion_plus_numeric(a,b)
onion_prod_onion(e1,e2)
octonion_prod_octonion(o1,o2)
quaternion_prod_quaternion(q1,q2)
onion_prod_numeric(a,b)
onion_power_singleinteger(o,n)
onion_power_numeric(o,p)
```

Arguments

```
z,e1,e2,a,b,o,o1,o2,n,q1,q2,p  
onions or numeric vectors
```

Details

The package implements the `Arith` group of S4 generics so that idiom like `A + B*C` works as expected with onions.

Functions like `onion_inverse()` and `onion_plus_onion()` are low-level helper functions. The only really interesting operation is multiplication; functions `octonion_prod_octonion()` and `quaternion_prod_quaternion()` dispatch to C.

Names are implemented and the rules are inherited (via `harmonize_oo()` and `harmonize_on()`) from `rbind()`.

Value

generally return an onion

Note

Previous versions of the package included the option to use native R rather than the faster compiled C code used here. But this was very slow and is now discontinued.

Author(s)

Robin K. S. Hankin

Examples

```
a <- rquat()  
b <- rquat()  
a  
Re(a)  
j(a) <- 0.2  
a*b  
b*a # quaternions are noncommutative  
  
x <- as.octonion(matrix(rnorm(40), nrow=8))  
y <- roct()  
z <- roct()  
  
x*(y*z) - (x*y)*z # octonions are nonassociative [use associator()]
```

biggest	<i>Returns the biggest type of a set of onions</i>
----------------	--

Description

Returns the biggest type of a set of onions; useful for “promoting” a set of onions to the most general type.

Usage

```
biggest(...)
```

Arguments

...	Onionic vectors
-----	-----------------

Details

If any argument passed to `biggest()` is an octonion, then return the string “octonion”. Failing that, if any argument is a quaternion, return the string “quaternion”, and failing that, return “scalar”.

Value

Character string representing the type

Author(s)

Robin K. S. Hankin

Examples

```
biggest(01,rquat(100),1:4)
```

bind	<i>Binding of onionmats</i>
-------------	-----------------------------

Description

Methods for `rbind()` and `cbind()` of `onionmats`. These are implemented by specifying methods for `rbind2()` and `cbind2()`.

Usage

```
bind_onion(x,bind,...)
bind_onion_onion(x,y,bind,...)
bind_onion_onionmat(x,y,bind,...)
bind_onionmat_onion(x,y,bind,...)
```

Arguments

x, y	Onions or onionmats
bind	Either rbind or cbind as appropriate
...	Further arguments

Value

Return onionmats

Author(s)

Robin K. S. Hankin

Examples

```
rbind(rquat(3),rquat(3))  
cbind(diag(5),roct(1))  
  
cbind(matrix(Oil,4,2),matrix(roct(12),4,3))
```

bunny

The Stanford Bunny

Description

A set of 3D points in the shape of a rabbit (the Stanford Bunny)

Usage

```
data(bunny)
```

Format

A three column matrix with 35947 rows. Each row is the Cartesian coordinates of a point on the surface of the bunny.

Value

as for format

Source

<https://graphics.stanford.edu/data/3Dscanrep/>

Examples

```
data(bunny)
p3d(rotate(bunny,Hk))
```

c

Concatenation

Description

Combines its arguments to form a single onion.

Usage

```
c_onionpair(x,y)
## S4 method for signature 'onion'
c(x,...)
```

Arguments

x, y, ...	onions
-----------	--------

Details

Returns an onion of the same type as its arguments. Names are inherited from the behaviour of `cbind()`, not `c()`.

Value

An onion

Note

The method is not perfect; it will not, for example, coerce its arguments to the `biggest()` type, so `c(rquat(),roct())` will fail. You will have to coerce the arguments by hand.

Dispatch is based on the class of the first argument, so `c(1,rquat())` will return a list (not an onion), and `c(rquat(),1)` will fail.

Author(s)

Robin K. S. Hankin

Examples

```
a <- roct(3)
b <- seq_onion(from=0i1,to=0j,len=6)
c(a,b)

c(rquat(3),H1,H0,Him)
```

Compare-methods	<i>Methods for compare S4 group</i>
-----------------	-------------------------------------

Description

Methods for comparison (equal to, greater than, etc) of onions. Only equality makes sense.

Value

Return a boolean

Examples

```
# roct() > 0 # meaningless and returns an error

x <- as.octonion(matrix(sample(0:1,800,TRUE,p=c(9,1)),nrow=8))
y <- as.octonion(matrix(sample(0:1,800,TRUE,p=c(9,1)),nrow=8))
x==y

matrix(as.quaternion(100+1:12),3,4) == 102
```

Complex	<i>Complex functionality for onions</i>
---------	---

Description

Functionality in the Complex group.

The *norm* `Norm(O)` of onion O is the product of O with its conjugate: $|O| = OO^*$ but a more efficient numerical method is used (see `dotprod()`).

The *Mod* `Mod(O)` of onion O is the square root of its norm.

The *sign* of onion O is the onion with the same direction as O but with unit Norm: `sign(O)=O/Mod(O)`.

Function `Im()` sets the real component of its argument to zero, and `Conj()` flips the sign of its argument's non-real components.

Usage

```
## S4 method for signature 'onion'
Re(z)
## S4 method for signature 'onion'
Im(z)
Re(z) <- value
Im(x) <- value
## S4 method for signature 'onion'
Conj(z)
## S4 method for signature 'onion'
Mod(z)
onion_abs(x)
onion_conjugate(z)
## S4 method for signature 'onion'
sign(x)
```

Arguments

<code>x, z</code>	Object of class onion or glub
<code>value</code>	replacement value

Value

All functions documented here return a numeric vector or matrix of the same dimensions as their argument, apart from functions `Im()` and `Conj()`, which return an object of the same class as its argument.

Note

If `x` is a numeric vector and `y` an onion, one might expect typing `x[1] <- y` to result in `x` being a onion. This is impossible, according to John Chambers.

Extract and set methods for components such as `i, j, k` are documented at `Extract.Rd`

Author(s)

Robin K. S. Hankin

See Also

[Extract](#)

Examples

```
a <- rquat()
Re(a)
Re(a) <- j(a)

Im(a)
```

```
b <- romat()  
  
A <- romat()  
Im(A) <- Im(A)*10
```

condense

Condense an onionic vector into a short form

Description

Condense an onion into a string vector showing whether the elements are positive, zero or negative.

Usage

```
condense(x, as.vector=FALSE)
```

Arguments

x	An onionic vector
as.vector	Boolean, indicating whether to return a vector or matrix

Value

If `as.vector` is TRUE, return a string vector of the same length as `x` whose elements are length 4 or 8 strings for quaternions or octonions respectively. If FALSE, return a matrix with these columns.

The characters are “+” for a positive, “-” for a negative, and “0” for a zero, element.

Author(s)

Robin K. S. Hankin

Examples

```
condense(roct(3))  
condense(roct(3), as.vector=TRUE)
```

cumsum

Cumulative sums and products of onions

Description

Cumulative sums and products of onions

Usage

```
onion_cumsum(x)
onion_cumprod(x)
```

Arguments

x onion

Value

An onion

Note

The octonions are nonassociative but cumprod() operates left-associatively, as in ((a[1]*a[2])*a[3])*a[4] etc.

Author(s)

Robin K. S. Hankin

Examples

```
cumsum(as.quaternion(matrix(runif(20),4,5)))
cumsum(roct(5))

cumprod(rquat(7))
```

Extract	<i>Extract or Replace Parts of onions or glubs</i>
---------	--

Description

Methods for "[" and "[<-", i.e., extraction or subsetting of onions.

Usage

```
## S4 method for signature 'onion'
i(z)
## S4 method for signature 'onion'
j(z)
## S4 method for signature 'onion'
k(z)
## S4 method for signature 'octonion'
l(z)
## S4 method for signature 'octonion'
il(z)
## S4 method for signature 'octonion'
jl(z)
## S4 method for signature 'octonion'
kl(z)
## S4 method for signature 'onionmat'
i(z)
## S4 method for signature 'onionmat'
j(z)
## S4 method for signature 'onionmat'
k(z)
## S4 method for signature 'onionmat'
il(z)
## S4 method for signature 'onionmat'
jl(z)
## S4 method for signature 'onionmat'
kl(z)
i(x) <- value
j(x) <- value
k(x) <- value
l(x) <- value
il(x) <- value
jl(x) <- value
kl(x) <- value
```

Arguments

x, z	Object of class onion
value	replacement value

Value

Extraction and methods return an onion or onionmat. Replacement methods return an object of the same class as *x*.

Note

If *x* is a numeric vector and *y* a onion, one might expect typing *x*[1] <- *y* to result in *x* being a onion. This is impossible, according to John Chambers.

Author(s)

Robin K. S. Hankin

Examples

```
a <- roct(9)
il(a)
Re(a) <- 1:9

j(a) <- l(a)
a
```

length

Length of an octonionic vector

Description

Get or set the length of onions

Usage

```
## S4 method for signature 'onion'
length(x)
```

Arguments

<i>x</i>	An onion
----------	----------

Details

Operates on the columns of the matrix as expected.

Value

integer

Author(s)

Robin K. S. Hankin

Examples

```
a <- roct(5)
length(a)
```

Logic

Logical operations on onions

Description

Logical operations on onions are not supported

Usage

```
onion_logic(e1,e2)
```

Arguments

e1, e2 onions

Value

none

Note

Carrying out logical operations in this group will report an error. Negation, “!”, is not part of this group.

Author(s)

Robin K. S. Hankin

Examples

```
# roct() & roct()    # reports an error
```

Description

Various elementary functions for onions

Usage

```
onion_log(x,base=exp(1))
onion_exp(x)
onion_sign(x)
onion_sqrt(x)
onion_cosh(x)
onion_sinh(x)
onion_acos(x)
onion_acosh(x)
onion_asin(x)
onion_asinh(x)
onion_atan(x)
onion_atanh(x)
onion_cos(x)
onion_sin(x)
onion_tan(x)
onion_tanh(x)
onion_cos(x)
onion_sin(x)
onion_tan(x)
onion_tanh(x)
```

Arguments

- | | |
|------|--|
| x | Object of class onion |
| base | In function log(), the base of the logarithm |

Details

Standard math stuff. I am not convinced that the trig functions (`sin()` etc) have any value.

Author(s)

Robin K. S. Hankin

Examples

```

x <- roct()
exp(x+x) - exp(x)*exp(x) # zero to numerical precision

jj <- exp(log(x)/2)      # use sqrt() here
jj*jj-x                  # also small

y <- roct()
exp(x+y) - exp(x)*exp(y) # some rules do not operate for onions

max(Mod(c(sin(asin(x))-x,asin(sin(x))-x))) # zero to numerical precision

```

names

Names of an onionic vector

Description

Functions to get or set the names of an onion

Usage

```

## S4 method for signature 'onion'
names(x)
## S4 method for signature 'onionmat'
rownames(x)
## S4 method for signature 'onionmat'
colnames(x)
## S4 method for signature 'onionmat'
dimnames(x)
## S4 method for signature 'onionmat'
dim(x)

```

Arguments

x	onion
---	-------

Details

Names attributes refers to colnames of the internal matrix, which are retrieved or set using colnames() or colnames<-().

Author(s)

Robin K. S. Hankin

Examples

```
a <- roct(5)
names(a) <- letters[1:5]

b <- romat()
dimnames(b) <- list(month = month.abb[1:5], location=names(islands)[1:6])
```

Description

Each of the eight unit quaternions and octonions

Usage

```
H1
Hi
Hj
Hk
H0
Him
Hall
O1
Oi
Oj
Ok
Ol
Oil
Ojl
O0
Oim
Oall
```

Format

Each one is an onionic vector of length one.

Details

Try `Hi` (`=quaternion(i=1)`) to get the pattern for the first four. The next ones are the zero quaternion, the pure imaginary quaternion with all components 1, and the quaternion with all components 1. The ones beginning with “O” follow a similar pattern.

These are just variables that may be overwritten and thus resemble `T` and `F` whose value may be changed.

Value

A length-one onion, either a quaternion or an octonion

Examples

```
Oall
seq_onion(from=01,to=0i1,len=6)

stopifnot(Hj*Hk ==  Hi)
stopifnot(Ok1*Oil == -Oj ) # See tests/test_aaa.R for the full set
```

Description

Construct, coerce to, test for, and print onions

Usage

```
octonion(length.out = NULL, Re = 0, i = 0, j = 0,
          k = 0, l = 0, il = 0, jl = 0, kl = 0)
as.octonion(x, single = FALSE)
is.octonion(x)
quaternion(length.out = NULL, Re = 0, i = 0, j = 0, k = 0)
as.quaternion(x, single = FALSE)
is.quaternion(x)
is.onion(x)
as.onion(x, type, single=FALSE)
quaternion_to_octonion(from)
octonion_to_quaternion(from)
## S4 method for signature 'onion'
as.matrix(x)
## S4 method for signature 'onion'
as.numeric(x)
```

Arguments

<code>length.out</code>	In functions <code>quaternion()</code> and <code>octonion()</code> , the length of the onionic vector returned
<code>Re</code>	The real part of the onionic vector returned
<code>i, j, k</code>	In functions <code>quaternion()</code> and <code>octonion()</code> , component i, j, k respectively of the returned onion
<code>l, il, jl, kl</code>	In function <code>octonion()</code> , component l, il, jl, kl respectively of the returned octonion
<code>x, from</code>	Onion to be tested or printed
<code>single</code>	In functions <code>as.octonion()</code> and <code>as.quaternion()</code> , Boolean with default FALSE meaning to interpret <code>x</code> as a vector of reals to be coerced into an onion with zero imaginary part; and TRUE meaning to interpret <code>x</code> as a length 4 (or length 8) vector and return the corresponding single onion.
<code>type</code>	In function <code>as.onion()</code> a string either “quaternion” or “octonion” denoting the algebra to be forced into

Details

Functions `quaternion()` and `octonion()` use standard recycling where possible; `rbind()` is used.

Functions `as.quaternion()` and `as.octonion()` coerce to quaternions and octonions respectively. If given a complex vector, the real and imaginary components are interpreted as `Re` and `i` respectively.

The output of `type()` is accepted as the `type` argument of function `as.onion()`; thus `as.onion(out, type=type(x))` works as expected.

Value

Generally return onions

Note

An *onion* is any algebra (over the reals) created by an iterated Cayley-Dickson process. Examples include quaternions, octonions, and sedenions. There does not appear to be a standard generic term for such objects (I have seen n-ion, anion and others. But “onion” is pronounceable and a bona fide English word).

Creating further onions—such as the sedenions—is intended to be straightforward.

There is a nice example of the onion package in use in the permutations package, under `cayley.Rd`. This also shows the quaternion group Q_8 , but from a different perspective.

Author(s)

Robin K. S. Hankin

Examples

```

x <- octonion(Re=1,il=1:3)
x
kl(x) <- 100
x

as.quaternion(diag(4))

# Cayley table for the quaternion group Q8:
a <- c(H1,-H1,Hi,-Hi,Hj,-Hj,Hk,-Hk)
names(a) <- c("+1","-1","+i","-i","+j","-j","+k","-k")

f <- Vectorize(function(x,y){names(a)[a==a[x]*a[y]]})
X <- noquote(outer(1:8,1:8, f))
rownames(X) <- names(a)
colnames(X) <- names(a)
X

```

onion-class

Class “onion”

Description

The formal S4 class for onion and onionmat objects

Objects from the Class

Class *onion* is a virtual S4 class extending classes *quaternion* and *octonion*. In package documentation, “onion” means an R object that behaves as a vector of quaternions or octonions, stored as a four- or eight- row numeric matrix.

Class *onionmat* is the S4 class for matrices whose elements are quaternions or octonions. An onionmat is stored as a two-element list, the first being an onion and the second an integer matrix which holds structural matrix attributes such as dimensions and dimnames. Most standard arithmetic R idiom for matrices should work for onionmats.

Class *index* is taken from the excellent **Matrix** package and is a `setClassUnion()` of classes *numeric*, *logical*, and *character*, which mean that it is an arity-one matrix index.

Author(s)

Robin K. S. Hankin

Examples

```

as.octonion(1:8,single=TRUE)
as.quaternion(matrix(runif(20),nrow=4))

H <- matrix(rquat(21),3,7)
dimnames(H) <- list(foo=letters[1:3],bar=state.abb[1:7])

i(H) <- 0.1

I <- matrix(rquat(14),7,2)
dimnames(I) <- list(foo=state.abb[1:7],baz=LETTERS[1:2])
H %*% I

```

Description

Simple functionality for quaternionic and octonionic matrices, intended for use in the jordan package. Use idiom like `matrix(Him, 4, 5)` or `matrix(roct(6), 2, 3)` to create an `onionmat` object, a matrix of onions.

The package is intended to match base R's matrix functionality in the sense that standard R idiom just goes through for onionic matrices. Determinants are not well-defined for quaternionic or octonionic matrices, and matrix inverses are not implemented.

Usage

```

newonionmat(d, M)
onionmat(data = NA, nrow = 1, ncol = 1, byrow = FALSE, dimnames = NULL)
as.onionmat(x)
is.onionmat(x)
onionmat_negative(e1)
onionmat_inverse(e1)
onionmat_prod_onionmat(e1,e2)
onionmat_power_onionmat(...)
onionmat_prod_single(x,y)
onionmat_power_single(e1,e2)
onionmat_plus_onionmat(e1,e2)
matrix_arith_onion(e1,e2)
onion_arith_matrix(e1,e2)
matrix_plus_onion(e1,e2)
matrix_prod_onion(e1,e2)
drop(x)
## S4 method for signature 'onionmat,onionmat'
cprod(x,y)

```

```
## S4 method for signature 'onionmat,missing'
cprod(x,y)
## S4 method for signature 'onionmat,ANY'
cprod(x,y)
## S4 method for signature 'ANY,ANY'
cprod(x,y)
## S4 method for signature 'onion,missing'
cprod(x,y)
## S4 method for signature 'onion,onion'
cprod(x,y)
## S4 method for signature 'onion,onionmat'
cprod(x,y)
## S4 method for signature 'onionmat,onion'
cprod(x,y)
## S4 method for signature 'onionmat,onionmat'
tprod(x,y)
## S4 method for signature 'onionmat,missing'
tprod(x,y)
## S4 method for signature 'onionmat,ANY'
tprod(x,y)
## S4 method for signature 'ANY,ANY'
tprod(x,y)
## S4 method for signature 'onion,missing'
cprod(x,y)
## S4 method for signature 'onion,onion'
cprod(x,y)
## S4 method for signature 'onion,onionmat'
cprod(x,y)
## S4 method for signature 'onionmat,onion'
cprod(x,y)
## S4 method for signature 'onionmat'
t(x)
## S4 method for signature 'onion'
t(x)
## S4 method for signature 'onionmat'
ht(x)
## S4 method for signature 'onion'
ht(x)
nrow(x)
ncol(x)
herm_onion_mat(real_diagonal, onions)
onionmat_complex(z)
onionmat_conjugate(z)
onionmat_imag(z)
onionmat_re(z)
onionmat_mod(z)
onionmat_matrixprod_onionmat(x,y)
onion_matrixprod_onionmat(x,y)
```

```
onionmat_matrixprod_numeric(x,y)
onionmat_matrixprod_onion(x,y)
```

Arguments

<code>d,M</code>	data and matrix index
<code>x,y,z,e1,e2</code>	Objects of class <code>onionmat</code>
<code>data,nrow,ncol,byrow,dimnames</code>	In function <code>onionmat()</code> , as for <code>matrix()</code>
<code>...</code>	Further arguments (currently ignored)
<code>real_diagonal, onions</code>	In function <code>herm_onion_mat()</code> , on- and off- diagonal elements of an Hermitian matrix

Details

An object of class `onionmat` is a two-element list, the first of which is an onion, and the second an integer matrix used for tracking attributes such as dimensions and dimnames. This device makes the extraction and replacement methods easy.

The S4 method for `matrix()` simply dispatches to `onionmat()`, which is a drop-in replacement for `matrix()`.

Function `newonionmat()` is lower-level: it also creates `onionmat` objects, but takes two arguments: an onion and a matrix; the matrix argument can be used to specify additional attributes via `attr()`, but this ability is not currently used in the package.

Functions such as `onionmat_plus_onionmat()` are low-level helper functions, not really designed for the end-user.

Vignette `onionmat` shows some use-cases.

Author(s)

Robin K. S. Hankin

Examples

```
matrix(rquat(28),4,7)

M <- onionmat(rquat(10),2,5)
cprod(M)

Re(M)
Re(M) <- 0.3

romat() %*% rquat(6)
```

orthogonal	<i>Orthogonal matrix equivalents</i>
------------	--------------------------------------

Description

Convert a quaternion to and from an equivalent orthogonal matrix

Usage

```
matrix2quaternion(M)
as.orthogonal(Q)
```

Arguments

M	A three-by-three orthogonal matrix
Q	A vector of quaternions

Value

Function `matrix2quaternion()` returns a quaternion.

Function `as.orthogonal()` returns either a 3×3 matrix or a $3 \times 3 \times n$ array of orthogonal matrices

Note

Function `matrix2quaternion()` is low-level; use `as.quaternion()` to convert arrays.

Author(s)

Robin K. S. Hankin

See Also

[rotate](#)

Examples

```
as.orthogonal(rquat(1))

o <- function(w){diag(3)-2*outer(w,w)/sum(w^2)} # Householder
matrix2quaternion(o(1:3)) # Booorrrriiinnnggg
matrix2quaternion(o(1:3) %*% o(3:1))

Q <- rquat(7)
Q <- Q/abs(Q)
as.quaternion(as.orthogonal(Q)) # +/- Q
```

```
A <- replicate(7,o(rnorm(3)) %*% o(rnorm(3)))
max(abs(as.orthogonal(as.quaternion(A))-A))
```

Description

Three dimensional plotting of points. Produces a nice-looking 3D scatterplot with greying out of further points giving a visual depth cue

Usage

```
p3d(x, y, z, xlim = NULL, ylim = NULL, zlim = NULL, d0 = 0.2, h = 1, ...)
```

Arguments

<code>x,y,z</code>	vector of x, y, z coordinates to be plotted. If <code>x</code> is a matrix, interpret the rows as 3D Cartesian coordinates
<code>xlim,ylim,zlim</code>	Limits of plot in the x, y, z directions, with default <code>NULL</code> meaning to use <code>range()</code>
<code>d0</code>	E-folding distance for graying out (depths are standardized to be between 0 and 1)
<code>h</code>	The hue for the points, with default value of 1 corresponding to red. If <code>NULL</code> , produce black points greying to white
<code>...</code>	Further arguments passed to <code>persp()</code> and <code>points()</code>

Value

Value returned is that given by function `trans3d()`.

Author(s)

Robin K. S. Hankin

See Also

[bunny](#)

Examples

```
data(bunny)
p3d(bunny,theta=3,phi=104,box=FALSE)
```

plot	<i>Plot onions</i>
------	--------------------

Description

Plotting method for onionic vectors

Usage

```
## S4 method for signature 'onion'  
plot(x,y, ...)
```

Arguments

x,y	Onions
...	Further arguments passed to <code>plot.default()</code>

Details

The function is `plot(Re(x),Mod(Im(x)),...)`, and thus behaves similarly to `plot()` when called with a complex vector.

Value

Called for its side-effect of plotting a diagram

Author(s)

Robin K. S. Hankin

Examples

```
plot(roct(30))
```

prods	<i>Various products of two onions</i>
-------	---------------------------------------

Description

Returns various inner and outer products of two onionic vectors.

Usage

```
x %<*>% y
x %>*<% y
x %<.>% y
x %>.<% y
x %.% y
onion_g_even(x,y)
onion_g_odd (x,y)
onion_e_even(x,y)
onion_e_odd (x,y)
dotprod(x,y)
```

Arguments

x,y	onions
-----	--------

Details

This page documents an attempt at a consistent notation for onionic products. The default product for onions (viz “*”) is sometimes known as the “Grassman product”. There is another product known as the Euclidean product defined by $E(p,q) = p'q$ where x' is the conjugate of x .

Each of these products separates into an “even” and an “odd” part, here denoted by functions `g_even()` and `g_odd()` for the Grassman product, and `e_even()` and `e_odd()` for the Euclidean product. These are defined as follows:

- `g_even(x,y)=(xy+yx)/2`
- `g_odd(x,y)=(xy-yx)/2`
- `e_even(x,y)=(x'y+y'x)/2`
- `e_odd(x,y)=(x'y-y'x)/2`

These functions have an equivalent binary operator.

The Grassman operators have a “*”; they are “%<*>%” for the even Grassman product and “%>*<%” for the odd product.

The Euclidean operators have a “.”; they are “%<.>%” for the even Euclidean product and “%>.<%” for the odd product.

Function `dotprod()` returns the Euclidean even product of two onionic vectors. That is, if `x` and `y` are eight-element vectors of the components of two onions, return `sum(x*y)`.

Note that the returned value is a numeric vector (compare `%<.>%`, `e.even()`, which return onionic vectors with zero imaginary part).

There is no binary operator for the ordinary Euclidean product (it seems to be rarely needed in practice). For `Conj(x)*x`, `Norm(x)` is much more efficient and accurate.

Function `prod()` is documented at [Summary.Rd](#).

Note

Frankly if you find yourself using these operators you might be better off using the **clifford** package, which has an extensive and consistent suite of product operators.

Author(s)

Robin K. S. Hankin

Examples

```
0j %<.>% 0all
```

rep	<i>Replicate elements of onionic vectors</i>
-----	--

Description

Replicate elements of onionic vectors

Usage

```
## S4 method for signature 'onion'  
rep(x, ...)
```

Arguments

x	Onionic vector
...	Further arguments passed to seq.default()

Author(s)

Robin K. S. Hankin

Examples

```
a <- roct(3)  
rep(a,2) + a[1]  
rep(a,each=2)  
rep(a,length.out=5)
```

<code>roct</code>	<i>Random octonionic vector</i>
-------------------	---------------------------------

Description

Random quaternion or octonion vectors and matrices

Usage

```
rquat(n=5)
roct(n=5)
romat(type="quaternion", nrow=5, ncol=6, ...)
```

Arguments

- `n` Length of random vector returned
- `nrow, ncol, ...` Further arguments specifying properties of the returned matrix
- `type` string specifying type of elements

Details

Function `rquat()` returns a quaternionic vector, `roct()` returns an octonionic vector, and `romat()` a quaternionic matrix.

Functions `rquat()` and `roct()` give a quick “get you going” random onion to play with. Function `romat()` gives a simple onionmat, although arguably `matrix(roct(4), 2, 2)` is as convenient.

Author(s)

Robin K. S. Hankin

References

K. Shoemake 1992. “Uniform random rotations”. In D. Kirk, editor, *Graphics Gems III* pages 129-130. Academic, New York.

Examples

```
rquat(3)
roct(3)
plot(roct(30))

romat()
```

rotate*Rotates 3D vectors using quaternions*

Description

Rotates a three-column matrix whose rows are vectors in 3D space, using quaternions

Usage

```
rotate(x, H)
```

Arguments

- | | |
|---|---|
| x | A matrix of three columns whose rows are points in 3D space |
| H | A quaternion. Does not need to have unit modulus |

Value

Returns a matrix of the same size as x

Author(s)

Robin K. S. Hankin

See Also

[orthogonal](#)

Examples

```
data(bunny)
par(mfrow=c(2,2))
par(mai=rep(0,4))
p3d(rotate(bunny,Hi),box=FALSE)
p3d(rotate(bunny,H1-Hi+Hj),box=FALSE)
p3d(rotate(bunny,Hk),box=FALSE)
p3d(rotate(bunny,Hall),box=FALSE)

o <- function(w){diag(3)-2*outer(w,w)/sum(w^2)} # Householder
o <- o(1:3) %*% o(3:1)

rotate(bunny,as.quaternion(O))
bunny %*% t(O)    # should be the same; note transpose
```

seq	<i>seq method for onions</i>
-----	------------------------------

Description

Rough equivalent of `seq()` for onions.

Usage

```
seq_onion(from=1, to=1, by=((to-from)/(length.out-1)), length.out=NULL, slerp=FALSE, ...)
```

Arguments

<code>from</code>	Onion for start of sequence
<code>to</code>	Onion for end of sequence
<code>by</code>	Onion for interval
<code>length.out</code>	Length of vector returned
<code>slerp</code>	Boolean, with default FALSE meaning to use linear interpolation and TRUE meaning to use spherical linear interpolation (useful for animating 3D rotation)
<code>...</code>	Further arguments (currently ignored)

Author(s)

Robin K. S. Hankin

Examples

```
seq(from=01,to=0i1,length.out=6)
seq(from=H1,to=(Hi+Hj)/2,len=10,slerp=TRUE)
```

show	<i>Print method for onions</i>
------	--------------------------------

Description

Show methods for onions

Usage

```
## S4 method for signature 'onion'
show(object)
onion_show(x,hgetOption("show_onions_horizontally"))
```

Arguments

x, object	Onions
h	Boolean, with default FALSE meaning to print horizontally and TRUE meaning to print by columns.

Details

If options("horiz") is TRUE, then print by rows rather than columns (provided that the default value of argument h is not overridden). The default behaviour is to print by columns; do this by setting horiz to anything other than TRUE, including leaving it unset.

Note

Print method for onionmat objects is also sensitive to this option.

Author(s)

Robin K. S. Hankin

Examples

```
roct(4)
```

sum	<i>Various summary statistics for onions</i>
-----	--

Description

Various summary statistics for onions

Usage

```
onion_allsum(x)
## S4 method for signature 'onion'
sum(x)
## S4 method for signature 'quaternion'
prod(x)
## S4 method for signature 'octonion'
sum(x)
## S4 method for signature 'onionmat'
sum(x)
## S4 method for signature 'octonion'
prod(x)
## S4 method for signature 'onion'
str(object, ...)
str_onion(object, vec.len = 4, ...)
onion_allsum(x)
onionmat_allsum(x)
quaternion_allprod(x)
```

Arguments

<code>x, object, ...</code>	Objects of class onion
<code>vec.len</code>	number of elements to display

Details

For a onion object, return the sum or product accordingly

Value

Return an onion

Note

Function `str()` uses functionality from `condense()`.

Author(s)

Robin K. S. Hankin

Examples

```
sum(roct())
str(roct())
```

threeform

Various non-field diagnostics

Description

Diagnostics of non-field behaviour: `threeform`, `associator`, `commutator`

Usage

```
threeform(x1, x2, x3)
associator(x1, x2, x3)
commutator(x1, x2)
```

Arguments

<code>x1, x2, x3</code>	onionic vectors
-------------------------	-----------------

Details

The `threeform` is defined as $\text{Re}(x_1 * (\text{Conj}(x_2) * x_3) - x_3 * (\text{Conj}(x_2) * x_1)) / 2$;
 the `associator` is $(x_1 * x_2) * x_3 - x_1 * (x_2 * x_3)$;
 the `commutator` is $x_1 * x_2 - x_2 * x_1$.

Value

Returns an octonionic vector.

Author(s)

Robin K. S. Hankin

Examples

```
x <- roct(7) ; y <- roct(7) ; z <- roct(7)
associator(x,y,z)
```

zapsmall

Concatenation

Description

Zapping small components to zero

Usage

```
## S4 method for signature 'onion'
zapsmall(x,digits=getOption("digits"))
## S4 method for signature 'onionmat'
zapsmall(x,digits=getOption("digits"))
```

Arguments

x	An onion or onionmat
digits	integer indicating the precision to be used as in base::zapsmall()

Details

Uses base::zapsmall() to zap small elements to zero.

Value

An onion

Author(s)

Robin K. S. Hankin

Examples

```
zapsmall(as.octonion(0.01^(1:8),single=TRUE))
```

```
a <- roct(7)
x <- a^1/a
x
zapsmall(x)
```

Index

* **array**
 c, 8
 condense, 11
 cumsum, 12
 length, 14
 names, 17
 plot, 27
 prods, 27
 rep, 29
 seq, 32
 show, 32
 threeform, 34

* **classes**
 onion-class, 21

* **datasets**
 bunny, 7
 01, 18

* **hplot**
 p3d, 26

* **math**
 Arith, 4
 biggest, 6
 Compare-methods, 9
 Complex, 9
 Extract, 13
 Logic, 15
 Math, 16
 sum, 33

* **methods**
 Arith, 4
 Compare-methods, 9

* **misc**
 onion, 19
 orthogonal, 25
 rotate, 31

* **package**
 onion-package, 2

+ ,onion,missing-method (onionmat), 22
+ ,onionmat,missing-method (onionmat), 22

- ,onion,missing-method (onionmat), 22
- ,onionmat,missing-method (onionmat), 22

[(Extract), 13

[,onion,ANY,ANY-method (Extract), 13

[,onion,index,ANY,ANY-method (Extract),
 13

[,onion,index,ANY-method (Extract), 13

[,onion,index,missing,ANY-method
 (Extract), 13

[,onion,index,missing-method (Extract),
 13

[,onion-method (Extract), 13

[,onionmat,ANY,ANY,ANY-method
 (Extract), 13

[,onionmat,ANY,ANY-method (Extract), 13

[,onionmat,index,index,ANY-method
 (Extract), 13

[,onionmat,index,index-method
 (Extract), 13

[,onionmat,index,missing,ANY-method
 (Extract), 13

[,onionmat,index,missing,missing-method
 (Extract), 13

[,onionmat,index,missing-method
 (Extract), 13

[,onionmat,matrix,missing,ANY-method
 (Extract), 13

[,onionmat,matrix,missing-method
 (Extract), 13

[,onionmat,missing,index,ANY-method
 (Extract), 13

[,onionmat,missing,index-method
 (Extract), 13

[,onionmat,missing,missing,ANY-method
 (Extract), 13

[,onionmat,missing,missing-method
 (Extract), 13

[.onion (Extract), 13

[.onionmat (onionmat), 22

[<- (Extract), 13
 [<-, onion, ANY, ANY-method (Extract), 13
 [<-, onion, index, ANY, ANY-method
 (Extract), 13
 [<-, onion, index, missing, ANY-method
 (Extract), 13
 [<-, onion, index, missing, numeric-method
 (Extract), 13
 [<-, onion, index, missing, onion-method
 (Extract), 13
 [<-, onion, missing, missing, numeric-method
 (Extract), 13
 [<-, onion, missing, missing, onion-method
 (Extract), 13
 [<-, onion-method (Extract), 13
 [<-, onionmat, ANY, missing, numeric-method
 (Extract), 13
 [<-, onionmat, ANY, missing, onion-method
 (Extract), 13
 [<-, onionmat, index, index, numeric-method
 (Extract), 13
 [<-, onionmat, index, index, onion-method
 (Extract), 13
 [<-, onionmat, index, missing, numeric-method
 (Extract), 13
 [<-, onionmat, index, missing, onion-method
 (Extract), 13
 [<-, onionmat, missing, index, numeric-method
 (Extract), 13
 [<-, onionmat, missing, index, onion-method
 (Extract), 13
 [<-.onion (Extract), 13
 [<-.onionmat (onionmat), 22
 %*% (onionmat), 22
 %*%, numeric, onion-method (onionmat), 22
 %*%, numeric, onionmat-method (onionmat),
 22
 %*%, onion, onionmat-method (onionmat), 22
 %*%, onionmat, numeric-method (onionmat),
 22
 %*%, onionmat, onion-method (onionmat), 22
 %*%, onionmat, onionmat-method
 (onionmat), 22
 %.% (prods), 27
 %<*>% (prods), 27
 %<.>>% (prods), 27
 %>*<% (prods), 27
 %>.<% (prods), 27

abs, onion-method (Math), 16
 acos (Math), 16
 acos, onion-method (Math), 16
 acosh (Math), 16
 acosh, onion-method (Math), 16
 Arith, 4
 Arith, ANY, onion-method (Arith), 4
 Arith, onion, ANY-method (Arith), 4
 Arith, onion, missing-method (Arith), 4
 Arith, onion, numeric-method (Arith), 4
 Arith, onion, onion-method (Arith), 4
 Arith-methods (Arith), 4
 as.matrix (onion), 19
 as.matrix, onion-method (onion), 19
 as.numeric, onion-method (onion), 19
 as.octonion (onion), 19
 as.octonionmat (onionmat), 22
 as.onion (onion), 19
 as.onionmat (onionmat), 22
 as.orthogonal (orthogonal), 25
 as.quaternion (onion), 19
 as.quaternionmat (onionmat), 22
 asin (Math), 16
 asin, onion-method (Math), 16
 asinh (Math), 16
 asinh, onion-method (Math), 16
 associator (threeform), 34
 atan (Math), 16
 atan, onion-method (Math), 16
 atanh (Math), 16
 atanh, onion-method (Math), 16

biggest, 6
 bind, 6
 bind_onion (bind), 6
 bind_onion_matrix (bind), 6
 bind_onion_onion (bind), 6
 bind_onion_onionmat (bind), 6
 bind_onionmat_onion (bind), 6
 bind_onionmat_onionmat (bind), 6
 bunny, 7, 26

c, 8
 c, onion-method (c), 8
 c.onion (c), 8
 c_onionpair (c), 8
 cbind (bind), 6
 cbind2, matrix, onion-method (bind), 6
 cbind2, matrix, onionmat-method (bind), 6

cbind2, numeric, onion-method (bind), 6
 cbind2, numeric, onionmat-method (bind), 6
 cbind2, onion, matrix-method (bind), 6
 cbind2, onion, numeric-method (bind), 6
 cbind2, onion, onion-method (bind), 6
 cbind2, onion, onionmat-method (bind), 6
 cbind2, onionmat, matrix-method (bind), 6
 cbind2, onionmat, numeric-method (bind), 6
 cbind2, onionmat, onion-method (bind), 6
 cbind2, onionmat, onionmat-method (bind), 6
 colnames (names), 17
 colnames, onion-method (names), 17
 colnames, onionmat-method (names), 17
 colnames<- (onionmat), 22
 colnames<-, onionmat-method (names), 17
 commutator (threeform), 34
 Compare, ANY, onionmat-method
 (Compare-methods), 9
 Compare, numeric, onion-method
 (Compare-methods), 9
 Compare, onion, numeric-method
 (Compare-methods), 9
 Compare, onion, onion-method
 (Compare-methods), 9
 Compare, onionmat, ANY-method
 (Compare-methods), 9
 Compare, onionmat, onionmat-method
 (Compare-methods), 9
 Compare-methods, 9
 Complex, 9
 concatenate.onion (c), 8
 condense, 11
 Conj (Complex), 9
 Conj, onion-method (Complex), 9
 Conj, onionmat-method (Complex), 9
 cos (Math), 16
 cos, onion-method (Math), 16
 cosh (Math), 16
 cosh, onion-method (Math), 16
 cprod (onionmat), 22
 cprod, ANY, ANY-method (onionmat), 22
 cprod, ANY, missing-method (onionmat), 22
 cprod, ANY, onionmat-method (onionmat), 22
 cprod, onion, missing-method (onionmat), 22
 cprod, onion, onion-method (onionmat), 22
 cprod, onion, onionmat-method (onionmat), 22
 cprod, onionmat, ANY-method (onionmat), 22
 cprod, onionmat, missing-method (onionmat), 22
 cprod, onionmat, onion-method (onionmat), 22
 cumsum, 12
 diag (onionmat), 22
 diag, onion-method (onionmat), 22
 diag, onionmat-method (onionmat), 22
 diag.onion (onionmat), 22
 diag.onionmat (onionmat), 22
 diag<, onionmat-method (onionmat), 22
 diag<-.onionmat (onionmat), 22
 dim (names), 17
 dim, onionmat-method (names), 17
 dim<- (names), 17
 dim<-, onionmat-method (names), 17
 dimnames, onionmat-method (names), 17
 dimnames<-, onionmat-method (names), 17
 dotprod (prods), 27
 drop (onionmat), 22
 drop, onionmat-method (onionmat), 22
 e_even.onion (prods), 27
 e_odd.onion (prods), 27
 exp (Math), 16
 exp, onion-method (Math), 16
 Extract, 10, 13
 g_even.onion (prods), 27
 g_odd.onion (prods), 27
 getd (onionmat), 22
 getM (onionmat), 22
 H0 (01), 18
 H1 (01), 18
 Hall (01), 18
 harmonize_on (Arith), 4
 harmonize_oo (Arith), 4
 herm_onion_mat (onionmat), 22
 Hi (01), 18
 Him (01), 18
 Hj (01), 18
 Hk (01), 18
 ht (onionmat), 22

ht.onion-method (onionmat), 22
 ht.onionmat-method (onionmat), 22
 i (Extract), 13
 i.onion-method (Extract), 13
 i.onionmat-method (Extract), 13
 i.octonion (Extract), 13
 i.quaternion (Extract), 13
 i<- (Extract), 13
 i<-, onion-method (Extract), 13
 i<-, onionmat-method (Extract), 13
 i<-.octonion (Extract), 13
 i<-.quaternion (Extract), 13
 il (Extract), 13
 il.octonion-method (Extract), 13
 il.onionmat-method (Extract), 13
 il.octonion (Extract), 13
 il<- (Extract), 13
 il<-, octonion-method (Extract), 13
 il<-, onionmat-method (Extract), 13
 il<-.octonion (Extract), 13
 Im(Complex), 9
 Im.onion-method (Complex), 9
 Im.onionmat-method (Complex), 9
 Im<- (Complex), 9
 Im<-, onion-method (Complex), 9
 Im<-, onionmat-method (Complex), 9
 Im<-.quaternion (Extract), 13
 index-class (onion-class), 21
 is.octonion (onion), 19
 is.onion (onion), 19
 is.onionmat (onionmat), 22
 is.quaternion (onion), 19
 is_orthogonal (orthogonal), 25
 j (Extract), 13
 j.onion-method (Extract), 13
 j.onionmat-method (Extract), 13
 j.octonion (Extract), 13
 j.quaternion (Extract), 13
 j<- (Extract), 13
 j<-, onion-method (Extract), 13
 j<-, onionmat-method (Extract), 13
 j<-.octonion (Extract), 13
 j<-.quaternion (Extract), 13
 jl (Extract), 13
 jl.octonion-method (Extract), 13
 jl.onionmat-method (Extract), 13
 jl.octonion (Extract), 13

jl<- (Extract), 13
 jl<-, octonion-method (Extract), 13
 jl<-, onionmat-method (Extract), 13
 jl<-.octonion (Extract), 13
 k (Extract), 13
 k.onion-method (Extract), 13
 k.onionmat-method (Extract), 13
 k.octonion (Extract), 13
 k.quaternion (Extract), 13
 k<- (Extract), 13
 k<-, onion-method (Extract), 13
 k<-, onionmat-method (Extract), 13
 k<-.octonion (Extract), 13
 k<-.quaternion (Extract), 13
 kl (Extract), 13
 kl.octonion-method (Extract), 13
 kl.onionmat-method (Extract), 13
 kl.octonion (Extract), 13
 kl<- (Extract), 13
 kl<-, octonion-method (Extract), 13
 kl<-, onionmat-method (Extract), 13
 kl<-.octonion (Extract), 13
 l (Extract), 13
 l.octonion-method (Extract), 13
 l.onion-method (Extract), 13
 l.onionmat-method (Extract), 13
 l.octonion (Extract), 13
 l<- (Extract), 13
 l<-, octonion-method (Extract), 13
 l<-, onionmat-method (Extract), 13
 l<-.octonion (Extract), 13
 length, 14
 length.onion-method (length), 14
 length.onion (length), 14
 length<- (length), 14
 length<-, onion-method (length), 14
 length<-.onion (length), 14
 log(Math), 16
 log.onion-method (Math), 16
 Logic, 15
 Logic, ANY.onion-method (Logic), 15
 Logic, onion, ANY-method (Logic), 15
 Logic, onion, missing-method (Logic), 15
 Logic, onion-method (Logic), 15
 logic.onion (Logic), 15
 Math, 16

matrix,onion-method (onionmat), 22
 matrix2quaternion (orthogonal), 25
 matrix_arith_onion (onionmat), 22
 matrix_arith_onionmat (onionmat), 22
 matrix_plus_onion (onionmat), 22
 matrix_plus_onionmat (onionmat), 22
 matrix_prod_onion (onionmat), 22
 max (sum), 33
 min (sum), 33
 Mod (Complex), 9
 Mod, onion-method (Complex), 9
 Mod, onionmat-method (Complex), 9

 names, 17
 names,onion-method (names), 17
 names,onionmat-method (names), 17
 names.onion (names), 17
 names.onion<- (names), 17
 names<- (names), 17
 names<-,onion-method (names), 17
 names<-,onionmat-method (names), 17
 names<-.onion (names), 17
 ncol (onionmat), 22
 ncol,ANY-method (onionmat), 22
 ncol,onionmat-method (names), 17
 ncol-methods (onionmat), 22
 ncol.onionmat (onionmat), 22
 newonionmat (onionmat), 22
 Norm (Complex), 9
 Norm,onion-method (Complex), 9
 Norm,onionmat-method (Complex), 9
 Norm.onion (Complex), 9
 nrow (onionmat), 22
 nrow,ANY-method (onionmat), 22
 nrow,onionmat-method (names), 17
 nrow-methods (onionmat), 22
 nrow.onionmat (onionmat), 22
 numeric_arith_onion (Arith), 4
 numeric_arith_onionmat (onionmat), 22
 numeric_matrixprod_onionmat (onionmat), 22

 00 (01), 18
 01, 18
 0all (01), 18
 Octonion (onion), 19
 octonion (onion), 19
 octonion-class (onion-class), 21
 octonion_prod_octonion (Arith), 4

 octonion_to_quaternion (onion), 19
 Oi (01), 18
 Oil (01), 18
 Oim (01), 18
 Oj (01), 18
 Ojl (01), 18
 Ok (01), 18
 Okl (01), 18
 Ol (01), 18
 om_cprod (onionmat), 22
 om_ht (onionmat), 22
 om_prod (onionmat), 22
 om_tcprod (onionmat), 22
 onion, 19
 onion-class, 21
 onion-package, 2
 onion_abs (Complex), 9
 onion_acos (Math), 16
 onion_acosh (Math), 16
 onion_allsum (sum), 33
 onion_arith_matrix (onionmat), 22
 onion_arith_numeric (Arith), 4
 onion_arith_onion (Arith), 4
 onion_arith_onionmat (onionmat), 22
 onion_arith_single (onionmat), 22
 onion_asin (Math), 16
 onion_asinh (Math), 16
 onion_atan (Math), 16
 onion_atanh (Math), 16
 onion_compare (Compare-methods), 9
 onion_complex (Complex), 9
 onion_conjugate (Complex), 9
 onion_cos (Math), 16
 onion_cosh (Math), 16
 onion_cumprod (cumsum), 12
 onion_cumsum (cumsum), 12
 onion_e_even (prods), 27
 onion_e_odd (prods), 27
 onion_exp (Math), 16
 onion_g_even (prods), 27
 onion_g_odd (prods), 27
 onion_imag (Complex), 9
 onion_inverse (Arith), 4
 onion_log (Math), 16
 onion_logic (Logic), 15
 onion_matrixprod_onionmat (onionmat), 22
 onion_mod (Complex), 9
 onion_negative (Arith), 4

onion_plus_numeric (Arith), 4
 onion_plus_onion (Arith), 4
 onion_power_matrix (onionmat), 22
 onion_power_numeric (Arith), 4
 onion_power_singleinteger (Arith), 4
 onion_prod_numeric (Arith), 4
 onion_prod_onion (Arith), 4
 onion_re (Complex), 9
 onion_show (show), 32
 onion_sign (Math), 16
 onion_sin (Math), 16
 onion_sinh (Math), 16
 onion_sqrt (Math), 16
 onion_tan (Math), 16
 onion_tanh (Math), 16
 onionmat, 22
 onionmat-class (onion-class), 21
 onionmat_allsum (sum), 33
 onionmat_arith_matrix (onionmat), 22
 onionmat_arith_onion (onionmat), 22
 onionmat_arith_onionmat (onionmat), 22
 onionmat_arith_single (onionmat), 22
 onionmat_compare_onionmat
 (Compare-methods), 9
 onionmat_compare_single
 (Compare-methods), 9
 onionmat_complex (onionmat), 22
 onionmat_conjugate (onionmat), 22
 onionmat_equal_onionmat
 (Compare-methods), 9
 onionmat_equal_single
 (Compare-methods), 9
 onionmat_imag (onionmat), 22
 onionmat_inv (onionmat), 22
 onionmat_inverse (onionmat), 22
 onionmat_matrixprod_numeric (onionmat),
 22
 onionmat_matrixprod_onion (onionmat), 22
 onionmat_matrixprod_onionmat
 (onionmat), 22
 onionmat_mod (onionmat), 22
 onionmat_neg (onionmat), 22
 onionmat_negative (onionmat), 22
 onionmat_plus_matrix (onionmat), 22
 onionmat_plus_onionmat (onionmat), 22
 onionmat_plus_single (onionmat), 22
 onionmat_power_matrix (onionmat), 22
 onionmat_power_onionmat (onionmat), 22

onionmat_power_single (onionmat), 22
 onionmat_prod_matrix (onionmat), 22
 onionmat_prod_onionmat (onionmat), 22
 onionmat_prod_single (onionmat), 22
 onionmat_re (onionmat), 22
 onionmat_show (show), 32
 onionmat_unary (onionmat), 22
 onionmatprod (onionmat), 22
 Ops.onionmat (onionmat), 22
 orthogonal, 25, 31

 p3d, 26
 plot, 27
 plot, onion-method (plot), 27
 plot.onion (plot), 27
 print (show), 32
 print, onion-method (show), 32
 print.octonion (show), 32
 print.onion (show), 32
 print.onionmat (show), 32
 print.quaternion (show), 32
 prod (sum), 33
 prod, octonion-method (sum), 33
 prod, quaternion-method (sum), 33
 prods, 27

 Quaternion (onion), 19
 quaternion (onion), 19
 quaternion-class (onion-class), 21
 quaternion_allprod (sum), 33
 quaternion_prod_quaternion (Arith), 4
 quaternion_to_octonion (onion), 19

 range (sum), 33
 rbind (bind), 6
 rbind2, matrix, onion-method (bind), 6
 rbind2, matrix, onionmat-method (bind), 6
 rbind2, numeric, onion-method (bind), 6
 rbind2, numeric, onionmat-method (bind), 6
 rbind2, onion, matrix-method (bind), 6
 rbind2, onion, numeric-method (bind), 6
 rbind2, onion, onion-method (bind), 6
 rbind2, onion, onionmat-method (bind), 6
 rbind2, onionmat, matrix-method (bind), 6
 rbind2, onionmat, numeric-method (bind), 6
 rbind2, onionmat, onion-method (bind), 6
 rbind2, onionmat, onionmat-method (bind),
 6
 Re (Complex), 9

Re, onion-method (Complex), 9
Re, onionmat-method (Complex), 9
Re<- (Complex), 9
Re<-, onion-method (Complex), 9
Re<-, onionmat-method (Complex), 9
Re<-. quaternion (Extract), 13
rep, 29
rep, onion-method (rep), 29
rep.onion (rep), 29
roct, 30
romat (roct), 30
ronionmat (roct), 30
rotate, 25, 31
rownames (names), 17
rownames, ANY-method (onionmat), 22
rownames, onionmat-method (names), 17
rownames-methods (onionmat), 22
rownames.onionmat (onionmat), 22
rownames<- (onionmat), 22
rownames<-, ANY-method (onionmat), 22
rownames<-, onionmat-method (names), 17
rownames<--methods (onionmat), 22
rownames<-. onionmat (onionmat), 22
rquat (roct), 30

seq, 32
seq, onion-method (seq), 32
seq.onion (seq), 32
seq_onion (seq), 32
show, 32
show, onion-method (show), 32
sign, onion-method (Complex), 9
sin (Math), 16
sin, onion-method (Math), 16
single_arith_onionmat (onionmat), 22
single_compare_onionmat
 (Compare-methods), 9
single_power_onionmat (onionmat), 22
single_prod_onionmat (onionmat), 22
sinh (Math), 16
sinh, onion-method (Math), 16
SLERP (seq), 32
slerp (seq), 32
sqrt (Math), 16
str, onion-method (sum), 33
str_onion (sum), 33
sum, 33
sum, octonion-method (sum), 33
sum, onion-method (sum), 33

sum, onionmat-method (sum), 33
sum, quaternion-method (sum), 33
Summary, onion-method (sum), 33

t, onion-method (onionmat), 22
t, onionmat-method (onionmat), 22
t.onion (onionmat), 22
t.onionmat (onionmat), 22
tan (Math), 16
tan, onion-method (Math), 16
tanh (Math), 16
tanh, onion-method (Math), 16
tcpd (onionmat), 22
tcpd, ANY, ANY-method (onionmat), 22
tcpd, ANY, missing-method (onionmat), 22
tcpd, ANY, onionmat-method (onionmat),
 22
tcpd, onion, missing-method (onionmat),
 22
tcpd, onion, onion-method (onionmat), 22
tcpd, onion, onionmat-method
 (onionmat), 22
tcpd, onionmat, ANY-method (onionmat),
 22
tcpd, onionmat, missing-method
 (onionmat), 22
tcpd, onionmat, onion-method
 (onionmat), 22
tcpd, onionmat, onionmat-method
 (onionmat), 22
threeform, 34
type (onion), 19

zap (zapsmall), 35
zapsmall, 35
zapsmall, onion-method (zapsmall), 35
zapsmall, onionmat-method (zapsmall), 35