

Package ‘synthACS’

August 18, 2022

Title Synthetic Microdata and Spatial MicroSimulation Modeling for ACS Data

Version 1.7.0

Maintainer Alex Whitworth <whitworth.alex@gmail.com>

Description Provides access to curated American Community Survey (ACS) base tables via a wrapper to library(acs). Builds synthetic micro-datasets at any user-specified geographic level with ten default attributes; and, conducts spatial microsimulation modeling (SMSM) via simulated annealing. SMSM is conducted in parallel by default. Lastly, we provide functionality for data-extensibility of micro-datasets.

Depends R (>= 3.5.0)

Imports data.table (>= 1.9.6), Rcpp, acs (>= 2.1), retry

License MIT + file LICENSE

LazyData true

Suggests testthat, sp (>= 1.2), knitr, rmarkdown, R.rsp

RoxygenNote 7.2.1

Encoding UTF-8

LinkingTo Rcpp

VignetteBuilder knitr, R.rsp

NeedsCompilation yes

Author Alex Whitworth [aut, cre]

Repository CRAN

Date/Publication 2022-08-18 17:30:01 UTC

R topics documented:

add_constraint	3
adjDR	4
AgeRaceDR	5
all_geogs_add_constraint	5
all_geog_constraint_age	7

all_geog_constraint_edu	7
all_geog_constraint_employment	8
all_geog_constraint_gender	9
all_geog_constraint_geog_mob	10
all_geog_constraint_income	10
all_geog_constraint_marital_status	11
all_geog_constraint_nativity	12
all_geog_constraint_poverty	13
all_geog_constraint_race	13
all_geog_optimize_microdata	14
all_geog_synthetic_new_attribute	15
BR2014	17
calculate_TAE	18
combine_smsm	19
derive_synth_datasets	19
fetch_data	21
gen_attr_vectors	21
get_best_fit	22
get_dataset_names	22
get_endyear	23
get_final_tae	23
get_geography	23
get_span	24
is.macroACS	24
is.macro_micro	25
is.micro_synthetic	25
is.smsm_set	26
is.synthACS	26
la_hospitals	27
LifeExp	27
marginalize_attr	28
MBR	29
optimize_microdata	30
plot_TAEpath	31
pull_acs_basetables	32
pull_bachelors	33
pull_edu	33
pull_geo_mobility	34
pull_household	35
pull_inc_earnings	35
pull_mar_status	36
pull_population	37
pull_pov_inc	37
pull_race_data	38
pull_synth_data	39
pull_transit_work	40
rawDR	40
split	41

add_constraint 3

stateFR	42
summary.smsm_set	43
synthetic_new_attribute	43
TFR	45

Index 46

add_constraint *Add new constraint to constraint table*

Description

Add a new constraint to the mapping between a given macro dataset (class "macroACS") and a matching micro dataset (class "micro_synthetic"). May be called repeatedly to create a set of constraints.

Usage

```
add_constraint(  
  attr_name = "variable",  
  attr_totals,  
  micro_data,  
  constraint_list = NULL  
)
```

Arguments

attr_name The name of the attribute, or variable, that you wish to constrain.

attr_totals A named integer vector of counts per level of the new constraining attribute.

micro_data The micro dataset, of class "micro_synthetic", for which you wish to add a constraint.

constraint_list
 A list of prior constraints on the same dataset which you wish to add to. Defaults to NULL (ie. the default is that this is the first constraint.)

Value

A list of constraints.

Examples

```
## Not run:  
## assumes that you have a micro_synthetic dataset named test_micro and attribute counts  
## named a,e,g respectively  
c_list <- add_constraint(attr_name= "age", attr_totals= a, micro_data= test_micro)  
c_list <- add_constraint(attr_name= "edu_attain", attr_totals= e, micro_data= test_micro,  
                          constraint_list= c_list)  
c_list <- add_constraint(attr_name= "gender", attr_totals= g, micro_data= test_micro,  
                          constraint_list= c_list)
```

```
## End(Not run)
```

 adjDR

Age-adjusted Death Rate by race and gender

Description

A dataset containing age-adjusted death rate data by race and gender of the deceased. Data is provided for 1980-2013.

Usage

```
adjDR
```

Format

A data.frame with 612 observations and 4 variables.

year The year for which data was recorded.

race The racial group of the deceased One of all all races; white whites; black_aa black / African-American; nat_amer American Indian or Native Alaskan; asian_isl Asian or Pacific Islander; hisp_lat Hispanic.

gender The gender of the deceased. One of c(both, male, female)

adj_death_rate The age-adjusted death rate. See details.

Details

- The age-adjusted death rates are used to compare relative mortality risks among groups and over time. They were computed by the direct method, which is defined

$$R' = \sum_i \frac{P_{si}}{P_s} R_i$$

where P_{si} is the standard population for age group i , P_s is the total US standard population and R_i is the raw death rate for age group i .

- Populations are based on census counts enumerated as of April 1 of the census year and estimated as of July 1 for non-census years.

Source

<https://www.cdc.gov/nchs/nvss/deaths.htm>

References

Xu, J. Q., S. L. Murphy, and K. D. Kochanek. "Deaths: final data for 2013." National Vital Statistics Reports 64.2 (2015).

AgeRaceDR

*Death rates in the United States by age and race, 2013***Description**

A dataset containing death rates for individuals by age group and race for the United States, 2013.

Usage

AgeRaceDR

Format

A data.frame with 360 observations and 4 variables.

age The exact age, in years, at which life expectancy is calculated.

race The racial group of the deceased One of all all races; white whites; black black / African-American; hispanic Hispanic; asian.isl Asian and Pacific Islander; nat.amer Native American or Alaska Native.

gender The gender of the deceased. One of c(both, male, female)

death_rate The raw death rate. See details.

Details

- The death rate is defined as deaths per 100,000 population.

Source

<https://www.cdc.gov/nchs/nvss/deaths.htm>

References

Xu, J. Q., S. L. Murphy, and K. D. Kochanek. "Deaths: final data for 2013." National Vital Statistics Reports 64.2 (2015).

all_geogs_add_constraint

*Add new constraint to a set of geographies***Description**

Add a new constraint to the mapping between a set of macro datasets and a matching set of micro dataset (supplied as class 'macro_micro'). May be called repeatedly to create a set of constraints across the sub-geographies.

Usage

```
all_geogs_add_constraint(
  attr_name = "variable",
  attr_total_list,
  macro_micro,
  constraint_list_list = NULL
)
```

Arguments

`attr_name` The name of the attribute, or variable, that you wish to constrain.

`attr_total_list` A list of named integer vectors containing counts per level of the new constraining attribute for each geography.

`macro_micro` The geographical dataset of macro and micro data. Should be of class "macro_micro".

`constraint_list_list` A list of lists containing prior constraints on the same dataset for which you wish to add to. Defaults to NULL (ie. the default is that this is the first constraint.)

Value

A list of constraint lists.

See Also

[add_constraint](#)

Examples

```
## Not run:
# assumes that micro_synthetic already exists in your environment

# 1. build constraints for gender and age
g <- all_geog_constraint_gender(micro_synthetic, method= "macro.table")

a <- all_geog_constraint_age(micro_synthetic, method= "macro.table")

# 2. bind constraints to geographies and macro-data
c11 <- all_geogs_add_constraint(attr_name= "age", attr_total_list= a,
                               macro_micro= micro_synthetic)
c11 <- all_geogs_add_constraint(attr_name= "gender", attr_total_list= g,
                               macro_micro= micro_synthetic, constraint_list_list= c11)

## End(Not run)
```

`all_geog_constraint_age`*Create age constraint list to a set of geographies*

Description

Create a new age constraint list to the mapping between a a set of macro datasets and a matching set of micro dataset (supplied as class 'synthACS').

Usage

```
all_geog_constraint_age(obj, method = c("synthetic", "macro.table"))
```

Arguments

<code>obj</code>	An object of class "synthACS".
<code>method</code>	One of <code>c("synthetic", "macro.table")</code> . Specifying "synthetic" indicates that constraints are built by marginalizing the synthetic micro datasets. Specifying "macro.table" indicates that the constraints are build from the data in the base ACS tables.

See Also

[all_geogs_add_constraint](#)

Examples

```
## Not run:  
# assumes that obj of class 'synthACS' already exists in your environment  
a1 <- all_geog_constraint_age(obj, "synthetic")  
a2 <- all_geog_constraint_age(obj, "macro_table")  
  
## End(Not run)
```

`all_geog_constraint_edu`*Create educational attainment constraint list to a set of geographies*

Description

Create a new educational attainment constraint list to the mapping between a a set of macro datasets and a matching set of micro dataset (supplied as class 'synthACS').

Usage

```
all_geog_constraint_edu(obj, method = c("synthetic", "macro.table"))
```

Arguments

obj	An object of class "synthACS".
method	One of c("synthetic", "macro.table"). Specifying "synthetic" indicates that constraints are built by marginalizing the synthetic micro datasets. Specifying "macro.table" indicates that the constraints are build from the data in the base ACS tables.

See Also

[all_geogs_add_constraint](#)

Examples

```
## Not run:  
# assumes that obj of class 'synthACS' already exists in your environment  
e1 <- all_geog_constraint_edu(obj, "synthetic")  
e2 <- all_geog_constraint_edu(obj, "macro_table")  
  
## End(Not run)
```

all_geog_constraint_employment

Create employment status constraint list to a set of geographies

Description

Create a new employment status constraint list to the mapping between a a set of macro datasets and a matching set of micro dataset (supplied as class 'synthACS').

Usage

```
all_geog_constraint_employment(obj, method = c("synthetic", "macro.table"))
```

Arguments

obj	An object of class "synthACS".
method	One of c("synthetic", "macro.table"). Specifying "synthetic" indicates that constraints are built by marginalizing the synthetic micro datasets. Specifying "macro.table" indicates that the constraints are build from the data in the base ACS tables.

See Also

[all_geogs_add_constraint](#)

Examples

```
## Not run:  
# assumes that obj of class 'synthACS' already exists in your environment  
e1 <- all_geog_constraint_employment(obj, "synthetic")  
e2 <- all_geog_constraint_employment(obj, "macro_table")  
  
## End(Not run)
```

all_geog_constraint_gender

Create gender constraint list to a set of geographies

Description

Create a new gender constraint list to the mapping between a a set of macro datasets and a matching set of micro dataset (supplied as class 'synthACS').

Usage

```
all_geog_constraint_gender(obj, method = c("synthetic", "macro.table"))
```

Arguments

obj	An object of class "synthACS".
method	One of c("synthetic", "macro.table"). Specifying "synthetic" indicates that constraints are built by marginalizing the synthetic micro datasets. Specifying "macro.table" indicates that the constraints are build from the data in the base ACS tables.

See Also

[all_geogs_add_constraint](#)

Examples

```
## Not run:  
# assumes that obj of class 'synthACS' already exists in your environment  
g1 <- all_geog_constraint_gender(obj, "synthetic")  
g2 <- all_geog_constraint_gender(obj, "macro_table")  
  
## End(Not run)
```

`all_geog_constraint_geog_mob`*Create geographic mobility constraint list to a set of geographies*

Description

Create a new geographic mobility constraint list to the mapping between a a set of macro datasets and a matching set of micro dataset (supplied as class 'synthACS').

Usage

```
all_geog_constraint_geog_mob(obj, method = c("synthetic", "macro.table"))
```

Arguments

<code>obj</code>	An object of class "synthACS".
<code>method</code>	One of <code>c("synthetic", "macro.table")</code> . Specifying "synthetic" indicates that constraints are built by marginalizing the synthetic micro datasets. Specifying "macro.table" indicates that the constraints are build from the data in the base ACS tables.

See Also

[all_geogs_add_constraint](#)

Examples

```
## Not run:  
# assumes that obj of class 'synthACS' already exists in your environment  
gm1 <- all_geog_constraint_geog_mob(obj, "synthetic")  
gm2 <- all_geog_constraint_geog_mob(obj, "macro.table")  
  
## End(Not run)
```

`all_geog_constraint_income`*Create individual income constraint list to a set of geographies*

Description

Create a new individual income constraint list to the mapping between a a set of macro datasets and a matching set of micro dataset (supplied as class 'synthACS').

Usage

```
all_geog_constraint_income(obj, method = c("synthetic", "macro.table"))
```

Arguments

obj	An object of class "synthACS".
method	One of c("synthetic", "macro.table"). Specifying "synthetic" indicates that constraints are built by marginalizing the synthetic micro datasets. Specifying "macro.table" indicates that the constraints are build from the data in the base ACS tables.

See Also

[all_geogs_add_constraint](#)

Examples

```
## Not run:  
# assumes that obj of class 'synthACS' already exists in your environment  
i1 <- all_geog_constraint_income(obj, "synthetic")  
i2 <- all_geog_constraint_income(obj, "macro.table")  
  
## End(Not run)
```

all_geog_constraint_marital_status

Create marital status constraint list to a set of geographies

Description

Create a new marital status constraint list to the mapping between a a set of macro datasets and a matching set of micro dataset (supplied as class 'synthACS').

Usage

```
all_geog_constraint_marital_status(obj, method = c("synthetic", "macro.table"))
```

Arguments

obj	An object of class "synthACS".
method	One of c("synthetic", "macro.table"). Specifying "synthetic" indicates that constraints are built by marginalizing the synthetic micro datasets. Specifying "macro.table" indicates that the constraints are build from the data in the base ACS tables.

See Also

[all_geogs_add_constraint](#)

Examples

```
## Not run:  
# assumes that obj of class 'synthACS' already exists in your environment  
m1 <- all_geog_constraint_marital_status(obj, "synthetic")  
m2 <- all_geog_constraint_marital_status(obj, "macro_table")  
  
## End(Not run)
```

all_geog_constraint_nativity

Create nativity status constraint list to a set of geographies

Description

Create a new nativity status constraint list to the mapping between a a set of macro datasets and a matching set of micro dataset (supplied as class 'synthACS').

Usage

```
all_geog_constraint_nativity(obj, method = c("synthetic", "macro.table"))
```

Arguments

obj	An object of class "synthACS".
method	One of c("synthetic", "macro.table"). Specifying "synthetic" indicates that constraints are built by marginalizing the synthetic micro datasets. Specifying "macro.table" indicates that the constraints are build from the data in the base ACS tables.

See Also

[all_geogs_add_constraint](#)

Examples

```
## Not run:  
# assumes that obj of class 'synthACS' already exists in your environment  
n1 <- all_geog_constraint_nativity(obj, "synthetic")  
n2 <- all_geog_constraint_nativity(obj, "macro_table")  
  
## End(Not run)
```

`all_geog_constraint_poverty`*Create poverty status constraint list to a set of geographies*

Description

Create a new poverty status constraint list to the mapping between a a set of macro datasets and a matching set of micro dataset (supplied as class 'synthACS').

Usage

```
all_geog_constraint_poverty(obj, method = c("synthetic", "macro.table"))
```

Arguments

<code>obj</code>	An object of class "synthACS".
<code>method</code>	One of <code>c("synthetic", "macro.table")</code> . Specifying "synthetic" indicates that constraints are built by marginalizing the synthetic micro datasets. Specifying "macro.table" indicates that the constraints are build from the data in the base ACS tables.

See Also

[all_geogs_add_constraint](#)

Examples

```
## Not run:
# assumes that obj of class 'synthACS' already exists in your environment
p1 <- all_geog_constraint_poverty(obj, "synthetic")
p2 <- all_geog_constraint_poverty(obj, "macro_table")

## End(Not run)
```

`all_geog_constraint_race`*Create race constraint list to a set of geographies*

Description

Create a new race constraint list to the mapping between a a set of macro datasets and a matching set of micro dataset (supplied as class 'synthACS').

Usage

```
all_geog_constraint_race(obj, method = c("synthetic", "macro.table"))
```

Arguments

obj	An object of class "synthACS".
method	One of c("synthetic", "macro.table"). Specifying "synthetic" indicates that constraints are built by marginalizing the synthetic micro datasets. Specifying "macro.table" indicates that the constraints are build from the data in the base ACS tables.

See Also

[all_geogs_add_constraint](#)

Examples

```
## Not run:
# assumes that obj of class 'synthACS' already exists in your environment
r1 <- all_geog_constraint_race(obj, "synthetic")
r2 <- all_geog_constraint_race(obj, "macro_table")

## End(Not run)
```

all_geog_optimize_microdata

Optimize the selection of a micro data population for a set of geographies.

Description

Optimize the candidate micro datasets such that the lowest loss against the macro dataset constraints are obtained. Loss is defined here as total absolute error (TAE) and constraints are defined by the constraint_list_list. Optimization is done by simulated annealing and geographies are run in parallel.

Usage

```
all_geog_optimize_microdata(
  macro_micro,
  prob_name = "p",
  constraint_list_list,
  p_accept = 0.4,
  max_iter = 10000L,
  seed = sample.int(10000L, size = 1, replace = FALSE),
  leave_cores = 1L,
  verbose = TRUE
)
```

Arguments

macro_micro	The geographical dataset of macro and micro data. Should be of class "macro_micro".
prob_name	It is assumed that observations are weighted and do not have an equal probability of occurrence. This string specifies the variable within each dataset that contains the probability of selection.
constraint_list_list	A list of constraint lists. See add_constraint , all_geogs_add_constraint
p_accept	The acceptance probability for the Metropolis acceptance criteria.
max_iter	The maximum number of allowable iterations. Defaults to 10000L
seed	A seed for reproducibility. See set.seed
leave_cores	An integer for the number of cores you wish to leave open for other processing.
verbose	Logical. Do you wish to see verbose output? Defaults to TRUE

See Also

[optimize_microdata](#)

Examples

```
## Not run:
# assumes that micro_synthetic and cll already exist in your environment
# see: examples for derive_synth_datasets() and all_geogs_add_constraint()
optimized_la <- all_geog_optimize_microdata(micro_synthetic, prob_name= "p",
  constraint_list_list= cll, p_accept= 0.01, max_iter= 1000L)

## End(Not run)
```

all_geog_synthetic_new_attribute

Add a new attribute to a set (ie list) of synthetic_micro datasets

Description

Add a new attribute to a set (ie list) of synthetic_micro datasets using conditional relationships between the new attribute and existing attributes (eg. wage rate conditioned on age and education level). The same attribute is added to *each* synthetic_micro dataset, where each dataset is supplied a distinct relationship for attribute creation.

Usage

```
all_geog_synthetic_new_attribute(
  df_list,
  prob_name = "p",
  attr_name = "variable",
  conditional_vars = NULL,
  st_list = NULL,
  leave_cores = 1L
)
```

Arguments

df_list	A list of R objects each of class "synthetic_micro".
prob_name	A string specifying the column name of each data.frame in df_list containing the probabilities for each synthetic observation.
attr_name	A string specifying the desired name of the new attribute to be added to the data.
conditional_vars	An character vector specifying the existing variables, if any, on which the new attribute (variable) is to be conditioned on for each dataset. Variables must be specified in order. Defaults to NULL ie- an unconditional new attribute.
st_list	A list of equal length to df_list. Each element of st_list is a data.frame symbol table with N + 2 columns. The last two columns must be: 1. A vector containing the new attribute counts or percentages; 2. is a vector of the new attribute levels. The first N columns must match the conditioning scheme imposed by the variables in conditional_vars. See synthetic_new_attribute and examples.
leave_cores	An integer for the number of cores you wish to leave open for other processing.

Value

A list of new synthetic_micro datasets each with class "synthetic_micro".

See Also

[synthetic_new_attribute](#)

Examples

```
## Not run:
set.seed(567L)
df <- data.frame(gender= factor(sample(c("male", "female"), size= 100, replace= TRUE)),
                 age= factor(sample(1:5, size= 100, replace= TRUE)),
                 pov= factor(sample(c("lt_pov", "gt_eq_pov"),
                                   size= 100, replace= TRUE, prob= c(.15,.85))),
                 p= runif(100))
df$p <- df$p / sum(df$p)
class(df) <- c("data.frame", "micro_synthetic")

# and example test elements
cond_v <- c("gender", "pov")
levels <- c("employed", "unemp", "not_in_LF")
sym_tbl <- data.frame(gender= rep(rep(c("male", "female"), each= 3), 2),
                     pov= rep(c("lt_pov", "gt_eq_pov"), each= 6),
                     cnts= c(52, 8, 268, 72, 12, 228, 1338, 93, 297, 921, 105, 554),
                     lvl= rep(levels, 4))

df_list <- replicate(10, df, simplify= FALSE)
st_list <- replicate(10, sym_tbl, simplify= FALSE)
```



```
# run
library(parallel)
syn <- all_geog_synthetic_new_attribute(df_list, prob_name= "p", attr_name= "variable",
                                       conditional_vars= cond_v, st_list= st_list)

## End(Not run)
```

BR2014

Birth Rates by Age and Race of Mother

Description

A dataset containing birth rate data in the United States by age and race of the mother. Data for all races is provided for 1970-2014 and for individual races from 1989-2014.

Usage

BR2014

Format

A data.frame with 1,750 observations and 4 variables.

year The year for which data was recorded.

race The racial group of the mothers. One of all all races; white non-hispanic whites; black_aa black / African-American; nat_amer American Indian or Native Alaskan; asian_isl Asian or Pacific Islander; hisp_lat Hispanic or Latin American.

age_group The age group of the mother.

birth_rate The birth rate. See Details.

Details

- The birth rate is defined as births per 1,000 women in the specified group (age and race).
- Populations are based on census counts enumerated as of April 1 of the census year and estimated as of July 1 for non-census years.
- Beginning in 1997, birth rates for age group 45up by relating births to all women age 45 or older to this group. Prior to 1997, only births to women age 45-49 were included.

Source

<https://www.cdc.gov/nchs/nvss/births.htm>

References

Hamilton, Brady E., et al. "Births: final data for 2014." National Vital Statistics Reports 64.12 (2015): 1-64.

calculate_TAE	<i>Calculate the total absolute error (TAE) between sample data and constraints.</i>
---------------	--

Description

Calculates the total absolute error (TAE) between sample micro data and constraining totals from the matching macro data. Allows for updating of prior TAE instead of re-calculating to improve speed in iterating. The updating feature is particularly helpful for optimizing micro data fitting via simulated annealing (see [optimize_microdata](#)).

Usage

```
calculate_TAE(
  sample_data,
  constraint_list,
  prior_sample_totals = NULL,
  dropped_obs_totals = NULL,
  new_obs = NULL
)
```

Arguments

sample_data	A data.frame with attributes matching constraint_list.
constraint_list	A list of constraints. See add_constraint .
prior_sample_totals	An optional list containing attribute counts of a prior sample corresponding to the constraint list. Defaults to NULL.
dropped_obs_totals	An optional list containing attribute counts from the dropped observations in a prior sample. Defaults to NULL.
new_obs	An optional data.frame containing new observations with attributes matching those in sample_data, constraint_list, and prior_sample_totals. Defaults to NULL.

Examples

```
## Not run:
## assumes that you have a micro_synthetic dataset named test_micro and attribute count
## named g respectively
c_list <- add_constraint(attr_name= "gender", attr_totals= g, micro_data= test_micro,
  constraint_list= c_list)
calculate_TAE(test_micro, c_list)

## End(Not run)
```

combine_smsm	<i>Combine separate SMSM optimizations</i>
--------------	--

Description

Combine objects of class "smsm_set" into a single object of class "smsm_set"

Usage

```
combine_smsm(...)
```

Arguments

... A list of objects of class 'smsm_set'.

See Also

[split](#), [all_geog_optimize_microdata](#)

Examples

```
## Not run:
combined <- combine_smsm(smsm1, smsm2, smsm3)

## End(Not run)
```

derive_synth_datasets	<i>Derive synthetic micro datasets for a given geography.</i>
-----------------------	---

Description

Derive synthetic micro datasets for each sub-geography of a given set of geographic macro data constraining tabulations. See Details... By default, micro dataset generation is run in parallel with load balancing. Macro data is assumed to have been pulled from the US Census API via the acs package.

Usage

```
derive_synth_datasets(macro_data, parallel = TRUE, leave_cores = 2)
```

Arguments

macro_data A macro dataset list: the result of [pull_synth_data](#).
parallel Logical, defaults to TRUE. Do you wish to run the operation in parallel?
leave_cores How many cores do you wish to leave open to other processing?

Value

A list of the input macro datasets produced by [pull_synth_data](#) and a list of synthetic micro datasets for each geographical subset within the specified macro geography.

Details

In the absence of true micro level datasets for a given geographic area, synthetic datasets can be used. This function uses conditional and marginal probability distributions (at the aggregate level) to generate synthetic micro population datasets, which are built one constraint at a time. Taking as input the macro level data (class "macroACS"), this function builds synthetic micro datasets for each lower level geographical area within the area of study.

In simplest terms, the goal is to generate a joint probability distribution for an attribute vector; and, to create synthetic individuals from this distribution. However, note that information for the full joint distribution is typically not available, so we construct it as a product of conditional and marginal probabilities. This is done one attribute at a time; where it is assumed that there is some sort of continuum of attribute dependence. That is, some attributes are more important (eg. gender, age) in 'determining' others (eg. educational attainment, marital status, etc). These more important attributes need to be assigned first, whereas less important attributes may be assigned later. Most of these distinctions are largely intuitive, but care must be taken in choosing the order of constructed attributes.

This function provides a synthetic population with the following characteristics as well as each synthetic individual's probability of inclusion. The included characteristics are: age, gender, marital status, educational attainment, employment status, nativity, poverty status, geographic mobility in the prior year, individual income, and race. Additional attributes which interest the user may be added in a similar manner via [synthetic_new_attribute](#).

Note: INDIVIDUAL, not HOUSEHOLD level, synthetic population datasets are created.

References

Birkin, Mark, and M. Clarke. "SYNTHESIS-a synthetic spatial information system for urban and regional analysis: methods and examples." *Environment and planning A* 20.12 (1988): 1645-1671.

See Also

[pull_synth_data](#), [acs.fetch](#), [geo.make](#)

Examples

```
## Not run:
# make geography
la_geo <- acs::geo.make(state= "CA", county= "Los Angeles", tract= "*" )
# pull data elements for creating synthetic data
la_dat <- pull_synth_data(2014, 5, la_geo)
# derive synthetic data
la_synthetic <- derive_synth_datasets(la_dat, leave_cores= 0)

## End(Not run)
```

fetch_data	<i>Get Aggregate Data Specified Geography</i>
------------	---

Description

Gets aggregate, macro, data, either estimate or standard error, for a specified geography and specified dataset.

Usage

```
fetch_data(acs, geography, dataset = c("estimate", "st.err"), choice = NULL)
```

Arguments

acs	An object of class "macroACS".
geography	A character vector allowing string matching via grep to a set of specified geographies. All values may be specified by "*".
dataset	Either "estimate" or "st.err". Do you want data on estimated population counts or estimated standard errors?
choice	A character vector specifying the name of one of the datasets in acs

gen_attr_vectors	<i>Generate attribute vectors</i>
------------------	-----------------------------------

Description

Generate a list of attribute vectors for new synthetic attribute creation from a "macroACS" object.

Usage

```
gen_attr_vectors(acs, choice)
```

Arguments

acs	An object of class "macroACS".
choice	A character vector specifying the name of one of the datasets in acs

See Also

[all_geog_synthetic_new_attribute](#), [synthetic_new_attribute](#)

get_best_fit	<i>Extract best fit for a specified geogrpahy from an 'smsm_set' object</i>
--------------	---

Description

Extract the best fit micro population (resulting from the simulated annealing algorithm) for a given geography.

Usage

```
get_best_fit(obj, geography)
```

Arguments

obj	An object of class 'smsm_set', typically a result of call to all_geog_optimize_microdata
geography	A string allowing string matching via grep to a specified geography.

get_dataset_names	<i>Get dataset names from a "macroACS" object.</i>
-------------------	--

Description

Get the names of the datasets in a given "macroACS" object.

Usage

```
get_dataset_names(acs)
```

Arguments

acs	An object of class "macroACS".
-----	--------------------------------

See Also

[fetch_data](#)

get_endyear	<i>Get the endyear from a "macroACS" object.</i>
-------------	--

Description

Get the data collection endyear from a "macroACS" object

Usage

```
get_endyear(acs)
```

Arguments

acs	An object of class "macroACS".
-----	--------------------------------

get_final_tae	<i>Extract the final TAE for a specified geogrpahy from an 'smsm_set' object</i>
---------------	--

Description

Extract the final TAE (resulting from the simulated annealing algorithm) for a given geography.

Usage

```
get_final_tae(obj, geography)
```

Arguments

obj	An object of class 'smsm_set', typically a result of call to all_geog_optimize_microdata
geography	A string allowing string matching via grep to a specified geography.

get_geography	<i>Get the geography title from a "macroACS" object.</i>
---------------	--

Description

Get the summary information of the geography selected from a "macroACS" object

Usage

```
get_geography(acs)
```

Arguments

acs	An object of class "macroACS".
-----	--------------------------------

get_span	<i>Get the span from a "macroACS" object.</i>
----------	---

Description

Get the data collection span from a "macroACS" object

Usage

```
get_span(acs)
```

Arguments

acs An object of class "macroACS".

is.macroACS	<i>Check macroACS class</i>
-------------	-----------------------------

Description

Function that checks if the target object is a macroACS object.

Usage

```
is.macroACS(x)
```

Arguments

x any R object.

Value

Returns TRUE if its argument has class "macroACS" among its classes and FALSE otherwise.

is.macro_micro	<i>Check macro_micro class</i>
----------------	--------------------------------

Description

Function that checks if the target object is a macro_micro object.

Usage

```
is.macro_micro(x)
```

Arguments

x any R object.

Value

Returns TRUE if its argument has class "macro_micro" among its classes and FALSE otherwise.

is.micro_synthetic	<i>Check micro_synthetic class</i>
--------------------	------------------------------------

Description

Function that checks if the target object is a micro_synthetic object.

Usage

```
is.micro_synthetic(x)
```

Arguments

x any R object.

Value

Returns TRUE if its argument has class "micro_synthetic" among its classes and FALSE otherwise.

is.smsm_set	<i>Check smsm_set class</i>
-------------	-----------------------------

Description

Function that checks if the target object is a smsm_set object.

Usage

```
is.smsm_set(x)
```

Arguments

x any R object.

Value

Returns TRUE if its argument has class "macroACS" among its classes and FALSE otherwise.

is.synthACS	<i>Check synthACS class</i>
-------------	-----------------------------

Description

Function that checks if the target object is a synthACS object.

Usage

```
is.synthACS(x)
```

Arguments

x any R object.

Value

Returns TRUE if its argument has class "synthACS" among its classes and FALSE otherwise.

la_hospitals	<i>Hospitals in Los Angeles County, CA USA</i>
--------------	--

Description

An anonymized dataset containing the geographic information of hospitals in Los Angeles County California, USA.

Usage

la_hospitals

Format

A data.frame with 631 observations and 7 variables

geo_long The hospital's longitude.

geo_lat The hospital's latitude.

city The hospital's postal city.

state_fips The hospital's alpha FIPS code.

zip The hospital's five digit postal ZIP code.

census_tract The census tract in which the hospital is located.

county_name The hospital's county – "LOS ANGELES".

LifeExp	<i>Life expectancy at certain ages; United States, 2013</i>
---------	---

Description

A dataset containing life expectancy at certain ages by race, hispanic origin and sex for the United States, 2013.

Usage

LifeExp

Format

A data.frame with 396 observations and 4 variables.

age The exact age, in years, at which life expectancy is calculated.

race The racial group of the deceased One of all all races; white whites; black black / African-American; hispanic Hispanic; non.hisp.white non Hispanic whites; non.hispanic.black non Hispanic blacks.

gender The gender of the deceased. One of c(both, male, female)

life_expectancy The life expectancy for an individual at the exact age with the given race and gender.

Source

<https://www.cdc.gov/nchs/nvss/deaths.htm>

References

Xu, J. Q., S. L. Murphy, and K. D. Kochanek. "Deaths: final data for 2013." National Vital Statistics Reports 64.2 (2015).

marginalize_attr *Marginalize synthetic attributes*

Description

Marginalize, (ie- reduce in number), attributes of a synthetic dataset of class 'micro_synthetic' or a list of synthetic datasets of class 'synthACS'. This is done by marginalizing the joint distribution based on a set of specified attributes (see Arguments below).

Usage

```
marginalize_attr(obj, varlist, marginalize_out = FALSE)
```

Arguments

obj An object of class "micro_synthetic".

varlist A character vector of variable, or attribute, names in obj.

marginalize_out Logical. Do you wish to *remove* the variables in varlist instead of keeping them? Defaults to FALSE

Examples

```
{
# dummy data setup
set.seed(567L)
df <- data.frame(gender= factor(sample(c("male", "female"), size= 100, replace= TRUE)),
                 age= factor(sample(1:5, size= 100, replace= TRUE)),
                 pov= factor(sample(c("below poverty", "at above poverty"),
                                   size= 100, replace= TRUE, prob= c(.15,.85))),
                 p= runif(100))
df$p <- df$p / sum(df$p)
class(df) <- c("data.frame", "micro_synthetic")

df2 <- marginalize_attr(df, varlist= "gender")
df3 <- marginalize_attr(df, varlist= c("gender", "age"))
df4 <- marginalize_attr(df, varlist= c("gender", "age"), marginalize_out= TRUE)

df_list <- replicate(10, df, simplify= FALSE)
dummy_list <- replicate(10, list(NULL), simplify= FALSE)
```

```
df_list <- mapply(function(a,b) {return(list(a, b))}, a= dummy_list, b= df_list, SIMPLIFY = FALSE)
class(df_list) <- c("list", "synthACS")

# run the function
df_list2 <- marginalize_attr(df_list, varlist= c("gender", "age"))
}
```

 MBR

Multiple Birth Rate data by year and race of mother

Description

A dataset containing multiple birth rate data by race of the mother. Data for all races is provided for 1980-2014 and for individual races from 1990-2014.

Usage

MBR

Format

A data.frame with 110 observations and 8 variables.

year The year for which data was recorded.

race The racial group of the mothers. One of all all races; white non-hispanic whites; black_aa non Hispanic black / African-American; hisp_lat Hispanic.

births Total births for the year and racial group in the United States.

twin_births Total twin births for the year and racial group in the United States.

triplet_more_births Total triplet or higher order births for the year and racial group in the United States.

MBRate The number of live births in all multiple deliveries per 1,000 live births.

twinBR The number of live births in all twin deliveries per 1,000 live births.

twinBR The number of live births in all triplet or higher order deliveries per 100,000 live births.

Details

- Data for race category "all" includes races other than white and black and origin not stated.
- Race and Hispanic origin are reported separately on birth certificates. Persons of Hispanic origin may be of any race.

Source

<https://www.cdc.gov/nchs/nvss/births.htm>

References

Hamilton, Brady E., et al. "Births: final data for 2014." National Vital Statistics Reports 64.12 (2015): 1-64.

optimize_microdata *Optimize the selection of a micro data population.*

Description

Optimize the candidate micro dataset such that the lowest loss against the macro dataset constraints is obtained. Loss is defined here as total absolute error (TAE) and constraints are defined by the `constraint_list`. Optimization is done by simulated annealing—see details.

Usage

```
optimize_microdata(
  micro_data,
  prob_name = "p",
  constraint_list,
  tolerance = round(sum(constraint_list[[1]])/2000 * length(constraint_list), 0),
  resample_size = min(sum(constraint_list[[1]]), max(500,
    round(sum(constraint_list[[1]]) * 0.005, 0))),
  p_accept = 0.4,
  max_iter = 10000L,
  seed = sample.int(10000L, size = 1, replace = FALSE),
  verbose = TRUE
)
```

Arguments

<code>micro_data</code>	A data.frame of micro data observations.
<code>prob_name</code>	It is assumed that observations are weighted and do not have an equal probability of occurrence. This string specifies the variable within <code>micro_data</code> that contains the probability of selection.
<code>constraint_list</code>	A list of constraining macro data attributes. See add_constraint
<code>tolerance</code>	An integer giving the maximum acceptable loss (TAE), enabling early stopping. Defaults to a misclassification rate of 1 individual per 1,000 per constraint.
<code>resample_size</code>	An integer controlling the rate of movement about the candidate space. Specifically, it specifies the number of observations to change between iterations. Defaults to 0.5% the number of observations.
<code>p_accept</code>	The acceptance probability for the Metropolis acceptance criteria.
<code>max_iter</code>	The maximum number of allowable iterations. Defaults to 10000L
<code>seed</code>	A seed for reproducibility. See set.seed
<code>verbose</code>	Logical. Do you wish to see verbose output? Defaults to TRUE

Details

Spatial microsimulation involves the study of individual-level phenomena within a specified set of geographies in which these individuals act. It involves the creation of synthetic data to model, via simulation, these phenomena. As a first step to simulation, an appropriate micro-level (ie. individual) dataset must be generated. This function creates such appropriate micro-level datasets given a set of candidate observations and macro-level constraints.

Optimization is done via simulated annealing, where we wish to minimize the total absolute error (TAE) between the micro-data and the macro-constraints. The annealing procedure is controlled by the parameters `tolerance`, `resample_size`, `p_accept`, and `max_iter`. Specifically, `tolerance` indicates the maximum allowable TAE between the output micro-data and the macro-constraints within a given `max_iter` allowable iterations to converge. `resample_size` and `p_accept` control movement about the candidate space. Specifically, `resample_size` controls the jump size between neighboring candidates and `p_accept` controls the hill-climbing rate for exiting local minima.

Please see the references for a more detailed discussion of the simulated annealing procedure.

References

Ingber, Lester. "Very fast simulated re-annealing." *Mathematical and computer modelling* 12.8 (1989): 967-973.

Metropolis, Nicholas, et al. "Equation of state calculations by fast computing machines." *The journal of chemical physics* 21.6 (1953): 1087-1092.

Szu, Harold, and Ralph Hartley. "Fast simulated annealing." *Physics letters A* 122.3 (1987): 157-162.

Examples

```
## Not run:
## assumes you have micro_synthetic object named test_micro and constraint_list named c_list
opt_data <- optimize_microdata(test_micro, "p", c_list, max_iter= 10, resample_size= 500,
                             p_accept= 0.01, verbose= FALSE)

## End(Not run)
```

plot_TAEpath

Plot simulated annealing path

Description

Plot the path TAE in the simulated annealing algorithm for a given geography

Usage

```
plot_TAEpath(object, geography, ...)
```

Arguments

object	An object of class 'smsm_set', typically a result of call to all_geog_optimize_microdata
geography	A string allowing string matching via grep to a specified geography.
...	additional arguments passed to other methods

pull_acs_basetables *Pull ACS base tables*

Description

A wrapper function to pull multiple base tables from ACS API via [acs.fetch](#).

Usage

```
pull_acs_basetables(endyear, span, geography, table_vec)
```

Arguments

endyear	An integer, indicating the latest year of the data in the survey.
span	An integer in <code>c(1, 3, 5)</code> indicating the span of the desired data.
geography	a valid <code>geo.set</code> object specifying the census geography or geographies to be fetched.
table_vec	A character vector specifying ACS base tables.

Value

A 'macroACS' class object

References

<https://data.census.gov/cedsci/>

Examples

```
## Not run:
# make geography
la_geo <- acs::geo.make(state= "CA", county= "Los Angeles")
# pull data
la_dat <- pull_acs_basetables(endyear= 2015, span= 1, geography= la_geo,
  table_vec= c("B01001", "B01002", "B01003"))

## End(Not run)
```

pull_bachelors	<i>Pull ACS data on field of bachelor's degree</i>
----------------	--

Description

Pull ACS data for a specified geography from base tables B15011 and B15012. Note: only 2014 data is supplied by ACS

Usage

```
pull_bachelors(endyear, span, geography)
```

Arguments

endyear	An integer, indicating the latest year of the data in the survey.
span	An integer in $c(1, 3, 5)$ indicating the span of the desired data.
geography	a valid <code>geo.set</code> object specifying the census geography or geographies to be fetched.

Value

A list containing the endyear, span, a `data.frame` of estimates, a `data.frame` of standard errors, and a `data.frame` of the geography metadata from [acs.fetch](#).

See Also

[acs.fetch](#), [geo.make](#)

pull_edu	<i>Pull ACS educational attainment and enrollment data</i>
----------	--

Description

Pull ACS data for a specified geography from base tables B14001, B14003, B15001, B15002. Not currently implemented: B15010, B28006 Additional fields, mainly percentages and aggregations, are calculated.

Usage

```
pull_edu(endyear, span, geography)
```

Arguments

endyear	An integer, indicating the latest year of the data in the survey.
span	An integer in $c(1, 3, 5)$ indicating the span of the desired data.
geography	a valid <code>geo.set</code> object specifying the census geography or geographies to be fetched.

Value

A list containing the endyear, span, a `data.frame` of estimates, a `data.frame` of standard errors, a character vector of the original column names, and a `data.frame` of the geography metadata from [acs.fetch](#).

See Also

[acs.fetch](#), [geo.make](#)

pull_geo_mobility	<i>Pull ACS geographic mobility data</i>
-------------------	--

Description

Pull ACS data for a specified geography from base tables B07001, B07003, B07008, B07009, B07010, and B07012. These tables provide data on geographic mobility in the past year by a number of slices. Additional fields, mainly percentages and aggregations, are calculated.

Usage

```
pull_geo_mobility(endyear, span, geography)
```

Arguments

endyear	An integer, indicating the latest year of the data in the survey.
span	An integer in $c(1, 3, 5)$ indicating the span of the desired data.
geography	a valid <code>geo.set</code> object specifying the census geography or geographies to be fetched.

Value

A list containing the endyear, span, a `data.frame` of estimates, a `data.frame` of standard errors, a character vector of the original column names, and a `data.frame` of the geography metadata from [acs.fetch](#).

See Also

[acs.fetch](#), [geo.make](#)

pull_household	<i>Pull ACS data on households and housing units</i>
----------------	--

Description

Pull ACS data for a specified geography from base tables B09019, B11011, B19081, B25002, B25003, B25004, B25010, B25024, B25056, B25058, B25071, and B27001. Additional fields, mainly percentages and aggregations, are calculated.

Usage

```
pull_household(endyear, span, geography)
```

Arguments

endyear	An integer, indicating the latest year of the data in the survey.
span	An integer in <code>c(1, 3, 5)</code> indicating the span of the desired data.
geography	a valid <code>geo.set</code> object specifying the census geography or geographies to be fetched.

Value

A list containing the endyear, span, a `data.frame` of estimates, a `data.frame` of standard errors, a character vector of the original column names, and a `data.frame` of the geography metadata from [acs.fetch](#).

See Also

[acs.fetch](#), [geo.make](#) B28001 - TYPES OF COMPUTERS IN HOUSEHOLD B28002 - PRESENCE AND TYPES OF INTERNET SUBSCRIPTIONS IN HOUSEHOLD

pull_inc_earnings	<i>Pull ACS income and earnings data</i>
-------------------	--

Description

Pull ACS data for a specified geography from base tables B19083, B19301, B19326, B21001, B22001, B23020, B24011. Not yet implemented: B28004 Additional fields, mainly percentages and aggregations, are calculated.

Usage

```
pull_inc_earnings(endyear, span, geography)
```

Arguments

endyear	An integer, indicating the latest year of the data in the survey.
span	An integer in <code>c(1, 3, 5)</code> indicating the span of the desired data.
geography	a valid <code>geo.set</code> object specifying the census geography or geographies to be fetched.

Value

A list containing the `endyear`, `span`, a `data.frame` of estimates, a `data.frame` of standard errors, a character vector of the original column names, and a `data.frame` of the geography metadata from [acs.fetch](#).

See Also

[acs.fetch](#), [geo.make](#)

pull_mar_status	<i>Pull ACS marital status data</i>
-----------------	-------------------------------------

Description

Pull ACS data for a specified geography from base tables B12001, B12006, B12007, 12501 Additional fields, mainly percentages and aggregations, are calculated.

Usage

```
pull_mar_status(endyear, span, geography)
```

Arguments

endyear	An integer, indicating the latest year of the data in the survey.
span	An integer in <code>c(1, 3, 5)</code> indicating the span of the desired data.
geography	a valid <code>geo.set</code> object specifying the census geography or geographies to be fetched.

Value

A list containing the `endyear`, `span`, a `data.frame` of estimates, a `data.frame` of standard errors, a character vector of the original column names, and a `data.frame` of the geography metadata from [acs.fetch](#).

See Also

[acs.fetch](#), [geo.make](#)

pull_population	<i>Pull ACS population data</i>
-----------------	---------------------------------

Description

Pull ACS data for a specified geography from base tables B01001, B01002, B02001, B06007, B06008, B06009, B06010, B06011, AND B06012. These tables reference population counts by a number of slices. Multiple additional fields, mainly percentages and aggregations, are calculated.

Usage

```
pull_population(endyear, span, geography)
```

Arguments

endyear	An integer, indicating the latest year of the data in the survey.
span	An integer in c(1, 3, 5) indicating the span of the desired data.
geography	a valid geo.set object specifying the census geography or geographies to be fetched.

Value

A list containing the endyear, span, a data.frame of estimates, a data.frame of standard errors, a character vector of the original column names, and a data.frame of the geography metadata from [acs.fetch](#).

See Also

[acs.fetch](#), [geo.make](#)

pull_pov_inc	<i>Pull ACS income and earnings data</i>
--------------	--

Description

Pull ACS data for a specified geography from base tables B17001, B17004, B18101, B19001, B19013, B19055, B19057. Not yet implemented: B17002 Additional fields, mainly percentages and aggregations, are calculated.

Usage

```
pull_pov_inc(endyear, span, geography)
```

Arguments

endyear	An integer, indicating the latest year of the data in the survey.
span	An integer in <code>c(1, 3, 5)</code> indicating the span of the desired data.
geography	a valid <code>geo.set</code> object specifying the census geography or geographies to be fetched.

Value

A list containing the `endyear`, `span`, a `data.frame` of estimates, a `data.frame` of standard errors, a character vector of the original column names, and a `data.frame` of the geography metadata from [acs.fetch](#).

See Also

[acs.fetch](#), [geo.make](#)

pull_race_data	<i>Pull ACS race data</i>
----------------	---------------------------

Description

Pull ACS data for a specified geography from base tables B01001B-I and B02001. ' These tables reference population counts by race.

Usage

```
pull_race_data(endyear, span, geography)
```

Arguments

endyear	An integer, indicating the latest year of the data in the survey.
span	An integer in <code>c(1, 3, 5)</code> indicating the span of the desired data.
geography	a valid <code>geo.set</code> object specifying the census geography or geographies to be fetched.

Value

A list containing the `endyear`, `span`, a `data.frame` of estimates, a `data.frame` of standard errors, and a `data.frame` of the geography metadata from [acs.fetch](#).

See Also

[acs.fetch](#), [geo.make](#)

pull_synth_data	<i>Pull ACS data for synthetic data creation.</i>
-----------------	---

Description

Pull ACS data for a specified geography from base tables B01001, B02001, B12002, B15001, B06001, B06010, B23001, B17005, and B17005. These tables reference population counts by a number of slices. Multiple additional fields, mainly percentages and aggregations, are calculated.

Usage

```
pull_synth_data(endyear, span, geography)
```

Arguments

endyear	An integer, indicating the latest year of the data in the survey.
span	An integer in <code>c(1, 3, 5)</code> indicating the span of the desired data.
geography	a valid <code>geo.set</code> object specifying the census geography or geographies to be fetched.

Value

A list containing the `endyear`, `span`, a list of `data.frames` of estimates, a list of `data.frames` of standard errors, and the geography metadata from [acs.fetch](#).

See Also

[acs.fetch](#), [geo.make](#)

Examples

```
## Not run:
# make geography
la_geo <- acs::geo.make(state= "CA", county= "Los Angeles", tract= "*")
# pull data elements for creating synthetic data
la_dat <- pull_synth_data(2014, 5, la_geo)

## End(Not run)
```

pull_transit_work *Pull ACS transit and work data*

Description

Pull ACS data for a specified geography from base tables B08012, B08101, B08121, B08103, B08124, B08016, B08017. Additional fields, mainly percentages and aggregations, are calculated.

Usage

```
pull_transit_work(endyear, span, geography)
```

Arguments

endyear	An integer, indicating the latest year of the data in the survey.
span	An integer in <code>c(1, 3, 5)</code> indicating the span of the desired data.
geography	a valid <code>geo.set</code> object specifying the census geography or geographies to be fetched.

Value

A list containing the endyear, span, a `data.frame` of estimates, a `data.frame` of standard errors, a character vector of the original column names, and a `data.frame` of the geography metadata from [acs.fetch](#).

See Also

[acs.fetch](#), [geo.make](#)

rawDR *Raw Death Rate by race and gender*

Description

A dataset containing raw death rate data by race and gender of the deceased. Data is provided for 1980-2013.

Usage

```
rawDR
```


Format

A data.frame with 612 observations and 4 variables.

year The year for which data was recorded.

race The racial group of the deceased One of all all races; white whites; black_aa black / African-American; nat_amer American Indian or Native Alaskan; asian_isl Asian or Pacific Islander; hisp_lat Hispanic.

gender The gender of the deceased. One of c(both, male, female)

death_rate The raw death rate. See details.

Details

- The death rate is defined as deaths per 100,000 population.
- Populations are based on census counts enumerated as of April 1 of the census year and estimated as of July 1 for non-census years.

Source

<https://www.cdc.gov/nchs/nvss/deaths.htm>

References

Xu, J. Q., S. L. Murphy, and K. D. Kochanek. "Deaths: final data for 2013." National Vital Statistics Reports 64.2 (2015).

split	<i>Split a "macroACS" object</i>
-------	----------------------------------

Description

Split a "macroACS" object into subsets. This may be helpful for users who have limited memory available on their machines before proceeding to derive sample synthetic micro data.

Usage

```
split(acs, n_splits)
```

Arguments

acs	An object of class "macroACS".
n_splits	An integer for the number of splits you wish to create.

See Also

[derive_synth_datasets](#)

stateFR	<i>Birth rates, by age of mother: United States, each state and territory, 2014</i>
---------	---

Description

A dataset containing birth rate data by US state and age for all US states and territories in 2014.

Usage

stateFR

Format

A data.frame with 612 observations and 3 variables.

state The state or territory for which data was recorded.

age_group The age group of the mother.

birth_rate The birth rate. See Details.

Details

- The birth rate is defined as births per 1,000 women in the specified group.
- Birth rates for age_group 45_49 are computed by relating births to women aged 45 and over to women aged 45-49
- Data for the "United States" as a whole excludes data for the territories.
- Data is missing (eg. NA) when data does not meet standards of reliability or percision; birth rates based on fewer than 20 births.

Source

<https://www.cdc.gov/nchs/nvss/births.htm>

References

Hamilton, Brady E., et al. "Births: final data for 2014." National Vital Statistics Reports 64.12 (2015): 1-64.

summary.smsm_set	<i>Summarizing SMSM fits</i>
------------------	------------------------------

Description

summary method for class 'smsm_set'.

Usage

```
## S3 method for class 'smsm_set'
summary(object, ...)
```

Arguments

object	An object of class 'smsm_set', typically a result of call to all_geog_optimize_microdata
...	additional arguments affecting the summary produced.

synthetic_new_attribute	<i>Add a new attribute to a synthetic_micro dataset</i>
-------------------------	---

Description

Add a new attribute to a synthetic_micro dataset using conditional relationships between the new attribute and existing attributes (eg. wage rate conditioned on age and education level).

Usage

```
synthetic_new_attribute(
  df,
  prob_name = "p",
  attr_name = "variable",
  conditional_vars = NULL,
  sym_tbl = NULL
)
```

Arguments

df	An R object of class "synthetic_micro".
prob_name	A string specifying the column name of the df containing the probabilities for each synthetic observation.
attr_name	A string specifying the desired name of the new attribute to be added to the data.

conditional_vars	An character vector specifying the existing variables, if any, on which the new attribute (variable) is to be conditioned on. Variables must be specified in order. Defaults to NULL ie- an unconditional new attribute.
sym_tbl	sym_tbl A data.frame symbol table with N + 2 columns. The last two columns must be: 1. A vector containing the new attribute counts or percentages; 2. is a vector of the new attribute levels. The first N columns must match the conditioning scheme imposed by the variables in conditional_vars. See details and examples.

Value

A new synthetic_micro dataset with class "synthetic_micro".

Details

New synthetic variables are introduced to the existing data via conditional probability. Similar to [derive_synth_datasets](#), the goal with this function is to generate a joint probability distribution for an attribute vector; and, to create synthetic individuals from this distribution. Although no limit is placed on the number of variables on which to condition, in practice, data rarely exists which allows more than two or three conditioning variables. Other variables are assumed to be independent from the new attribute.

** There are four different types of conditional/marginal probability models which may be considered for a given new attribute: (1) Independence: it is assumed that each of the variables is independent of the others (2) Pairwise conditional independence: it is assumed that attributes are related to only one other attribute and independent of all others. (3) Conditional independence: Attributes can be dependent on some subset of other attributes and independent of the rest. (4) In the most general case, all attributes are jointly interrelated.

Conditioning is implemented via symbol-tables (sym_tbl) to ensure accurate matching between conditioning variables, new attribute levels, and new attribute probabilities. The symbol table is constructed such that the key in the symbol-table's key-value pair is the specific values for the set of conditioning variables. This key is the first N columns of sym_tbl. A recursive approach is employed to conditionally partition sym_tbl. In this sense, the **order** in which the conditional variables are supplied matters.

The value is final 2 columns of sym_tbl which are a pair of (A) either counts or percentages used to specify the probability for the new attribute and (B) the level that the new attribute takes on.

Examples

```
{
set.seed(567L)
df <- data.frame(gender= factor(sample(c("male", "female"), size= 100, replace= TRUE)),
                 edu= factor(sample(c("LT_college", "BA_degree"), size= 100, replace= TRUE)),
                 p= runif(100))
df$p <- df$p / sum(df$p)
class(df) <- c("data.frame", "micro_synthetic")
ST <- data.frame(gender= c(rep("male", 3), rep("female", 3)),
                 attr_pct= c(0.1, 0.8, 0.1, 0.05, 0.7, 0.25),
                 levels= rep(c("low", "middle", "high"), 2))
```

```

df2 <- synthetic_new_attribute(df, prob_name= "p", attr_name= "SES", conditional_vars= "gender",
  sym_tbl= ST)

ST2 <- data.frame(gender= c(rep("male", 3), rep("female", 6)),
  edu= c(rep(NA, 3), rep(c("LT_college", "BA_degree"), each= 3)),
  attr_pct= c(0.1, 0.8, 0.1, 10, 80, 10, 5, 70, 25),
  levels= rep(c("low", "middle", "high"), 3))
df2 <- synthetic_new_attribute(df, prob_name= "p", attr_name= "SES",
  conditional_vars= c("gender", "edu"),
  sym_tbl= ST2)
}

```

TFR

*Total Fertility Rate by race of mother***Description**

A dataset containing total fertility rate data by race of the mother. Data for all races is provided for 1970-2014 and for individual races from 1989-2014.

Usage

TFR

Format

A data.frame with 175 observations and 3 variables.

year The year for which data was recorded.

race The racial group of the mothers. One of all all races; white non-hispanic whites; black_aa black / African-American; nat_amer American Indian or Native Alaskan; asian_isl Asian or Pacific Islander; hisp_lat Hispanic or Latin American.

tfr The Total Fertility Rate. See Details

Details

The Total Fertility Rate is defined as the sums of the birth rates for the 5-year age groups found in [BR2014](#) multiplied by 5.

Source

<https://www.cdc.gov/nchs/nvss/births.htm>

References

Hamilton, Brady E., et al. "Births: final data for 2014." National Vital Statistics Reports 64.12 (2015): 1-64.

Index

* datasets

- adjDR, 4
 - AgeRaceDR, 5
 - BR2014, 17
 - la_hospitals, 27
 - LifeExp, 27
 - MBR, 29
 - rawDR, 40
 - stateFR, 42
 - TFR, 45
- acs.fetch, 20, 32–40
- add_constraint, 3, 6, 15, 18, 30
- adjDR, 4
- AgeRaceDR, 5
- all_geog_constraint_age, 7
- all_geog_constraint_edu, 7
- all_geog_constraint_employment, 8
- all_geog_constraint_gender, 9
- all_geog_constraint_geog_mob, 10
- all_geog_constraint_income, 10
- all_geog_constraint_marital_status, 11
- all_geog_constraint_nativity, 12
- all_geog_constraint_poverty, 13
- all_geog_constraint_race, 13
- all_geog_optimize_microdata, 14, 19, 22, 23, 32, 43
- all_geog_synthetic_new_attribute, 15, 21
- all_geogs_add_constraint, 5, 7–15
- BR2014, 17, 45
- calculate_TAE, 18
- combine_smsm, 19
- derive_synth_datasets, 19, 41, 44
- fetch_data, 21, 22
- gen_attr_vectors, 21
- geo.make, 20, 33–40
- get_best_fit, 22
- get_dataset_names, 22
- get_endyear, 23
- get_final_tae, 23
- get_geography, 23
- get_span, 24
- grep, 21–23, 32
- is_macro_micro, 25
- is_macroACS, 24
- is_micro_synthetic, 25
- is_smsm_set, 26
- is_synthACS, 26
- la_hospitals, 27
- LifeExp, 27
- marginalize_attr, 28
- MBR, 29
- optimize_microdata, 15, 18, 30
- plot_TAEpath, 31
- pull_acs_basetables, 32
- pull_bachelors, 33
- pull_edu, 33
- pull_geo_mobility, 34
- pull_household, 35
- pull_inc_earnings, 35
- pull_mar_status, 36
- pull_population, 37
- pull_pov_inc, 37
- pull_race_data, 38
- pull_synth_data, 19, 20, 39
- pull_transit_work, 40
- rawDR, 40
- set.seed, 15, 30
- split, 19, 41

stateFR, [42](#)

summary.ssm_set, [43](#)

synthetic_new_attribute, [16](#), [20](#), [21](#), [43](#)

TFR, [45](#)