

Package ‘tablaxlsx’

October 20, 2020

Title Write Formatted Tables in Excel Workbooks

Version 1.2.4

Date 2020-10-01

Author Jesus Maria RodrÃguez RodrÃguez

Maintainer Jesus Maria Rodriguez Rodriguez <jesusmro@gmail.com>

Description For writing tables with custom formats in a Excel file ready to be distributed.

Depends R (>= 3.2),openxlsx

License GPL-3

LazyData true

Encoding latin1

NeedsCompilation no

Repository CRAN

Date/Publication 2020-10-19 23:10:02 UTC

R topics documented:

bordear	2
escribirTabla	3
estilosDGE	5
estilosDGPYE	5
reducir	6
tablaxlsx.estilos.set	6
trim	7
verXL	8
Index	9

 bordear

Draw borders an area in an Excel sheet

Description

Draw borders an area in an Excel sheet, with the characteristics indicated in the parameters

Usage

```
bordear(wb, hoja, fila = 1, columna = 1, ancho = 1, alto = 1,
        estilo = createStyle(border = "topleftbottomright",
                             borderStyle = "double", borderColour = "blue4"))
```

Arguments

wb	An object of Workbook class
hoja	The name, if it is a text, or the position, if it is numeric, of the sheet
fila	The row of the upper-left corner of the area
columna	The column of the upper-left corner of the area
ancho	The number of cells in the width of the area
alto	The number of cells in the height of the area
estilo	The border style. It must be an object of class Style, and he border styles are used

Details

Of the parameter estilo is used: border, borderColour and borderStyle. The last two can be vectors, in such a way that each feature is applied to the corresponding edge, according to the order established in border

See Also

[createStyle](#)

Examples

```
## Example
require(openxlsx)
wb=createWorkbook()
addWorksheet(wb,"Primera")
bordear(wb,"Primera",3,2,5,4)
##openXL(wb)

## Otro ejemplo
wb=createWorkbook()
addWorksheet(wb,"Primera")
bordear(wb,"Primera",3,2,5,4,
```

```
estilo=createStyle(border="bottomtop",borderColour=c("red","blue"),
borderStyle=c("double","thin"))
##openXL(wb)
```

escribirTabla *Write a matrix or data.frame with styles in a sheet of a excel workbook*

Description

Write a matrix or data.frame with format in a sheet of a excel workbook, In the position and styles indicated in the parameters

Usage

```
escribirTabla(tabla, wb=NULL,hoja=NULL,fichero=NULL,
limpiarFilas=TRUE,limpiarColumnas=TRUE,limpiarValores=NA,
cabecera = "", fuente = "", notas = "",
fila = 7, columna = 3, decimales = 1, porcentaje = FALSE,
cabecerasFila = TRUE, cabecerasColumna = TRUE,
cabeceraFilas="",cabeceraColumnas="",
anchoCabecera = 10,anchoDatos = 14,
escudo = NULL,posEscudo=c(1,1),
tamEscudo=c(2.7,4.5),unidadesEscudo="cm",
estilos=options("tablxlsx.Estilos")[[1]],
bordes = c("TABLA","CABECERA","CABECERASFILA","CABECERASCOLUMNA","DATOS"),
estilosBordes = NULL)
```

Arguments

- tabla The matrix, data.frame or ftable to write
- wb The Workbook. If NULL is created
- hoja The name o position of Worksheet. If it does not exist or is NULL is created
- fichero The name of a file where the Workbook is saved. If NULL it is not saved
- limpiarFilas If it is TRUE are deleted rows in which all values are in limpiarValores
- limpiarColumnas If it is TRUE are deleted columns in which all values are in limpiarValores
- limpiarValores Values used for cleaning
- cabecera A text to be written in the header of the table
- fuentes A text that is written at the end of the table
- notas One or more texts to write after the fuente
- fila The row of tht upper-left cell where the table will be written
- columna The column of tht upper-left cell where the table will be written

decimales	Number of decimal places that are written with the numerical data. It can be a vector, in which case it is applied successively to each column, recycling the values if necessary
porcentaje	If the data is given percentage format or not. It may be a vector, in which case it is applied successively to each column, recycling values if required
cabecerasFila	If you write or not the rows headers, which will be the names of the rows of the matrix or the corresponding elements of a ftable
cabecerasColumna	If you write or not the columns headers, which will be the names of the rows of the matrix or the corresponding elements of a ftable
cabeceraFilas	Text to write above the row's headers
cabeceraColumnas	Text to write above the row's headers
anchoCabecera	The width, in characters, of the columns of the row header
anchoDatos	The width, in characters, of the data columns
escudo	If it is NULL does not any figure, if it is a text is inserted the figure that is in the file
posEscudo	Position, row and column, of the figure, if escudo is not NULL
tamEscudo	A vector with Height and Width of the figure
unidadesEscudo	Units of the height of the image. By default "cm"
estilos	A list with the styles to apply to the various elements of the table.
bordes	A vector with the names of the elements in the table will be to surround with edges, the possible values are: CABECERA, CABECERASFILA, CABECERASCOLUMNA, DATOS, TABLA (the entire table)
estilosBordes	A list with the styles of the various edges. Each item will be called with one of the possible names on bordes.

Details

Edges are drawn in the order: CABECERA,CABECERASFILA,CABECERASCOLUMNA,DATOS,TABLA

Value

If it have created a Workbook returns the Workbook created, otherwise returns a vector with the row and column of the lower-right cell of the table with notes and source in the worksheet and the lower-right cell of the table only.

See Also

[createStyle](#)

Examples

```
## Example 1
matriz=matrix(runif(20),4,5)
wb=createWorkbook()
hoja=addWorksheet(wb,"Prueba")
escribirTabla(matriz,wb,hoja,fila=4,columna=4)
if(interactive()) openXL(wb)

# Example 2
f1=ftable(mtcars[,c(2,8:11)],col.vars=3:4)
wb=escribirTabla(f1,estilos=estilosDGE,bordes=c("TABLA","DATOS"),
                escudo=system.file("img/logoJMR.png",package="tablxlsx"))
l1=escribirTabla(f1,wb,"otra",anchoCabecera=20,estilos=estilosDGE,bordes=c("TABLA","DATOS"),
                escudo=system.file("img/logoJMR.png",package="tablxlsx"),
                posEscudo=c(2,2),tamEscudo=c(1,1))
if(interactive()) openXL(wb)
```

 estilosDGE

An example of styles for to use

Description

Styles's list of example

Usage

```
data("estilosDGE")
```

Format

Styles's list of example

Examples

```
data(estilosDGE)
```

 estilosDGPYE

An example of styles for to use

Description

Styles's list of example

Usage

```
data("estilosDGPYE")
```

Format

Styles's list of example

Examples

```
data(estilosDGPYE)
```

<code>reducir</code>	<i>Reduce a matrix, ftable or data.frame</i>
----------------------	--

Description

Reduce the matrix, ftable o data.frame suppressing rows or columns whose elements are all equal to one of the values of valores.

Usage

```
reducir(x, valores=NA, filas=TRUE, columnas=TRUE)
```

Arguments

<code>x</code>	Matrix, ftable or data.frame
<code>valores</code>	Vector values to compare
<code>filas</code>	If TRUE (default) the rows with all values in valores will be deleted
<code>columnas</code>	If TRUE (default) the columns with all values in valores will be deleted

Value

Returns a matrix or data.frame without the rows o columns with all values equals to a value from the valores. If x is a ftable returns an array with two attributes, cabColumna and cabFila which contain an array of header rows and columns.

<code>tablxlsx.estilos.set</code>	<i>Write a matrix or data.frame with styles in a sheet of a excel workbook</i>
-----------------------------------	--

Description

Puts the styles used by default in escribirTabla

Usage

```
tablxlsx.estilos.set(estilos.defecto)
```

Arguments

`estilos.defecto`
The list of styles to use by default in `escribirTabla`

Details

Puts the list `estilos.defecto` in the `tablaxlsx.Estilos` option for use by default in `escribirTabla`.

See Also

[escribirTabla](#), [createStyle](#) and [estilosDGE](#)

<code>trim</code>	<i>It removes the spaces from the beginning or end of a text</i>
-------------------	--

Description

Returns a text or a vector of texts as the of the parameter but no spaces at the end or at the beginning of each text

Usage

```
trim(x)
```

Arguments

`x` Text o vector of texts

Value

text or a vector of texts as the of the parameter but no spaces at the end or at the beginning of each text

Examples

```
## Example  
texto=trim(" Esto es una prueba ")
```

`verXL`*Show in excel a matrix or data.frame*

Description

Show in excel a matrix or data.frame

Usage

```
verXL(tabla,...)
```

Arguments

<code>tabla</code>	Matrix, data.frame or any object that can handle <code>escribirTabla</code>
<code>...</code>	parameters of <code>escribirTabla</code>

Examples

```
## Example
## Not run:
  verXL(iris, fila=1, columna=1)

## End(Not run)
```


Index

- * **datasets**

- estilosDGE, 5

- estilosDGPYE, 5

- * **excel**

- bordear, 2

- * **table**

- bordear, 2

bordear, 2

createStyle, 2, 4, 7

escribirTabla, 3, 7

estilosDGE, 5, 7

estilosDGPYE, 5

reducir, 6

tablaxlsx.estilos.set, 6

trim, 7

verXL, 8