

Package ‘tipmap’

September 2, 2022

Type Package

Title Tipping Point Analysis for Bayesian Dynamic Borrowing

Version 0.3.5

Description Tipping point analysis for clinical trials that employ Bayesian dynamic borrowing via robust meta-analytic predictive (MAP) priors. Mainly an implementation of an approach proposed by Best and colleagues (2021) is provided <[doi:10.1002/pst.2093](https://doi.org/10.1002/pst.2093)>. Further functions facilitate the specification of the robust MAP prior via expert elicitation (using the roulette method) and computation of the posterior distribution of the treatment effect with either fixed or stochastic expert-elicited weights. Intended use is the planning, analysis and interpretation of extrapolation studies in pediatric drug development, but applicability is generally wider.

License GPL (>= 3)

Encoding UTF-8

Imports dplyr, ggplot2, RBesT, purrr

Suggests knitr, rmarkdown, testthat (>= 3.0.0)

Config/testthat/edition 3

RoxygenNote 7.2.0

Depends R (>= 3.5.0)

NeedsCompilation no

Author Morten Dreher [aut],
Christian Stock [aut, cre] (<<https://orcid.org/0000-0002-3493-3234>>),
Emma Torrini [ctb]

Maintainer Christian Stock <christian.stock@boehringer-ingenelheim.com>

Repository CRAN

Date/Publication 2022-09-02 19:10:02 UTC

R topics documented:

create_new_trial_data	2
create_posterior_data	3
create_prior_data	4

create_tipmap_data	5
default_quantiles	6
default_weights	6
draw_beta_mixture_1sample	7
draw_beta_mixture_nsamples	7
fit_beta_1exp	8
fit_beta_mult_exp	9
get_cum_probs_1exp	10
get_model_input_1exp	10
get_posterior_by_weight	11
get_stochast_weight_posterior	12
get_summary_mult_exp	13
get_tipping_point	14
load_tipmap_data	15
tipmap_darkblue	15
tipmap_lightred	16
tipmap_plot	16

Index	18
--------------	-----------

create_new_trial_data *Data on new trial in target population*

Description

Creates a vector containing data on the new trial in the target population. This may be hypothetical data in the planning stage.

Usage

```
create_new_trial_data(n_total, est, se)
```

Arguments

n_total	The total sample size.
est	Treatment effect estimate.
se	Standard error of the treatment effect estimate.

Value

A numeric vector with data on the new trial, incl. quantiles of an assumed normal data likelihood.

See Also

[create_posterior_data](#), [create_tipmap_data](#)

Examples

```
new_trial_data <- create_new_trial_data(  
  n_total = 30, est = 1.27, se = 0.95  
)
```

`create_posterior_data` *Creates posterior distributions for a range of weights on the informative component of the robust MAP prior*

Description

Returns a data frame containing the default quantiles of posterior mixture distributions generated with varying weights on the informative component of the MAP prior.

Usage

```
create_posterior_data(map_prior, new_trial_data, sigma, null_effect = 0)
```

Arguments

<code>map_prior</code>	A MAP prior containing information about the trial(s) in the source population, created using RBEST.
<code>new_trial_data</code>	A vector containing information about the new trial. See <code>create_new_trial_data()</code> .
<code>sigma</code>	Standard deviation to be used for the weakly informative component of the MAP prior, recommended to be the unit-information standard deviation.
<code>null_effect</code>	The mean of the robust component of the MAP prior. Defaults to 0.

Value

A data frame containing posterior distributions for varying weights

References

Best, N., Price, R. G., Pouliquen, I. J., & Keene, O. N. (2021). Assessing efficacy in important subgroups in confirmatory trials: An example using Bayesian dynamic borrowing. *Pharm Stat*, 20(3), 551–562. <https://doi.org/10.1002/pst.2093>

See Also

[create_new_trial_data](#), [create_prior_data](#)

Examples

```
# create vector containing data on new trial
new_trial_data <- create_new_trial_data(
  n_total = 30,
  est = 1.27,
  se = 0.95
)

# read MAP prior created by RBEST
map_prior <- load_tipmap_data("tipmapPrior.rds")

# create posterior data
## Not run:
posterior_data <- create_posterior_data(
  map_prior = map_prior,
  new_trial_data = new_trial_data,
  sigma = 12
)

## End(Not run)
```

create_prior_data	<i>Creates input data frame for construction of MAP prior</i>
-------------------	---

Description

Assembling information from trials in the source population in a structured way (required as a pre-processing step for MAP prior creation).

Usage

```
create_prior_data(study_label = NULL, n_total, est, se)
```

Arguments

study_label	An optional vector containing trial labels.
n_total	A vector containing total sample sizes.
est	A vector containing treatment effect estimates.
se	A vector containing standard errors of the effect estimates.

Value

A data frame containing data on the trials in the source population.

See Also

[create_new_trial_data](#), [create_posterior_data](#)

Examples

```
prior_data <- create_prior_data(  
  n_total = c(160, 240, 320),  
  est = c(1.23, 1.40, 1.51),  
  se = c(0.4, 0.36, 0.31)  
)
```

create_tipmap_data *Create data frame ready to use for tipping point analysis*

Description

Combines new trial data created by `createTargetData()`, a posterior distribution created by `create_posterior_data()` and a robust MAP prior using `RBeST::automixfit()` and an optional meta-analysis, e.g. created using the meta package, into a data frame needed for the functions `tipmap_plot()` and `get_tipping_point()`.

Usage

```
create_tipmap_data(new_trial_data, posterior, map_prior, meta_analysis = NULL)
```

Arguments

`new_trial_data` A data frame containing data on the new trial in the target population. See `create_new_trial_data()`.

`posterior` A mixture combining MAP prior and target population. See `create_posterior_data()`.

`map_prior` A robust MAP prior created by `RBeST::automixfit()`.

`meta_analysis` A data frame containing a meta-analysis of trial(s) to be borrowed from. See `createPriorData()`.

Value

A data frame ready to be used for `tipmap_plot()` and `get_tipping_point()`

See Also

[create_new_trial_data](#), [create_posterior_data](#), [tipmap_plot](#), [get_tipping_point](#)

Examples

```
# specify new trial data  
new_trial_data <- create_new_trial_data(n_total = 30, est = 1.5, se = 2.1)  
  
# read MAP prior data  
map_prior <- load_tipmap_data("tipmapPrior.rds")
```

```
# read posterior data
posterior <- load_tipmap_data("tipPost.rds")

tip_dat <- create_tipmap_data(
  new_trial_data = new_trial_data,
  posterior = posterior,
  map_prior = map_prior
)
```

default_quantiles *Default quantiles*

Description

Default quantiles

Usage

```
default_quantiles
```

Format

An object of class `numeric` of length 13.

default_weights *Default weights*

Description

Default weights

Usage

```
default_weights
```

Format

An object of class `numeric` of length 201.

`draw_beta_mixture_1sample`*Draw a single sample from a mixture of beta distributions*

Description

Internal function needed for expert elicitation methods.

Usage

```
draw_beta_mixture_1sample(params, weights = NULL)
```

Arguments

`params` Dataframe with parameters of beta distributions. Parameters need to be provided in columns named "alpha" and "beta", respectively, i.e. with one row per distribution).

`weights` Optional vector of weights assigned to experts. Defaults to equal weights.

Value

One draw (numeric value) from a mixture of beta distributions.

Examples

```
beta_fits <- fit_beta_mult_exp(
  chips_mult =
    rbind(
      c(0, 0, 0, 0, 2, 3, 3, 2, 0, 0),
      c(0, 0, 0, 1, 2, 4, 2, 1, 0, 0),
      c(0, 0, 0, 2, 2, 2, 2, 2, 0, 0)
    )
)
draw_beta_mixture_1sample(beta_fits)
```

`draw_beta_mixture_nsamples`*Draw n samples from a mixture of beta distributions*

Description

Draws samples from a mixture of beta distributions, representing pooled weights on the informative component of a robust MAP prior, as elicited from experts via the roulette method.

Usage

```
draw_beta_mixture_nsamples(n, chips_mult, weights = NULL)
```

Arguments

n The number of samples to be drawn.

chips_mult A data frame or matrix containing expert weights. Rows should represent experts, columns should represent bins / weights.

weights An optional vector containing the weight assigned to each expert. Defaults to equal weights.

Value

A numeric vector containing samples from a pooled distribution of expert opinions.

Examples

```
rweights <- draw_beta_mixture_nsamples(
  n = 50,
  chips_mult = rbind(
    c(0, 0, 0, 0, 2, 3, 3, 2, 0, 0),
    c(0, 0, 0, 1, 2, 4, 2, 1, 0, 0),
    c(0, 0, 0, 2, 2, 2, 2, 2, 0, 0)
  ))
rweights
```

 fit_beta_1exp

Fit beta distribution for one expert

Description

Fit beta distribution to weights elicited from one expert via the roulette method.

Usage

```
fit_beta_1exp(df)
```

Arguments

df A dataframe generated by get_model_input_1exp.

Details

This function is based on `SHELF::fitdist` and yields identical results.

Value

Parameters of beta fit.

Examples

```
chips <- c(0, 2, 3, 2, 1, 1, 1, 0, 0, 0)
x <- get_cum_probs_1exp(chips)
y <- get_model_input_1exp(x)
fit_beta_1exp(df = y)$par
```

fit_beta_mult_exp	<i>Fit beta distributions for multiple experts</i>
-------------------	--

Description

Fit beta distributions to weights elicited from multiple experts via the roulette method.

Usage

```
fit_beta_mult_exp(chips_mult)
```

Arguments

`chips_mult` A dataframe or matrix containing weights. It should contain one row per expert and 10 columns, one for each bin, representing weights from 0 to 1.

Value

Parameters of the individual beta distributions.

Examples

```
beta_fits <- fit_beta_mult_exp(
  chips_mult =
    rbind(
      c(0, 0, 0, 0, 2, 3, 3, 2, 0, 0),
      c(0, 0, 0, 1, 2, 4, 2, 1, 0, 0),
      c(0, 0, 0, 2, 2, 2, 2, 2, 0, 0)
    )
  )
beta_fits
```

get_cum_probs_1exp *Get cumulative probabilities from distribution of chips of one expert*

Description

Internal function needed for expert elicitation methods.

Usage

```
get_cum_probs_1exp(chips)
```

Arguments

chips A numeric vector representing the distribution of chips of one expert. The vector must be of length 10 and contents must add up to 10. The first column represents weight on interval 0 to 0.1.

Value

A vector of cumulative probabilities.

Examples

```
chips <- c(0,2,3,2,1,1,1,0,0,0)
x <- get_cum_probs_1exp(chips)
x
```

get_model_input_1exp *Transform cumulative probabilities to fit beta distributions*

Description

Internal function needed for expert elicitation methods.

Usage

```
get_model_input_1exp(cum_probs, w = NULL)
```

Arguments

cum_probs Cumulative probabilities of weights of one expert.
w Weight of bins.

Value

Dataframe that can be used as input to fit beta distributions by `fit_beta_1exp()`.

Examples

```
chips <- c(0,2,3,2,1,1,1,0,0,0)
x <- get_cum_probs_1exp(chips)
y <- get_model_input_1exp(x)
y
```

get_posterior_by_weight

Filter posterior by given weights

Description

Returns quantiles of the posterior distribution of the treatment effect for one or more specified weights.

Usage

```
get_posterior_by_weight(posterior, weight)
```

Arguments

posterior	The posterior data to be filtered (see <code>create_posterior_data()</code>).
weight	The weight(s) to be filtered by.

Value

The filtered posterior values

See Also

[create_posterior_data](#)

Examples

```
get_posterior_by_weight(
  posterior = load_tipmap_data("tipPost.rds"),
  weight = c(0.05, 0.1)
)
```

`get_stochast_weight_posterior`

Average over posteriors created using weights randomly drawn from a distribution of weights

Description

Runs Monte Carlo simulations with different weights on the informative component of the MAP prior and averages over them. Weights may be drawn randomly from the pooled distribution of expert-weightings obtained in an expert elicitation exercise.

Usage

```
get_stochast_weight_posterior(  
  map_prior,  
  new_trial_dat,  
  weights,  
  null_effect = 0,  
  sigma,  
  mc_error_margin = 0.05  
)
```

Arguments

<code>map_prior</code>	The MAP prior to be robustified, created using <code>RBest::automixfit()</code> .
<code>new_trial_dat</code>	A vector summarising the new trial data. See <code>createNewTrialData()</code> .
<code>weights</code>	A vector containing the weights to be assigned to the informative component.
<code>null_effect</code>	The null treatment effect. Defaults to 0.
<code>sigma</code>	Unit information standard deviation used by <code>RBest::robustify()</code> .
<code>mc_error_margin</code>	Monte Carlo error margin. Defaults to 0.05.

Value

List object containing averaged estimates of posterior quantiles (obtained with different weights) and data on Monte Carlo error.

See Also

[create_new_trial_data](#), [draw_beta_mixture_nsamples](#).

Examples

```
new_trial_dat <- create_new_trial_data(
  n_total = 30,
  est = 1.27,
  se = 0.95
)
expert_weights <- rbind(
  c(0, 0, 0, 0, 2, 3, 3, 2, 0, 0),
  c(0, 0, 0, 1, 2, 4, 2, 1, 0, 0),
  c(0, 0, 0, 1, 2, 3, 2, 2, 0, 0)
)
set.seed(123)
get_stochast_weight_posterior(
  map_prior = load_tipmap_data("tipmapPrior.rds"),
  new_trial_dat = new_trial_dat,
  weights = draw_beta_mixture_nsamples(expert_weights, n = 100),
  sigma = 12
)
```

get_summary_mult_exp *Summarize expert weights*

Description

Computes minimum, maximum, mean and quartiles for expert weights.

Usage

```
get_summary_mult_exp(chips_mult, n = 500, weights = NULL)
```

Arguments

chips_mult	A data frame or matrix containing expert weights.
n	The number of samples to be drawn to obtain summary statistics. Defaults to 500.
weights	Weights assigned to each expert. Defaults to equal weights.

Value

A vector containing summary statistics.

Examples

```
get_summary_mult_exp(rbind(
  c(0, 0, 0, 0, 2, 3, 3, 2, 0, 0),
  c(0, 0, 0, 1, 2, 4, 2, 1, 0, 0),
  c(0, 0, 0, 2, 2, 2, 2, 2, 0, 0)
))
```

get_tipping_point *Identify tipping point for a specific quantile.*

Description

Identifies the weight closest to tipping point for one or multiple specified quantiles.

Usage

```
get_tipping_point(tipmap_data, quantile, null_effect = 0)
```

Arguments

tipmap_data	A data frame created by create_tipmap_data().
quantile	The quantile or quantiles of the tipping point. Possible values are 0.025, 0.05, 0.1, 0.2, 0.8, 0.9, 0.95 and 0.975.
null_effect	The null treatment effect. Defaults to 0.

Value

The weight closest to the tipping point for the specified quantile

See Also

[create_tipmap_data](#)

Examples

```
tip_dat <- load_tipmap_data("tipdat.rds")#'  
get_tipping_point(tip_dat, quantile = 0.025)  
get_tipping_point(tip_dat, quantile = c(0.025, 0.05, 0.1, 0.2), null_effect = 0.1)
```

load_tipmap_data	<i>Load exemplary datasets</i>
------------------	--------------------------------

Description

Loads one of three exemplary datasets in the package.

Usage

```
load_tipmap_data(file)
```

Arguments

file The dataset to be loaded.

Value

A pre-saved dataset.

Examples

```
load_tipmap_data(file = "tipdat.rds")
load_tipmap_data(file = "tipmapPrior.rds")
load_tipmap_data(file = "tipPost.rds")
```

tipmap_darkblue	<i>Custom dark blue</i>
-----------------	-------------------------

Description

Custom dark blue

Usage

```
tipmap_darkblue
```

Format

An object of class character of length 1.

tipmap_lightred	<i>Custom light red</i>
-----------------	-------------------------

Description

Custom light red

Usage

```
tipmap_lightred
```

Format

An object of class character of length 1.

tipmap_plot	<i>Visualize tipping point analysis</i>
-------------	---

Description

Uses a data frame created by `create_tipmap_data()` to visualize the tipping point analysis.

Usage

```
tipmap_plot(
  tipmap_data,
  target_pop_lab = "Trial in target\n population",
  y_range = NULL,
  y_breaks = NULL,
  title = NULL,
  y_lab = "Endpoint",
  x_lab = "Weight on informative component",
  map_prior_lab = "MAP\nprior",
  meta_analysis_lab = "MA",
  legend_title = "Posterior quantile",
  null_effect = 0
)
```

Arguments

tipmap_data	A data frame containing tipping point data, generated by <code>create_tipmap_data()</code> .
target_pop_lab	A label for the trial in the target population.
y_range	An optional argument specifying range of the y-axis.
y_breaks	An optional vector specifying breaks on the y-axis.

<code>title</code>	The plot title.
<code>y_lab</code>	The label for the y axis. Defaults to "Endpoint".
<code>x_lab</code>	The label for the x axis. Defaults to "Weight on informative component".
<code>map_prior_lab</code>	The label for the MAP prior. Defaults to "MAP prior"
<code>meta_analysis_lab</code>	An optional label for a meta-analysis (if included).
<code>legend_title</code>	An optional title for the plot legend. Defaults to "Posterior quantile".
<code>null_effect</code>	The null treatment effect, determining where tipping points are calculated. Defaults to 0.

Value

A ggplot object of the tipping point plot

See Also

[create_tipmap_data](#)

Examples

```
tipmap_data <- load_tipmap_data("tipdat.rds")
tipmap_plot(tipmap_data)
```

Index

* datasets

- default_quantiles, 6
- default_weights, 6
- tipmap_darkblue, 15
- tipmap_lightred, 16

- create_new_trial_data, 2, 3–5, 12
- create_posterior_data, 2, 3, 4, 5, 11
- create_prior_data, 3, 4
- create_tipmap_data, 2, 5, 14, 17

- default_quantiles, 6
- default_weights, 6
- draw_beta_mixture_1sample, 7
- draw_beta_mixture_nsamples, 7, 12

- fit_beta_1exp, 8
- fit_beta_mult_exp, 9

- get_cum_probs_1exp, 10
- get_model_input_1exp, 10
- get_posterior_by_weight, 11
- get_stochast_weight_posterior, 12
- get_summary_mult_exp, 13
- get_tipping_point, 5, 14

- load_tipmap_data, 15

- tipmap_darkblue, 15
- tipmap_lightred, 16
- tipmap_plot, 5, 16