

# Package ‘wrMisc’

July 7, 2022

**Version** 1.9.2

**Title** Analyze Experimental High-Throughput (Omics) Data

**Author** Wolfgang Raffelsberger [aut, cre]

**Maintainer** Wolfgang Raffelsberger <w.raffelsberger@gmail.com>

**Description** The efficient treatment and convenient analysis of experimental high-throughput (omics) data gets facilitated through this collection of diverse functions. Several functions address advanced object-conversions, like manipulating lists of lists or lists of arrays, reorganizing lists to arrays or into separate vectors, merging of multiple entries, etc. Another set of functions provides speed-optimized calculation of standard deviation (sd), coefficient of variance (CV) or standard error of the mean (SEM) for data in matrixes or means per line with respect to additional grouping (eg n groups of replicates). Other functions facilitate dealing with non-redundant information, by indexing unique, adding counters to redundant or eliminating lines with respect redundancy in a given reference-column, etc. Help is provided to identify very closely matching numeric values to generate (partial) distance matrixes for very big data in a memory efficient manner or to reduce the complexity of large data-sets by combining very close values. Many times large experimental datasets need some additional filtering, adequate functions are provided. Batch reading (or writing) of sets of files and combining data to arrays is supported, too. Convenient data normalization is supported in various different modes, parameter estimation via permutations or boot-strap as well as flexible testing of multiple pair-wise combinations using the framework of 'limma' is provided, too.

**VignetteBuilder** knitr

**Depends** R (>= 3.1.0)

**Imports** grDevices, graphics, MASS, stats, utils

**Suggests** BBmisc, boot, coin, data.table, data.tree, fdrtool, flexclust, knitr, limma, markdown, mixdist, NbClust, preprocessCore, qvalue, Rcpp, RColorBrewer, readxl, rmarkdown, som, stringi, VGAM, vsn, wrGraph

**License** GPL-3

**Encoding** UTF-8

**RoxygenNote** 7.2.0

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2022-07-06 23:20:03 UTC

## R topics documented:

|                                     |    |
|-------------------------------------|----|
| addBeforFileExtension . . . . .     | 5  |
| adjBy2ptReg . . . . .               | 6  |
| appendNR . . . . .                  | 7  |
| arrayCV . . . . .                   | 8  |
| asSepList . . . . .                 | 8  |
| buildTree . . . . .                 | 10 |
| cbindNR . . . . .                   | 11 |
| checkAvSd . . . . .                 | 12 |
| checkGrpOrder . . . . .             | 13 |
| checkGrpOrderSEM . . . . .          | 14 |
| checkSimValueInSer . . . . .        | 15 |
| checkStrictOrder . . . . .          | 16 |
| checkVectLength . . . . .           | 16 |
| cleanReplicates . . . . .           | 17 |
| closeMatchMatrix . . . . .          | 18 |
| coinPermTest . . . . .              | 20 |
| colMedSds . . . . .                 | 21 |
| colorAccording2 . . . . .           | 22 |
| colSds . . . . .                    | 23 |
| combinatIntTable . . . . .          | 24 |
| combineAsN . . . . .                | 25 |
| combineByEitherFactor . . . . .     | 26 |
| combineOverlapInfo . . . . .        | 27 |
| combineRedBasedOnCol . . . . .      | 29 |
| combineReplFromListToMatr . . . . . | 30 |
| combineSingleT . . . . .            | 31 |
| completeArrLst . . . . .            | 31 |
| confInt . . . . .                   | 32 |
| contribToContigPerFrag . . . . .    | 33 |
| conv01toColNa . . . . .             | 34 |
| convColorToTransp . . . . .         | 34 |
| convMatr2df . . . . .               | 35 |
| convToNum . . . . .                 | 36 |
| coordOfFilt . . . . .               | 38 |
| correctToUnique . . . . .           | 39 |
| correctWinPath . . . . .            | 40 |
| countCloseToLimits . . . . .        | 41 |
| countSameStartEnd . . . . .         | 42 |

|                                      |    |
|--------------------------------------|----|
| cutArrayInCluLike . . . . .          | 43 |
| cutAtMultSites . . . . .             | 43 |
| cutToNgrp . . . . .                  | 44 |
| diffCombin . . . . .                 | 45 |
| diffPPM . . . . .                    | 45 |
| elimCloseCoord . . . . .             | 46 |
| equLenNumber . . . . .               | 47 |
| exclExtrValues . . . . .             | 48 |
| exponNormalize . . . . .             | 49 |
| extr1chan . . . . .                  | 51 |
| extractLast2numericParts . . . . .   | 52 |
| extrColsDeX . . . . .                | 52 |
| extrNumericFromMatr . . . . .        | 53 |
| extrSpcText . . . . .                | 54 |
| filt3dimArr . . . . .                | 55 |
| filterLiColDeList . . . . .          | 56 |
| filterList . . . . .                 | 57 |
| filterNetw . . . . .                 | 58 |
| filtSizeUniq . . . . .               | 60 |
| findCloseMatch . . . . .             | 61 |
| findRepeated . . . . .               | 62 |
| findSimilFrom2sets . . . . .         | 63 |
| findUsableGroupRange . . . . .       | 65 |
| firstLineOfDat . . . . .             | 65 |
| firstOfRepeated . . . . .            | 66 |
| firstOfRepLines . . . . .            | 67 |
| fuseAnnotMatr . . . . .              | 68 |
| fuseCommonListElem . . . . .         | 69 |
| fusePairs . . . . .                  | 70 |
| get1stOfRepeatedByCol . . . . .      | 71 |
| getValuesByUnique . . . . .          | 72 |
| gitDataUrl . . . . .                 | 73 |
| htmlSpecCharConv . . . . .           | 74 |
| keepCommonText . . . . .             | 74 |
| levIndex . . . . .                   | 76 |
| linModelSelect . . . . .             | 77 |
| linRegrParamAndPVal . . . . .        | 79 |
| listBatchReplace . . . . .           | 80 |
| listGroupsByNames . . . . .          | 81 |
| lmSelClu . . . . .                   | 81 |
| lrbind . . . . .                     | 83 |
| makeMAList . . . . .                 | 84 |
| makeNRedMatr . . . . .               | 85 |
| matchNamesWithReverseParts . . . . . | 86 |
| matchSampToPairw . . . . .           | 87 |
| matr2list . . . . .                  | 88 |
| mergeSelCol . . . . .                | 89 |
| mergeSelCol3 . . . . .               | 90 |

|                      |     |
|----------------------|-----|
| mergeVectors         | 91  |
| mergeW2              | 92  |
| minDiff              | 94  |
| moderTest2grp        | 95  |
| moderTestXgrp        | 96  |
| multiCharReplace     | 97  |
| multiMatch           | 99  |
| naOmit               | 100 |
| nFragments           | 101 |
| nFragments0          | 102 |
| nNonNumChar          | 102 |
| nonAmbiguousMat      | 103 |
| nonAmbiguousNum      | 104 |
| nonredDataFrame      | 105 |
| nonRedundLines       | 106 |
| normalizeThis        | 106 |
| numPairDeColNames    | 108 |
| organizeAsListOfRepl | 109 |
| packageDownloadStat  | 110 |
| pairsAsPropensMatr   | 111 |
| partialDist          | 112 |
| partUnlist           | 113 |
| pasteC               | 114 |
| presenceFilt         | 115 |
| protectSpecChar      | 116 |
| pVal2lfd             | 117 |
| randIndFx            | 118 |
| rankToContigTab      | 119 |
| ratioAllComb         | 120 |
| ratioToPpm           | 121 |
| readCsvBatch         | 122 |
| readTabulatedBatch   | 123 |
| readVarColumns       | 125 |
| readXlsxBatch        | 126 |
| reduceTable          | 128 |
| regrBy1or2point      | 129 |
| regrMultBy1or2point  | 130 |
| renameColumns        | 131 |
| reorgByCluNo         | 131 |
| replicateStructure   | 133 |
| replNAbyLow          | 134 |
| replPlateCV          | 136 |
| rmDupl2colMatr       | 137 |
| rnormW               | 137 |
| rowCVs               | 139 |
| rowGrpCV             | 139 |
| rowGrpMeans          | 140 |
| rowGrpNA             | 141 |

|                                    |     |
|------------------------------------|-----|
| rowGrpSds . . . . .                | 142 |
| rowGrpSums . . . . .               | 142 |
| rowMedSds . . . . .                | 143 |
| rowSds . . . . .                   | 144 |
| rowSEMs . . . . .                  | 144 |
| sampNoDeMArrayLM . . . . .         | 145 |
| scaleXY . . . . .                  | 146 |
| searchDataPairs . . . . .          | 147 |
| searchLinesAtGivenSlope . . . . .  | 148 |
| simpleFragFig . . . . .            | 150 |
| singleLineAnova . . . . .          | 151 |
| sortBy2CategorAnd1IntCol . . . . . | 151 |
| sortByNRepeated . . . . .          | 152 |
| stableMode . . . . .               | 154 |
| standardW . . . . .                | 155 |
| stdErrMedBoot . . . . .            | 156 |
| summarizeCols . . . . .            | 157 |
| sumNAperGroup . . . . .            | 158 |
| sysDate . . . . .                  | 159 |
| tableToPlot . . . . .              | 160 |
| test2factLimma . . . . .           | 161 |
| transpGraySca . . . . .            | 162 |
| treatTxtDuplicates . . . . .       | 163 |
| triCoord . . . . .                 | 164 |
| trimRedundText . . . . .           | 165 |
| tTestAllVal . . . . .              | 166 |
| uniqCountReport . . . . .          | 167 |
| upperMaCoord . . . . .             | 168 |
| withinRefRange . . . . .           | 169 |
| writeCsv . . . . .                 | 169 |
| XYToDiffPpm . . . . .              | 171 |

**Index****172**


---

addBeforFileExtension *Add text before file-extension*

---

**Description**

This function helps changing character strings like file-names and allows adding the character vector 'add' (length 1) before the extension (defined by last '.') of the input string 'x'. Used for easily creating variants/additional filenames but keeping current extension.

**Usage**

```
addBeforFileExtension(x, add, sep = "_")
```

**Arguments**

|     |   |
|-----|---|
| x   | main character vector   |
| add | character vector to be added                                    |
| sep | (character) separator between 'x' & 'add' (character, length 1) |

**Value**

modified character vector

**Examples**

```
addBeforeFileExtension(c("abd.txt", "ghg.ijij.txt", "kjh"), "new")
```

---

adjBy2ptReg

*Linear rescaling of numeric vector or matrix*


---

**Description**

adjBy2ptReg takes data within window defined by 'lims' and determines linear transformation so that these points get the regression characteristics 'regrTo', all other points (ie beyond the limits) will follow the same transformation. In other words, this function performs 'linear rescaling', by adjusting (normalizing) the vector 'dat' by linear regression so that points falling in 'lims' (list with upper & lower boundaries) will end up as 'regrTo'.

**Usage**

```
adjBy2ptReg(dat, lims, regrTo = c(0.1, 0.9), refLines = NULL, callFrom = NULL)
```

**Arguments**

|          |  |
|----------|--|
| dat      | numeric vector, matrix or data.frame   |
| lims     | (list, length=2) should be list giving limits (list(lo=c(min,max),hi=c(min,max)) in data allowing identifying which points will be used for determining slope & offset |
| regrTo   | (numeric, length=2) to which characteristics data should be regressed  |
| refLines | (NULL or integer) optional subselection of lines of dat (will be used internal as refDat)  |
| callFrom | (character) for better tracking of use of functions  |

**Value**

matrix with normalized values

**See Also**

[normalizeThis](#)

### Examples

```
set.seed(2016); dat1 <- round(runif(50,0,100),1)
## extreme values will be further away :
adjBy2ptReg(dat1,lims=list(c(5,9),c(60,90)))
plot(dat1,adjBy2ptReg(dat1,lims=list(c(5,9),c(60,90))))
```

---

appendNR

*Append vectors or lists, without duplicating common elements*

---

### Description

This function allows combining two vectors or lists without duplicating common content (defined by name of list-elements).

### Usage

```
appendNR(x, y, rmDuplicate = TRUE, silent = FALSE, callFrom = NULL)
```

### Arguments

|             |   |
|-------------|---|
| x           | (vector or list) must have names to allow checking for duplicate names in y                         |
| y           | (vector or list) must have names to allow checking for duplicate names in x                         |
| rmDuplicate | (logical) avoid duplicating list-elements present in both x and y (based on names of list-elements) |
| silent      | (logical) suppress messages   |
| callFrom    | (character) allow easier tracking of message(s) produced  |

### Details

When setting the argument `rmDuplicate=FALSE` the function will behave like `append`.

### Value

If both x and y are vectors, the output will be a vector, otherwise it will be a list

### See Also

[append](#); [lrbind](#)

### Examples

```
li1 <- list(a=1, b=2, c=3)
li2 <- list(A=11, B=12, c=3)
appendNR(li1, li2)
append(li1, li2)
```

---

|         |                    |
|---------|--------------------|
| arrayCV | <i>CV of array</i> |
|---------|--------------------|

---

### Description

arrayCV gets CVs for replicates in 2 or 3 dim array and returns CVs as matrix. This function may be used to calculate CVs from replicate microtiter plates (eg 8x12) where replicates are typically done as multiple plates, ie initial matrixes that are the organized into arrays.

### Usage

```
arrayCV(arr, byDim = 3, silent = TRUE, callFrom = NULL)
```

### Arguments

|          |   |
|----------|---|
| arr      | (3-dim) array of numeric data like where replicates are along one dimesion of the array |
| byDim    | (integer) over which dimension repliates are found                                      |
| silent   | (logical) suppres messages  |
| callFrom | (character) allow easier tracking of message produced                                   |

### Value

matrix of CV values

### See Also

[rowCVs](#), [rowGrpCV](#), [replPlateCV](#)

### Examples

```
set.seed(2016); dat1 <- matrix(c(runif(200)+rep(1:10,20)),ncol=10)
head(arrayCV(dat1,byDim=2))
```

---

|           |   |
|-----------|---|
| asSepList | <i>Organize data as separate list-entries</i> |
|-----------|---|

---

### Description

asSepList allows reorganizing list into separate numeric vectors. For example, matrixes or data.frames will be split into separate columns (differnt to [partUnlist](#) which maintains the original structure). This function also works with lists of lists. This function may be helpful for reorganizing data for plots.

**Usage**

```
asSepList(
  y,
  asNumeric = TRUE,
  minLen = 4,
  exclElem = NULL,
  fxArg = NULL,
  silent = FALSE,
  callFrom = NULL,
  debug = FALSE
)
```

**Arguments**

|           |  |
|-----------|--|
| y         | list to be separated/split in vectors  |
| asNumeric | (logical) to transform all list-elements in simple numeric vectors (won't work if some entries are character)                              |
| minLen    | (integer) min length (or number of rows), as add'l element to eliminate arguments given without names when asSepList is called in vioplot2 |
| exclElem  | (character) optional names to exclude if any (lazy matching) matches (to exclude other arguments be misinterpreted as data)                |
| fxArg     | deprecated, replaced by exclElem   |
| silent    | (logical) suppress messages  |
| callFrom  | (character) allow easier tracking of messages produced   |
| debug     | (logical) display additional messages for debugging  |

**Value**

This function returns a list, partially unlisted to vectors

**See Also**

[partUnlist](#), [unlist](#)

**Examples**

```
bb <- list(fa=gl(2,2), c=31:33, L2=matrix(21:28,nc=2),
  li=list(li1=11:14, li2=data.frame(41:44)))
asSepList(bb)
## multi data-frame examples
ca <- data.frame(a=11:15, b=21:25, c=31:35)
cb <- data.frame(a=51:53, b=61:63)
cc <- list(gl(3,2), ca, cb, 91:94, short=81:82, letters[1:5])
asSepList(cc)
cd <- list(e1=gl(3,2), e2=ca, e3=cb, e4=91:94, short=81:82, e6=letters[1:5])
asSepList(cd)
```

---

 buildTree

*Connect edges to from tree and extract all possible branches*


---

## Description

It is assumed that multiple fragments from a common ancestor bay be charcterized by the their start- and end-sites by integer values. For example, If 'abcdefg' is the ancestor, the fragments 'bcd' (from position 2 to 4) to and 'efg' may then be assembled. To do so, all fragments must be presented as matix specifying all start- and end-sites (and fragment-names). buildTree searches contiguous fragments from columns 'posCo' (start/end) from 'disDat' to build tree & extract path information starting with line 'startFr'. Made for telling if dissociated fragments contribute to long assemblies. This function uses various functions of package [data.tree](#) which must be installed, too.

## Usage

```
buildTree(
  disDat,
  startFr = NULL,
  posCo = c("beg", "end"),
  silent = FALSE,
  callFrom = NULL
)
```

## Arguments

|          |   |
|----------|---|
| disDat   | (matrix or data.frame) integer values with 1st column, ie start site of fragment, 2nd column as end of fragments, rownames as unique IDs (node-names) |
| startFr  | (integer) index for 1st node (typically =1 if 'disDat' sorted by "beg"), should point to a terminal node for consecutive growing of branches          |
| posCo    | (character) colnames specifying the begin & start sites in 'disDat', if NULL 1st & 2nd col will be used   |
| silent   | (logical) suppress messages   |
| callFrom | (character) allow easier tracking of message(s) produced  |

## Value

This function returns a list with \$paths (branches as matrix with columns 'sumLen' & 'n'), \$usedNodes (character vector of all names used to build tree) and \$tree (object from data.tree)

## See Also

package [data.tree](#) original function used [Node](#); in this package : for exploiting edge/tree related issues [simpleFragFig](#), [countSameStartEnd](#) and [contribToContigPerFrag](#),

**Examples**

```
frag2 <- cbind(beg=c(2,3,7,13,13,15,7,9,7,3,7,5,7,3),end=c(6,12,8,18,20,20,19,12,12,4,12,7,12,4))
rownames(frag2) <- c("A","E","B","C","D","F","H","G","I", "J","K","L","M","N")
buildTree(frag2)
countSameStartEnd(frag2)
```

---

|         |                               |
|---------|-------------------------------|
| cbindNR | <i>cbind to non-redundant</i> |
|---------|-------------------------------|

---

**Description**

cbindNR combines all matrixes given as arguments to non-redundant column names (by ADDING the number of 'duplicated' columns !). Thus, this function works similar to cbind, but allows combining multiple matrix-objects containing redundant column-names. Of course, all input-matrixes must have the same number of rows ! By default, the output gets sorted by column-names. Note, due to the use of '...' arguments must be given by their full argument-names, lazy evaluation might not recognize properly argument names.

**Usage**

```
cbindNR(
  ...,
  convertDFtoMatr = TRUE,
  sortOutput = TRUE,
  summarizeAs = "sum",
  silent = FALSE,
  callFrom = NULL
)
```

**Arguments**

|                 |   |
|-----------------|---|
| ...             | all matrixes to get combined in cbind way   |
| convertDFtoMatr | (logical) decide if output should be converted to matrix                                      |
| sortOutput      | (logical) optional sorting by column-names  |
| summarizeAs     | (character) decide of combined values should get summed (default, 'sum') or averaged ('mean') |
| silent          | (logical) suppress messages   |
| callFrom        | (character) allow easier tracking of messages produced  |

**Value**

This function returns a matrix or data.frame (as cbind would return)

**See Also**

[cbind](#), [nonAmbiguousNum](#), [firstOfRepLines](#)

**Examples**

```
ma1 <- matrix(1:6, ncol=3, dimnames=list(1:2,LETTERS[3:1]))
ma2 <- matrix(11:16, ncol=3, dimnames=list(1:2,LETTERS[3:5]))
cbindNR(ma1, ma2)
cbindNR(ma1, ma2, summarizeAs="mean")
```

---

|           |   |
|-----------|---|
| checkAvSd | <i>Check how multiple groups of data separate or overlap based on mean +/- sd</i> |
|-----------|---|

---

**Description**

checkAvSd compares if/how neighbour groups separate/overlap via the 'engineering approach' (+/- 2 standard-deviations is similar to  $\alpha=0.05$  t. test). This approach may be used as less elegant alternative to (multi-group) logistic regression. The function uses 'daAv' as matrix of means (rows are tested for up/down character/progression) which get compared with boundaries taken from daSd (for Sd values of each mean in 'daAv').

**Usage**

```
checkAvSd(
  daAv,
  daSd,
  nByGr = NULL,
  multSd = 2,
  codeConst = "const",
  extSearch = FALSE,
  outAsLogical = TRUE,
  silent = FALSE,
  callFrom = NULL
)
```

**Arguments**

|              |   |
|--------------|---|
| daAv         | matrix or data.frame  |
| daSd         | matrix or data.frame  |
| nByGr        | optinal specifying number of Elements per group, allows rather using SEM (adopt to variable n of different groups)    |
| multSd       | (numeric) the factor specifyin how many sd values should be used as margin  |
| codeConst    | (character) which term/word to use when specifying 'constant'   |
| extSearch    | (logical) if TRUE, extend search to one group further (will call result 'nearUp' or 'nearDw')                         |
| outAsLogical | to switch between 2col-output (separate col for 'up' and 'down') or simple categorical vector ('const','okDw','okUp') |
| silent       | (logical) suppress messages   |
| callFrom     | (character) allow easier tracking of message(s) produced  |

**Value**

vector describing character as 'const' or 'okUp','okDw' (or if extSearch=TRUE 'nearUp','nearDw')

**See Also**

[rowGrpMeans](#)

**Examples**

```
mat1 <- matrix(rep(11:24,3)[1:40],byrow=TRUE,ncol=8)
checkGrpOrderSEM(mat1,grp=g1(3,3)[-1])
checkAvSd(rowGrpMeans(mat1,g1(3,3)[-1]),rowGrpSds(mat1,g1(3,3)[-1]) )
# consider variable n :
checkAvSd(rowGrpMeans(mat1,g1(3,3)[-1]),rowGrpSds(mat1,g1(3,3)[-1]),nByGr=c(2,3,3))
```

---

checkGrpOrder

*checkGrpOrder*

---

**Description**

checkGrpOrder tests each line of 'x' if expected order appears. Used for comparing groups of measures with expected profile (simply by matching expected order)

**Usage**

```
checkGrpOrder(x, rankExp = NULL, revRank = TRUE)
```

**Arguments**

|         |  |
|---------|--|
| x       | matrix or data.frame   |
| rankExp | (numeric) expected order for values in columns, default 'rankExp' =1:ncol(x)   |
| revRank | (logical) if 'revRank'=TRUE, the initial ranks & reversed ranks will be tested |

**Value**

vector of logical values

**See Also**

[checkGrpOrderSEM](#)

**Examples**

```
set.seed(2005); mat <- matrix(round(runif(40),1),ncol=4)
checkGrpOrder(mat)
checkGrpOrder(mat,c(1,4,3,2))
```

---

|                  |   |
|------------------|---|
| checkGrpOrderSEM | <i>Check order of multiple groups including non-overlapping SEM-margins</i> |
|------------------|---|

---

### Description

checkGrpOrderSEM tests each line of 'x' if expected order of (replicate-) groups (defined in 'grp') appears intact, while including SEM of groups (replicates) via a proportional weight 'sdFact' as  $(avGr1-gr1SEM) < (avGr1+gr1SEM) < (avGr2-gr2SEM) < (avGr2+gr2SEM)$ . Used for comparing groups of measures with expected profile (by matching expected order) to check if data in 'x' representing groups ('grp') as lines follow. Groups of size=1: The sd (and SEM) can't be estimated directly without any replicates, however, an estimate can be given by shrinking if 'shrink1sampSd'=TRUE under the hypothesis that the overall mechanisms determining the variances is constant across all samples.

### Usage

```
checkGrpOrderSEM(
  x,
  grp,
  sdFact = 1,
  revRank = TRUE,
  shrink1sampSd = TRUE,
  silent = FALSE,
  callFrom = NULL
)
```

### Arguments

|               |   |
|---------------|---|
| x             | matrix or data.frame  |
| grp           | (factor) to organize replicate columns of (x)   |
| sdFact        | (numeric) is proportional factor how many units of SEM will be used for defining lower & upper bounds of each group |
| revRank       | (logical) optionally revert ranks   |
| shrink1sampSd | (logical)   |
| silent        | (logical) suppress messages   |
| callFrom      | (character) allow easier tracking of message(s) produced  |

### Value

logical vector if order correct (as expected based on ranks)

### See Also

takes only 10

**Examples**

```
mat1 <- matrix(rep(11:24,3)[1:40],byrow=TRUE,ncol=8)
checkGrpOrderSEM(mat1,grp=gl(3,3)[-1])
```

---

checkSimValueInSer      *Check for similar values in series*

---

**Description**

checkSimValueInSer checks all values of 'x' for similar values outside/within (relative) range of 'ppm' (ie ambiguous within given range). Return logical vector : FALSE for each entry of 'x' if value inside of ppm range to neighbour

**Usage**

```
checkSimValueInSer(x, ppm = 5, sortX = TRUE)
```

**Arguments**

|       |   |
|-------|---|
| x     | numeric vector  |
| ppm   | (numeric) ppm-range for considering as similar  |
| sortX | (logical) allows speeding up function when set to FALSE, for large data that are already sorted |

**Value**

logical vector : FALSE for each entry of 'x' if value inside of ppm range to neighbour

**See Also**

similar with more options [withinRefRange](#)

**Examples**

```
va1 <- c(4:7,7,7,7,7,8:10)+(1:11)/28600; checkSimValueInSer(va1)
cbind(va=va1,simil=checkSimValueInSer(va1))
```

---

|                  |   |
|------------------|---|
| checkStrictOrder | <i>Check for strict (ascencing or descending) order</i> |
|------------------|---|

---

**Description**

checkStrictOrder tests lines of 'dat' (matrix of data.frame) for strict order (ascending, descending or constant), each col of data is tested relative to the col on its left.

**Usage**

```
checkStrictOrder(dat, invertCount = TRUE)
```

**Arguments**

|             |                      |
|-------------|----------------------|
| dat         | matrix or data.frame |
| invertCount | (logical)            |

**Value**

matrix with counts of (non-)up pairs, (non-)down pairs, (non-)equal-pairs, if 'invertCount'=TRUE resulting 0 means that all columns are following the described characteristics (with variable column numbers easier to count)

**See Also**

[order](#)

**Examples**

```
set.seed(2005); mat <- matrix(round(runif(40),1),nc=4)
checkStrictOrder(mat); mat[which(checkStrictOrder(mat)[,2]==0),]
```

---

|                 |                               |
|-----------------|-------------------------------|
| checkVectLength | <i>Check length of vector</i> |
|-----------------|-------------------------------|

---

**Description**

checkVectLength checks argument 'x' for expected length 'expeL' and return either message or error when expectation not met. Used for parameter ('sanity') checking in other user front-end functions.

**Usage**

```

checkVectLength(
  x,
  expL = 1,
  stopOnProblem = FALSE,
  silent = FALSE,
  callFrom = NULL
)

```

**Arguments**

x (numeric or character vector) input to check length

expL (numeric) expected length

stopOnProblem (logical) continue on problems with message or stop (as error message)

silent (logical) suppress messages if TRUE

callFrom (character) allows easier tracking of message(s) produced

**Value**

NULL (produces only optional message if length is OK or error-message if length is not OK)

**Examples**

```
aa <- 1:5; checkVectLength(aa,exp=3)
```

---

|                 |  |
|-----------------|--|
| cleanReplicates | <i>Replace most distant values by NA</i> |
|-----------------|--|

---

**Description**

This procedure aims to straighten (clean) the most extreme of noisy replicates by identifying the most distant points (among a set of replicates). The input 'x' (matrix or data.frame) is supposed to come from multiple different measures taken in replicates (eg weight of different individuals as rows taken as multiple replicate measures in subsequent columns). With the argument nOut1 the user chooses the total number of most extreme values to replace by NA. how many of the most extreme replicates of the whole dataset will be replaced by NA, ie with nOut1=1 only the single most extreme outlier will be replaced by NA. Outlier points are determined as point(s) with highest distance to (row) center (median and mean choice via argument 'centrMeth'). Returns input data with "removed" points set to NA, or if retOffPos=TRUE the most extreme/outlier positions.

**Usage**

```
cleanReplicates(
  x,
  centrMeth = "median",
  nOutl = 2,
  retOffPos = FALSE,
  silent = FALSE,
  callFrom = NULL
)
```

**Arguments**

|           |  |
|-----------|--|
| x         | matrix (or data.frame)   |
| centrMeth | (character) method to summarize (mean or median)   |
| nOutl     | (integer) determines how many points per line will be set to NA (with n=1 the worst row of replicates will be 'cleaned') |
| retOffPos | (logical) if TRUE, replace the most extreme outlier only   |
| silent    | (logical) suppress messages  |
| callFrom  | (character) allow easier tracking of message(s) produced   |

**Value**

input data with "removed" points set as NA, or if retOffPos=TRUE the most extreme/outlier positions

**Examples**

```
mat3 <- matrix(c(19,20,30, 18,19,28, 16,14,35),ncol=3)
cleanReplicates(mat3,nOutl=1)
```

---

|                  |   |
|------------------|---|
| closeMatchMatrix | <i>Reorganize results of search for close (similar) values in matrix-view</i> |
|------------------|---|

---

**Description**

closeMatchMatrix reorganizes/refines results from simple search of similar values of 2 sets of data by [findCloseMatch](#) (as list for one-to many relations) to more human friendly/readable matrix. This function returns results combining two sets of data which were initially compared (eg measured and theoretical values) as matrix-view using output of [findCloseMatch](#) and both original datasets. Additional information (covariables, annotation, ...) may be included as optional columns for either 'predMatr' or 'measMatr'. Note : It is important to run [findCloseMatch](#) with sortMatch=FALSE ! Note : Results presented based on view of 'predMatr', so if multiple 'measMatr' are at within tolerated distance, lines of 'measMatr' will be repeated; Note : Distances 'disToMeas' and 'ppmTo-Pred' are oriented : neg value if measured is lower than predicted (and pos values if higher than predicted); Note : Returns NULL when nothing within given limits of comparison;

**Usage**

```
closeMatchMatrix(
  closeMatch,
  predMatr,
  measMatr,
  prefMatch = c("^x", "^y"),
  colPred = 1,
  colMeas = 1,
  limitToBest = TRUE,
  asDataFrame = FALSE,
  origNa = TRUE,
  silent = FALSE,
  callFrom = NULL,
  debug = FALSE
)
```

**Arguments**

|             |  |
|-------------|--|
| closeMatch  | (list) output from <a href="#">findCloseMatch</a> , ie list with hits for each 'x' (1st argument) : named vectors of value & x index in name; run with 'sortMatch'=F   |
| predMatr    | (vector or matrix) predicted values, the column 'colPred' indicates which column is used for matching from <a href="#">findCloseMatch</a> ; if column 'id' present this column will be used as identifier for matching |
| measMatr    | (vector or matrix) measured values, the column 'colMeas' indicates which column is used for matching from <a href="#">findCloseMatch</a> ; if column 'id' present this column will be used as identifier for matching  |
| prefMatch   | (character, length=2) prefixes ('^x' and/or '^y') they may have been added by <a href="#">findCloseMatch</a>   |
| colPred     | (integer or text, length=1) column of 'predMatr' with main values of comparison  |
| colMeas     | (integer or text, length=1) column of 'measMatr' with main measures of comparison  |
| limitToBest | (integer) column of 'measMatr' with main measures of comparison  |
| asDataFrame | (logical) convert results to data.frame if non-numeric matrix produced (may slightly slow down big results)  |
| origNa      | (logical) will try to use original names of objects 'predMatr', 'measMatr', if they are not multi-column and not conflicting other output-names (otherwise 'predMatr', 'measMatr' will appear)                         |
| silent      | (logical) suppress messages  |
| callFrom    | (character) allows easier tracking of message(s) produced  |
| debug       | (logical) for bug-tracking: more/enhanced messages   |

**Value**

results as matrix-view based on initial results from [findCloseMatch](#), including optional columns of supplemental data for both sets of data for comparison. Returns NULL when nothing within limits

**See Also**

[findCloseMatch](#), [checkSimValueInSer](#)

**Examples**

```
aA <- c(11:17); bB <- c(12.001,13.999); cC <- c(16.2,8,9,12.5,15.9,13.5,15.7,14.1,5)
(cloMa <- findCloseMatch(aA,cC,com="diff",lim=0.5,sor=FALSE))
# all matches (of 2d arg) to/within limit for each of 1st arg ('x'); 'y' ..to 2nd arg = cC
(maAa <- closeMatchMatrix(cloMa,aA,cC,lim=TRUE)) #
(maAa <- closeMatchMatrix(cloMa,aA,cC,lim=FALSE,origN=TRUE)) #
(maAa <- closeMatchMatrix(cloMa,cbind(valA=81:87,aA),cbind(valC=91:99,cC),colM=2,
  colP=2,lim=FALSE))
(maAa <- closeMatchMatrix(cloMa,cbind(aA,valA=81:87),cC,lim=FALSE,deb=TRUE)) #
a2 <- aA; names(a2) <- letters[1:length(a2)]; c2 <- cC; names(c2) <- letters[10+1:length(c2)]
(cloM2 <- findCloseMatch(x=a2,y=c2,com="diff",lim=0.5,sor=FALSE))
(maA2 <- closeMatchMatrix(cloM2,predM=cbind(valA=81:87,a2),measM=cbind(valC=91:99,c2),
  colM=2,colP=2,lim=FALSE,asData=TRUE))
(maA2 <- closeMatchMatrix(cloM2,cbind(id=names(a2),valA=81:87,a2),cbind(id=names(c2),
  valC=91:99,c2),colM=3,colP=3,lim=FALSE,deb=FALSE))
```

---

coinPermTest

*Compare means of two vectors by permutation test*

---

**Description**

Run coin-flipping like permutation tests (to compare difference of 2 means: 'x1' and 'x2') without any distribution-assumptions. This function uses the package `coin`, if not installed, the function will return NULL and give a warning.

**Usage**

```
coinPermTest(
  x1,
  x2,
  orient = "two.sided",
  nPerm = 5000,
  silent = FALSE,
  callFrom = NULL
)
```

**Arguments**

|          |  |
|----------|--|
| x1       | numeric vector (to be compared with vector 'x2')       |
| x2       | numeric vector (to be compared with vector 'x1')       |
| orient   | (character) may be "two.sided","greater" or "less"     |
| nPerm    | (integer) number of permutations                       |
| silent   | (logical) suppress messages                            |
| callFrom | (character) allow easier tracking of messages produced |

**Value**

This function returns an object of "MCp" class numeric output with p-values

**See Also**

oneway\_test in [LocationTests](#)

**Examples**

```
coinPermTest(2, 3, nPerm=200)
```

---

colMedSds

*Standard error of median for each column by bootstrap*

---

**Description**

Determine standard error (sd) of median by bootstrapping for multiple sets of data (rows in input matrix 'dat'). Note: The package [boot](#) must be installed from CRAN.

**Usage**

```
colMedSds(dat, nBoot = 99, silent = FALSE, callFrom = NULL)
```

**Arguments**

|          |  |
|----------|--|
| dat      | (numeric) matrix                                       |
| nBoot    | (integer) number of iterations                         |
| silent   | (logical) suppress messages                            |
| callFrom | (character) allow easier tracking of messages produced |

**Value**

This function returns a (numeric) vector with estimated standard errors

**See Also**

[boot](#)

**Examples**

```
set.seed(2016); dat1 <- matrix(c(runif(200) + rep(1:10,20)), ncol=10)
colMedSds(dat1)
```

---

 colorAccording2

*Transform numeric values to color-gradient*


---

### Description

This function helps making color-gradients for plotting a numerical variable. It requires the package 'RColorBrewer' being installed from CRAN. Note : RColorBrewer palettes were not integrated here, since they are not continuous.

### Usage

```
colorAccording2(
  x,
  gradTy = "rainbow",
  nStartOmit = NULL,
  nEndOmit = NULL,
  revCol = FALSE,
  alpha = 1,
  callFrom = NULL
)
```

### Arguments

|            |  |
|------------|--|
| x          | (character) color input  |
| gradTy     | (character) type of gradeint may be 'rainbow', 'heat.colors', 'terrain.colors', 'topo.colors', 'cm.colors', 'hcl.colors', 'grey.colors', 'gray.colorsW' or 'logGray'                                   |
| nStartOmit | (integer) omit n steps from beginning of gradient range  |
| nEndOmit   | (integer or "sep") omit n steps from end of gradient range, if nEndOmit="sep" 20 percent of initial grades will be removed to obtain 'separate' ie non-closing color-circles/gradients eg with rainbow |
| revCol     | (logical) reverse order  |
| alpha      | (numeric) optional transparency value (1 for no transparency, 0 for complete opaqueness)   |
| callFrom   | (character) allow easier tracking of message(s) produced   |

### Value

This function returns a character vector (of same length as x) with color encoding

### See Also

[cut](#)

### Examples

```
set.seed(2015); dat1 <- round(runif(15),2)
plot(1:15,dat1,pch=16,cex=2,col=colorAccording2(dat1))
plot(1:15,dat1,pch=16,cex=2,col=colorAccording2(dat1,nStart0=0,nEnd0=4,revCol=TRUE))
plot(1:9,pch=3)
points(1:9,1:9,col=transpGraySca(st=0,en=0.8,nSt=9,trans=0.3),cex=42,pch=16)
```

---

|        |                           |
|--------|---------------------------|
| colSds | <i>sd for each column</i> |
|--------|---------------------------|

---

### Description

colSds is a speed optimized sd for matrix or data.frames. It and treats each line as an independent set of data for calculating the sd (equiv to `apply(dat, 1, sd)`). NAs are ignored from data.

### Usage

```
colSds(dat)
```

### Arguments

dat                   matrix (or data.frame) with numeric values (may contain NAs)

### Value

numeric vector of sd values

### See Also

[sd](#)

### Examples

```
set.seed(2016); dat1 <- matrix(c(runif(200)+rep(1:10,20)),nc=10)
colSds(dat1)
```

---

combinatIntTable      *Planing for making all multiplicative combinations*

---

### Description

Provide all combinations for each of n elements of vector 'nMax' (positive integer, eg number of max multiplicative value). For example, imagine, we have 3 cities and the (maximum) voting participants per city. Results must be read vertically and allow to see all total possible compositions.

### Usage

```
combinatIntTable(
  nMax,
  include0 = TRUE,
  asList = FALSE,
  callFrom = NULL,
  silent = TRUE
)
```

### Arguments

|          |  |
|----------|--|
| nMax     | (positive integer) could be max number of voting participants form different cities, eg Paris max 2 persons, Lyon max 1 person ... |
| include0 | (logical) include 0 occurances, ie provide al combinations starting from 0 or from 1 up to nMax                                    |
| asList   | (logical) return result as list or as array  |
| callFrom | (character) allow easier tracking of messages produced   |
| silent   | (logical) suppress messages  |

### Value

list or array (as 2- or 3 dim) with possible number of occurances for each of the 3 elements in nMax. Read results vertical : out[[1]] or out[,1] .. (multiplicative) table for 1st element of nMax; out[,2] .. for 2nd

### See Also

[combn](#)

### Examples

```
combinatIntTable(c(1,1,1,2), include0=TRUE, asList=FALSE, silent=TRUE)
## Imagine we have 3 cities and the (maximum) voting participants per city :
nMa <- c(Paris=2, Lyon=1, Strasbourg=1)
combinatIntTable(nMa, include0=TRUE, asList=TRUE, silent=TRUE)
```

## Description

The aim of this function is to choose a fixed number (`nCombin`) of list-elements from `lst` and count the number of common values/words. Furthermore, one can define levels to fine-tune the types of combinations to examine. In case multiple combinations for a given level are possible, some basic summary statistics are provided, too

## Usage

```
combineAsN(  
  lst,  
  lev = NULL,  
  nCombin = 3,  
  remDouble = TRUE,  
  silent = FALSE,  
  debug = FALSE,  
  callFrom = NULL  
)
```

## Arguments

|                        |  |
|------------------------|--|
| <code>lst</code>       | (list of character or integer vectors) main input                  |
| <code>lev</code>       | (character) define groups of <code>lst</code>                      |
| <code>nCombin</code>   | (integer) number of list-elements to combine from <code>lst</code> |
| <code>remDouble</code> | (logical) remove intra-duplicates (defaults to TRUE)               |
| <code>silent</code>    | (logical) suppress messages  |
| <code>debug</code>     | (logical) additional messages for debugging                        |
| <code>callFrom</code>  | (character) allow easier tracking of messages produced             |

## Details

When a given level appears multiple times, all possible combinations using one of the respective entries will be made with the other levels. For example, when you ask several students from city A about only one student each from city B and city C to state their preferred hobbies, one could declare the cities as levels. Then, all combinations of the students from city A with the students from city B and C will be made when counting the number of common hobbies (by either 2 or 3 students). In such a case, all counting results will be summarized to the average count for the various categories (seen once, twice or 3 times...), `sem` (standard error of the mean) and `CI` (confidence interval), as well as `sd`.

With very long lists and high numbers of repeats of given levels, however, the computational effort increases very much (like it does when using `table`).

**Value**

This function returns an array with 3 dimensions : i) ii) the combinations of nCombin list-elements, iii) the number of counts (n), sem (standard error of the mean), CI (confidence interval) and sd

**See Also**

[table](#), [replicateStructure](#)

**Examples**

```
## all list-elements are considered equal
tm1 <- list(a1=LETTERS[1:17], a2=LETTERS[3:19], a3=LETTERS[6:20], a4=LETTERS[8:22])
combineAsN(tm1, lev=gl(1,4))[,1,]

## different levels/groups in list-elements
tm4 <- list(a1=LETTERS[1:15], a2=LETTERS[3:16], a3=LETTERS[6:17], a4=LETTERS[8:19],
  b1=LETTERS[5:19], b2=LETTERS[7:20], b3=LETTERS[11:24], b4=LETTERS[13:25], c1=LETTERS[17:26],
  d1=LETTERS[4:12], d2=LETTERS[5:11], d3=LETTERS[6:12], e1=LETTERS[7:10]) #
te4 <- combineAsN(tm4, nCombin=4, lev=substr(names(tm4),1,1))
str(te4)
te4[, ,1]
```

---

*combineByEitherFactor Create factor-like column regrouping data regrouping simultaneously by two factors*

---

**Description**

This function aims to address the situation when two somehow different groupings (of the same data) exist and need to be joined. It is not necessary that both alternative groupings use the same labels, neither. `combineByEitherFactor` adds new (last) column named 'grp' to input matrix representing the combined factor relative to 2 specified columns from input matrix 'mat' (via 'refC1', 'refC2'). Optionally, the output may be sorted and a column giving n per factor-level may be added. The function treats selected columns of 'mat' as pairwise combination of 2 elements (that may occur multiple times over all lines of 'mat') and sorts/organizes all instances of such combined elements (ie from both selected columns) as repeats of a given group, who's class number is given in output column 'grp', the (total) number of repeats may be displayed in column 'nGrp' (nByGrp=TRUE). If groups are overlapping (after re-ordering), an iterative process of max 3x2 passes will be launched after initial matching. Works on numeric as well as character input.

**Usage**

```
combineByEitherFactor(
  mat,
  refC1,
  refC2,
  nByGrp = FALSE,
  convergeMax = TRUE,
```

```

    callFrom = NULL,
    silent = FALSE
  )

```

### Arguments

|             |   |
|-------------|---|
| mat         | input matrix  |
| refC1       | (integer) column-number of 'mat' to use as 1st set                                    |
| refC2       | (integer) column-number of 'mat' to use as 2nd set                                    |
| nByGrp      | (logical) add last col with n by group  |
| convergeMax | (logical) if TRUE, run 2 add'l iterative steps to search convergence to stable result |
| callFrom    | (character) allows easier tracking of message(s) produced                             |
| silent      | (logical) suppresses messages   |

### Value

matrix containing both selected columns plus additional column(s) indicating group-number of the pair-wise combination (and optional the total n by group)

### Examples

```

nn <- rep(c("a", "e", "b", "c", "d", "g", "f"), c(3, 1, 2, 2, 1, 2, 1))
qq <- rep(c("m", "n", "p", "o", "q"), c(2, 1, 1, 4, 4))
nq <- cbind(nn, qq)[c(4, 2, 9, 11, 6, 10, 7, 3, 5, 1, 12, 8), ]
combineByEitherFactor(nq, 1, 2, nBy=TRUE); combineByEitherFactor(nq, 1, 2, nBy=FALSE)
combineByEitherFactor(nq, 1, 2, conv=FALSE); combineByEitherFactor(nq, 1, 2, conv=TRUE)
##
mm <- rep(c("a", "b", "c", "d", "e"), c(3, 4, 2, 3, 1)); pp <- rep(c("m", "n", "o", "p", "q"), c(2, 2, 2, 2, 5))
combineByEitherFactor(cbind(mm, pp), 1, 2, con=FALSE, nBy=TRUE);
combineByEitherFactor(cbind(mm, pp), 1, 2, con=TRUE, nBy=TRUE)

```

---

combineOverlapInfo      *Find and combine points located very close in x/y space*

---

### Description

Search points in x,y space that are located very close and thus likely to overlap. In case of points close enough, various options for joining names (and shortening longer descriptions) are available.

**Usage**

```
combineOverlapInfo(
  dat,
  suplInfo = NULL,
  disThr = 0.01,
  addNsimil = TRUE,
  txtSepChar = ", ",
  combSym = "+",
  maxOverl = 50,
  callFrom = NULL,
  debug = FALSE,
  silent = FALSE
)
```

**Arguments**

|                         |  |
|-------------------------|--|
| <code>dat</code>        | (matrix) matrix or data.frame with 2 cols (used ONLY 1st & 2nd column !), used as x & y coordinates  |
| <code>suplInfo</code>   | (NULL or character) when points are considered overlapping the text from 'suplInfo' will be reduced to fragment before 'txtSepChar' and combined (with others from overlapping text) using 'combSym', if NULL \$combInf will appear with row-numbers |
| <code>disThr</code>     | (numeric) distance-threshold for considering as similar via searchDataPairs()  |
| <code>addNsimil</code>  | (logical) include number of fused points   |
| <code>txtSepChar</code> | (character) for use with .retain1stPart(): where to cut (& keep 1st part) text from 'suplInfo' to return in out\$CombInf; only 1st element used !  |
| <code>combSym</code>    | (character) concatenation symbol (character, length=1) for points considered overlaying, see also 'suplInfo'   |
| <code>maxOverl</code>   | (integer) if NULL no limit or max limit of group/clu size (avoid condensing too many neighbour points to single cloud)   |
| <code>callFrom</code>   | (character) allow easier tracking of message(s) produced   |
| <code>debug</code>      | (logical) additional messages for debugging  |
| <code>silent</code>     | (logical) suppress messages  |

**Value**

matrix with fused (condensed) information for cluster of overlapping points

**Examples**

```
set.seed(2013)
datT2 <- matrix(round(rnorm(200)+3,1),ncol=2,dimnames=list(paste("li",1:100,sep=""),
  letters[23:24]))
# (mimick) some short and longer names for each line
inf2 <- cbind(sh=paste(rep(letters[1:4],each=26),rep(letters,4),1:(26*4),sep=""),
  lo=paste(rep(LETTERS[1:4],each=26),rep(LETTERS,4),1:(26*4),",",rep(letters[sample.int(26)],4),
```

```

rep(letters[sample.int(26)],4),sep=""))[1:100,]
head(datT2,n=10)
head(combineOverlapInfo(datT2,disThr=0.03),n=10)
head(combineOverlapInfo(datT2,suplI=inf2[,2],disThr=0.03),n=10)

```

---

combineRedBasedOnCol *Combine/reduce redundant lines based on specified column*

---

### Description

This function works similar to unique, but it takes a matrix as input and considers one specified column to find unique instances. It identifies 'repeated' lines of the input-matrix (or data.frame) 'mat' based on (repeated) elements in/of column with name 'colNa' (or column-number). Redundant lines (ie repeated lines) will disappear in output. Eg used with extracted annotation where 1 gene has many lines for different GO annotation.

### Usage

```
combineRedBasedOnCol(mat, colNa, sep = ",", silent = FALSE, callFrom = NULL)
```

### Arguments

|          |  |
|----------|--|
| mat      | input matrix or data.frame   |
| colNa    | character vector (length 1) macting 1 column name (if mult only 1st will be used), in case of mult matches only 1st used |
| sep      | (character) separator (default=",")  |
| silent   | (logical) suppress messages  |
| callFrom | (character) allow easier tracking of message(s) produced   |

### Value

matrix containing the input matrix without lines considered repeated (unique-like)

### See Also

[findRepeated](#), [firstOfRepLines](#), [organizeAsListOfRepl](#)

### Examples

```

matr <- matrix(c(letters[1:6],"h","h","f","e",LETTERS[1:5]),ncol=3,
  dimnames=list(letters[11:15],c("xA","xB","xC")))
combineRedBasedOnCol(matr,colN="xB")
combineRedBasedOnCol(rbind(matr[1,],matr),colN="xB")

```

---

`combineReplFromListToMatr`*Combine replicates from list to matrix*

---

### Description

Suppose multiple measures (like multiple channels) are taken for subjects and these measures are organized as groups in a list, like multiple parameters (= channels) or types of measurements (typically many parameters are recorded when screening compounds in microtiter plates). Within one parameter/channel all replicate-data from separate list-entries ('lst') will get combined according to names of list-elements. The function will trim any redundant text in names of list-elements, try to isolate separator (may vary among replicate-groups, but should be 1 character long). eg names "hct116 1.1.xlsx" & "hct116 1.2.xlsx" will be combined as replicates, "hct116 2.1.xlsx" will be considered as new group.

### Usage

```
combineReplFromListToMatr(lst, callFrom = NULL)
```

### Arguments

|                       |  |
|-----------------------|--|
| <code>lst</code>      | (list) list of arrays (typically multi-parameter measures of microtiterplate data) |
| <code>callFrom</code> | (character) allows easier tracking of message(s) produced                          |

### Value

list of arrays now with same dimension of arrays (but shorter, since replicate-arrays were combined)

### See Also

[extr1chan](#), [organizeAsListOfRepl](#)

### Examples

```
lst2 <- list(aa_1x=matrix(1:12,nrow=4,byrow=TRUE),ab_2x=matrix(24:13,nrow=4,byrow=TRUE))
combineReplFromListToMatr(lst2)
```

---

|                |  |
|----------------|--|
| combineSingleT | <i>Get all combinations with TRUE from each column</i> |
|----------------|--|

---

### Description

This function addresses the case when multiple alternative ways exist to combine two elements. combineSingleT makes combinatory choices : if multiple TRUE in given column of 'mat' make all multiple selections with always one TRUE from each column. The resultant output contains index for first and second input columns elements to be combined.

### Usage

```
combineSingleT(mat)
```

### Arguments

mat                    2-column matrix of logical values

### Value

matrix with indexes of combinations of TRUE

### Examples

```
## Example: First column indicates which boys want to dance and second column
## which girls want to dance. So if several boys want to dance each of the girls
## will have the chance to dance with each of them.
matr <- matrix(c(TRUE,FALSE,TRUE,FALSE,TRUE,FALSE),ncol=2)
combineSingleT(matr)
```

---

|                |  |
|----------------|--|
| completeArrLst | <i>Complete list of arrays for same dimensions</i> |
|----------------|--|

---

### Description

This function aims to inspect repeating structures of data given as list of arrays and will try to complete arrays with fewer lines or columns (as this may appear eg with the very last set of high-throughput screening data if fewer measures remain in the last set). Thus, the dimensions of the arrays are compared and cases with fewer (lost) columns (eg fewer experimental replicates) will be adjusted/completed by adding column(s) of NA. Used eg when at reading microtiterplate data the last set is not complete.

### Usage

```
completeArrLst(arrLst, silent = FALSE, callFrom = NULL)
```

**Arguments**

arrLst (list) list of arrays (typically 1st and 2nd dim for specific genes/objects, 3rd for different measures associated with)

silent (logical) suppress messages

callFrom (character) allows easier tracking of message(s) produced

**Value**

list of arrays, now with same dimension of arrays

**See Also**

[organizeAsListOfRepl](#), [extr1chan](#)

**Examples**

```
arr1 <- array(1:24,dim=c(4,3,2),dimnames=list(c(LETTERS[1:4]),
  paste("col",1:3,sep=""),c("ch1","ch2")))
arr3 <- array(81:96,dim=c(4,2,2),dimnames=list(c(LETTERS[1:4]),
  paste("col",1:2,sep=""),c("ch1","ch2")))
arrL3 <- list(pl1=arr1,pl3=arr3)
completeArrLst(arrL3)
```

---

confInt

*Confidence Interval To Given Alpha*

---

**Description**

This little function returns the confidence interval associated to a given significance level alpha under the hypothesis of the Normal distribution is valid.

**Usage**

```
confInt(x, alpha = 0.05, distrib = "Normal", silent = FALSE, callFrom = NULL)
```

**Arguments**

x (numeric) main input

alpha (numeric) significance level, accepted type I error

distrib (character) distribution, so far only Normal is implemented

silent (logical) suppress messages

callFrom (character) allow easier tracking of message(s) produced

**Value**

This function returns the confidence interval to a given alpha under the hypothesis of the Normal distribution.

**See Also**

[TDist](#); [confint](#)

**Examples**

```
confInt(c(5,2:6))
```

---

```
contribToContigPerFrag
```

*Characterize individual contribution of single edges in tree-structures*

---

**Description**

This function helps investigating tree-like structures with the aim of indicating how much individual tree components contribute to compose long stretches. `contribToContigPerFrag` characterizes individual (isolated) contribution of single edges in tree-structures. Typically used to process/exploit summarized trees (as matrix) made by [buildTree](#) which makes use of the package [data.tree](#). For example if A,B and C can be joined aa well and B +D, this function will check if A+B+C is longer and if A contributes to the longest tree.

**Usage**

```
contribToContigPerFrag(joinMat, fullLength = NULL, nDig = 3)
```

**Arguments**

|                         |   |
|-------------------------|---|
| <code>joinMat</code>    | (matrix) matrix with concatenated edges as rownames (separated by slashes), column <code>sumLen</code> for total length and column <code>n</code> for number of edges |
| <code>fullLength</code> | (integer) custom total length (useful if the concatenated edges do not cover 100 percent of the original precursor whose fragments are studied)                       |
| <code>nDig</code>       | (integer) rounding: number of digits for 3rd column <code>len.rat</code> in output  |

**Value**

matrix of 3 columns: with length of longest tree-branches where given edge participates (column `sumLen`), the (total) number of edges therein (col `n.frag`) and a relative value (`len.rat`)

**See Also**

to build tree [buildTree](#)

**Examples**

```
path1 <- matrix(c(17,19,18,17, 4,4,2,3),ncol=2,
  dimnames=list(c("A/B/C/D","A/B/G/D","A/H","A/H/I"),c("sumLen","n")))
contribToContigPerFrag(path1)
```

---

conv01toColNa                    *Convert matrix of integer to matrix of x-times repeated column-names*

---

### Description

conv01toColNa transforms matrix of integers (eg 0 and 1) to repeated & concatenated text from argument colNa, the character string for 0 occurrences of argument zeroTex may be customized. Used eg when specifying (and concatenating) various counted elements (eg properties) along a vector like variable peptide modifications in proteomics.

### Usage

```
conv01toColNa(mat, colNa = NULL, zeroTex = "", pasteCol = FALSE)
```

### Arguments

|          |  |
|----------|--|
| mat      | input matrix (with integer values)   |
| colNa    | alternative (column-)names to the ones from 'mat' (default colnames of 'mat')    |
| zeroTex  | text to display if 0 (default "")  |
| pasteCol | (logical) allows to collapse all columns to single chain of characters in output |

### Value

character vector

### Examples

```
(ma1 <- matrix(sample(0:3,40, repl=TRUE), ncol=4, dimnames=list(NULL, letters[11:14])))
conv01toColNa(ma1)
conv01toColNa(ma1, colNa=LETTERS[1:4], ze=".")
conv01toColNa(ma1, colNa=LETTERS[1:4], pasteCol=TRUE)
```

---

convColorToTransp                    *Assign new transparency to given colors*

---

### Description

This function allows (re-)defining a new transparency. A color encoding vector will be transformed to the same color(s) but with new transparency (alpha).

### Usage

```
convColorToTransp(color, alph = 1)
```

**Arguments**

color (character) color input

alph (numeric) transparency value (1 for no transparency, 0 for complete opacity), values <1 will be treated as percent-values

**Value**

character vector (of same length as input) with color encoding for new transparency

**See Also**

[rgb](#), [par](#)

**Examples**

```
col0 <- c("#998FCC", "#5AC3BA", "#CBD34E", "#FF7D73")
col1 <- convColorToTransp(col0, alph=0.7)
layout(1:2)
pie(rep(1, length(col0)), col=col0)
pie(rep(1, length(col1)), col=col1, main="new transparency")
```

---

convMatr2df

---

*Convert matrix (eg with redundant) row-names to data.frame*


---

**Description**

This function provides flexible converting of matrix to data.frame. For example repeated/redundant rownames are not allowed in data.frame(), thus the corresponding column-names have to be renamed using a counter-suffix. In case of non-redundant rownames, a new column 'addIniNa' will be introduced at beginning to document the initial (redundant) rownames, non-redundant rownames will be created. Finally, this functions converts the corrected matrix to data.frame and checks/converts columns for transforming character to numeric if possible. If the input is a data.frame containing factors, they will be converted to character before potential conversion. Note: for simpler version (only text to numeric) see from this package `.convertMatrToNum`.

**Usage**

```
convMatr2df(
  mat,
  addIniNa = TRUE,
  duplTxtSep = "_",
  silent = FALSE,
  callFrom = NULL
)
```

**Arguments**

|                         |  |
|-------------------------|--|
| <code>mat</code>        | matrix (or data.frame) to be converted   |
| <code>addIniNa</code>   | (logical) if TRUE an additional column ('ID') with rownames will be added at beginning |
| <code>duplTxtSep</code> | (character) separator for enumerating replicated names                                 |
| <code>silent</code>     | (logical) suppress messages  |
| <code>callFrom</code>   | (character) allow easier tracking of message(s) produced                               |

**Value**

This functions returns a data.frame equivalent to the input matrix, an additional column named 'ID' will be added for initial rownames

**See Also**

[numeric](#), for simpler version (only text to numeric) see from this package `.convertMatrToNum`

**Examples**

```
dat1 <- matrix(1:10, ncol=2)
rownames(dat1) <- letters[c(1:3,2,5)]
## as.data.frame(dat1) ... would result in an error
convMatr2df(dat1)

df1 <- data.frame(a=as.character((1:3)/2), b=LETTERS[1:3], c=1:3)
str(convMatr2df(df1))

df2 <- df1; df2$b <- as.factor(df2$b)
str(convMatr2df(df2))
```

---

convToNum

*Convert vector to numeric*


---

**Description**

This function checks if input vector/character string contains numbers (with or without comma) and attempts converting to numeric. This functions was designed for extracting the numeric part of character-vectors (or matrix) containing both numbers and character-elements. Depending on the parameters `convert` and `remove text-entries` can be converted to NA (in resulting numeric objects) or removed (the number of elements/lines gets reduced, in consequence). Note: if 'x' is a matrix, its matrix-dimensions & -names will be preserved. Note: so far Inf and -Inf do not get recognized as numeric.

**Usage**

```
convToNum(
  x,
  autoConv = TRUE,
  spaceRemove = TRUE,
  convert = c(NA, "sparseChar"),
  remove = NULL,
  euroStyle = TRUE,
  sciIncl = TRUE,
  callFrom = NULL,
  silent = TRUE
)
```

**Arguments**

|             |  |
|-------------|--|
| x           | vector to be converted   |
| autoConv    | (logical) simple automatic conversion based on <code>as.numeric</code> ; if TRUE all other arguments except <code>spaceRemove</code> will not be considered  |
| spaceRemove | (logical) to remove all heading and trailing (white) space (until first non-space character)   |
| convert     | (character) define which type of non-conform entries to convert to NAs. Note, if <code>remove</code> is selected to eliminate character-entries they cannot be converted any more. Use <code>'allChar'</code> for all character-entries; <code>'sparseChar'</code> sparse (ie rare) character entries; NA for converting <code>'Na'</code> or <code>'na'</code> to NA; if <code>'none'</code> or NULL no conversions at all. |
| remove      | (character) define which type of non-conform entries to remove, removed items cannot be converted to NA any more. Use <code>'allChar'</code> for removing all character entries; NA for removing all instances of NA (except those created by converting text); all elements will be kept if <code>'none'</code> or NULL.  |
| euroStyle   | (logical) if TRUE will convert all <code>'.'</code> (eg used as European decimal-separator) to <code>'.'</code> (as internally used by R as decimal-separator), thus allowing converting the European decimal format.  |
| sciIncl     | (logical) include recognizing scientific notation (eg <code>2e-4</code> )  |
| callFrom    | (character) allow easier tracking of messages produced   |
| silent      | (logical) suppress messages  |

**Details**

This function may be used in two modes, depending if argument `autoConv` is TRUE or FALSE. The first option allows accessing an automatic mode based on `as.numeric`, while the second option investigates all characters if they may belong to numeric expressions and allows removing specific text-elements.

**Value**

This function returns a numeric vector (or matrix (if `'x'` is matrix))

**See Also**

[numeric](#) and `as.numeric` (on same help-page)

**Examples**

```
x1 <- c("+4", " + 5", "6", "bb", "Na", "-7")
convToNum(x1)
convToNum(x1, autoConv=FALSE, convert=c("allChar"))
convToNum(x1, autoConv=FALSE)      # too many non-numeric instances for 'sparseChar'

x2 <- c("+4", " + 5", "6", "-7", " - 8", "1e6", "+ 2.3e4", "-3E4", "- 4E5")
convToNum(x2)
convToNum(x2, autoConv=FALSE, convert=NA, remove=c("allChar", NA))
convToNum(x2, autoConv=FALSE, convert=NA, remove=c("allChar", NA), sciIncl=FALSE)
```

---

|             |  |
|-------------|--|
| coordOfFilt | <i>get coordinates of values/points in matrix according to filtering condition</i> |
|-------------|--|

---

**Description**

Get coordinates of values/points in matrix according to filtering condition

**Usage**

```
coordOfFilt(mat, cond, sortByRows = FALSE, silent = FALSE, callFrom = NULL)
```

**Arguments**

|            |  |
|------------|--|
| mat        | (matrix or data.frame) matrix or data.frame  |
| cond       | (logical or integer) condition/test to see which values of mat fulfill test, or integer of index passing |
| sortByRows | (logical) optional sorting of results by row-index   |
| silent     | (logical) suppress messages  |
| callFrom   | (character) allow easier tracking of message(s) produced   |

**Value**

matrix columns 'row' and 'col'

**See Also**

[which](#)

**Examples**

```
set.seed(2021); ma1 <- matrix(sample.int(n=40,size=27,replace=TRUE), ncol=9)
## let's test which values are >37
which(ma1 >37)      # doesn't tell which row & col
coordOfFilt(ma1, ma1 >37)
```

---

|                 |                                 |
|-----------------|---------------------------------|
| correctToUnique | <i>Correct vector to unique</i> |
|-----------------|---------------------------------|

---

**Description**

correctToUnique checks 'x' for unique entries, while maintaining the original length. If necessary a counter will added to non-unique entries.

**Usage**

```
correctToUnique(
  x,
  sep = "_",
  atEnd = TRUE,
  maxIter = 4,
  NAenum = TRUE,
  silent = FALSE,
  callFrom = NULL
)
```

**Arguments**

|          |   |
|----------|---|
| x        | input character vector  |
| sep      | (character) separator used when adding counter  |
| atEnd    | (logical) decide location of placing the counter (at end or at beginning of initial text) |
| maxIter  | (numeric) max number of iterations  |
| NAenum   | (logical) if TRUE all NAs will be enumerated (NA_1,NA_2,...)                              |
| silent   | (logical) suppress messages   |
| callFrom | (character) for better tracking of use of functions                                       |

**Value**

This function returns a character vector

**See Also**

[unique](#) will simply remove repeated elements, ie length of 'x' won't remain constant, [filtSizeUniq](#) is more complex and slower, [treatTxtDuplicatas](#)

**Examples**

```
correctToUnique(c("li0", "n", NA, NA, rep(c("li2", "li3"), 2), rep("n", 4)))
```

---

|                |   |
|----------------|---|
| correctWinPath | <i>Correct mixed slash and backslash in file path</i> |
|----------------|---|

---

**Description**

This function corrects paths character strings for mixed slash and backslash in file path. In Windows the function `tempdir()` will use double backslashes as separator while `file.path()` uses regular slashes. So when combining these two one might encounter a mix of slashes and double backslashes which may cause trouble, unless this is streightened out to a single separator used. When pointig to given files inside html-files, paths need to have a prefix, this can be added using the argument `asHtml`.

**Usage**

```
correctWinPath(
  x,
  asHtml = FALSE,
  anyPlatf = FALSE,
  silent = TRUE,
  callFrom = NULL
)
```

**Arguments**

|                       |   |
|-----------------------|---|
| <code>x</code>        | (character) input path to test and correct                                |
| <code>asHtml</code>   | (logical) option for use in html : add prefix "file:"                     |
| <code>anyPlatf</code> | (logical) if TRUE, checking will only be performed in Windows environment |
| <code>silent</code>   | (logical) suppress messages   |
| <code>callFrom</code> | (character) allows easier tracking of message(s) produced                 |

**Value**

character vector with corrected path

**See Also**

[tempfile](#), [file.path](#)

**Examples**

```
path1 <- 'D:\\temp\\Rtmp6X8\\working_dir\\RtmpKC\\example.txt'
(path1b <- correctWinPath(path1, anyPlatf=TRUE))
(path1h <- correctWinPath(path1, anyPlatf=TRUE, asHtml=TRUE))
```

---

countCloseToLimits      *Count from two vectors number of values close within given limits*

---

### Description

This functions summarizes the serach of similar (or identical) numeric values from 2 initial vectors, it evaluates the result from initial search run by findCloseMatch(), whose output is a less convenient list. countCloseToLimits checks furthermore how many results within additional (more stringent) distance-limits may be found and returns the number of distance values within the limits tested. Designed for checking if threshold used with findCloseMatch() may be set more stringent, eg when searching reasonable FDR limits ...

### Usage

```
countCloseToLimits(closeMatch, limitIdent = 5, prefix = "lim_")
```

### Arguments

|            |  |
|------------|--|
| closeMatch | (list) output from findCloseMatch(), ie list indicating which instances of 2 series of data have close matches                   |
| limitIdent | (numeric) max limit or panel of threshold values to test (if single value, in addition a panel with values below will be tested) |
| prefix     | (character) prefix for names of output   |

### Value

integer vector with counts for number of list-elements with at least one absolue value below threshold, names

### See Also

[findCloseMatch](#)

### Examples

```
set.seed(2019); aa <- sample(12:15,20, repl=TRUE) +round(runif(20),2)-0.5
bb <- 11:18
match1 <- findCloseMatch(aa,bb,com="diff",lim=0.65)
head(match1)
(tmp3 <- countCloseToLimits(match1,lim=c(0.5,0.35,0.2)))
(tmp4 <- countCloseToLimits(match1,lim=0.7))
```

---

countSameStartEnd      *Count same start- and end- sites of edges (or fragments)*

---

### Description

Suppose a parent sequence/string 'ABCDE' gets cut in various fragments (eg 'ABC', 'AB' ...). countSameStartEnd counts how many (ie re-occurring) start- and end- sites of edges do occur in the input-data. The input is presented as matrix of/indicating start- and end-sites of edges. The function is used to characterize partially redundant edges and accumulation of cutting/breakage sites.

### Usage

```
countSameStartEnd(frag, minFreq = 2, nDig = 4)
```

### Arguments

|         |  |
|---------|--|
| frag    | (matrix) 1st column beg start-sites, 2nd column end end-sites of edges, row-names to precise fragment identities are recommended |
| minFreq | (integer) min number of accumulated sites for taking into account (allows filtering with large datasets)                         |
| nDig    | (integer) rounding: number of digits for columns beg.rat and end.rat in output   |

### Value

matrix of 6 columns: input (beg and end), beg.n, beg.rat, end.n, end.rat

### See Also

to build initial tree [buildTree](#), [contribToContigPerFrag](#), [simpleFragFig](#)

### Examples

```
frag1 <- cbind(beg=c(2,3,7,13,13,15,7,9,7, 3,3,5), end=c(6,12,8,18,20,20,19,12,12, 4,5,7))
rownames(frag1) <- letters[1:nrow(frag1)]
countSameStartEnd(frag1)
simpleFragFig(frag1)
```

---

|                   |  |
|-------------------|--|
| cutArrayInCluLike | <i>Cut 3-dim array in list of matrixes (or arrays) similar to organizing into clusters</i> |
|-------------------|--|

---

**Description**

cutArrayInCluLike cuts 'dat' (matrix,data.frame or 3-dim array) in list (of appended lines) according to 'cluOrg', which serves as instruction which line of 'dat' should be placed in which list-element (like sorting according to cluster-numbers).

**Usage**

```
cutArrayInCluLike(dat, cluOrg, callFrom = NULL)
```

**Arguments**

|          |   |
|----------|---|
| dat      | array (3 dim)   |
| cluOrg   | (factor) organization of lines to clusters                |
| callFrom | (character) allows easier tracking of message(s) produced |

**Value**

list of matrixes (or arrays)

**Examples**

```
mat1 <- matrix(1:30,nc=3,dimnames=list(letters[1:10],1:3))
cutArrayInCluLike(mat1,cluOrg=factor(c(2,rep(1:4,2),5)))
```

---

|                |   |
|----------------|---|
| cutAtMultSites | <i>Cut character-vector at multiple sites</i> |
|----------------|---|

---

**Description**

This function cuts character vector after 'cutAt' (ie keep the search substing 'cutAt', different to strsplit). Used for theoretical enzymatic digestion (eg in proteomics)

**Usage**

```
cutAtMultSites(y, cutAt)
```

**Arguments**

|       |  |
|-------|--|
| y     | character vector (better if of length=1, otherwise one won't know which fragment stems from which input) |
| cutAt | (character) search substing, ie 'cutting rule'   |

**Value**

modified (ie cut) character vector

**See Also**

[strsplit](#), [nFragments0](#), [nFragments](#)

**Examples**

```
tmp <- "MSVSRTMEDSCELDLVYVTERIIAVSFPSTANEENFRSNLREVAQMLKSKHGGNYLLFNLSERRPDITKLHAKVLEFGWPDLHTPALEKI"
cutAtMultSites(c(tmp,"ojioRij"),c("R","K"))
```

---

cutToNgrp

*Cut numeric vector to n groups (ie convert to factor)*

---

**Description**

cutToNgrp is a more elaborate version of [cut](#) for cutting a the content of a numeric vector 'x' into a given number of groups, taken from the length of 'lev'. Besides, this function provides the group borders/limits for convention use with legends.

**Usage**

```
cutToNgrp(x, lev, NAuse = FALSE, callFrom = NULL)
```

**Arguments**

|          |   |
|----------|---|
| x        | numeric vector  |
| lev      | (character or numeric), the length of this argument tells the number of groups to be used for cutting |
| NAuse    | (logical) include NAs as separate group   |
| callFrom | (character) for better tracking of use of functions   |

**Value**

list with \$grouped telling which element of 'x' goes in which group and \$legTxt with group-borders for convenient use with legends

**See Also**

[cut](#)

**Examples**

```
set.seed(2019); dat <- runif(30) +(1:30)/2
cutToNgrp(dat,1:5)
plot(dat,col=(1:5)[as.numeric(cutToNgrp(dat,1:5)$grouped)])
```

---

|            |  |
|------------|--|
| diffCombin | <i>Compute matrix of differences for all pairwise combinations of numeric vector</i> |
|------------|--|

---

### Description

diffCombin returns matrix of differences (eg resulting from substitution) for all pairwise combinations of numeric vector 'x'.

### Usage

```
diffCombin(x, diagAsNA = FALSE, prefix = TRUE, silent = FALSE, callFrom = NULL)
```

### Arguments

|          |   |
|----------|---|
| x        | numeric vector to compute differences for all combinations                                |
| diagAsNA | (logical) return all self-self combinations as NA (otherwise 0)                           |
| prefix   | (logical) if TRUE, dimnames of output will specify orientation (prefix='from.' and 'to.') |
| silent   | (logical) suppress messages   |
| callFrom | (character) allow easier tracking of message(s) produced                                  |

### Value

numeric matrix of all pairwise differences

### See Also

[diff](#) for simple differences

### Examples

```
diffCombin(c(10,11.1,13.3,16.6))
```

---

|         |   |
|---------|---|
| diffPPM | <i>Difference in ppm between numeric values</i> |
|---------|---|

---

### Description

This is a diff()-like function to return difference in ppm between subsequent values. Result is oriented, ie neg ppm value means decrease (from higher to lower value). Note that if the absolute difference remains the same the difference in ppm will not remain same. Any difference to NA is returned as NA, thus a single NA will result in two NAs in output (unless NA is 1st or last).

**Usage**

```
diffPPM(dat, toPrev = FALSE, silent = FALSE, callFrom = NULL)
```

**Arguments**

```
dat          (numeric) vector for calculating difference to preceding/following value in ppm
toPrev      (logical) determine orientation
silent      (logical) suppress messages
callFrom    (character) allows easier tracking of messages produced
```

**Value**

This function returns a list with close matches of 'x' to given 'y', the numeric value depends on 'sortMatch' (if FALSE then always value of 'y' otherwise of longest of x&y)

**See Also**

[checkSimValueInSer](#) and (from this package) [.compareByDiff](#), [diff](#)

**Examples**

```
aa <- c(1000.01, 1000.02, 1000.05, 1000.08, 1000.09, 1000.08)
.compareByPPM(list(aa,aa), 30, TRUE)           # tabular 'long' version
diffPPM(aa)
```

---

|                |  |
|----------------|--|
| elimCloseCoord | <i>Eliminate close (overlapping) points (in x &amp; y space)</i> |
|----------------|--|

---

**Description**

elimCloseCoord reduces number of rows in 'dat' by eliminating lines where x & y coordinates (columns of matrix 'dat' defined by 'useCol') are identical (overlay points) or very close. The stringency for 'close' values may be fine-tuned using nDig), this function uses internally [firstOfRepeated](#).

**Usage**

```
elimCloseCoord(
  dat,
  useCol = 1:2,
  elimIdentOnly = FALSE,
  refine = 2,
  nDig = 3,
  callFrom = NULL,
  silent = FALSE
)
```

**Arguments**

|               |  |
|---------------|--|
| dat           | matrix (or data.frame) with main numeric input   |
| useCol        | (numeric) index for numeric columns of 'dat' to use/consider   |
| elimIdentOnly | (logical) if TRUE, eliminate real duplicated points only (ie identical values only)  |
| refine        | (numeric) allows increasing stringency even further (higher 'refine' .. more lines considered equal)   |
| nDig          | (integer) number of significant digits used for rounding, if two 'similar' values are identical after this rounding the second will be eliminated. |
| callFrom      | (character) allows easier tracking of message(s) produced  |
| silent        | (logical) suppress messages  |

**Value**

resultant matrix/data.frame

**See Also**

[findCloseMatch](#), [firstOfRepeated](#)

**Examples**

```
da1 <- matrix(c(rep(0:4,5),0.01,1.1,2.04,3.07,4.5),nc=2); da1[,1] <- da1[,1]*99; head(da1)
elimCloseCoord(da1)
```

---

|              |                                      |
|--------------|--------------------------------------|
| equLenNumber | <i>Equal character-length number</i> |
|--------------|--------------------------------------|

---

**Description**

equLenNumber convert numeric entry 'x' to text, with all elements getting the same number of characters (ie by adding preceding or trailing 0s, if needed). So far, the function cannot handle scientific annotations.

**Usage**

```
equLenNumber(x, silent = FALSE, callFrom = NULL)
```

**Arguments**

|          |   |
|----------|---|
| x        | (character) input vector                                  |
| silent   | (logical) suppress messages                               |
| callFrom | (character) allows easier tracking of message(s) produced |

**Value**

character vector formatted as equal number of characters per value

**See Also**[sprintf](#)**Examples**

```
equLenNumber(c(12,-3,321))
equLenNumber(c(12,-3.3,321))
```

---

|                |   |
|----------------|---|
| exclExtrValues | <i>Exclude extreme values (based on distance to mean)</i> |
|----------------|---|

---

**Description**

This function aims to identify extreme values (values most distant to mean, thus potential outliers), mark them as NA or directly exclude them (depending on 'showNAs'). Note that every set of non-identical values will have at least one most extreme value. Extreme values are part of many distributions, they are not necessarily true outliers.

**Usage**

```
exclExtrValues(
  dat,
  result = "val",
  CVlim = NULL,
  maxExcl = 1,
  showNA = FALSE,
  goodValues = TRUE,
  silent = FALSE,
  callFrom = NULL
)
```

**Arguments**

|            |  |
|------------|--|
| dat        | numeric vector, main input   |
| result     | (character) may be 'val' for returning data without extreme values or 'pos' for returning position/index of extreme values                                     |
| CVlim      | (NULL or numeric) allows to retain extreme values only if a certain CV (for all 'dat') is exceeded (to avoid calling extreme values form homogenous data-sets) |
| maxExcl    | (integer) max number of elments to explude   |
| showNA     | (logical) will display extrelme values as NA   |
| goodValues | (logical) allows to display rather the good values instead of the extreme values   |
| silent     | (logical) suppress messages  |
| callFrom   | (character) allow easier tracking of message(s) produced   |

**Value**

numeric vector wo extremle values or index-position of extreme values

**See Also**

[firstOfRepLines](#), [get1stOfRepeatedByCol](#) for treatment of matrix

**Examples**

```
x <- c(rnorm(30),-6,20)
exclExtrValues(x)
```

---

|                |  |
|----------------|--|
| exponNormalize | <i>Normalize by adjusting exponent</i> |
|----------------|--|

---

**Description**

This function normalizes 'dat' by optimizing exponent function (ie  $\text{dat}^{\text{exp}}$ ) to fit best to 'ref' (default: average of each line of 'dat').

**Usage**

```
exponNormalize(
  dat,
  useExpon,
  dynExp = TRUE,
  nStep = 20,
  startExp = 1,
  simMeas = "cor",
  refDat = NULL,
  refGrp = NULL,
  refLines = NULL,
  rSquare = FALSE,
  silent = FALSE,
  callFrom = NULL
)
```

**Arguments**

|          |   |
|----------|---|
| dat      | matrix or data.frame of numeric data to be normalized   |
| useExpon | (numeric vector or matrix) exponent values to be tested   |
| dynExp   | (logical) require 'useExpon' as 2 values (matrix), will gradually increase exponent from 1st to 2nd; may be matrix or data.frame for dynamic, in this case 1st line for exp for lowest data, 2nd line for highest |
| nStep    | (integer) number of exponent variations (steps) when testing range from-to  |
| startExp | (numeric)   |

|          |   |
|----------|---|
| simMeas  | (character) similarity metric to be used (so far only "cor"), if rSquare=TRUE, the r-squared will be returned   |
| refDat   | (matrix or data.frame) if null average of each line from 'dat' will be used as reference in similarity measure  |
| refGrp   | (factor) designating which col of 'ref' should be used with which col of 'dat' (length equal to number of cols in 'dat'). Note: 'refGrp' not yet coded optimally to extract numeric part of character vector, potential problems when all lines or cols of dat are NA |
| refLines | (NULL or integer) optional subset of lines to be considered (only) when determining normalization factors   |
| rSquare  | (logical) if TRUE, add r-squared  |
| silent   | (logical) suppress messages   |
| callFrom | (character) allow easier tracking of message(s) produced  |

### Value

matrix of normalized data

### See Also

more evolved than [normalizeThis](#) with argument set to 'exponent'

### Examples

```
set.seed(2016); dat1 <- matrix(c(runif(200)+rep(1:10,20)),nc=10)
head(rowGrpCV(dat1,gr=gl(4,3,labels=LETTERS[1:4])[2:11]))
set.seed(2016); dat1 <- c(0.1,0.2,0.3,0.5)*rep(c(1,10),each=4)
dat1 <- matrix(round(c(sqrt(dat1),dat1^1.5,3*dat1+runif(length(dat1)))),2),nc=3)
dat2a <- exponNormalize(dat1[,1],useExpon=2,nSte=1,refD=dat1[,3])
layout(matrix(1:2,nc=2))
plot(dat1[,1],dat1[,3],type="b",main="init",ylab="ref")
plot(dat2a$datNor[,1],dat1[,3],type="b",main="norm",ylab="ref")
dat2b <- exponNormalize(dat1[,1],useExpon=c(1.7,2.3),nSte=5,refD=dat1[,3])
plot(dat1[,1],dat1[,3],type="b",main="init",ylab="ref")
plot(dat2b$datNor[,1],dat1[,3],type="b",main="norm",ylab="ref")

dat2c <- exponNormalize(dat1[, -3],useExpon=matrix(c(1.7,2.3,0.6,0.8),nc=2),nSte=5,refD=dat1[,3]);
plot(dat1[,1],dat1[,3],type="b",main="init",ylab="ref")
plot(dat2c$datNor[,1],dat1[,3],type="b",main="norm 1",ylab="ref")
plot(dat1[,2],dat1[,3],type="b",main="init",ylab="ref")
plot(dat2c$datNor[,2],dat1[,3],type="b",main="norm 2",ylab="ref");
```

---

|           |   |
|-----------|---|
| extr1chan | <i>Extract just one series, ie channel, of list of arrays</i> |
|-----------|---|

---

### Description

This function was designed for handling measurements stored as list of multiple arrays, like eg compound-screens using microtiter-plates where multiple parameters ('channels') were recorded for each well (element). The elements (eg compounds screened) are typically stored in the 1st dimension of the arrays, the replicated in the second dimension and different measure types/parameters in the 3rd channel. In order to keep the structure of individual microtiter-plates, typically each plate forms a separate array (of same dimensions) in a list. The this function allows extracting a single channel of the list of arrays (3rd dim of each array) and return row-appended matrix.

### Usage

```
extr1chan(arrLst, cha, na.rm = TRUE, rowSep = "__")
```

### Arguments

|        |  |
|--------|--|
| arrLst | (list) list of arrays (typically 1st and 2nd dim for specific genes/objects, 3rd for different measures associated with) |
| cha    | (integer) channel number   |
| na.rm  | (logical) default =TRUE to remove NAs  |
| rowSep | (character) separator for rows   |

### Value

list with just single channel extracted

### See Also

[organizeAsListOfRepl](#)

### Examples

```
arr1 <- array(1:24,dim=c(4,3,2),dimnames=list(c(LETTERS[1:4]),
  paste("col",1:3,sep=""),c("ch1","ch2")))
arr2 <- array(74:51,dim=c(4,3,2),dimnames=list(c(LETTERS[1:4]),
  paste("col",1:3,sep=""),c("ch1","ch2")))
arrL1 <- list(p1=arr1,p2=arr2)
extr1chan(arrL1,ch=2)
```

---

```
extractLast2numericParts
```

*Extract last two numeric parts from character vector*

---

### Description

`extractLast2numericParts` extracts last 2 (integer) numeric parts between punctuations out of character vector 'x'. Runs faster than `gregexpr`. Note: won't work correctly with decimals or exponential signs !! (such characters will be considered as punctuation, ie as separator)

### Usage

```
extractLast2numericParts(x, silent = FALSE, callFrom = NULL)
```

### Arguments

|          |  |
|----------|--|
| x        | main character input                                     |
| silent   | (logical) suppress messages                              |
| callFrom | (character) allow easier tracking of message(s) produced |

### Value

(numeric) matrix with 2 columns (eg from initial concatenated coordinates)

### See Also

`gregexpr` from [grep](#)

### Examples

```
extractLast2numericParts(c("M01.1-4", "M001/2.5", "M_0001_03-16", "zyx", "012", "a1.b2.3-7,2"))
```

---

```
extrColsDeX
```

*Flexible extraction of columns*

---

### Description

This function provides flexible checking if a set of columns may be extracted from a matrix or data.frame 'x'. If argument `extrCol` is list of character vectors, this allows to search among given options, the first matching name for each vector will be identified.

### Usage

```
extrColsDeX(x, extrCol, doExtractCols = FALSE, callFrom = NULL, silent = FALSE)
```

**Arguments**

|                            |   |
|----------------------------|---|
| <code>x</code>             | (matrix or data.frame) main input (where data should be extracted from)   |
| <code>extrCol</code>       | (character, integer or list) columns to be extracted, may be column-names or column index; if is list each first-level element will be considered as options for one choice |
| <code>doExtractCols</code> | (logical) if default FALSE only the column indexes will be returned   |
| <code>callFrom</code>      | (character) allows easier tracking of message(s) produced   |
| <code>silent</code>        | (logical) suppress messages   |

**Value**

integer-vector (ifdoExtractCols=FALSE return depending on input matrix or data.frame)

**See Also**

[read.table](#), [filterList](#)

**Examples**

```
dFr <- data.frame(a=11:14, b=24:21, cc=LETTERS[1:4], dd=rep(c(TRUE,FALSE),2))
extrColsDeX(dFr,c("b","cc","notThere"))
extrColsDeX(dFr,c("b","cc","notThere"), doExtractCols=TRUE)
extrColsDeX(dFr, list(c("nn","b","a"), c("cc","a"),"notThere"))
```

---

`extrNumericFromMatr`     *Extract numeric part of matrix or data.frame*

---

**Description**

`extrNumericFromMatr` extracts numeric part of matrix or data.frame, removing remaining non-numeric elements if `trimToData` is set to TRUE. Note, that cropping entire lines where a (single) text element appeared may quickly reduce the overall content of the input data.

**Usage**

```
extrNumericFromMatr(dat, trimToData = TRUE, silent = FALSE, callFrom = NULL)
```

**Arguments**

|                         |   |
|-------------------------|---|
| <code>dat</code>        | matrix (or data.frame) for extracting numeric parts   |
| <code>trimToData</code> | (logical) default to remove (crop) lines and cols contributing to NA, non-numeric data is transformed to NA |
| <code>silent</code>     | (logical) suppress messages   |
| <code>callFrom</code>   | (character) allow easier tracking of message(s) produced  |

**Value**

matrix of numeric data

**Examples**

```
mat <- matrix(c(letters[1:7],14:16,LETTERS[1:6]),nrow=4,dimnames=list(1:4,letters[1:4]))
mat; extrNumericFromMatr(mat)
mat <- matrix(c(letters[1:4],1,"e",12:19,LETTERS[1:6]),nr=5,dimnames=list(11:15,letters[1:4]))
mat; extrNumericFromMatr(mat)
```

---

extrSpcText

*Extract specific text*

---

**Description**

This function extracts/cuts text-fragments out of txt following specific anchors defined by arguments cutFrom and cutTo.

**Usage**

```
extrSpcText(
  txt,
  cutFrom = " GN=",
  cutTo = " PE=",
  missingAs = NA,
  exclFromTag = TRUE,
  silent = FALSE,
  callFrom = NULL
)
```

**Arguments**

|             |   |
|-------------|---|
| txt         | character vector to be treated                                      |
| cutFrom     | (character) text where to start cutting                             |
| cutTo       | (character) text where to stop cutting                              |
| missingAs   | (character) specific content of output at line/location of 'exclLi' |
| exclFromTag | (logical) to exclude text given in 'cutFrom' from result            |
| silent      | (logical) suppress messages   |
| callFrom    | (character) allow easier tracking of messages produced              |

**Details**

In case cutFrom is not found missingAs will be returned. In case cutTo is not found, text gets extracted with chaMaxEl characters.

**Value**

This function returns a modified character vector

**See Also**

[substr](#)

**Examples**

```
extrSpcText(c(" ghjg GN=thisText PE=001", " GN=_ PE=", NA, "abcd"))
extrSpcText(c("ABCDEF.3-6", "05g", "bc.4-5"), cutFr="\\. ", cutT="-")
```

---

filt3dimArr

*Filter a three-dimensional array of numeric data*

---

**Description**

Filtering of 3-dim array ('x'): filter column 'filtCrit' as 'larger as' (according to 'filtTy') 'filtVal' and extract/display all col matching 'displCrit'.

**Usage**

```
filt3dimArr(x, filtCrit, filtVal, filtTy = ">", displCrit = NULL)
```

**Arguments**

|           |   |
|-----------|---|
| x         | array (3-dim) of numeric data   |
| filtCrit  | (character, length=1) which column-name consider when filtering filter with 'filtVal' and 'filtTy'              |
| filtVal   | (numeric) for testing inferior/superior/equal condition   |
| filtTy    | (character) which type of testing to perform ('eq', 'inf', 'infeq', 'sup', 'supeq', '>', '<', '>=', '<=', '==') |
| displCrit | (character) column-name(s) to display   |

**Value**

list of filtered matrixes (by 3rd dim)

**Examples**

```
arr1 <- array(1:24, dim=c(4,3,2), dimnames=list(c(LETTERS[1:4]),
  paste("col", 1:3, sep=""), c("ch1", "ch2")))
filt3dimArr(arr1, displCrit=c("col1", "col2"), filtCrit="col2", filtVal=7)
```

---

filterLiColDeList      *Filter lines(rows) and/or columns from all suitable elements of list*

---

### Description

Filter all elements of list (or S3-object) according to criteria designed to one selected reference-element of the list. All simple vectors, matrix, data.frames and 3-dimensional arrays will be checked if matching number of rows and/or columns to decide if they should be filtered the same way. If the reference element has same number of rows and columns simple (1-dimensional) vectors won't be filtered since it not clear if this should be done to lines or columns.

### Usage

```
filterLiColDeList(
  lst,
  useLines,
  useCols = NULL,
  ref = 1,
  silent = FALSE,
  callFrom = NULL
)
```

### Arguments

|          |   |
|----------|---|
| lst      | (list or S3 object) main input  |
| useLines | (integer, logical or character) vector to assign lines to keep when filtering along lines; set to NULL for no filtering; if 'allNA' all lines composed uniquely of NA values will be removed. |
| useCols  | (integer, logical or character) vector for filtering columns; set to NULL for no filtering; if 'allNA' all columns uniquely NA values will be removed   |
| ref      | (integer) index for designating the element of 'lst' to take as reference for checking which other list-elements have suitable number of rows or columns                                      |
| silent   | (logical) suppress messages   |
| callFrom | (character) allow easier tracking of message(s) produced  |

### Details

This function is used eg in package wrProteo to simultaneously filter raw and transformed data.

### Value

correct input (object of same class, same length)

### See Also

[moderTest2grp](#) for single comparisons, [lmFit](#)

**Examples**

```
lst1 <- list(m1=matrix(11:18,ncol=2), m2=matrix(21:30,ncol=2), indR=31:34,
            m3=matrix(c(21:23,NA,25:27,NA),ncol=2))
## here $m2 has more lines than $m1, and thus will be ignored when ref=1
filterLiColDeList(lst1, useLines=2:3)
filterLiColDeList(lst1, useLines="allNA", ref=4)
```

---

 filterList

*Filter for unique elements*


---

**Description**

This function aims to apply a given filter-criterion, a matrix or vector of FALSE/TRUE which is typically combined with a second layer which filters for a min content of filter-passing values per line for the first/main criterion. Then all lines concerned will be removed. This will be done for all list-elements (of appropriate size) of the input-list (while maintaining the list-structure in the output) not matching the filtering criteria.

**Usage**

```
filterList(lst, filt, minLineRatio = 0.5, silent = FALSE, callFrom = NULL)
```

**Arguments**

|              |   |
|--------------|---|
| lst          | (list) main input, each vector, matrix or data.frame in this list will be filtered if its length or number of lines fits to filt  |
| filt         | (logical) vector of FALSE/TRUE to use for filtering. If this a matrix is given, the value of minLineRatio will be applied as threshold of min content of TRUE for each line of filt |
| minLineRatio | (numeric) in case filt is a matrix of FALSE/TRUE, this value will be used as threshold of min content of TRUE for each line of filt   |
| silent       | (logical) suppress messages   |
| callFrom     | (character) allow easier tracking of message(s) produced  |

**Value**

filtered list

**See Also**

[correctToUnique](#), [unique](#), [duplicated](#), [extrColsDeX](#)

**Examples**

```

set.seed(2020); dat1 <- round(runif(80),2)
list1 <- list(m1=matrix(dat1[1:40],ncol=8), m2=matrix(dat1[41:80],ncol=8), other=letters[1:8])
rownames(list1$m1) <- rownames(list1$m2) <- paste0("line",1:5)
filterList(list1, list1$m1[,1] >0.4)
filterList(list1, list1$m1 >0.4)

```

---

|            |   |
|------------|---|
| filterNetw | <i>Filter nodes &amp; edges for extracting networks This function allows extracting and filtering network-data based on fixed threshold (limInt) and add sandwich-nodes (nodes inter-connecting initial nodes) out of node-based queries.</i> |
|------------|---|

---

**Description**

Filter nodes & edges for extracting networks

This function allows extracting and filtering network-data based on fixed threshold (limInt) and add sandwich-nodes (nodes inter-connecting initial nodes) out of node-based queries.

**Usage**

```

filterNetw(
  lst,
  filtCol = 3,
  limInt = 5000,
  sandwLim = 5000,
  filterAsInf = TRUE,
  outFormat = "matrix",
  remOrphans = TRUE,
  remRevPairs = TRUE,
  reverseCheck = TRUE,
  elemNa = "genes",
  silent = FALSE,
  callFrom = NULL,
  debug = FALSE
)

```

**Arguments**

|             |   |
|-------------|---|
| lst         | (list, composed of multiple matrix or data.frames ) main input (each list-element should have same number of columns) |
| filtCol     | (integer, length=1) which column of lst should be used to filter using thresholds limInt and sandwLim                 |
| limInt      | (numeric, length=1) filter main edge-scores according to filterAsInf  |
| sandwLim    | (numeric, length=1) filter sandwich connection edge-scores according to filterAsInf                                   |
| filterAsInf | (logical) filter as 'inferior or equal' or 'superior or equal'  |

|              |  |
|--------------|--|
| outFormat    | (character) may be 'matrix' for tabular output, 'all' as list with matrix and list of node-names                                   |
| remOrphans   | (logical) remove networks consisting only of 2 connected edges   |
| remRevPairs  | (logical) remove duplicate edges due to reverse massping (eg A - B and B - A); NOTE : use only when edges don't have orientation ! |
| reverseCheck | (logical) depreciated  |
| elemNa       | (character) used only for messages   |
| silent       | (logical) suppress messages  |
| callFrom     | (character) allow easier tracking of message(s) produced   |
| debug        | (logical) display additional messages for debugging  |

### Value

This function returns a matrix or data.frame

### See Also

in [cbind](#)

### Examples

```
lst2 <- list('121'=data.frame(ID=as.character(c(141,221,228,229,449)),11:15),
  '131'=data.frame(ID=as.character(c(228,331,332,333,339)),11:15),
  '141'=data.frame(ID=as.character(c(121,151,229,339,441,442,449)),c(11:17)),
  '151'=data.frame(ID=as.character(c(449,141,551,552)),11:14),
  '161'=data.frame(ID=as.character(171),11), '171'=data.frame(ID=as.character(161),11),
  '181'=data.frame(ID=as.character(881:882),11:12) )

lst2 <- list('121'=data.frame(ID=as.character(c(141,221,228,229,449)),11:15, 21:25),
  '131'=data.frame(ID=as.character(c(228,331,332,333,339)),11:15, 21:25),
  '141'=data.frame(ID=as.character(c(121,151,229,339,441,442,449)), c(11:17), 21:27),
  '151'=data.frame(ID=as.character(c(449,141,551,552)), 11:14, 21:24),
  '161'=data.frame(ID=as.character(171), 11,21), '171'=data.frame(ID=as.character(161), 11,21),
  '181'=data.frame(ID=as.character(881:882), 11:12,21:22) )

(te1 <- filterNetw(lst2, limInt=90, remOrphans=FALSE))
(te2 <- filterNetw(lst2, limInt=90, remOrphans=TRUE))

(te3 <- filterNetw(lst2, limInt=13, remOrphans=FALSE))
(te4 <- filterNetw(lst2, limInt=13, remOrphans=TRUE))
```

---

 filtSizeUniq

*Filter for unique elements*


---

### Description

This function aims to identify and remove duplicated elements in a list and maintain the list-structure in the output. `filtSizeUniq` filters 'lst' (list of character-vectors or character-vector) for elements being unique (to 'ref' or if NULL to all 'lst') and of character length. In addition, the min- and max- character length may be filtered, too. Eg, in proteomics this helps removing peptide sequences which would not be measured/detected any way.

### Usage

```

filtSizeUniq(
  lst,
  ref = NULL,
  minSize = 6,
  maxSize = 36,
  filtUnique = TRUE,
  byProt = TRUE,
  inclEmpty = TRUE,
  silent = FALSE,
  callFrom = NULL
)

```

### Arguments

|                         |   |
|-------------------------|---|
| <code>lst</code>        | list of character-vectors or character-vector   |
| <code>ref</code>        | (character) optional alternative 'reference', if not NULL used in addition to 'lst' for considering elements of 'lst' as unique |
| <code>minSize</code>    | (integer) minimum number of characters, if NULL set to 0  |
| <code>maxSize</code>    | (integer) maximum number of characters  |
| <code>filtUnique</code> | (logical) if TRUE return unique-only character-strings  |
| <code>byProt</code>     | (logical) if TRUE organize output as list (by names of input, eg protein-names) - if 'lst' was named list                       |
| <code>inclEmpty</code>  | (logical) optional including empty list-elements when all elements have been filtered away - if 'lst' was named list            |
| <code>silent</code>     | (logical) suppress messages   |
| <code>callFrom</code>   | (character) allow easier tracking of message(s) produced  |

### Value

list of filtered input

**See Also**

[correctToUnique](#), [unique](#), [duplicated](#)

**Examples**

```
filtSizeUniq(list(A="a",B=c("b","bb","c"),D=c("dd","d","ddd","c")),filtUn=TRUE,minSi=NULL)
# input: c and dd are repeated
filtSizeUniq(list(A="a",B=c("b","bb","c"),D=c("dd","d","ddd","c")),ref=c(letters[c(1:26,1:3)]),
  "dd","dd","bb","ddd"),filtUn=TRUE,minSi=NULL) # a,b,c,dd repeated
```

---

 findCloseMatch

*Find close numeric values between two vectors*


---

**Description**

findCloseMatch finds close matches (similar values) between two numeric vectors ('x','y') based on method 'compTy' and threshold 'limit'. Return list with close matches of 'x' to given 'y', the numeric value depends on 'sortMatch' (if FALSE then always value of 'y' otherwise of longest of x&y). Note: Speed & memory improvement if 'sortMatch'=TRUE (but result might be inverted!): adopt search of x->y or y->x to searching matches of each longest to each shorter (ie flip x &y). Otherwise, if length of 'x' & 'y' are very different, it may be advantageous to use a long(er) 'x' and short(er) 'y' (with 'sortMatch'=FALSE). Note: Names of 'x' & 'y' or (if no names) prefix letters 'x' & 'y' are always added as names to results.

**Usage**

```
findCloseMatch(
  x,
  y,
  compTy = "ppm",
  limit = 5,
  asIndex = FALSE,
  maxFitShort = 100,
  sortMatch = FALSE,
  silent = FALSE,
  callFrom = NULL
)
```

**Arguments**

|        |   |
|--------|---|
| x      | numeric vector for comparison   |
| y      | numeric vector for comparison   |
| compTy | (character) may be 'diff' or 'ppm', will be used with threshold from argument 'limit'                 |
| limit  | (numeric) threshold value for retaining values, used with distace-type specified in argument 'compTy' |

|             |   |
|-------------|---|
| asIndex     | (logical) optionally rather report index of retained values   |
| maxFitShort | (numeric) limit output to max number of elements (avoid returning high number of results if filtering was not enough stringent)   |
| sortMatch   | (logical) if TRUE than matching will be performed as 'match longer (of x & y) to closer', this may process slightly faster (eg 'x' longer: list for each 'y' all 'x' that are close, otherwise list of each 'x'), |
| silent      | (logical) suppress messages   |
| callFrom    | (character) allow easier tracking of message(s) produced  |

### Value

list with close matches of 'x' to given 'y', the numeric value depends on 'sortMatch' (if FALSE then always value of 'y' otherwise of longest of x&y)

### See Also

[checkSimValueInSer](#) and (from this package) `.compareByDiff`, for convenient output [countCloseToLimits](#)

### Examples

```
aa <- 11:14 ; bb <- c(13.1,11.5,14.3,20:21)
findCloseMatch(aa,bb,com="diff",lim=0.6)
findCloseMatch(c(a=5,b=11,c=12,d=18),c(G=2,H=11,I=12,J=13)+0.5,comp="diff",lim=2)
findCloseMatch(c(4,5,11,12,18),c(2,11,12,13,33)+0.5,comp="diff",lim=2)
findCloseMatch(c(4,5,11,12,18),c(2,11,12,13,33)+0.5,comp="diff",lim=2,sort=FALSE)
.compareByDiff(list(c(a=10,b=11,c=12,d=13),c(H=11,I=12,J=13,K=33)+0.5),limit=1) #' return matrix

a2 <- c(11:20); names(a2) <- letters[11:20]
b2 <- c(25:5)+c(rep(0,5),(1:10)/50000,rep(0,6)); names(b2) <- LETTERS[25:5]
which(abs(b2-a2[8]) < a2[8]*1e-6*5) #' find R=18 : no10
findCloseMatch(a2,b2,com="ppm",lim=5) #' find Q,R,S,T
findCloseMatch(a2,b2,com="ppm",lim=5,asI=TRUE) #' find Q,R,S,T
findCloseMatch(b2,a2,com="ppm",lim=5,asI=TRUE,sort=FALSE)
findCloseMatch(a2,b2,com="ratio",lim=1.000005) #' find Q,R,S,T
findCloseMatch(a2,b2,com="diff",lim=0.00005) #' find S,T
```

---

findRepeated *Find repeated elements*

---

### Description

findRepeated gets index of repeated items/values in vector 'x' (will be treated as character). Return (named) list of indexes for each of the repeated values, or NULL if all values are unique. This approach is similar but more basic compared to [get1stOfRepeatedByCol](#).

### Usage

```
findRepeated(x, nonRepeated = FALSE, silent = FALSE, callFrom = NULL)
```

**Arguments**

|             |  |
|-------------|--|
| x           | character vector   |
| nonRepeated | (logical) if =TRUE, return list with elements \$rep and \$nonrep |
| silent      | (logical) suppress messages                                      |
| callFrom    | (character) allow easier tracking of message(s) produced         |

**Value**

(named) list of indexes for each of the repeated values, or NULL if all values unique

**See Also**

similar approach but more basic than [get1stOfRepeatedByCol](#)

**Examples**

```
aa <- c(11:16,14:12,14); findRepeated(aa)
```

---

findSimilFrom2sets      *Find similar numeric values from two vectors/matrixes*

---

**Description**

findSimilFrom2sets compares to vectors or matrixes and returns combined view including only all close (by [findCloseMatch](#)). Return matrix (predMatr) with add'l columns for index to and 'grp' (group of similar values (1-to-many)), 'nGrp' (n of grp), 'isBest' or 'nBest', 'disToMeas' (distance/difference between pair) & 'ppmToPred' (distance in ppm). Note: too wide 'limitComp' will result in large window and many 'good' hits will compete (and be mutually excluded) if selection 'bestOnly' is selected

**Usage**

```
findSimilFrom2sets(
  predMatr,
  measMatr,
  colMeas = 1,
  colPre = 1,
  compareTy = "diff",
  limitComp = 0.5,
  bestOnly = FALSE,
  silent = FALSE,
  callFrom = NULL,
  debug = FALSE
)
```

**Arguments**

|           |   |
|-----------|---|
| predMatr  | (matrix or numeric vector) dataset number 1, referred to as 'predicted', the column specified in argument colPre points to the data to be used  |
| measMatr  | (matrix or numeric vector) dataset number 2, referred to as 'measured', the column specified in argument colMeas points to the data to be used  |
| colMeas   | (integer) which column number of 'measMatr' to consider   |
| colPre    | (integer) which column number of 'predMatr' to consider   |
| compareTy | (character) 'diff' (difference) 'ppm' (relative difference)   |
| limitComp | (numeric) limit used by 'compareTy'   |
| bestOnly  | (logical) allows to filter only hits with min distance (defined by 'compareTy'), 3rd last col will be 'nBest' - otherwise 3rd last col 'isBest' |
| silent    | (logical) suppress messages   |
| callFrom  | (character) allow easier tracking of message(s) produced  |
| debug     | (logical) for bug-tracking: more/enhanced messages  |

**Value**

matrix (predMatr) with add'l columns for index to and 'grp' (group of similar values (1-to-many)), 'nGrp' (n of grp), 'isBest' or 'nBest', 'disToMeas' (distance/difference between pair) & 'ppmToPred' (distance in ppm)

**See Also**

[checkSimValueInSer](#) [findCloseMatch](#) [closeMatchMatrix](#)

**Examples**

```
aA <- c(11:17); bB <- c(12.001,13.999); cC <- c(16.2,8,9,12.5,12.6,15.9,14.1)
aZ <- matrix(c(aA,aA+20),ncol=2,dimnames=list(letters[1:length(aA)],c("aa","aZ")))
cZ <- matrix(c(cC,cC+20),ncol=2,dimnames=list(letters[1:length(cC)],c("cc","cZ")))
findCloseMatch(cC,aA,com="diff",lim=0.5,sor=FALSE)
findSimilFrom2sets(aA,cC)
findSimilFrom2sets(cC,aA)
findSimilFrom2sets(aA,cC,best=FALSE)
findSimilFrom2sets(aA,cC,comp="ppm",lim=5e4,deb=TRUE)
findSimilFrom2sets(aA,cC,comp="ppm",lim=9e4,best0=FALSE)
# below: find fewer 'best matches' since search window larger (ie more good hits compete !)
findSimilFrom2sets(aA,cC,comp="ppm",lim=9e4,best0=TRUE)
```

---

findUsableGroupRange *Select groups within given range*

---

### Description

This function aims to help finding stretches/segments of data with a given maximum number of NA-instances. This function is used to inspect/filter each lines of 'dat' for a subset with sufficient presence/absence of NA values (ie limit number of NAs per level of 'grp'). Note : optimal performance with n.lines » n.groups

### Usage

```
findUsableGroupRange(dat, grp, maxNA = 1, callFrom = NULL)
```

### Arguments

dat (matrix or data.frame) main input  
 grp (factor) information which column of 'dat' is replicate of whom  
 maxNA (interger) max number of tolerated NAs  
 callFrom (character) allow easier tracking of message(s) produced

### Value

matrix with boundaries of 1st and last usable column (NA if there were no suitable groups found)

### Examples

```
dat1 <- matrix(1:56,nc=7)
dat1[c(2,3,4,5,6,10,12,18,19,20,22,23,26,27,28,30,31,34,38,39,50,54)] <- NA
rownames(dat1) <- letters[1:nrow(dat1)]
findUsableGroupRange(dat1,gl(3,3)[-3:4])
```

---

firstLineOfDat *Filter matrix to keep only first of repeated lines*

---

### Description

This function aims to reduce the complexity of a matrix (or data.frame) in case column 'refCol' has multiple lines with same value. In this case, it reduces the input-data to 1st line of redundant entries and returns a matrix (or data.frame) without lines identified as redundant entries for 'refCol'. In sum, this functions works like using unique on a given column, and propagates the same treatment to all other columns.

### Usage

```
firstLineOfDat(dat, refCol = 2, silent = FALSE, callFrom = NULL)
```

**Arguments**

|          |  |
|----------|--|
| dat      | (matrix or data.frame) main input                        |
| refCol   | (integer) column number of reference-column              |
| silent   | (logical) suppress messages                              |
| callFrom | (character) allow easier tracking of message(s) produced |

**Value**

matrix (same number of columns as input)

**See Also**

[firstOfRepeated](#), [unique](#), [duplicated](#)

**Examples**

```
(mat1 <- matrix(c(1:6,rep(1:3,1:3)),ncol=2,dimnames=list(letters[1:6],LETTERS[1:2])))
firstLineOfDat(mat1)
```

---

|                 |  |
|-----------------|--|
| firstOfRepeated | <i>Find first of repeated elements</i> |
|-----------------|--|

---

**Description**

This function works similar to `unique`, but provides additional information about which elements of original input 'x' are repeated by providing indexes relative to the input. `firstOfRepeated` makes list with 3 elements: `$indRepeated..` index for first of repeated 'x', `$indUniq..` index of all unique + first of repeated, `$indRedund..` index of all redundant entries, ie non-unique (wo 1st). Used for reducing data to non-redundant status, however, for large numeric input the function `nonAmbiguousNum()` may perform better/faster. NAs won't be considered (NAs do not appear in reported index of results), see also `firstOfRepLines()`.

**Usage**

```
firstOfRepeated(x, callFrom = NULL)
```

**Arguments**

|          |  |
|----------|--|
| x        | (character or numeric) main input                        |
| callFrom | (character) allow easier tracking of message(s) produced |

**Value**

list with indices: `$indRepeated`, `$indUniq`, `$indRedund`

**See Also**

[duplicated](#), [nonAmbiguousNum](#), [firstOfRepLines](#) gives less detail in output (lines/elements/indexes of omitted not directly accessible) and works faster

**Examples**

```
x <- c(letters[c(3,2:4,8,NA,3:1,NA,5:4)]); names(x) <- 100+(1:length(x))
firstOfRepeated(x)
x[firstOfRepeated(x)$indUniq]          # only unique with names
```

---

|                 |   |
|-----------------|---|
| firstOfRepLines | <i>Reduce to first occurrence of repeated lines</i> |
|-----------------|---|

---

**Description**

This function concatenates all columns of input-matrix and then searches like `unique` for unique elements, optionally the indexes of unique elements may get returned. Note: This function treats input as character (thus won't understand `10==10.0`). Returns simplified/non-redundant vector/matrix (ie fewer lines), or respective index. faster than [firstOfRepeated](#)

**Usage**

```
firstOfRepLines(mat, outTy = "ind", useCol = NULL, callFrom = NULL)
```

**Arguments**

|                       |  |
|-----------------------|--|
| <code>mat</code>      | initial matrix to treat  |
| <code>outTy</code>    | for output type: 'ind'.. index to 1st occurrence (non-red), 'orig'..non-red lines of mat, 'conc'.. non-red concatenated values, 'num'.. index to which group/category the lines belong |
| <code>useCol</code>   | (integer) custom choice of which columns to paste/concatenate  |
| <code>callFrom</code> | (character) allows easier tracking of messages produced  |

**Value**

simplified/non-redundant vector/matrix (ie fewer lines for matrix), or respective index

**See Also**

[unique](#), [nonAmbiguousNum](#), faster than [firstOfRepeated](#) which gives more detail in output (lines/elements/indexes of omitted)

**Examples**

```
mat <- matrix(c("e","n","a","n","z","z","n","z","z","b",
               "", "n", "c", "n", "", "", "n", "", "", "z"), ncol=2)
firstOfRepLines(mat, out="conc")
```

---

|               |   |
|---------------|---|
| fuseAnnotMatr | <i>Fuse annotation matrix to initial matrix</i> |
|---------------|---|

---

### Description

In a number of instances experimental measurements and additional information (annotation) are provided by separate objects (matrixes) as they may not be generated the same time. The aim of this function is provide help when matching appropriate lines for 2 sets of data (experimental measures in `iniTab` and annotation from `annotTab`) for fusing. `fuseAnnotMatr` adds supplemental columns/annotation to an initial matrix `iniTab` : using column `'refIniT'` as key (in `iniTab`) to compare with key `'refAnnotT'` (from `'annotTab'`). The columns to be added from `annotTab` must be chosen explicitly. Note: if non-unique IDs in `iniTab` : runs slow (but save) due to use of loop for each unique ID.

### Usage

```
fuseAnnotMatr(  
  iniTab,  
  annotTab,  
  refIniT = "Uniprot",  
  refAnnotT = "combName",  
  addCol = c("ensembl_gene_id", "description", "geneName", "combName"),  
  debug = TRUE,  
  silent = FALSE,  
  callFrom = NULL  
)
```

### Arguments

|                        |   |
|------------------------|---|
| <code>iniTab</code>    | (matrix), that may have lines with multiple (=repeated) key entries                               |
| <code>annotTab</code>  | (matrix) containing reference annotation  |
| <code>refIniT</code>   | (character) type of reference (eg <code>'Uniprot'</code> )  |
| <code>refAnnotT</code> | (character) column name to use for reference-annotation   |
| <code>addCol</code>    | (character) column-names of <code>'annotTab'</code> to use/extract (if no matches found, use all) |
| <code>debug</code>     | (logical) for bug-tracking: more/enhanced messages  |
| <code>silent</code>    | (logical) suppress messages   |
| <code>callFrom</code>  | (character) allow easier tracking of message(s) produced  |

### Value

combined matrix (elements not found in `'annotTab'` are displayed as NA)

### See Also

[merge](#)

**Examples**

```

tab0 <- matrix(rep(letters[1:25], 8), ncol=10)
tab1 <- cbind(Uniprot=paste(tab0[, 1], tab0[, 2]), col1=paste(tab0[, 3],
  tab0[, 4], tab0[, 5], " ", tab0[, 7], tab0[, 6]))
tab2 <- cbind(combName=paste(tab0[, 1], tab0[, 2]), col2=paste(tab0[, 8], tab0[, 9], tab0[, 10]))
fuseAnnotMatr(tab1, tab2[c(20:11, 2:5), ], refIni="Uniprot", refAnnotT="combName", addCol="col2")
fuseAnnotMatr(tab2[c(20:11, 2:5), ], tab1, refAnnotT="Uniprot", refIni="combName", addCol="col1")

```

---

fuseCommonListElem      *Fuse content of list-elements with redundant (duplicated) names*

---

**Description**

fuseCommonListElem fuses (character or numeric) elements of list re-occurring under same name, so that resultant list has unique names. Note : will not work with list of matrixes

**Usage**

```

fuseCommonListElem(
  lst,
  initOrd = TRUE,
  removeDuplicates = FALSE,
  callFrom = NULL
)

```

**Arguments**

lst                    (list) main input, list of numeric vectors

initOrd                (logical) preserve initial order in output (if TRUE) or otherwise sort alphabetically

removeDuplicates      (logical) allow to remove duplicate entries (if vector contains names, both the name and the value need to be identical to be removed; note: all names must have names with more than 0 characters to be considered as names)

callFrom               (character) allows easier tracking of message(s) produced

**Value**

fused list (same names as elements of input)

**See Also**

[unlist](#)

**Examples**

```
val1 <- 10 +1:26
names(val1) <- letters
lst1 <- list(c=val1[3:6],a=val1[1:3],b=val1[2:3],a=val1[12],c=val1[13])
fuseCommonListElem(lst1)
```

---

 fusePairs

*Fuse pairs to generate cluster-names*


---

**Description**

Fuse previously identified pairs to 'clusters', return vector with cluster-numbers.

**Usage**

```
fusePairs(
  datPair,
  refDatNames = NULL,
  inclRepLst = FALSE,
  maxFuse = NULL,
  debug = FALSE,
  silent = TRUE,
  callFrom = NULL
)
```

**Arguments**

|             |   |
|-------------|---|
| datPair     | 2-column matrix where each line represents 1 pair   |
| refDatNames | (NULL or character) allows placing selected pairs in context of larger data-set (names to match those of 'datPair')         |
| inclRepLst  | (logical) if TRUE, return list with 'clu' (clu-numbers, default output) and 'refLst' (list of clustered elements, only n>1) |
| maxFuse     | (integer, default NULL) maximal number of groups/clusters   |
| debug       | (logical) for bug-tracking: more/enhanced messages and intermediate objects written in global name-space                    |
| silent      | (logical) suppress messages   |
| callFrom    | (character) allow easier tracking of message(s) produced  |

**Value**

vector with cluster-numbers

**Examples**

```
daPa <- matrix(c(1:5,8,2:6,9),ncol=2)
fusePairs(daPa,maxFuse=4)
```

---

get1stOfRepeatedByCol *Get first of repeated by column*

---

### Description

get1stOfRepeatedByCol sorts matrix 'mat' and extracts only 1st occurrence of values in column 'sortBy'. Returns then non-redundant matrix (ie for column 'sortBy', if 'markIfAmbig' specifies existing col, mark ambig there). Note : problem when sortSupl or sortBy not present (or not intended for use)

### Usage

```
get1stOfRepeatedByCol(
  mat,
  sortBy = "seq",
  sortSupl = "ty",
  asFirstLast = c("full", "inter"),
  markIfAmbig = c("ambig", "seqNa"),
  asList = FALSE,
  abmiPref = "_"
)
```

### Arguments

|             |   |
|-------------|---|
| mat         | (matrix or data.frame) numeric vector to be tested  |
| sortBy      | column name for which elements should be made unique, numeric or character column; 'sortSupl' .. add'l colname to always select specific 1st)           |
| sortSupl    | default="ty"  |
| asFirstLast | (character,length=2) to force specific strings from coluln 'sortSupl' as first and last when selecting 1st of repeated terms, default=c("full","inter") |
| markIfAmbig | (character,length=2) 1st will be set to 'TRUE' if ambiguous/repeated, 2nd will get (heading) prefix, default=c("ambig","seqNa")                         |
| asList      | (logical) to return list with non-redundant ('unique') and removed lines ('repeats')  |
| abmiPref    | (character) prefix to note ambiguous entries/terms, default="_"   |

### Value

depending on 'asList' either list with non-redundant ('unique') and removed lines ('repeats')

### See Also

[firstOfRepeated](#) for (more basic) treatment of simple vector, [nonAmbiguousNum](#) for numeric use (much faster !!!)

**Examples**

```
aa <- cbind(no=as.character(1:20), seq=sample(LETTERS[1:15], 20, repl=TRUE),
  ty=sample(c("full", "Nter", "inter"), 20, repl=TRUE), ambig=rep(NA, 20), seqNa=1:20)
get1stOfRepeatedByCol(aa)
```

---

```
getValuesByUnique      Print matrix-content as plot
```

---

**Description**

When data have repeated elements (defined by names inside the vector), it may be advantageous to run some operations only on a unique set of the initial data, or sometimes all repeated occurrences need to be replaced by a common (summarizing) value. This function allows to re-introduce new values from on second vector with unique names, to return a final vector of initial input-length and order of names (elements) like initial, too. Normally the user would provide 'datUniq' (without repeated names) containing new values which will be expanded to structure of 'dat', if 'datUniq' is not provided a vector with unique names will be made using the first occurrence of repeated value(s). For more complex cases the indexing relative to 'datUniq' can be returned (setting asIndex=TRUE). Note: If not all names of 'dat' are found in 'datUniq' the missing spots will be returned as NA.

**Usage**

```
getValuesByUnique(
  dat,
  datUniq = NULL,
  asIndex = FALSE,
  silent = FALSE,
  callFrom = NULL
)
```

**Arguments**

|          |  |
|----------|--|
| dat      | (numeric or character) main long input, must have names  |
| datUniq  | (numeric or character) will be used to impose values on dat, must have names that should match names (at least partially) from dat |
| asIndex  | (logical) if TRUE index values will be returned instead of replacing values  |
| silent   | (logical) suppress messages  |
| callFrom | (character) allow easier tracking of message(s) produced   |

**Value**

vector of length dat with imposed values, or index values if asIndex=TRUE

**See Also**

[unique](#), [findRepeated](#), [correctToUnique](#), [treatTxtDuplicates](#)

**Examples**

```

dat <- 11:19
names(dat) <- letters[c(6:3,2:4,8,3)]
## let's make a 'datUniq' with the mean of repeated values :
datUniq <- round(tapply(dat,names(dat),mean),1)
## now propagate the mean values to the full vector
getValuesByUnique(dat,datUniq)
cbind(ini=dat,firstOfRep=getValuesByUnique(dat,datUniq),
      indexUniq=getValuesByUnique(dat,datUniq,asIn=TRUE))

```

---

gitDataUrl

*Convert url-name for reading in raw-mode*


---

**Description**

This functions converts a given urlName so that from data from git-hub can be read correctly that tabular data. Thus, this will remove '/blob/' and change starting characters to 'raw.githubusercontent.com'

**Usage**

```
gitDataUrl(urlName, replTxt = NULL, silent = FALSE, callFrom = NULL)
```

**Arguments**

|          |  |
|----------|--|
| urlName  | (character) main url-address   |
| replTxt  | (NULL or matrix) adjust/ custom-modify search- and replacement items; should be matrix with 2 columns, the 1st colimn entries will be used as 'search-for' and the 2nd as 'replace by' fro each row. |
| silent   | (logical) suppress messages  |
| callFrom | (character) allow easier tracking of message(s) produced   |

**Value**

corrected urlName

**See Also**

[sub](#);

**Examples**

```

ur11 <- paste0("https://github.com/bigbio/proteomics-metadata-standard/blob/",
              "master/annotated-projects/PXD001819/PXD001819.sdrf.tsv")
gitDataUrl(ur11)

```

---

htmlSpecCharConv      *Html special character conversion*

---

### Description

Converts 'txt' so that (the most common) special characters (like 'beta', 'micro', 'square' etc) will be displayed correctly when used for display in html (eg at mouse-over). Note : The package `stringi` is required for the conversions (the input will get returned if `stringi` is not available). Currently only the 16 most common special characters are implemented.

### Usage

```
htmlSpecCharConv(txt, callFrom = NULL)
```

### Arguments

`txt`                      character vector including special characters  
`callFrom`                (character) allow easier tracking of message produced

### Value

This function returns a corrected character vector adopted for html display

### See Also

tables on <https://www.htmlhelp.com/reference/html40/entities/latin1.html>, <https://www.degraeve.com/reference/specialcharacters.php>, <https://ascii.cl/htmlcodes.htm>

### Examples

```
(x <- stringi::stri_unescape_unicode("\u00b5\u003d\u0061\u0062"))  
htmlSpecCharConv(x)
```

---

keepCommonText      *Extract Longest Common Text Out Of Character Vector*

---

### Description

This function allows recovering the single longest common text-fragments (from center, head or tail) out of character vector `txt`. Only the first of all of the longest solutions will be returned.

**Usage**

```
keepCommonText(
  txt,
  minNchar = 1,
  side = "center",
  hiResol = TRUE,
  silent = TRUE,
  callFrom = NULL,
  debug = FALSE
)
```

**Arguments**

|          |  |
|----------|--|
| txt      | character vector to be treated   |
| minNchar | (integer) minimum number of characters that must remain  |
| side     | (character) may be either 'center', 'any', 'terminal', 'left' or 'right'; only with side='center' or 'any' internal text-segments may be found               |
| hiResol  | (logical) find best solution, but at much higher computational cost (eg 3x slower, however hiResol=FALSE rather finds anchor which may need to get extended) |
| silent   | (logical) suppress messages  |
| callFrom | (character) allow easier tracking of messages produced   |
| debug    | (logical) display additional messages for debugging  |

**Details**

Please note, that finding common parts between chains of characters is not a completely trivial task. This topic still has ongoing research for the application of sequence-alignments, where chains of characters to be compared get very long. This function uses a k-mer inspired approach. The initial aim with this function was allowing to treat smaller chains of characters (and finding shorter stretches of common text), like eg with column-names.

Important : This function identifies only the first best hit, ie other shared/common character-chains of the same length will not be found !

Using the argument hiResol=FALSE it is possible to accelerate the search approx 3x (with larger character-vectors), however, frequently the very best solution may not be found. This means, that in this case the result should rather be considered a 'seed', allowing check if further extension may improve the result, ie for identifying a (slightly) longer chain of common characters.

With longer vectors and longer character chains this may get demanding on computational resources, the argument hiResol=FALSE allows reducing this at the price of missing the best solution. With this argument single common/matching characters will not be searched if all text-elements are longer than 500 characters, an empty character vector will be returned.

When argument side is either left, right or terminal only terminal common text may be found (a potentially even longer internal text will be lost). Of course, choosing this option makes searches much faster.

This function does not return the position of the shared/common characters within the text, you may use grexpr or regex to locate them.

**Value**

This function returns a character vector of length=1, ie only one (normally the longest) common sequence of characters is identified. If nothing is found common/shared an empty character-vector is returned

**See Also**

Use `gregexpr` or `regexec` in [grep](#) for locating the identified common characters in the initial query.

Inverse : Trim redundant text (from either side) to keep only variable part using [trimRedundText](#); you may also look for related functions in package [stringr](#)

**Examples**

```
txt1 <- c("abcd_abc_kjh", "bcd_abc123", "cd_abc_po")
keepCommonText(txt1, side="center")      # trim from right

txt2 <- c("ddd_ab", "ddd_bcd", "ddd_cde")
trimRedundText(txt2, side="left")       #
keepCommonText(txt2, side="center")     #
```

---

levIndex

*Transform (factor) levels into index*


---

**Description**

This function helps transforming a numeric or character vector into indexes of levels (of its original values). By default indexes are assigned by order of occurrence, ie, the first value of x will be get the index of 1. Using the argument `byOccurance=FALSE` the resultant indexes will follow the sorted values.

**Usage**

```
levIndex(dat, byOccurance = TRUE, silent = FALSE, callFrom = NULL)
```

**Arguments**

|                          |   |
|--------------------------|---|
| <code>dat</code>         | (numeric or character vector or factor) main input  |
| <code>byOccurance</code> | (logical) toggle if lowest index should be based on alphabetical order or on order of input |
| <code>silent</code>      | (logical) suppress messages   |
| <code>callFrom</code>    | (character) allow easier tracking of message(s) produced                                    |

**Value**

matrix with mean values

**See Also**

[rowSds](#), [colSums](#)

**Examples**

```
x1 <- letters[rep(c(5,2:3),1:3)]
levIndex(x1)
levIndex(x1, byOccurance=FALSE)
## with factor
fa1 <- factor(letters[rep(c(5,2:3),1:3)], levels=letters[1:6])
levIndex(fa1)
levIndex(fa1, byOccurance=FALSE)
```

---

|                |  |
|----------------|--|
| linModelSelect | <i>Test multiple starting levels for linear regression model, select best and plot</i> |
|----------------|--|

---

**Description**

The aim of this function is to select the data suiting set of levels of the main input data to construct a linear regression model. In real world measurements one may be confronted to the case of very low level analytes below the detection limit (LOD) and resulting read-outs fluctuate around around a common baseline (instead of NA). With such data it may be preferable to omit the read-outs for the lowest concentrations/levels of analytes if they are spread around a base-line value. This function allows trying to omit all starting levels designed in `startLev`, then the resulting p-values for the linear regression slopes will be checked and the best p-value chosen. The input may also be a `MArrayLM`-type object from package `limma` or from `moderTestXgrp` or `moderTest2grp`. In the graphical representation all points associated to levels omitted are shown in light green. For the graphical display additional information can be used : If the `dat` is list or `MArrayLM`-type object, the list-elements `$raw` (according to argument `lisNa` will be used to display points initially given as NA and imputed later on in grey. Logarithmic (ie log-linear) data can be treated by setting argument `logExpect=TRUE`. Then the levels will be taken as exponent of 2 for the regression, while the original values will be displayed in the figure.

**Usage**

```
linModelSelect(
  rowNa,
  dat,
  expect,
  logExpect = FALSE,
  startLev = NULL,
  lisNa = c(raw = "raw", annot = "annot", datImp = "datImp"),
  plotGraph = TRUE,
  tit = NULL,
  pch = c(1, 3),
  cexLeg = 0.95,
```

```

    cexSub = 0.85,
    xLab = NULL,
    yLab = NULL,
    cexXAxis = 0.85,
    cexYAxis = 0.9,
    xLabLas = 1,
    cexLab = 1.1,
    silent = FALSE,
    callFrom = NULL
)

```

### Arguments

|           |   |
|-----------|---|
| rowNa     | (character, length=1) rowname for line to be extracted from dat   |
| dat       | (matrix, list or MArrayLM-object from limma) main input of which columns should get re-ordered, may be output from <a href="#">moderTestXgrp</a> or <a href="#">moderTest2grp</a> .   |
| expect    | (numeric or character) the expected levels; if character, constant unit-characters will be stripped away to extract the numeric content   |
| logExpect | (logical) toggle to TRUE if the main data are logarithmic but expect is linear  |
| startLev  | (integer) specify all starting levels to test for omitting here (multiple start sites for modelling linear regression may be specified to finally pick the best model)  |
| lisNa     | (character) in case dat is list or MArrayLM-type object, the list-elements with these names will be used as \$raw (for indicating initial NA-values, \$datImp (the main quantitation data to use) and \$annot for displaying the corresponding value from the "Accession"-column. |
| plotGraph | (logical) display figure  |
| tit       | (character) optional custom title   |
| pch       | (integer) symbols to use n optional plot; 1st for regular values, 2nd for values not used in regression   |
| cexLeg    | (numeric) size of text in legend  |
| cexSub    | (numeric) text-size for line (as subtitle) giving regression details of best linear model)  |
| xLab      | (character) custom x-axis label   |
| yLab      | (character) custom y-axis label   |
| cexXAxis  | (character) cex-type for size of text for x-axis labels   |
| cexYAxis  | (character) cex-type for size of text for y-axis labels   |
| xLabLas   | (integer) las-type orientation of x-axis labels (set to 2 for vertical axis-labels)   |
| cexLab    | (numeric) cex-type for size of text in x & y axis labels (will be passed to cex.lab in plot())  |
| silent    | (logical) suppress messages   |
| callFrom  | (character) allow easier tracking of messages produced  |

**Value**

This function returns a list with \$coef (coefficients), \$name (as/from input rowNa), \$startLev the best starting level)

**See Also**

[moderTestXgrp](#) for single comparisons, [order](#)

**Examples**

```
## Construct data
li1 <- rep(c(4,3,3:6),each=3) + round(runif(18)/5,2)
names(li1) <- paste0(rep(letters[1:5], each=3), rep(1:3,6))
li2 <- rep(c(6,3:7), each=3) + round(runif(18)/5, 2)
dat2 <- rbind(P1=li1, P2=li2)
exp2 <- rep(c(11:16), each=3)

## Check & plot for linear model
linModelSelect("P2", dat2, expect=exp2)

## Log-Linear data
## Suppose dat2 is result of measures in log2, but exp4 is not
exp4 <- rep(c(3,10,30,100,300,1000), each=3)
linModelSelect("P2", dat2, expect=exp4, logE=FALSE) # bad
linModelSelect("P2", dat2, expect=exp4, logE=TRUE)
```

---

linRegrParamAndPVal *Fit linear regression, return parameters and p-values*

---

**Description**

This function fits a linear regression and returns the parameters, including p-values from Anova. Here the vector 'y' (scalar response or dependent variable, ie the value that should get estimated) will be estimated according to 'dep' (explanatory or independent variable). Alternatively, 'dep' may me a matrix where 1st column will be used as 'dep' and the 2nd column as 'y'.

**Usage**

```
linRegrParamAndPVal(dep, y = NULL, asVect = TRUE)
```

**Arguments**

|        |   |
|--------|---|
| dep    | (numeric vector, matrix or data.frame) explanatory or dependent variable, if matrix or data.frame the 1st column will be used, if 'y'=NULL the 2nd column will be used as 'y' |
| y      | (numeric vector) independent variable (the value that should get estimated based on 'dep')  |
| asVect | (logical) return numeric vector (Intercept, slope, p.intercept, p.slope) or matrix or results   |

**Value**

numeric vector (Intercept, slope, p.intercept, p.slope), or if asVect==TRUE as matrix (p.values in 2nd column)

**See Also**

[lm](#)

**Examples**

```
linRegrParamAndPVal(c(5,5.1,8,8.2),gl(2,2))
```

---

|                  |                             |
|------------------|-----------------------------|
| listBatchReplace | <i>Replacements in list</i> |
|------------------|-----------------------------|

---

**Description**

listBatchReplace replaces in list lst all entries with value searchValue by replaceBy

**Usage**

```
listBatchReplace(lst, searchValue, replaceBy, silent = FALSE, callFrom = NULL)
```

**Arguments**

|             |  |
|-------------|--|
| lst         | input-list to be used for replacing                      |
| searchValue | (character, length=1)                                    |
| replaceBy   | (character, length=1)                                    |
| silent      | (logical) suppress messages                              |
| callFrom    | (character) allow easier tracking of message(s) produced |

**Value**

This function returns a corrected list

**See Also**

basic replacement sub in [grep](#)

**Examples**

```
lst1 <- list(aa=1:4, bb=c("abc","efg","abh","effge"), cc=c("abdc","efg"))
listBatchReplace(lst1, search="efg", repl="EFG", sil=FALSE)
```

---

|                   |  |
|-------------------|--|
| listGroupsByNames | <i>Organize values into list and sort by names</i> |
|-------------------|--|

---

**Description**

Sort values of 'x' by its names and organize as list by common names, the names until 'sep' are used for (re)grouping. Note that typical separators occurring the initial names may need protection by '\` (this is automatically taken care of for the case of the dot ('.') separator).

**Usage**

```
listGroupsByNames(x, sep = ".", silent = FALSE, callFrom = NULL)
```

**Arguments**

|          |   |
|----------|---|
| x        | (list) main input   |
| sep      | (character) separator (note that typical separators may need to be protected, only automatically added for '.') |
| silent   | (logical) suppress messages   |
| callFrom | (character) allows easier tracking of message(s) produced   |

**Value**

matrix or data.frame

**See Also**

rbind in [cbind](#)

**Examples**

```
listGroupsByNames((1:10)/5)
ser1 <- 1:6; names(ser1) <- c("AA", "BB", "AA.1", "CC", "AA.b", "BB.e")
listGroupsByNames(ser1)
```

---

|          |   |
|----------|---|
| lmSelClu | <i>Run lm on segmented data (from clustering)</i> |
|----------|---|

---

**Description**

lmSelClu runs linear regression on data segmented previously (eg by clustering). This function offers various types of (2-coefficient) linear regression on 2 columns of 'dat' (matrix with 3rd column named 'clu' or 'cluID', numeric elements for cluster-number). If argument 'clu' is (default) 'max', the column 'clu' will be inspected to take most frequent value of 'clu', otherwise a numeric entry specifying the cluster to extract is expected. Note: this function was initially made for use with results from diagCheck() Note: this function lacks means of judging goodness of fit of the regression performed & means for plotting

**Usage**

```
lmSelClu(
  dat,
  useCol = 1:2,
  clu = "max",
  regTy = "lin",
  filt1 = NULL,
  filt2 = NULL,
  silent = FALSE,
  callFrom = NULL
)
```

**Arguments**

|          |  |
|----------|--|
| dat      | matrix or data.frame   |
| useCol   | (integer or character) specify which 2 columns of 'dat' to use for linear regression   |
| clu      | (character) name of cluster to be extracted and treated  |
| regTy    | (character) change type used for linear regression : 'lin' for 1st col ~ 2nd col, 'res' for residue ~ 2nd col, 'norRes' for residue/2nd col ~ 2nd col or 'sqNorRes', 'inv' for 1st col ~ 1/(2nd col), 'invRes' for residue ~ 1/(2nd col) |
| filt1    | (logical or numerical) filter criteria for 1st of 'useCol' , if numeric then select all lines of dat less than max of filt1  |
| filt2    | (logical or numerical) filter criteria for 2nd of 'useCol' , if numeric then select all lines of dat less than max of filt2  |
| silent   | (logical) suppress messages  |
| callFrom | (character) allows easier tracking of message(s) produced  |

**Value**

lm object (or NULL if no data left)

**See Also**

[lm](#)

**Examples**

```
set.seed(2016); ran1 <- runif(220)
mat1 <- round(rbind(matrix(c(1:100+ran1[1:100], rep(1,50)), ncol=3),
  matrix(c(1:60, 68:9+ran1[101:160], rep(2,60)), nc=3)), 1)
colnames(mat1) <- c("a", "BB", "clu")
lmSelClu(mat1)
plot(mat1[which(mat1[,3]=="2"), 1:2], col=grey(0.6))
abline(lmSelClu(mat1), lty=2, lwd=2)
#
mat2 <- round(rbind(matrix(c(1:100+ran1[1:100], rep(1,50)), ncol=3),
  matrix(c(1:60, (2:61+ran1[101:160])^2, rep(2,60)), nc=3)), 1)
colnames(mat2) <- c("a", "BB", "clu")
```

```
(reg2 <- lmSelClu(mat2,regTy="sqNor"))
plot(function(x) coef(reg2)[2]+ (coef(reg2)[2]*x^2),xlim=c(1,70))
points(mat2[which(mat2[,3]=="2"),1:2],col=2)
```

---

lrbind

*rbind on lists*

---

## Description

rbind-like function to append list-elements containing matrixes (or data.frames) and return one long table. All list-elements must have same number of columns (and same types of classes in case of data.frames. Simple vectors (as list-elements) will be considered as sigle lines for attaching.

## Usage

```
lrbind(lst, silent = FALSE, callFrom = NULL)
```

## Arguments

|          |  |
|----------|--|
| lst      | (list, composed of multiple matrix or data.frames or simple vectors) main input (each list-element should have same number of columns, numeric vectors will be converted to number of columns of other columns/elements) |
| silent   | (logical) suppress messages  |
| callFrom | (character) allow easier tracking of message(s) produced   |

## Value

This function returns (depending on input) a matrix or data.frame

## See Also

rbind in [cbind](#)

## Examples

```
lst1 <- list(matrix(1:9, ncol=3, dimnames=list(letters[1:3],c("AA","BB","CC"))),
  11:13, matrix(51:56, ncol=3))
lrbind(lst1)
```

---

`makeMAList`*Make MA-List object*

---

### Description

`makeMAList` extracts sets of data-pairs (like R & G series) and makes MA objects as MA-List object (eg for ratio oriented analysis). The grouping of columns as sets of replicate-measurements is done according to argument 'MAfac'. The output is fully compatible to functions of package [limma](#) (Bioconductor).

### Usage

```
makeMAList(  
  mat,  
  MAfac,  
  useF = c("R", "G"),  
  isLog = TRUE,  
  silent = FALSE,  
  callFrom = NULL  
)
```

### Arguments

|                       |   |
|-----------------------|---|
| <code>mat</code>      | main input matrix   |
| <code>MAfac</code>    | (factor) factor organizing columns of 'mat' (if useF contains the default 'R' and 'G', they should also be part of MAfac) |
| <code>useF</code>     | (character) two specific factor-levels of MAfac that will be used/extracted   |
| <code>isLog</code>    | (logical) tell if data is already log2 (will be considered when computing M and A values)                                 |
| <code>silent</code>   | (logical) suppress messages   |
| <code>callFrom</code> | (character) allows easier tracking of messages produced   |

### Details

This function requires Bioconductor package [limma](#) being installed.

### Value

limma-type "MAList" containing M and A values

### See Also

[test2factLimma](#), for creating RG-lists within limma: MA.RG in [normalizeWithinArrays](#)

**Examples**

```
set.seed(2017); t4 <- matrix(round(runif(40,1,9),2), ncol=4,
  dimnames=list(letters[c(1:5,3:4,6:4)], c("AA1","BB1","AA2","BB2")))
makeMAList(t4, gl(2,2,labels=c("R","G")))
```

---

|              |                                  |
|--------------|----------------------------------|
| makeNRedMatr | <i>Make non-redundant matrix</i> |
|--------------|----------------------------------|

---

**Description**

makeNRedMatr takes matrix or data.frame 'dat' to summarize redundant lines (column argument iniID) along method specified in summarizeRedAs to treat all lines with redundant iniID by same approach (ie for all columns the line where specified column is at eg max = 'maxOfRef' ). If no name given, the function will take the last numeric (factors may be used - they will be read as levels).

**Usage**

```
makeNRedMatr(
  dat,
  summarizeRedAs,
  iniID = "iniID",
  retDataFrame = TRUE,
  callFrom = NULL,
  silent = FALSE,
  debug = FALSE
)
```

**Arguments**

|                |  |
|----------------|--|
| dat            | (matrix or data.frame) main input for making non-redundant   |
| summarizeRedAs | (character) summarization method(s), typical choices 'median', 'mean', 'min' or 'maxOfRef', 'maxAbsOfRef' for summarizing according to 1 specified column, may be single method for all or different method for each column (besides col 'iniID') or special method looking at column (if found, first of special methods used, everything else not considered). |
| iniID          | (character) column-name used as initial ID (default="iniID")   |
| retDataFrame   | (logical) if TRUE, check if text-columns may be converted to data.frame with numeric   |
| callFrom       | (character) allows easier tracking of message(s) produced  |
| silent         | (logical) suppress messages  |
| debug          | (logical) for bug-tracking: more/enhanced messages   |

**Value**

(numeric) matrix or data.frame with summarized data and add'l col with number of initial redundant lines

**See Also**

simple/partial functionality in [summarizeCols](#), [checkSimValueInSer](#)

**Examples**

```
t3 <- data.frame(ref=rep(11:15,3),tx=letters[1:15],
  matrix(round(runif(30,-3,2),1),nc=2),stringsAsFactors=FALSE)
by(t3,t3[,1],function(x) x)
t(sapply(by(t3,t3[,1],function(x) x), summarizeCols, me="maxAbsOfRef"))
(xt3 <- makeNRedMatr(t3, summ="mean", iniID="ref"))
(xt3 <- makeNRedMatr(t3, summ=unlist(list(X1="maxAbsOfRef")), iniID="ref"))
```

---

matchNamesWithReverseParts

*Value Matching with optional reversing of sub-parts of non-matching elements*

---

**Description**

This function provides a variant to [match](#), where initially non-matching elements of *x* will be tested by decomposing non-matching elements, reversing the parts in front and after the separator *sep* and re-matching. If separator *sep* does not occur, a warning will be issued, if it occurs more than once, the parts before and after the first separator will be used and a warning issued.

**Usage**

```
matchNamesWithReverseParts(x, y, sep = "-", silent = FALSE, callFrom = NULL)
```

**Arguments**

|                 |  |
|-----------------|--|
| <i>x</i>        | (character) first vector for match                       |
| <i>y</i>        | (character) second vector for match                      |
| <i>sep</i>      | (character) separator between elements                   |
| <i>silent</i>   | (logical) suppress messages                              |
| <i>callFrom</i> | (character) allow easier tracking of message(s) produced |

**Value**

index for matching (integer) *x* to *y*

**See Also**

[match](#)

**Examples**

```
tx1 <- c("a-b","a-c","d-a","d-b","b-c","d-c")
tmp <- triCoord(4)
tx2 <- paste(letters[tmp[,1]],letters[tmp[,2]],sep="-")
## Some matches won't be found, since 'a-d' got reversed to 'd-a', etc...
match(tx1,tx1)
matchNamesWithReverseParts(tx1,tx2)
```

---

|                  |   |
|------------------|---|
| matchSampToPairw | <i>Match names to concatenated pairs of names</i> |
|------------------|---|

---

**Description**

The column-names of multiple pairwise testing contain the names of the initial groups/conditions tested, plus there is a separator (eg '-' in moderTestXgrp). Thus function allows to map back which groups/conditions were used by returning the index of the respective groups used in pair-wise sets.

**Usage**

```
matchSampToPairw(grpNa, pairwNa, sep = NULL, silent = FALSE, callFrom = NULL)
```

**Arguments**

|          |  |
|----------|--|
| grpNa    | (character) the names of the groups of replicates (ie conditions) used to test |
| pairwNa  | (character) the names of pairwise-testing (ie 'concatenated' sampNa            |
| sep      | (character) if not NULL the characters given will be used via stringsplit      |
| silent   | (logical) suppress messages  |
| callFrom | (character) allows easier tracking of message(s) produced                      |

**Details**

There are two modes of operation : 1) Argument sep is set to NULL : The names of initial groups/conditions (grpNa) will be tested for exact pattern matching either at beginning or at end of pair-wise names (pairwNa). This approach has the advantage that it does not need to be known what character(s) were used as separator (or they may change), but the disadvantage that in case the perfect grpNa was not given, the longest best match of grpNa will be returned.

2) The separator sep is given and exact matches at both sides will be searched. However, if the character(s) from sep do appear inside grpNa no matches will be found.

If some grpNa are not found in pairwNa this will be marked as NA.

**Value**

matrix of 2 columns with indices of sampNa with pairwNa as rows

**See Also**

(for running multiple pair-wise test) [moderTestXgrp](#), [grep](#), [strsplit](#)

**Examples**

```
pairwNa1 <- c("abc-efg", "abc-hij", "efg-hij")
grpNa1 <- c("hij", "abc", "abcc", "efg", "klm")
matchSampToPairw(grpNa1, pairwNa1)

pairwNa2 <- c("abc-efg", "abcc-hij", "abc-hij", "abc-hijj", "zz-zz", "efg-hij")
matchSampToPairw(grpNa1, pairwNa2)
```

---

matr2list

*Transform columns of matrix to list of vectors*


---

**Description**

convert matrix to list of vectors: each column of 'mat' as vector of list

**Usage**

```
matr2list(mat, concSym = ".", silent = FALSE, callFrom = NULL)
```

**Arguments**

|          |  |
|----------|--|
| mat      | (matrix) main input  |
| concSym  | (character) symbol for concatenating: concatenation of named vectors in list names as colname(s)+'concSym'+rowname |
| silent   | (logical) suppress messages  |
| callFrom | (character) allow easier tracking of messages produced   |

**Value**

matrix or array (1st dim is intraplate-position, 2nd .. plate-group/type, 3rd .. channels)

**See Also**

[convToNum](#)

**Examples**

```
mat1 <- matrix(1:12, ncol=3, dimnames=list(letters[1:4], LETTERS[1:3]))
mat2 <- matrix(LETTERS[11:22], ncol=3, dimnames=list(letters[1:4], LETTERS[1:3]))
matr2list(mat1); matr2list(mat2)
```

---

|             |  |
|-------------|--|
| mergeSelCol | <i>Merge selected columns out of 2 matrix or data.frames</i> |
|-------------|--|

---

**Description**

mergeSelCol merges selected columns out of 2 matrix or data.frames. 'selCols' will be used to define columns to be used; optionally may be different for 'dat2' : define in 'supCols2'. Output-cols will get additions specified in newSuff (default '.x' and '.y')

**Usage**

```
mergeSelCol(
  dat1,
  dat2,
  selCols,
  supCols2 = NULL,
  byC = NULL,
  useAll = FALSE,
  setRownames = TRUE,
  newSuff = c(".x", ".y"),
  callFrom = NULL
)
```

**Arguments**

|             |  |
|-------------|--|
| dat1        | matrix or data.frame for fusing  |
| dat2        | matrix or data.frame for fusing  |
| selCols     | will be used to define columns to be used; optionally may be different for 'dat2' : define in 'supCols2'     |
| supCols2    | if additional column-names should be extracted form dat2   |
| byC         | (character) 'by' value used in <a href="#">merge</a>   |
| useAll      | (logical) use all lines (will produce NAs when given identifier not found un 2nd group of data)              |
| setRownames | (logical) if TRUE, will use values of col used as 'by' as rownames instead of showing as add'l col in output |
| newSuff     | (character) prefix (argument 'suffixes' in merge)  |
| callFrom    | (character) allow easier tracking of message(s) produced   |

**Value**

data.frame

**See Also**

[merge](#), merge 3 data.frames using [mergeSelCol3](#)

**Examples**

```
mat1 <- matrix(c(1:7, letters[1:7], 11:17), ncol=3, dimnames=list(LETTERS[1:7], c("x1", "x2", "x3")))
mat2 <- matrix(c(1:6, c("b", "a", "e", "f", "g", "k"), 31:36),
  ncol=3, dimnames=list(LETTERS[11:16], c("y1", "x2", "x3")))
mergeSelCol(mat1, mat2, selC=c("x2", "x3"))
```

---

```
mergeSelCol3
```

```
mergeSelCol3
```

---

**Description**

successive merge of selected columns out of 3 matrix or data.frames. 'selCols' will be used to define columns to be used; optionally may be different for 'dat2' : define in 'supCols2'. Output-cols will get additions specified in newSuff (default '.x' and '.y')

**Usage**

```
mergeSelCol3(
  dat1,
  dat2,
  dat3,
  selCols,
  supCols2 = NULL,
  supCols3 = NULL,
  byC = NULL,
  useAll = FALSE,
  setRownames = TRUE,
  newSuff = c(".x", ".y", ".z"),
  callFrom = NULL
)
```

**Arguments**

|             |  |
|-------------|--|
| dat1        | matrix or data.frame for fusing  |
| dat2        | matrix or data.frame for fusing  |
| dat3        | matrix or data.frame for fusing  |
| selCols     | will be used to define columns to be used; optionally may be different for 'dat2' : define in 'supCols2' |
| supCols2    | if additional column-names should be extracted form dat2   |
| supCols3    | if additional column-names should be extracted form dat3   |
| byC         | (character) 'by' value used in <a href="#">merge</a>   |
| useAll      | (logical) use all lines (will produce NAs when given identifier not found un 2nd group of data)          |
| setRownames | if TRUE, will use values of col used as 'by' as rownames instead of showing as add'l col in output       |
| newSuff     | (character) prefix (argument 'suffixes' in merge)  |
| callFrom    | (character) allow easier tracking of message(s) produced   |

**Value**

data.frame

**See Also**[merge](#), [mergeSelCol](#)**Examples**

```
mat1 <- matrix(c(1:7, letters[1:7]), 11:17, ncol=3, dimnames=list(LETTERS[1:7], c("x1", "x2", "x3")))
mat2 <- matrix(c(1:6, c("b", "a", "e", "f", "g", "k"), 31:36), ncol=3,
  dimnames=list(LETTERS[11:16], c("y1", "x2", "x3")))
mat3 <- matrix(c(1:6, c("c", "a", "e", "b", "g", "k"), 51:56), ncol=3,
  dimnames=list(LETTERS[11:16], c("z1", "x2", "x3")))
mergeSelCol3(mat1, mat2, mat3, selC=c("x2", "x3"))
```

mergeVectors

*Merge Named Vectors***Description**

This function allows merging for multiple simple named vectors (each element needs to be named). Basically, all elements carrying the same name across different input-vectors will be aligned in the same column of the output (input-vectors appear as lines). If vectors are not given using a name (see first example below), they will be names 'x.1' etc (see argument `namePrefix`).

**Usage**

```
mergeVectors(
  ...,
  namePrefix = "x.",
  NAto0 = FALSE,
  callFrom = NULL,
  silent = FALSE
)
```

**Arguments**

|            |  |
|------------|--|
| ...        | all vectors that need to be merged   |
| namePrefix | (character) prefix to numbers used when vectors are not given with explicit names (second example) |
| NAto0      | (logical) optional replacement of NAs by 0   |
| callFrom   | (character) allow easier tracking of message produced  |
| silent     | (logical) suppress messages  |

**Details**

Note : The arguments 'namePrefix', 'NAto0', 'callFrom' and 'silent' must be given with full name to be recognized as such (and not get considered as vector for merging).

**Value**

matrix of merged values

**See Also**

[merge](#) (for two data.frames)

**Examples**

```
x1 <- c(a=1, b=11, c=21)
x2 <- c(b=12, c=22, a=2)
x3 <- c(a=3, d=43)
mergeVectors(vect1=x1, vect2=x2, vect3=x3)
x4 <- 41:44      # no names - not conform for merging
mergeVectors(x1, x2, x3, x4)
```

---

mergeW2

*Extended version of merge for multiple objects (even without row-names)*

---

**Description**

mergeW2 provides flexible merging out of 'MArrayLM'-object (if found, won't consider any other input-data) or of separate vectors or matrixes. The main idea was to have something not adding add'l lines as merge might do, but to stay within the frame of the 1st argument given, even when IDs are repeated, so the output follows the order of the 1st argument, non-redundant IDs are created (orig IDs as new column). If no 'MArrayLM'-object found: try to combine all elements of input '...', input-names must match predefined variants 'chInp'. IDs given in 1st argument and not found in later arguments will be displayed as NA in the output matrix of data.frame. Note : (non-data) arguments must be given with full name (so far no lazy evaluation, may conflict with names in 'inputNamesLst'). Note : special characters in colnames bound to give trouble. Note : when no names given, mergeW2 will presume order of elements (names) from 'inputNamesLst'. **PROBLEM** : error after xxMerg3 when several entries have matching (row)names but some entries match only partially (what to do : replace with NAs ??)

**Usage**

```
mergeW2(
  ...,
  nonRedundID = TRUE,
  convertDF = TRUE,
  selMerg = TRUE,
  inputNamesLst = NULL,
```

```

noMatchPursue = TRUE,
standColNa = FALSE,
lastOfMultCols = c("p.value", "Lfdr"),
duplTxtSep = "_",
silent = FALSE,
debug = FALSE,
callFrom = NULL
)

```

### Arguments

|                |   |
|----------------|---|
| ...            | all data (vectors, matrixes or data.frames) intended for merge  |
| nonRedundID    | (logical) if TRUE, always add 1st column with non-redundant IDs (add anyway if non-redundant IDs found)   |
| convertDF      | (logical) allows converting output in data.frame, add new heading col with non-red rownames & check which cols should be numeric  |
| selMerg        | (logical) if FALSE toggle to classic merge() (will give more rows in output in case of redundant names)   |
| inputNamesLst  | (list) named list with character vectors (should be unique), search these names in input for extracting/merging elements use for 'lazy matching' when checking names of input, default : 7 groups ('Mvalue', 'Avalue', 'p.value', 'mouseInfo', 'Lfdr', 'link', 'filt') with common short versions |
| noMatchPursue  | (logical) allows using entries where 0 names match (just as if no names given)  |
| standColNa     | (logical) if TRUE return standard colnames as defined in 'inputNamesLst' (ie 'chInp'), otherwise colnames as initially provided   |
| lastOfMultCols | may specify input groups where only last col will be used/extracted   |
| duplTxtSep     | (character) separator for counting/denominating multiple occurrences of same name   |
| silent         | (logical) suppress messages   |
| debug          | (logical) for bug-tracking: more/enhanced messages and intermediate objects written in global name-space  |
| callFrom       | (character) allows easier tracking of message(s) produced   |

### Value

matrix or data.frame of fused data

### See Also

[merge](#)

### Examples

```

t1 <- 1:10; names(t1) <- letters[c(1:7,3:4,8)]
t2 <- 20:11; names(t2) <- letters[c(1:7,3:4,8)]
t3 <- 101:110; names(t3) <- letters[c(11:20)]
t4 <- matrix(100:81, ncol=2, dimnames=list(letters[1:10], c("co1", "co2")))

```

```
t5 <- cbind(t1=t1,t52=t1+20,t53=t1+30)
t1; t2; t3; cbind(t1,t2)
mergeW2(Mval=t1,p.value=t2,debug=FALSE)
```

---

minDiff

*Minimum distance/difference between values*


---

### Description

minDiff aims to find the min distance (ie closest point) to any other x (numeric value), ie intra 'x' and returns matrix with 'index','value','dif','ppm','ncur','nbest','best'. At equal distance to lower & upper neighbour point, the upper (following) point is chosen (as single best). In case of multiple ex-aequo distance returns 1st of multiple, may be different at various repeats.

### Usage

```
minDiff(x, digSig = 3, ppm = TRUE, initOrder = TRUE, callFrom = NULL)
```

### Arguments

|           |  |
|-----------|--|
| x         | (numeric) vector to search minimum difference  |
| digSig    | number of significant digits, used for ratio or ppm column   |
| ppm       | (logical) display distance as ppm (1e6*diff/refValue, ie normalized difference eg as used in mass spectrometry), otherwise the ratio is given as : value(from 'x') / closestValue (from 'x') |
| initOrder | (logical) return matrix so that 'x' matches exactly 2nd col of output  |
| callFrom  | (character) allow easier tracking of message(s) produced   |

### Value

matrix

### See Also

[dist](#)

### Examples

```
set.seed(2017); aa <- 100*c(0.1+round(runif(20),2),0.53,0.53)
minDiff(aa); minDiff(aa,initO=TRUE,ppm=FALSE); .minDif(unique(aa))
```

moderTest2grp

*Moderated pair-wise t-test from limma***Description**

Runs moderated t-test from package 'limma' on each line of data. Note: This function requires the package **limma** from bioconductor. The limma contrast-matrix has to be read by column, the lines in the contrast-matrix containing '+1' will be compared to the '-1' lines, eg grpA-grpB . Local false discovery rates (lfdr) estimations will be made using the CRAN-package **fdrtool** (if available).

**Usage**

```
moderTest2grp(
  dat,
  grp,
  limmaOutput = TRUE,
  addResults = c("lfdr", "FDR", "Mval", "means"),
  testOrientation = "=",
  silent = FALSE,
  callFrom = NULL
)
```

**Arguments**

|                 |  |
|-----------------|--|
| dat             | matrix or data.frame with rows for multiple (independent) tests, use ONLY with 2 groups; assumed as log2-data  |
| grp             | (factor) describes column-relationship of 'dat' (1st factor is considered as reference -> orientation of M-values !!)  |
| limmaOutput     | (logical) return full (or extended) MArrayLM-object from limma or 'FALSE' for only the (uncorrected) p.values  |
| addResults      | (character) types of results to add besides basic limma-output, data are assumed to be log2 ! (eg "lfdr" using fdrtool-package, "FDR" or "BH" for BH-FDR, "BY" for BY-FDR, "bonferroni" for Bonferroni-correction, "qValue" for lfdr by qvalue, "Mval", "means" or "nonMod" for non-moderated test and he equivalent all (other) multiple testing corrections chosen here) |
| testOrientation | (character) for one-sided test (">","greater" or "<","less"), NOTE : 2nd grp is considered control/reference, '<' will identify grp1 < grp2  |
| silent          | (logical) suppress messages  |
| callFrom        | (character) allow easier tracking of message(s) produced   |

**Value**

This function returns a limma-type object of class MArrayLM

**See Also**

[lmFit](#) and the eBayes-family of functions in package [limma](#), [p.adjust](#)

**Examples**

```
set.seed(2017); t8 <- matrix(round(rnorm(1600,10,0.4),2), ncol=8,
  dimnames=list(paste("1",1:200),c("AA1","BB1","CC1","DD1","AA2","BB2","CC2","DD2")))
t8[3:6,1:2] <- t8[3:6,1:2]+3 # augment lines 3:6 for AA1&BB1
t8[5:8,5:6] <- t8[5:8,5:6]+3 # augment lines 5:8 for AA2&BB2 (c,d,g,h should be found)
t4 <- log2(t8[,1:4]/t8[,5:8])
## Two-sided testing
fit4 <- moderTest2grp(t4,gl(2,2))
# If you have limma installed we can now see further
if("list" %in% mode(fit4)) limma::topTable(fit4, coef=1, n=5) # effect for 3,4,7,8

## One-sided testing
fit4in <- moderTest2grp(t4,gl(2,2),test0="<")
# If you have limma installed we can now see further
if("list" %in% mode(fit4)) limma::topTable(fit4in, coef=1, n=5)
```

---

moderTestXgrp

*Multiple moderated pair-wise t-tests from limma*


---

**Description**

Runs all pair-wise combinations of moderated t-tests from package 'limma' on each line of data against 1st group from 'grp'. Note: This function requires the package [limma](#) from bioconductor. The limma contrast-matrix has to be read by column, the lines in the contrast-matrix containing '+1' will be compared to the '-1' lines, eg grpA-grpB .

**Usage**

```
moderTestXgrp(
  dat,
  grp,
  limmaOutput = TRUE,
  addResults = c("lfd", "FDR", "Mval", "means"),
  testOrientation = "=",
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

**Arguments**

**dat** matrix or data.frame with rows for multiple (independent) tests, use ONLY with 2 groups; assumed as log2-data !!!

|                 |  |
|-----------------|--|
| grp             | (factor) describes column-relationship of 'dat' (1st factor is considered as reference -> orientation of M-values !!)  |
| limmaOutput     | (logical) return full (or extended) MArrayLM-object from limma or 'FALSE' for only the (uncorrected) p.values  |
| addResults      | (character) types of results to add besides basic limma-output, data are assumed to be log2 ! (eg "lfd" using fdrtool-package, "FDR" or "BH" for BH-FDR, "BY" for BY-FDR, "bonferroni" for Bonferroni-correction, "qValue" for lfd by qvalue, "Mval", "means" or "nonMod" for non-moderated test and he equivalent all (other) multiple testing corrections chosen here) |
| testOrientation | (character) for one-sided test (">","greater" or "<","less"), NOTE : 2nd grp is considered control/reference, '<' will identify grp1 < grp2  |
| silent          | (logical) suppress messages  |
| debug           | (logical) additional messages for debugging  |
| callFrom        | (character) allow easier tracking of message(s) produced   |

**Value**

This function returns a limma-type MA-object (list)

**See Also**

[moderTest2grp](#) for single comparisons, [lmFit](#) and the eBayes-family of functions in package [limma](#)

**Examples**

```
grp <- factor(rep(LETTERS[c(3,1,4)],c(2,3,3)))
set.seed(2017); t8 <- matrix(round(rnorm(208*8,10,0.4),2), ncol=8,
  dimnames=list(paste(letters[],rep(1:8,each=26),sep=""), paste(grp,c(1:2,1:3,1:3),sep="")))
t8[3:6,1:2] <- t8[3:6,1:2] +3 # augment lines 3:6 (c-f)
t8[5:8,c(1:2,6:8)] <- t8[5:8,c(1:2,6:8)] -1.5 # lower lines
t8[6:7,3:5] <- t8[6:7,3:5] +2.2 # augment lines
## expect to find C/A in c,d,g, (h)
## expect to find C/D in c,d,e,f
## expect to find A/D in f,g,(h)
test8 <- moderTestXgrp(t8, grp)
# If you have limma installed we can now see further
if("list" %in% mode(test8)) head(test8$p.value, n=8)
```

---

multiCharReplace

*Multiple replacement of entire character elements in simple vector, matrix or data.frame*

---

**Description**

This functions allows multiple types of replacements of entire character elements in simple vector, matrix or data.frame. In addition, the result may be optionally directly transformed to logical or numeric

**Usage**

```
multiCharReplace(mat, repl, convTo = NULL, silent = FALSE, callFrom = NULL)
```

**Arguments**

|          |  |
|----------|--|
| mat      | (character vector, matrix or data.frame) main data   |
| repl     | (matrix or list) tells what to replace by what: If matrix the 1st oolumn will be considered as 'old' and the 2nd as 'replaceBy'; if named list, the names of the list-elements will be considered as 'replaceBy' |
| convTo   | (character) optional conversion of content to 'numeric' or 'logical'   |
| silent   | (logical) suppress messages  |
| callFrom | (character) allow easier tracking of message(s) produced   |

**Value**

This function returns an object of same dimension as input (with replaced content)

**See Also**

[grep](#)

**Examples**

```
x1 <- c("ab", "bc", "cd", "efg", "ghj")
multiCharReplace(x1, cbind(old=c("bc", "efg"), new=c("BBCC", "EF")))

x2 <- c("High", "n/a", "High", "High", "Low")
multiCharReplace(x2, cbind(old=c("n/a", "Low", "High"), new=c(NA, FALSE, TRUE)), convTo="logical")

# works also to replace numeric content :
x3 <- matrix(11:16, ncol=2)
multiCharReplace(x3, cbind(12:13, 112:113))
```

---

multiMatch

*Simple Multi-to-Multi Matching of (Concatenated) Terms*


---

## Description

This function allows convenient matching of multi-to-multi relationships between two objects/vectors. It was designed for finding common elements in multiple to multiple matching situations (eg when comparing `c("aa; bb", "cc")` to `c("bb; ab", "dd")`, ie to find 'bb' as matching between both objects).

## Usage

```
multiMatch(
  x,
  y,
  sep = "; ",
  sep2 = NULL,
  method = "byX",
  silent = FALSE,
  callFrom = NULL
)
```

## Arguments

|          |   |
|----------|---|
| x        | (vector or list) first object to compare; if vector, the (partially) concatenated identifiers (will be split using separator sep), or list of items to be matched (ie already split)  |
| y        | (vector or list) second object to compare; if vector, the (partially) concatenated identifiers (will be split using separator sep), or list of items to be matched (ie already split) |
| sep      | (character, length=1) separator used to split concatenated identifiers (if x or y is vector)  |
| sep2     | (character, length=1) optional separator used when method="matched" to concatenate all indexes of y for column y.allInd   |
| method   | (character) mode of operation: 'asIndex' to return index of y (those hwo have matches) with names of x (which x are the correponding match)   |
| silent   | (logical) suppress messages   |
| callFrom | (character) allow easier tracking of message(s) produced  |

## Details

method='byX' .. returns data.frame with view oriented towards entries of x: character column x for entire content of x; integer column x.Ind for index of x; character column TagBest for most frequent matching isolated tag/ID; integer column y.IndBest index of most frequent matching y; character column y.IndAll index for all y matching any of the tags; character column y.Match

for entire content of best matching *y*; character column *y*.Adj for *y* adjusted to best matching *y* for easier subsequent perfect matching.

method=c("byX", "filter") .. combined argument to keep only lines with any matches

method='byTag' .. returns matrix (of integers) from view of isolated tags from *x* (a separate line for each tag from *x* matching to *y*);

method=c("byTag", "filter") ..if combined as arguments, this will return a data.frame for all unique tags with any matches between *x* and *y*, with additional columns *x.AllInd* for all matching *x*-indexes, *y.IndBest* best matching *y* index; *x.n* for number of different *x* conatining this tag; *y.AllInd* for all matching *y*-indexes

method='adjustXtoY' .. returns vector with *x* adjusted to *y*, ie those elements of *x* matching are replace by the exact corresponding term of *y*.

method=NULL .. If no term matching the options shown above is given, another version of 'asIndex' is returned, but indexes to *y* *\_after\_* splitting by *sep*. Again, this method can be filtered by using method="filter" to focus on the best matches to *x*.

### Value

matrix, data.frame or list with matching results depending on method chosen

### See Also

[match](#); [strsplit](#)

### Examples

```
aa <- c("m","k", "j; aa", "m; aa; bb; o; ee", "n; dd; cc", "aa", "cc")
bb <- c("dd; r", "aa", "ee; bb; q; cc", "p; cc")
(match1 <- multiMatch(aa, bb, method=NULL))      # match bb to aa
(match2 <- multiMatch(aa, bb, method="byX"))     # match bb to aa
(match3 <- multiMatch(aa, bb, method="byTag"))   # match bb to aa
(match4 <- multiMatch(aa, bb, method=c("byTag","filter")))) # match bb to aa
```

---

naOmit

*Fast na.omit*

---

### Description

naOmit removes NAs from input vector. This function has no slot for removed elements while na.omit does so. Resulting objects from naOmit are smaller in size and subsequent execution (on large vectors) is faster (in particular if many NAs get encountered). Note : Behaves differently to na.omit with input other than plain vectors. Will not work with data.frames !

### Usage

```
naOmit(x)
```

**Arguments**

x (vector or matrix) input

**Value**

vector without NAs (matrix input will be transformed to vector). Returns NULL if input consists only of NAs.

**See Also**

[na.fail](#), [na.omit](#)

**Examples**

```
aA <- c(11:13,NA,10,NA);
naOmit(aA)
```

---

|            |   |
|------------|---|
| nFragments | <i>Number of fragments after cut at specific character(s) within size-range</i> |
|------------|---|

---

**Description**

nFragments determines number of fragments /entry within range of 'sizeRa' (numeric,length=2) when cutting after 'cutAt'

**Usage**

```
nFragments(protSeq, cutAt, sizeRa)
```

**Arguments**

protSeq (character) text to be cut  
 cutAt (character) position to cut  
 sizeRa (numeric,length=2) min and max size to consider

**Value**

numeric vector with number of fragments for each entry 'protSeq' (names are 'protSeq')

**See Also**

[cutAtMultSites](#), simple version {nFragments0} (no size-range)

**Examples**

```
tmp <- "MSVSREDSCELDLVYVTERIIAVSFPSTANEENFRSNLREVAQMLKSKHGGNYLLFNLSERRPDITKLHAKVLEFGWPDLPALKEI"
nFragments(c(tmp,"ojioRij"),c("R","K"),c(4,31))
```

---

|             |   |
|-------------|---|
| nFragments0 | <i>Number of fragments after cut at specific character(s)</i> |
|-------------|---|

---

**Description**

nFragments0 tells the number of fragments/entry when cutting after 'cutAt'

**Usage**

```
nFragments0(protSeq, cutAt)
```

**Arguments**

|         |                            |
|---------|----------------------------|
| protSeq | (character) text to be cut |
| cutAt   | (integer) position to cut  |

**Value**

numeric vector with number of fragments for each entry 'protSeq' (names are 'protSeq')

**See Also**

more elaborate {nFragments}; [cutAtMultSites](#)

**Examples**

```
tmp <- "MSVSRMEDSCELDLVYVTERIIAVSFPSTANEENFRSNLREVAQMLKSKHGNYLLFNLSERRPDITKLHAKVLEFGWPDLHTPALEKI"
nFragments0(c(tmp, "ojoRij"), c("R", "K"))
```

---

|             |   |
|-------------|---|
| nNonNumChar | <i>Count number of non-numeric characters</i> |
|-------------|---|

---

**Description**

nNonNumChar counts number of non-numeric characters. Made for positive non-scientific values (eg won't count neg-sign, neither Euro comma ',')

**Usage**

```
nNonNumChar(txt)
```

**Arguments**

|     |                                |
|-----|--------------------------------|
| txt | character vector to be treated |
|-----|--------------------------------|

**Value**

numeric vector with numer of non-numeric characters (ie not '.' or 0-9))

**See Also**

[nchar](#)

**Examples**

```
nNonNumChar("a1b "); sapply(c("aa","12ab","a1b2","12","0.5"),nNonNumChar)
```

---

|                 |  |
|-----------------|--|
| nonAmbiguousMat | <i>Transform matrix to non-ambiguous matrix (in respect to given column)</i> |
|-----------------|--|

---

**Description**

nonAmbiguousMat makes values of matrix 'mat' in col 'byCol' unique.

**Usage**

```
nonAmbiguousMat(
  mat,
  byCol,
  uniqOnly = FALSE,
  asList = FALSE,
  nameMod = "amb_",
  callFrom = NULL
)
```

**Arguments**

|          |  |
|----------|--|
| mat      | numeric or character matrix (or data.frame), column specified by 'byCol' must be/will be used as.numeric, 1st column of 'mat' will be considered like index & used for adding prefix 'nameMod' (unless byCol=1, then 2nd col will be used) |
| byCol    | (character or integer-index) column by which ambiguity will be tested  |
| uniqOnly | (logical) if =TRUE return unique only, if =FALSE return unique and single representative of non-unique values (with " added to name), selection of representative of repeated: first (of sorted) or middle if >2 instances                 |
| asList   | (logical) return result as list  |
| nameMod  | (character) prefix added to 1st column of 'mat' (expect 'by') for indicating non-unique/ambiguous values   |
| callFrom | (character) allow easier tracking of message(s) produced   |

**Value**

sorted non-ambiguous numeric vector (or list if 'asList'=TRUE and 'uniqOnly'=FALSE)

**See Also**

for non-numeric use [firstOfRepeated](#) - but 1000x much slower !; [get1stOfRepeatedByCol](#)

**Examples**

```
set.seed(2017); mat2 <- matrix(c(1:100,round(rnorm(200),2)),ncol=3,
  dimnames=list(1:100,LETTERS[1:3]));
head(mat2U <- nonAmbiguousMat(mat2,by="B",na="_",uniq0=FALSE),n=15)
head(get1stOfRepeatedByCol(mat2,sortB="B",sortS="B"))
```

---

|                 |  |
|-----------------|--|
| nonAmbiguousNum | <i>make numeric vector non-ambiguous (ie unique)</i> |
|-----------------|--|

---

**Description**

nonAmbiguousNum makes (named) values of numeric vector 'x' unique. Note: for non-numeric use [firstOfRepeated](#) - but 1000x slower ! Return sorted non-ambiguous numeric vector (or list if 'asList'=TRUE and 'uniqOnly'=FALSE)

**Usage**

```
nonAmbiguousNum(
  x,
  uniqOnly = FALSE,
  asList = FALSE,
  nameMod = "amb_",
  callFrom = NULL
)
```

**Arguments**

|          |   |
|----------|---|
| x        | (numeric) main input  |
| uniqOnly | (logical) if=TRUE return unique only, if =FALSE return unique and single representative of non-unique values (with " added to name), selection of representative of repeated: first (of sorted) or middle if >2 instances |
| asList   | (logical) return list   |
| nameMod  | (character) text to add in case on ambiguous values, default="amb_"   |
| callFrom | (character) allow easier tracking of message(s) produced  |

**Value**

sorted non-ambiguous numeric vector (or list if 'asList'=TRUE and 'uniqOnly'=FALSE)

**See Also**

[firstOfRepeated](#) for non-numeric use (much slower !!!), [duplicated](#)

**Examples**

```
set.seed(2017); aa <- round(rnorm(100),2); names(aa) <- 1:length(aa)
str(nonAmbiguousNum(aa))
str(nonAmbiguousNum(aa,uniq=FALSE,asLi=TRUE))
```

---

nonredDataFrame      *Filter for unique elements*

---

**Description**

nonredDataFrame filters 'x' (list of char-vectors or char-vector) for elements unique (to 'ref' or if NULL to all 'x') and of character length. May be used for different 'accession' for same pep sequence (same 'peptide\_id'). Note : made for treating data.frames, may be slightly slower than matrix equivalent

**Usage**

```
nonredDataFrame(
  dataFr,
  useCol = c(pepID = "peptide_id", protID = "accession", seq = "sequence", mod =
    "modifications"),
  sepCollapse = "//",
  callFrom = NULL
)
```

**Arguments**

|             |  |
|-------------|--|
| dataFr      | (data.frame) main input  |
| useCol      | (character,length=2) column names of 'dataFr' to use : 1st value designates where redundant values should be gathered; 2nd value designates column of which information should be concatenated |
| sepCollapse | (character) concatenation symbol   |
| callFrom    | (character) allow easier tracking of messages produced   |

**Value**

This function returns a data.frame of filtered (fewer lines) with additional 2 columns 'nSamePep' (number of redundant entries) and 'concID' (concatenated content)

**See Also**

[combineRedBasedOnCol](#), [correctToUnique](#), [unique](#)

**Examples**

```
df1 <- data.frame(cbind(xA=letters[1:5], xB=c("h","h","f","e","f"), xC=LETTERS[1:5]))
nonredDataFrame(df1, useCol=c("xB","xC"))
```

---

|                |                                      |
|----------------|--------------------------------------|
| nonRedundLines | <i>Non-redundant lines of matrix</i> |
|----------------|--------------------------------------|

---

### Description

nonRedundLines reduces complexity of matrix (or data.frame) if multiple consecutive (!) lines with same values. Return matrix (or data.frame) without repeated lines (keep 1st occurrence)

### Usage

```
nonRedundLines(dat, callFrom = NULL)
```

### Arguments

|          |  |
|----------|--|
| dat      | (matrix or data.frame) main input                        |
| callFrom | (character) allow easier tracking of message(s) produced |

### Value

matrix (or data.frame) without repeated lines (keep 1st occurrence)..

### See Also

[firstLineOfDat](#), [firstOfRepLines](#), [findRepeated](#), [firstOfRepeated](#), [get1stOfRepeatedByCol](#), [combineRedBasedOnCol](#), [correctToUnique](#)

### Examples

```
mat2 <- matrix(rep(c(1,1:3,3,1),2),ncol=2,dimnames=list(letters[1:6],LETTERS[1:2]))
nonRedundLines(mat2)
```

---

|               |  |
|---------------|--|
| normalizeThis | <i>Normalize data in various modes</i> |
|---------------|--|

---

### Description

Generic normalization of 'dat' (by columns), multiple methods may be applied. The choice of normalization procedures must be done with care, plotting the data before and after normalization may be critical to understanding the initial data structure and the effect of the procedure applied. Inappropriate methods chosen may render interpretation of (further) results incorrect. Normalization using the method vsn runs [justvsn](#) from [vsn](#) (this requires a minimum of 42 rows of input-data). Note : Depending on the procedure chosen, the normalized data may appear on a different scale.

**Usage**

```
normalizeThis(
  dat,
  method = "mean",
  refLines = NULL,
  refGrp = NULL,
  trimFa = NULL,
  quantFa = NULL,
  expFa = NULL,
  silent = FALSE,
  callFrom = NULL
)
```

**Arguments**

|          |   |
|----------|---|
| dat      | matrix or data.frame  |
| method   | (character) may be "mean", "median", "NULL", "none", "trimMean", "slope", "exponent", "slope2Sections", "vsn"; When NULL or 'none' is chosen the input will be returned |
| refLines | (NULL or numeric) allows to consider only specific lines of 'dat' when determining normalization factors (all data will be normalized)                                  |
| refGrp   | Only the columns indicated will be used as reference, default all columns (integer or colnames)   |
| trimFa   | (numeric, length=1) additional parameters for trimmed mean  |
| quantFa  | (numeric, length=2) additional parameters for quantiles to use with method='slope'  |
| expFa    | (numeric, length=1) additional parameters for method='exponent'   |
| silent   | (logical) suppress messages   |
| callFrom | (character) allow easier tracking of messages produced  |

**Value**

This function returns a matrix of normalized data

**See Also**

[exponNormalize](#), [adjBy2ptReg](#), [justvsn](#)

**Examples**

```
set.seed(2015); rand1 <- round(runif(300)+rnorm(300,0,2),3)
dat1 <- cbind(ser1=round(100:1+rand1[1:100]), ser2=round(1.2*(100:1+rand1[101:200])-2),
  ser3=round((100:1 +rand1[201:300])^1.2-3))
dat1 <- cbind(dat1, ser4=round(dat1[,1]^seq(2,5,length.out=100)+rand1[11:110],1))
dat1[dat1 <1] <- NA
summary(dat1)
head( .normalize(dat1,"mean",list()))
dat1[c(1:5,50:54,95:100),]
```

```

no1 <- normalizeThis(dat1, refGrp=1:3, meth="mean")
no2 <- normalizeThis(dat1, refGrp=1:3, meth="trimMean", trim=0.4)
no3 <- normalizeThis(dat1, refGrp=1:3, meth="median")
no4 <- normalizeThis(dat1, refGrp=1:3, meth="slope", quantFa=c(0.2,0.8))
dat1[c(1:10,91:100),]
cor(dat1[,3],rowMeans(dat1[,1:2],na.rm=TRUE),use="complete.obs")      # high
cor(dat1[,4],rowMeans(dat1[,1:2],na.rm=TRUE),use="complete.obs")      # bad
cor(dat1[c(1:10,91:100),4],rowMeans(dat1[c(1:10,91:100),1:2],na.rm=TRUE),use="complete.obs")
cor(dat1[,3],rowMeans(dat1[,1:2],na.rm=TRUE)^(1/seq(2,5,length.out=100)),use="complete.obs")

```

---

numPairDeColNames      *Extract pair of numeric values from vector or column-names*

---

### Description

This function extracts a pair of numeric values out of a vector or colnames (from a matrix). This is useful when pairwise comparisons are concatenated like '10c-100c', return matrix with 'index'=selComp, log2rat and both numeric. Additional white space or character text can be removed via the argument stripTxt. Of course, the separator sep needs to be specified and should not be included to 'stripTxt'.

### Usage

```

numPairDeColNames(
  dat,
  selComp = NULL,
  stripTxt = NULL,
  sep = "-",
  columLabel = "conc",
  sortByAbsRatio = FALSE,
  silent = FALSE,
  callFrom = NULL
)

```

### Arguments

|                |   |
|----------------|---|
| dat            | (matrix or data.frame) main input   |
| selComp        | (character) the column index selected   |
| stripTxt       | (character, max length=2) text to ignore, if NULL heading letter and punctuation characters will be removed; default will remove all letters (and following spaces) |
| sep            | (character, length=1) separator between pair of numeric values to extract   |
| columLabel     | (character) column labels in output   |
| sortByAbsRatio | (logical) optional sorting of output by (absolute) log-ratios (most extreme ratios on top)  |
| silent         | (logical) suppress messages   |
| callFrom       | (character) allow easier tracking of messages produced  |

**Value**

This function returns a matrix

**See Also**

[strsplit](#) and help on regex

**Examples**

```
## composed column names
mat1 <- matrix(1:8, nrow=2, dimnames=list(NULL, paste0(1:4,"-",6:9)))
numPairDeColNames(mat1)
numPairDeColNames(colnames(mat1))
## works also with simple numeric column names
mat2 <- matrix(1:8, nrow=2, dimnames=list(NULL, paste0("a",6:9)))
numPairDeColNames(mat2)
```

---

organizeAsListOfRepl (re)organize data of (3-dim) array as list of replicates

---

**Description**

Organize array of all data ('arrIn', long table) into list of (replicate-)arrays (of similar type/layout) based on dimension number 'byDim' of 'arrIn' (eg 2nd or 3rd dim). Argument `inspNChar` defines the number of characters to consider, so if the beginning of names is the same they will be separated as list of multiple arrays. Default will search for '\_' separator or trim from end if not found in the relevant dimnames

**Usage**

```
organizeAsListOfRepl(
  arrIn,
  inspNChar = 0,
  byDim = 3,
  silent = TRUE,
  callFrom = NULL
)
```

**Arguments**

|                        |  |
|------------------------|--|
| <code>arrIn</code>     | (array) main input   |
| <code>inspNChar</code> | (integer) if <code>inspNChar=0</code> the array-names (2nd dim of 'arrIn') will be cut before last '_'   |
| <code>byDim</code>     | (integer, length=1) dimension number along which data will be split in separate elements (considering the first <code>inspNChar</code> characters) |
| <code>silent</code>    | (logical) suppress messages  |
| <code>callFrom</code>  | (character) allows easier tracking of message(s) produced  |

**Value**

list of arrays (typically 1st and 2nd dim for specific genes/objects, 3rd for different measures associated with)

**Examples**

```
arr1 <- array(1:24,dim=c(4,3,2),dimnames=list(c(LETTERS[1:4]),
  paste("col",1:3,sep=""),c("ch1","ch2")))
organizeAsListOfRepl(arr1)
```

---

packageDownloadStat    *Simple Package Download Statistics from CRAN*

---

**Description**

This function allows accessing the most recent counts of package downloads available on <http://www.datasciencemeta.com/> obtaining rank quantiles and to compare (multiple) given packages to the bulk data, optionally a plot can be drawn.

**Usage**

```
packageDownloadStat(
  queryPackages = c("wrMisc", "wrProteo", "cif", "bcv", "FinCovRegularization"),
  countUrl = "http://www.datasciencemeta.com/rpackages",
  refQuant = (1:10)/10,
  figure = TRUE,
  log = "",
  silent = FALSE,
  callFrom = NULL
)
```

**Arguments**

|               |  |
|---------------|--|
| queryPackages | (character or integer) package names of interest, if integer, n random packages will be picked by random |
| countUrl      | (character) the url where the daily counts are available   |
| refQuant      | (numeric) add reference quantile values to output matrix   |
| figure        | (logical) decide if figure should be printed   |
| log           | (character) set count-axis of figure to linear or log-scale (by setting log="y")                         |
| silent        | (logical) suppress messages  |
| callFrom      | (character) allow easier tracking of messages produced   |

## Details

The task of checking the number of downloads for a given package has been addressed by several packages (eg dlstats, cranlogs, adjustedcranlogs). Detailed articles on this subject have been published on R-Hub (<https://blog.r-hub.io/2020/05/11/packagerank-intro/>) and on R-bloggers (<https://www.r-bloggers.com/2020/10/a-cran-downloads-experiment/>).

This function only allows accessing the most recent counts as listed on the website of [www.datasciencemeta.com](http://www.datasciencemeta.com). Please note, that reading all lines from the website may take a few seconds. To get a better understanding of the counts read, reference quantiles for download-counts get added by default (see argument refQuant). The (optional) figure can be drawn in linear scale (default, with minor zoom to lower number of counts) or in log (necessary for proper display of the entire range of counts), by setting the argument log="y".

The number of downloads counted by RStudio may not be a perfect measure for the actual usage/popularity of a given package, the articles cited above discuss this in more detail. For example, multiple downloads from the same IP or subsequent downloads of multiple (older) versions of the same package are counted, too.

## Value

This function returns a matrix with download counts (or NULL if the web-site can't be accessed or the query-packages are not found there)

## See Also

packages [cranlogs](#) and [packageRank](#)

## Examples

```
## Let's try a microscopic test-file (NOT representative for true up to date counts !!)
pack1 <- c("cif", "bcv", "FinCovRegularization", "wrMisc", "wrProteo")
testFi <- file.path(system.file("extdata", package="wrMisc"), "rpackagesMicro.html")
packageDownloadStat(pack1, countUrl=testFi, log="y", figure=FALSE)
## For real online counting simply drop the argument countUrl
```

---

pairsAsPropensMatr      *Convert Pairs of Node-Names to Non-Oriented Propensity Matrix*

---

## Description

Numerous network query tools produce a listing of pairs of nodes (with one pair of nodes per line). Using this function such a matrix (or data.frame) can be combined to this more comprehensive view as propensity-matrix.

## Usage

```
pairsAsPropensMatr(mat, silent = FALSE, debug = FALSE, callFrom = NULL)
```

**Arguments**

|          |   |
|----------|---|
| mat      | (matrix) main input, matrix of interaction partners with each line as a separate pair of nodes; the first two columns should contain identifiers of the nodes |
| silent   | (logical) suppress messages   |
| debug    | (logical) additional messages for debugging   |
| callFrom | (character) allow easier tracking of messages produced  |

**Details**

Note, this has been primarily developed for undirected interaction networks, the resulting propensity-matrix does not show any orientation any more. In a number of applications (eg in protein-protein interaction networks, PPI) the resulting matrix may be rather sparse.

**Value**

This function returns matrix or data.frame

**See Also**

uses typically input from [filterNetw](#)

**Examples**

```
pairs3L <- matrix(LETTERS[c(1,3,3, 2,2,1)], ncol=2) # loop of 3
(netw13pr <- pairsAsPropensMatr(pairs3L)) # as prop matr
```

---

partialDist                      *Partial distance matrix (focus on closest)*

---

**Description**

partialDist calculates distance matrix like dist for 1- or 2-dim data, but only partially, ie only cases of small distances. This function was made for treating very large data-sets where only very close distances to a given point need to be found, it allows to overcome memory-problems with larger data (and faster execution with > 50 rows of 'dat').

**Usage**

```
partialDist(
  dat,
  groups,
  overLap = TRUE,
  method = "euclidean",
  silent = FALSE,
  callFrom = NULL
)
```

**Arguments**

|          |   |
|----------|---|
| dat      | (matrix of numeric values) main input   |
| groups   | (factor) to split using cut or specific custom grouping (length of dat)                     |
| overLap  | (logical) if TRUE make groups overlapping by 1 value (ie maintain some context-information) |
| method   | 'character' name of method passed to dist   |
| silent   | (logical) suppress messages   |
| callFrom | (character) allow easier tracking of message(s) produced                                    |

**Value**

matrix (not of class 'dist')

**See Also**

[dist](#)

**Examples**

```
set.seed(2016); mat3 <- matrix(runif(300),nr=30)
round(dist(mat3),1)
round(partialDist(mat3,gr=3),1)
```

---

|            |   |
|------------|---|
| partUnlist | <i>Partial unlist of lists of lists</i> |
|------------|---|

---

**Description**

partUnlist does partial unlist for treating list of lists : New (returned) list has one level less of hierarchy (Highest level list will be appended). In case of conflicting (non-null) listnames a prefix will be added. Behaviour different to [unlist](#) when unlisting list of matrixes.

**Usage**

```
partUnlist(lst)
```

**Arguments**

|     |                               |
|-----|-------------------------------|
| lst | list to be partially unlisted |
|-----|-------------------------------|

**Value**

This function returns a list with partially reduced nested structure

**See Also**

[unlist](#), [asSeplist](#)

**Examples**

```
partUnlist(list(list(a=11:12,b=21:24), list(c=101:101,d=201:204)))
li4 <- list(c=1:3, M2=matrix(1:4,ncol=2), L3=list(L1=11:12, M3=matrix(21:26,ncol=2)))
partUnlist(li4)
unlist(li4, rec=FALSE)
```

---

 pasteC

*Advanced paste-collapse*


---

**Description**

pasteC is a variant of [paste](#) for convenient use of paste-collapse and separation of last element to paste (via 'lastCol'). This function was mode for more human like enumerating in output and messages. If multiple arguments are given without names they will all be concatenated, if they contain names lazy evaluation for names will be tried (with preference to longest match to argument names). Note that some special characters (like backslash) may need to be protected when used with 'collapse' or 'quoteC'. Returns character vector of length 1 (everything pasted together)

**Usage**

```
pasteC(..., collapse = ", ", lastCol = " and ", quoteC = "")
```

**Arguments**

|          |   |
|----------|---|
| ...      | (character) main input to be collapsed                      |
| collapse | (character,length=1) element to use for collapsing          |
| lastCol  | (character) text to use before last item enumerated element |
| quoteC   | character to use for citing with quotations (default "")    |

**Value**

character vector of length=1 of the concatenated input/values.

**See Also**

[paste](#) for basic paste

**Examples**

```
pasteC(1:4)
```

---

presenceFilt                      *Filter lines of matrix for max number of NAs*

---

### Description

presenceFilt produces logical matrix to be used as filter for lines of 'dat' for sufficient presence of non-NA values (ie limit number of NAs per line). Filter abundance/expression data for min number and/or ratio of non-NA values in at east 1 of multiple groups. This type of procedure is common in proteomics and tanscriptomics, where a NA can many times be assocaued with quantitation below detetction limit.

### Usage

```
presenceFilt(
  dat,
  grp,
  maxGrpMiss = 1,
  ratMaxNA = 0.8,
  minVal = NULL,
  silent = FALSE,
  callFrom = NULL
)
```

### Arguments

|            |  |
|------------|--|
| dat        | matrix or data.frame (abundance or expression-values which may contain some NAs).                          |
| grp        | factor of min 2 levels describing which column of 'dat' belongs to which group (levels 1 & 2 will be used) |
| maxGrpMiss | (numeric) at least 1 group has not more than this number of NAs (otherwise marke line as bad)              |
| ratMaxNA   | (numeric) at least 1 group reaches this content of non-NA values   |
| minVal     | (default NULL or numeric), any value below will be treated like NA   |
| silent     | (logical) suppress messages  |
| callFrom   | (character) allow easier tracking of message produced  |

### Value

logical matrix (with separate col for each pairwise combination of 'grp' levels) indicating if line of 'dat' acceptable based on NAs (and values minVal)

**Examples**

```

mat <- matrix(rep(8,150), ncol=15, dimnames=list(NULL,
  paste0(rep(LETTERS[4:2],each=6),1:6)[c(1:5,7:16)]))
mat[lower.tri(mat)] <- NA
mat[,15] <- NA
mat[c(2:3,9),14:15] <- NA
mat[c(1,10),13:15] <- NA
mat
presenceFilt(mat ,rep(LETTERS[4:2], c(5,6,4)))
presenceFilt(mat, rep(1:2,c(9,6)))

# one more example
dat1 <- matrix(1:56, ncol=7)
dat1[c(2,3,4,5,6,10,12,18,19,20,22,23,26,27,28,30,31,34,38,39,50,54)] <- NA
dat1; presenceFilt(dat1,gr=gl(3,3)[-(3:4)], maxGr=0)
presenceFilt(dat1, gr=gl(2,4)[-1], maxGr=1, ratM=0.1)
presenceFilt(dat1, gr=gl(2,4)[-1], maxGr=2, rat=0.5)

```

---

protectSpecChar

*Protect Special Characters*


---

**Description**

Some characters do have a special meaning when used with regular expressions. This concerns characters like a point, parenthesis, backslash etc. Thus, when using grep or any related command, such special characters must get protected in order to get considered as they are.

**Usage**

```

protectSpecChar(
  x,
  prot = c(".", "\\ ", "|", "(", ")", "[", "{", "^", "$", "*", "+", "?"),
  silent = TRUE,
  callFrom = NULL
)

```

**Arguments**

|          |  |
|----------|--|
| x        | character vector to be prepared for use in regular expressions |
| prot     | (character) collection of characters that need to be protected |
| silent   | (logical) suppress messages                                    |
| callFrom | (character) allow easier tracking of messages produced         |

**Value**

This function returns a modified character vector

**Examples**

```
aa <- c("abc", "abcde", "ab.c", "ab.c.e", "ab*c", "ab\\d")
grepl("b.", aa)           # all TRUE
grepl("b\\. ", aa)        # manual protection
grepl(protectSpecChar("b."), aa)
```

---

pVal2lfdr                      *Convert p-values to lfdr*

---

**Description**

This function takes a numeric vector of p-values and returns a vector of lfdr-values (local false discovery) using the package `fdrtool`. Multiple testing correction should be performed with caution, short series of p-values typically pose problems for transforming to lfdr. The transformation to lfdr values may give warning messages, in this case the resultant lfdr values may be invalid !

**Usage**

```
pVal2lfdr(x, silent = TRUE, callFrom = NULL)
```

**Arguments**

x                            (numeric) vector of p.values  
 silent                      (logical) suppress messages  
 callFrom                    (character) allow easier tracking of messages produced

**Value**

This function returns a (numeric) vector of lfdr values (or NULL if data insufficient to run the function 'fdrtool')

**See Also**

lfdr from [fdrtool](#), other p-adjustments (multiple test correction, eg FDR) in [p.adjust](#)

**Examples**

```
## Note that this example is too small for estimating really meaningful fdr values
## In consequence, a warning will be issued.
set.seed(2017); t8 <- matrix(round(rnorm(160,10,0.4),2), ncol=8,
  dimnames=list(letters[1:20], c("AA1", "BB1", "CC1", "DD1", "AA2", "BB2", "CC2", "DD2")))
t8[3:6,1:2] <- t8[3:6,1:2]+3 # augment lines 3:6 (c-f) for AA1&BB1
t8[5:8,5:6] <- t8[5:8,5:6]+3 # augment lines 5:8 (e-h) for AA2&BB2 (c,d,g,h should be found)
head(pVal2lfdr(apply(t8, 1, function(x) t.test(x[1:4], x[5:8])$p.value)))
```

---

|           |   |
|-----------|---|
| randIndFx | <i>Distance of categorical data (Jaccard, Rand and adjusted Rand index)</i> |
|-----------|---|

---

### Description

randIndFx calculates distance of categorical data (as Rand Index, Adjusted Rand Index or Jaccard Index). Note: uses/requires package **flexclust** Methods so far available (via flexclust): "ARI" .. adjusted Rand Index, "RI" .. Rand index, "J" .. Jaccard, "FM" .. Fowlkes-Mallows.

### Usage

```
randIndFx(ma, method = "ARI", adjSense = TRUE, silent = FALSE, callFrom = NULL)
```

### Arguments

|          |   |
|----------|---|
| ma       | (matrix) main input for distance calculation  |
| method   | (character) name of distance method (eg "ARI", "RI", "J", "FM")                                   |
| adjSense | (logical) allows introducing correlation/anticorrelation (interpret neg distance results as anti) |
| silent   | (logical) suppress messages   |
| callFrom | (character) allow easier tracking of messages produced  |

### Value

This function returns a distance matrix

### See Also

comPart in [randIndex](#)

### Examples

```
set.seed(2016); tab2 <- matrix(sample(1:2, size=42, replace=TRUE), ncol=7)
if(requireNamespace("flexclust")) { flexclust::comPart(tab2[1,], tab2[2,])
  flexclust::comPart(tab2[1,], tab2[3,])
  flexclust::comPart(tab2[1,], tab2[4,]) }
## via randIndFx():
randIndFx(tab2, adjSense=FALSE)
cor(t(tab2))
randIndFx(tab2, adjSense=TRUE)
```

rankToContigTab

*Contingency tables for fit of ranking***Description**

Count the number of instances where the corresponding columns of 'dat' have a value matching the group number as specified by 'grp'. Counting will be performed/repeated independently for each line of 'dat'. Returns array (1st dim is rows of dat, 2nd is unique(grp), 3rd dim is ok/bad), these results may be tested using eg [fisher.test](#). This function was made for preparing to test the ranking of multiple features (lines in 'mat') including replicates (levels of 'grp').

**Usage**

```
rankToContigTab(dat, grp)
```

**Arguments**

|     |  |
|-----|--|
| dat | (matrix or data.frame of integer values) ranking of multiple features (lines), equal ranks may occur |
| grp | (integer) expected ranking   |

**Value**

array (1st dim is rows of dat, 2nd is unique(grp), 3rd dim is ok/bad)

**See Also**

[lm](#)

**Examples**

```
# Let's create a matrix with ranks (equal ranks do occur)
ma0 <- matrix(rep(1:3,each=6), ncol=6, dimnames=list(
  c("li1","li2","ref"), letters[1:6]))
ma0[1,6] <- 1 # create item not matching correctly
ma0[2,] <- c(3:1,2,1,3) # create items not matching correctly
gr0 <- gl(3,2) # the expected ranking (as duplicates)
(count0 <- rankToContigTab(ma0,gr0))
cTab <- t(apply(count0, c(1,3), sum))
# Now we can compare the ranking of line1 to ref ...
fisher.test(cTab[,c(3,1)]) # test li1 against ref
fisher.test(cTab[,c(3,2)]) # test li2 against ref
```

---

|              |   |
|--------------|---|
| ratioAllComb | <i>Calculate all ratios between x and y</i> |
|--------------|---|

---

### Description

This function calculates all possible pairwise ratios between all individual values of x and y, or samples up to a maximum number of combinations.

### Usage

```
ratioAllComb(  
  x,  
  y,  
  maxLim = 10000,  
  isLog = FALSE,  
  silent = FALSE,  
  callFrom = NULL  
)
```

### Arguments

|          |  |
|----------|--|
| x        | (numeric) vector, numerator for constructing ratios                  |
| y        | (numeric) vector, denominator for constructing ratios                |
| maxLim   | (integer) allows reducing complexity by drawing for very long x or y |
| isLog    | (logical) adjust ratio calculation to log-data                       |
| silent   | (logical) suppress (less important) messages                         |
| callFrom | (character) allow easier tracking of messages produced               |

### Value

This function returns a (numeric) vector with all ratios

### Examples

```
set.seed(2014); ra1 <- c(rnorm(9,2,1),runif(8,1,2))  
ratioAllComb(ra1[1:9],ra1[10:17])  
boxplot(list(norm=ra1[1:9], unif=ra1[10:17], rat=ratioAllComb(ra1[1:9],ra1[10:17])))
```

---

|            |                             |
|------------|-----------------------------|
| ratioToPpm | <i>Convert ratio to ppm</i> |
|------------|-----------------------------|

---

### Description

ratioToPpm transforms ratio 'x' to ppm (parts per million). If 'y' not given (or different length as 'x'), then 'x' is assumed as ratio otherwise ratios are constructed as x/y is used lateron. Does additional checking : negative values not expected - will be made absolute !

### Usage

```
ratioToPpm(x, y = NULL, nSign = NULL, silent = FALSE, callFrom = NULL)
```

### Arguments

|          |   |
|----------|---|
| x        | (numeric) main input  |
| y        | (numeric) optional value to construct ratios (x/y). If NULL (or different length as 'x'), then 'x' will be considered as ratio. |
| nSign    | (numeric) number of significant digits  |
| silent   | (logical) suppress messages   |
| callFrom | (character) allow easier tracking of message(s) produced  |

### Value

numeric vector of ppm values

### See Also

[XYToDiffPpm](#) for ppm of difference as used in mass spectrometry

### Examples

```
set.seed(2017); aa <- c(1.000001, 0.999999, 1+rnorm(10, 0, 0.001))
cbind(x=aa, ppm=ratioToPpm(aa, nSign=4))
```

---

readCsvBatch                      *Read batch of csv-files*

---

### Description

This function was designed to read screening data split in parts (with common structure) and saved to multiple files, to extract the numeric columns and to compile all (numeric) data to a single array (or list). Some screening platforms save results while progressing through a pile of microtiter-plates separately. The organization of the resultant files is structured through file-names and all files have exactly the same organization of lines and columns/ European or US-formatted csv files can be read, if argument `fileFormat` is NULL both types will be tested, otherwise it allows to specify a given format. The presence of headers (to be used as column-names) may be tested using `checkFormat`.

### Usage

```
readCsvBatch(
  fileNames = NULL,
  path = ".",
  fileFormat = "Eur",
  checkFormat = TRUE,
  returnArray = TRUE,
  columns = c("Plate", "Well", "StainA"),
  excludeFiles = "All infected plates",
  simpleNames = TRUE,
  minNamesLe = 4,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

### Arguments

|                           |  |
|---------------------------|--|
| <code>fileNames</code>    | (character) names of files to be read, if NULL all files fitting 'fileFormat'  |
| <code>path</code>         | (character) where files should be read (folders should be written in R-style)  |
| <code>fileFormat</code>   | (character) may be NULL (both US and European formats will be tried), 'Eur' or 'US'  |
| <code>checkFormat</code>  | (logical) if TRUE: check header, remove empty columns, 1st line if all empty, set output format for each file to matrix, if rownames are increasing integers try to use 2nd of 'columns' as rownames |
| <code>returnArray</code>  | (logical) allows switching from array to list-output   |
| <code>columns</code>      | (NULL or character) column-headers to be extracted (if specified), 2nd value may be column with rownames (if rownames are encountered as increasing rownames)  |
| <code>excludeFiles</code> | (character) names of files to exclude (only used when reading all files of given directory)  |

|             |   |
|-------------|---|
| simpleNames | (logical) allows truncating names (from beginning) to get to variable part (using <code>.trimFromStart()</code> ), but keeping 'minNamesLe' |
| minNamesLe  | (integer) min length of column-names if simpleNames=TRUE  |
| silent      | (logical) suppress messages   |
| debug       | (logical) additional messages for debugging   |
| callFrom    | (character) allows easier tracking of messages produced   |

**Value**

This function returns an array (or list if `returnArray=FALSE`) of all numeric data read (numerical columns only) from individual files

**See Also**

[read.table](#), [writeCsv](#), [readXlsxBatch](#)

**Examples**

```
path1 <- system.file("extdata", package="wrMisc")
fiNa <- c("pl01_1.csv", "pl01_2.csv", "pl02_1.csv", "pl02_2.csv")
datAll <- readCsvBatch(fiNa, path1)
str(datAll)
## batch reading of all csv files in specified path :
datAll2 <- readCsvBatch(fileNames=NULL, path=path1, silent=TRUE)
```

---

readTabulatedBatch      *Batch reading of Tabulated Text-Files*

---

**Description**

This function allows batch reading of multiple tabulated text files n batch. The files can be designed specifically, or, alternatively all files from a given directory can be read. If package `data.table` is available, faster reading of files will be performed using the function [fread](#).

**Usage**

```
readTabulatedBatch(
  query,
  path = NULL,
  dec = ".",
  header = "auto",
  strip.white = FALSE,
  blank.lines.skip = TRUE,
  fill = FALSE,
  filtCol = 2,
  filterAsInf = TRUE,
  filtVal = 5000,
```

```

    silent = FALSE,
    callFrom = NULL,
    debug = FALSE
  )

```

### Arguments

|                  |  |
|------------------|--|
| query            | (character) vector of file-names to be read, if "." all files will be read (no matter what their extension might be)   |
| path             | (character) path for reading files, if NULL or NA the current directory will be used   |
| dec              | (character, length=1) decimals to use, will be passed to <a href="#">fread</a> or <a href="#">read.delim</a>   |
| header           | (character, length=1) path for reading files, if NULL or NA the current directory will be used, will be passed to <a href="#">fread</a> or <a href="#">read.delim</a>            |
| strip.white      | (logical, length=1) Strips leading and trailing whitespaces of unquoted fields, will be passed to <a href="#">fread</a> or <a href="#">read.delim</a>                            |
| blank.lines.skip | (logical, length=1) If TRUE blank lines in the input are ignored. will be passed to <a href="#">fread</a> or <a href="#">read.delim</a>  |
| fill             | (logical, length=1) If TRUE then in case the rows have unequal length, blank fields are implicitly filled, will be passed to <a href="#">fread</a> or <a href="#">read.delim</a> |
| filtCol          | (integer, length=1) which columns should be used for filtering, if NULL or NA all data will be returned  |
| filterAsInf      | (logical, length=1) filter as inferior or equal (TRUE) or superior or equal threshold <code>filtVal</code>   |
| filtVal          | (numeric, length=1) which numeric threshold should be used for filtering, if NULL or NA all data will be returned  |
| silent           | (logical) suppress messages  |
| callFrom         | (character) allow easier tracking of messages produced   |
| debug            | (logical) display additional messages for debugging  |

### Details

If you want to provide a flexible pattern of file-names, this has to be done before calling this function, eg using `grep` to provide an explicit collection of files. However, it is possible to read different files from different locations/directories, the length of path must match the length of query

### Value

This function returns a list of data.frames

### See Also

[fread](#), [read.delim](#), for reading batch of csv files : [readCsvBatch](#)

**Examples**

```

path1 <- system.file("extdata", package="wrMisc")
fiNa <- c("a1.txt", "a2.txt")
allTxt <- readTabulatedBatch(fiNa, path1)
str(allTxt)

```

---

readVarColumns

*Read tabular content of files with variable number of columns*


---

**Description**

Reading the content of files where the number of separators (eg tabulation) is variable poses problems with traditional methods for reading files, like [read.table](#). This function reads each line independently and then parses all separators therein. The first line is assumed to be column-headers. Finally, all data will be returned in a matrix adopted to the line with most separators and if the number of column-headers is insufficient, new (unique) column-headers will be generated. Thus, the lines may contain different number of elements, empty elements (ie tabular fields) will always get added to right of data read and their content will be as defined by argument `emptyFields` (default NA).

**Usage**

```

readVarColumns(
  fiName,
  path = NULL,
  sep = "\t",
  header = TRUE,
  emptyFields = NA,
  refCo = NULL,
  supNa = NULL,
  silent = FALSE,
  callFrom = NULL
)

```

**Arguments**

|                          |  |
|--------------------------|--|
| <code>fiName</code>      | (character) file-name  |
| <code>path</code>        | (character) optional path  |
| <code>sep</code>         | (character) separator (between columns)  |
| <code>header</code>      | (logical) indicating whether the file contains the names of the variables as its first line.   |
| <code>emptyFields</code> | (NA or character) missing headers will be replaced by the content of 'emptyFields', if NA the last column-name will be re-used and a counter added |
| <code>refCo</code>       | (integer) for custom choice of column to be used as row-names (default will use 1st text-column)   |

supNa (character) base for constructing name for columns wo names (+counter starting at 2), default column-name to left of 1st col wo colname  
 silent (logical) suppress messages  
 callFrom (character) allow easier tracking of messages produced

### Details

Note, this functions assumes one line of header and at least one line of data ! Note, for numeric data the comma is assumed to be US-Style (as '.'). Note, that it is assumed, that any missing fields for the complete tabular view are missing on the right (ie at the end of line) !

### Value

This function returns a matrix (character or numeric)

### See Also

for regular 'complete' data [read.table](#)

### Examples

```

path1 <- system.file("extdata",package="wrMisc")
fiNa <- "Names1.tsv"
datAll <- readVarColumns(fiName=file.path(path1,fiNa))
str(datAll)

```

---

readXlsxBatch      *Read Batch of Excel xlsx-Files*

---

### Description

readXlsxBatch reads data out of multiple xlsx files, the sheet indicated by 'sheetInd' will be considered. All files must have the same organization of data, as this is typically the case when high-throughput measurements are automatically saved while experiments progress. In particular, the first file read is used to structure the output.

### Usage

```

readXlsxBatch(
  fileNames = NULL,
  path = ".",
  fileExtension = "xlsx",
  excludeFiles = NULL,
  sheetInd = 1,
  checkFormat = TRUE,
  returnArray = TRUE,
  columns = c("Plate", "Well", "StainA"),

```

```

    simpleNames = 3,
    silent = FALSE,
    callFrom = NULL
  )

```

### Arguments

|               |   |
|---------------|---|
| fileNames     | (character) provide either explicit list of file-names to be read or leave NULL for reading all files ending with 'xlsx' in path specified with argument path   |
| path          | (character) there may be a different path for each file   |
| fileExtension | (character) extension of files (default='xlsx')   |
| excludeFiles  | (character) names of files to exclude (only used when reading all files of given directory)   |
| sheetInd      | (character or integer) specify which sheet to extract (as exact name of sheet or sheet-number, eg sheetInd=2 will extract always the 2nd sheet (no matter the name); if given as sheet-name but not present in file an empty list-element will be returned) |
| checkFormat   | (logical) if TRUE: check header, remove empty columns, if rownames are increasing integers it will search for first column with different entries to use as rownames  |
| returnArray   | (logical) allows switching from array to list-output  |
| columns       | (NULL or character) column-headers to be extracted (if specified, otherwise all columns will be extracted)  |
| simpleNames   | (integer), if NULL all characters of fileNames will be maintained, otherwise allows truncating names (from beginning) to get to variable part (using .trimFromStart()), but keeping at least the number of characters indicated by this argument            |
| silent        | (logical) suppress messages   |
| callFrom      | (character) allows easier tracking of messages produced   |

### Details

By default all columns with text-content may be eliminated to keep the numeric part only, which may then get organized to a 3-dim numeric array (where the additional files will be used as 2nd dimension and multiple columns per file shown as 3rd dimension).

NOTE : (starting from version wrMisc-1.5.5) requires packages **readxl** and **Rcpp** being installed ! (This allows much faster and memory efficient processing than previous use of package 'xlsx')

### Value

This function returns a list of data.frames

### See Also

[read\\_excel](#); for simple reading of (older) xls-files under 32-bit R one may also see the package **RODBC**

**Examples**

```

path1 <- system.file("extdata", package="wrMisc")
fiNa <- c("pl01_1.xlsx", "pl01_2.xlsx", "pl02_1.xlsx", "pl02_2.xlsx")
datAll <- readXlsxBatch(fiNa, path1)
str(datAll)
## Now let's read all xlsx files of directory
datAll2 <- readXlsxBatch(path=path1, silent=TRUE)
identical(datAll, datAll2)

```

---

reduceTable

*Reduce table by aggregating smaller groups*


---

**Description**

reduceTable treats/reduces results from [table](#) to 'nGrp' groups, optional indiv resolution of 'separFirst' (numeric or NULL). Mainly made for reducing the number of classes for better plots with [pie](#)

**Usage**

```
reduceTable(tab, separFirst = 4, nGrp = 15)
```

**Arguments**

|            |  |
|------------|--|
| tab        | output of <a href="#">table</a>  |
| separFirst | (integer or NULL) optional separation of n 'separFirst' groups (value <2 or NULL will privilege more uniform size of groups, higher values will cause small initial and larger tailing groups) |
| nGrp       | (integer) number of groups expected  |

**Value**

This function returns a numeric vector with number of counts and class-borders as names (like [table](#)).

**See Also**

[table](#)

**Examples**

```

set.seed(2018); dat <- sample(11:60, 200, repl=TRUE)
pie(table(dat))
pie(reduceTable(table(dat), sep=NULL))
pie(reduceTable(table(dat), sep=NULL), init.angle=90,
  clockwise=TRUE, col=rainbow(20)[1:15], cex=0.8)

```

---

|                 |   |
|-----------------|---|
| regrBy1or2point | <i>Rescaling according to reference data using linear regression.</i> |
|-----------------|---|

---

### Description

regrBy1or2point does rescaling: linear transform simple vector 'inDat' that (mean of) elements of names cited in 'refLst' will end up as values 'regrTo'. Regress single vector according to 'refLst' (describing names of inDat). If 'refLst' contains 2 groups, the 1st group will be set to the 1st value of 'regrTo' (and the 2nd group of 'refLst' to the 2nd 'regrTo')

### Usage

```
regrBy1or2point(  
  inDat,  
  refLst,  
  regrTo = c(1, 0.5),  
  silent = FALSE,  
  callFrom = NULL  
)
```

### Arguments

|          |   |
|----------|---|
| inDat    | matrix or data.frame  |
| refLst   | list of names existing in inDat (one group of names for each value in 'regrTo'), to be transformed in values precised in 'regrTo'; if no matches to names of 'inDat' found, the 2 lowest and/or highest highest values will be chosen |
| regrTo   | (numeric,length=2) range (at scale 0-1) of target-values for mean of elements cited in 'refLst'   |
| silent   | (logical) suppress messages   |
| callFrom | (character) allows easier tracking of message(s) produced   |

### Value

normalized matrix

### See Also

[adjBy2ptReg](#), [regrMultBy1or2point](#)

### Examples

```
set.seed(2016); dat1 <- 1:50 +(1:50)*round(runif(50),1)  
names(dat1) <- 1:length(dat1)  
reg1 <- regrBy1or2point(dat1,refLst=c("2", "49"))  
plot(reg1,dat1)
```

---

|                     |   |
|---------------------|---|
| regrMultBy1or2point | <i>Rescaling of multiple data-sets according to reference data using regression</i> |
|---------------------|---|

---

### Description

regrMultBy1or2point regresses each col of matrix according to 'refLst' (describing rownames of inDat). If 'refLst' contains 2 groups, the 1st group will be set to the 1st value of 'regrTo' (and the 2nd group of 'refLst' to the 2nd 'regrTo')

### Usage

```
regrMultBy1or2point(
  inDat,
  refLst,
  regrTo = c(1, 0.5),
  silent = FALSE,
  callFrom = NULL
)
```

### Arguments

|          |   |
|----------|---|
| inDat    | matrix or data.frame  |
| refLst   | list of names existing in inDat (one group of names for each value in 'regrTo'), to be transformed in values precised in 'regrTo'; if no matches to names of 'inDat' found, the 2 lowest and/or highest values will be chosen |
| regrTo   | (numeric,length=2) range (at scale 0-1) of target-values for mean of elements cited in 'refLst'   |
| silent   | (logical) suppress messages   |
| callFrom | (character) allow easier tracking of message(s) produced  |

### Value

normalized matrix

### See Also

[adjBy2ptReg](#), [regrBy1or2point](#)

### Examples

```
set.seed(2016); dat2 <- round(cbind(1:50 +(1:50)*runif(50),2.2*(1:50) +rnorm(50,0,3)),1)
rownames(dat2) <- 1:nrow(dat2)
reg1 <- regrBy1or2point(dat2[,1],refLst=list(as.character(5:7),as.character(44:45)))
reg2 <- regrMultBy1or2point(dat2,refLst=list(as.character(5:7),as.character(44:45)))
plot(dat2[,1],reg2[,1])
identical(reg1,reg2[,1])
identical(dat2[,1],reg2[,1])
```

---

|               |                       |
|---------------|-----------------------|
| renameColumns | <i>Rename columns</i> |
|---------------|-----------------------|

---

**Description**

renameColumns renames columns of 'refMatr' using 2-column matrix (or data.frame) indicating old and new names (for replacement).

**Usage**

```
renameColumns(refMatr, newName, silent = FALSE, callFrom = NULL)
```

**Arguments**

|          |   |
|----------|---|
| refMatr  | matrix (or data.frame) where column-names should be changed   |
| newName  | (matrix of character) giving correspondence of old to new names (number of lines must match number of columns of 'refMatr') |
| silent   | (logical) suppresses messages   |
| callFrom | (character) allows easier tracking of message(s) produced   |

**Value**

matrix (or data.frame) with renamed columns

**Examples**

```
ma <- matrix(1:8, ncol=4, dimnames=list(1:2, LETTERS[1:4]))
replBy1 <- cbind(new=c("dd", "bb", "z_"), old=c("D", "B", "zz"))
replBy2 <- matrix(c("D", "B", "zz", "dd", "bb", "z_"), ncol=2)
replBy3 <- matrix(c("X", "Y", "zz", "xx", "yy", "z_"), ncol=2)
renameColumns(ma, replBy1)
renameColumns(ma, replBy2)
renameColumns(ma, replBy3)
```

---

|              |   |
|--------------|---|
| reorgByCluNo | <i>Reorganize matrix according to clustering-output</i> |
|--------------|---|

---

**Description**

Reorganize input matrix as sorted by cluster numbers (and geometric mean) according to vector with cluster names, and index for sorting per cluster and per geometric mean. In case mat is an array, the 3rd dimension will be considered as 'column' with arguments useColumn ( and cluNo, if it designs a 'column' of mat).

**Usage**

```
reorgByCluNo(
  mat,
  cluNo,
  useColumn = NULL,
  meanCol = NULL,
  addInfo = TRUE,
  retList = FALSE,
  silent = FALSE,
  callFrom = NULL,
  debug = FALSE
)
```

**Arguments**

|           |   |
|-----------|---|
| mat       | (matrix or data.frame) main input   |
| cluNo     | (positive integer, length to match nrow(dat) initial cluster numbers for each line of 'mat' (obtained by separate clustering or other segmentation) or may design column of mat to use as cluster-numbers |
| useColumn | (character or integer) the columns to use from mat as main data (default will use all, except cluCol and/or meanCol if they design columns))  |
| meanCol   | (character or integer) alternative summarizing data for intra-cluster sorting (instead of geometric mean)   |
| addInfo   | (logical) allows adding of columns 'index', 'geoMean' and 'cluNo' (or array if FALSE)   |
| retList   | (logical) return as list of matrixes (or array if FALSE)  |
| silent    | (logical) suppress messages   |
| callFrom  | (character) allow easier tracking of messages produced  |
| debug     | (logical) additional messages for debugging   |

**Value**

This function returns a list or array (as 2- or 3 dim) with possible number of occurrences for each of the 3 elements in nMax. Read results vertical : out[[1]] or out[,1] .. (multiplicative) table for 1st element of nMax; out[,2] .. for 2nd

**See Also**

pairwise combinations [combn](#), clustering [kmeans](#)

**Examples**

```
dat1 <- matrix(round(runif(24),2), ncol=3, dimnames=list(NULL,letters[1:3]))
clu <- stats::kmeans(dat1, 5)$cluster
reorgByCluNo(dat1, clu)

dat2 <- cbind(dat1, clu=clu)
reorgByCluNo(dat2, "clu")
```

---

 replicateStructure      *Search and Select Groups of Replicates*


---

### Description

This function was designed for mining annotation information organized in multiple columns to identify the grouping of multiple samples.

### Usage

```
replicateStructure(
  x,
  method = "median",
  sep = "__",
  exclNoRepl = TRUE,
  trimNames = FALSE,
  silent = FALSE,
  callFrom = NULL,
  debug = FALSE
)
```

### Arguments

|            |   |
|------------|---|
| x          | (matrix or data.frame) the annotation to inspect; each column is supposed to describe another set of annotation/metadata for the rows of x (min 1 row and 1 column),  |
| method     | (character, length=1) the procedure to choose column(s) with properties of information, may be highest (max number of levels) lowest (min number of levels), median (median of all options for number of levels), combAll (combine all columns of x) or combNonOrth (combine only non-orthogonal columns of x, to avoid avoid n lines with n levels); lazy evaluation of the argument is possible |
| sep        | (character) separator used when any method combining multiple columns (eg combAll, combNonOrth) is chosen (should not appear anywhere in x)   |
| exclNoRepl | (logical) decide whether columns with all values different (ie no replicates or max divergency) should be excluded  |
| trimNames  | (logical) optional trimming of names in x by removing redundant heading and tailing text  |
| silent     | (logical) suppress messages   |
| callFrom   | (character) allow easier tracking of messages produced  |
| debug      | (logical) additional messages for debugging   |

## Details

Statistical tests requite specifying which samples should be considered as replicates. In some cases, like the Sdrf-format, automatic mining of such annotation to indentify an experiment's underlying structure of replicates may be challanging, since the key information may not always be found in the same column. For this reason this function allows inspecting all columns of a matrix of data.frame to identify which colmns may serve describing groups of replicates.

The argument `exclNoRepl=TRUE` allows excluding all columns with different content for each line (like line-numbers), ie information without any replicates. It is set by default to `TRUE` to exclude such columns, since statistical tests usually do require some replicates.

When using as `method="combAll"`, there is risk all lines (samples) will be be considered different and no replicates remain. To avoid this situation the argument can be set to `method="combNonOrth"`. Using this mode it will be checked if adding more columns will lead to complete loss of replicates, and -if so- concerned columns omitted.

## Value

This function returns a list with `$col` (column index relativ to `x`), `$lev` (abstract labels of level), `$meth` (note of method finally used) and `$allCols` with general replicate structure of all columns of `x`

## See Also

[duplicated](#), uses [trimRedundText](#)

## Examples

```
## a is all different, b is groups of 2,
## c & d are groups of 2 nut NOT 'same general' pattern as b
strX <- data.frame(a=letters[18:11], b=letters[rep(c(3:1,4), each=2)],
  c=letters[rep(c(5,8:6), each=2)], d=letters[c(1:2,1:3,3:4,4)],
  e=letters[rep(c(4,8,4,7),each=2)], f=rep("z",8) )
strX
replicateStructure(strX[,1:2])
replicateStructure(strX[,1:4], method="combAll")
replicateStructure(strX[,1:4], method="combAll", exclNoRepl=FALSE)
replicateStructure(strX[,1:4], method="combNonOrth", exclNoRepl=TRUE)
replicateStructure(strX, method="lowest")
```

**Description**

With several screening techniques used in high-throughput biology values at/below detection limit are returned as NA. However, the resultant NA-values may be difficult to analyse properly, simply ignoring NA-values may not be a good choice. When (technical) replicate measurements are available, one can look for cases where one gave an NA while the other did not with the aim of investigating such 'NA-neighbours'. `replNAbyLow` locates and replaces NA values by (random) values from same line & same group 'grp'. The origin of NAs should be predominantly absence of measure (quantitation) due to signal below limit of detection and not saturation at upper detection limit or other technical problems. Note, this approach may be not optimal if the number of NA-neighbours is very low. Replacement is done -depending on argument 'unif'- by Gaussian random model based on neighbour values (within same group), using their means and sd, or a uniform random model (min and max of neighbour values). Then numeric matrix (same dim as 'x') with NA replaced is returned.

**Usage**

```
replNAbyLow(
  x,
  grp,
  quant = 0.8,
  signific = 3,
  unif = TRUE,
  absOnly = FALSE,
  seed = NULL,
  silent = FALSE,
  callFrom = NULL
)
```

**Arguments**

|                       |  |
|-----------------------|--|
| <code>x</code>        | (numeric matrix or data.frame) main input  |
| <code>grp</code>      | (factor) to organize replicate columns of (x)                                      |
| <code>quant</code>    | (numeric) quantile form 'neighbour' values to use as upper limit for random values |
| <code>signific</code> | number of signif digits for random values  |
| <code>unif</code>     | (logical) toggle between uniform and Gaussian random values                        |
| <code>absOnly</code>  | (logical) if TRUE, make negative NA-replacement values positive as absolute values |
| <code>seed</code>     | (integer) for use with <code>set.seed</code> for reproducible output               |
| <code>silent</code>   | (logical) suppress messages  |
| <code>callFrom</code> | (character) allow easier tracking of message(s) produced                           |

**Value**

numeric matrix (same dim as 'x') with NA replaced

**See Also**

[naOmit](#), [na.fail](#)

**Examples**

```
dat <- matrix(round(rnorm(30),2),ncol=6); grD <- gl(2,3)
dat[sort(sample(1:30,9,repl=FALSE))] <- NA
dat; replNabyLow(dat,gr=grD)
```

---

replPlateCV

*CV of replicate plates (list of matrixes)*


---

**Description**

replPlateCV gets CVs of replicates from list of 2 or 3-dim arrays (where 2nd dim is replicates, 3rd dim may be channel). Note : all list-elements of must **MUST** have SAME dimensions ! When treating data from microtiter plates (eg 8x12) data are typically spread over multiple plates, ie initial matrixes that are the organized into arrays. Returns matrix or array (1st dim is intraplate-position, 2nd .. plate-group/type, 3rd .. channels)

**Usage**

```
replPlateCV(lst, callFrom = NULL)
```

**Arguments**

lst                   list of matrixes : suppose lines are independent elements, columns are replicates of the 1st column. All matrixes must have same dimensions

callFrom             (character) allows easier tracking of messages produced

**Value**

matrix or array (1st dim is intraplate-position, 2nd .. plate-group/type, 3rd .. channels)

**See Also**

[rowCVs](#), [@seealso](#) [arrayCV](#)

**Examples**

```
set.seed(2016); ra1 <- matrix(rnorm(3*96),nrow=8)
pla1 <- list(ra1[,1:12],ra1[,13:24],ra1[,25:36])
replPlateCV(pla1)
arrL1 <- list(a=array(as.numeric(ra1)[1:192],dim=c(8,12,2)),
             b=array(as.numeric(ra1)[97:288],dim=c(8,12,2)))
replPlateCV(arrL1)
```

---

|                |  |
|----------------|--|
| rmDupl2colMatr | <i>Remove lines of matrix redundant /duplicated for 1st and 2nd column</i> |
|----------------|--|

---

**Description**

rmDupl2colMatr removes lines of matrix that are redundant /duplicated for 1st and 2nd column (irrespective of content of their columns). The first occurrence of redundant /duplicated elements is kept.

**Usage**

```
rmDupl2colMatr(mat, useCol = c(1, 2))
```

**Arguments**

mat (matrix or data.frame) main input  
useCol (integer, length=2) columns to consider/use when looking for duplicated entries

**Value**

matrix with duplicated lines removed

**See Also**

[unlist](#)

**Examples**

```
mat <- matrix(1:12, ncol=3)  
mat[3,1:2] <- mat[1,1:2]  
rmDupl2colMatr(mat)
```

---

|        |   |
|--------|---|
| rnormW | <i>Normal random number generation with close fit to expected mean and sd</i> |
|--------|---|

---

**Description**

This function allows creating a vector of random values similar to rnorm, but resulting value get recorrected to fit to expected mean and sd. When the number of random values to generate is low, the mean and sd of the resultant values may deviate from the expected mean and sd when using the standard rnorm function. In such cases the function rnormW helps getting much closer to the expected mean and sd.

**Usage**

```
rnormW(
  n,
  mean = 0,
  sd = 1,
  seed = NULL,
  digits = 8,
  silent = FALSE,
  callFrom = NULL
)
```

**Arguments**

|          |  |
|----------|--|
| n        | (integer, length=1) number of observations. If length(n) > 1, the length is taken to be the number required. |
| mean     | (numeric, length=1) expected mean  |
| sd       | (numeric, length=1) expected sd  |
| seed     | (integer, length=1) seed for generating random numbers   |
| digits   | (integer, length=1 or NULL) number of significant digits for output, set to NULL to get all digits           |
| silent   | (logical) suppress messages  |
| callFrom | (character) allow easier tracking of messages produced   |

**Details**

For making result reproducible, a seed for generating random numbers can be set via the argument seed. However, with n=2 the resulting values are 'fixed' since no random component is possible at n < 3.

**Value**

This function returns a numeric vector of random values

**See Also**

[Normal](#)

**Examples**

```
x1 <- (11:16)[-5]
mean(x1); sd(x1)
## the standard way
ra1 <- rnorm(n=length(x1), mean=mean(x1), sd=sd(x1))
## typically the random values deviate (slightly) from expected mean and sd
mean(ra1) -mean(x1)
sd(ra1) -sd(x1)
## random numbers with close fit to expected mean and sd :
ra2 <- rnormW(length(x1), mean(x1), sd(x1))
```

```
mean(ra2) -mean(x1)
sd(ra2) -sd(x1)      # much closer to expected value
```

---

|        |               |
|--------|---------------|
| rowCVs | <i>rowCVs</i> |
|--------|---------------|

---

### Description

rowCVs returns CV for values in each row (using speed optimized standard deviation). Note : NaN values get replaced by NA.

### Usage

```
rowCVs(dat, autoconvert = NULL)
```

### Arguments

|             |   |
|-------------|---|
| dat         | (numeric) matrix  |
| autoconvert | (NULL or character) allows converting simple vectors in matrix of 1 row (autoconvert="row") |

### Value

(numeric) vector with CVs for each row of 'dat'

### See Also

[colSums](#), [rowGrpCV](#), [rowSds](#)

### Examples

```
set.seed(2016); dat1 <- matrix(c(runif(200)+rep(1:10,20)),ncol=10)
head(rowCVs(dat1))
```

---

|          |                     |
|----------|---------------------|
| rowGrpCV | <i>row group CV</i> |
|----------|---------------------|

---

### Description

rowGrpCV calculates CVs for matrix with multiple groups of data, ie one CV for each group of data. Groups are specified as columns of 'x' in 'grp' (so length of grp should match number of columns of 'x', NAs are allowed)

### Usage

```
rowGrpCV(x, grp, means = NULL, listOutp = FALSE)
```

**Arguments**

|          |  |
|----------|--|
| x        | numeric matrix where replicates are organized into separate columns          |
| grp      | (factor) defining which columns should be grouped (considered as replicates) |
| means    | (numeric) alternative values instead of means by <code>.rowGrpMeans()</code> |
| listOutp | (logical) if TRUE, provide output as list with \$CV, \$mean and \$n          |

**Value**

matrix of CV values

**See Also**

[rowCVs](#), [arrayCV](#), [replPlateCV](#)

**Examples**

```
set.seed(2016); dat1 <- matrix(c(runif(200)+rep(1:10,20)),ncol=10)
head(rowGrpCV(dat1,grp=gl(4,3,labels=LETTERS[1:4])[2:11]))
```

---

|             |  |
|-------------|--|
| rowGrpMeans | <i>rowMeans with distinction of groups (of columns, eg groups of replicates)</i> |
|-------------|--|

---

**Description**

`rowGrpMeans` calculates column-means for matrix with multiple groups of data, ie similar to `rowMeans` but one mean for each group of data. Groups are specified as columns of 'x' in 'grp' (so length of grp should match number of columns of 'x', NAs are allowed).

**Usage**

```
rowGrpMeans(x, grp, na.rm = TRUE)
```

**Arguments**

|       |  |
|-------|--|
| x     | matrix or data.frame   |
| grp   | (character or factor) defining which columns should be grouped (considered as replicates)                  |
| na.rm | (logical) a logical value indicating whether NA-values should be stripped before the computation proceeds. |

**Value**

matrix with mean values

**See Also**[rowSds](#), [colSums](#)**Examples**

```
set.seed(2016); dat1 <- matrix(c(runif(200) + rep(1:10,20)), ncol=10)
head(rowGrpMeans(dat1, gr=gl(4, 3, labels=LETTERS[1:4])[2:11]))
```

rowGrpNA

*Count number of NAs per row and group of columns***Description**

This functions allows easy counting the number of NAs per row in data organized in multiple sub-groups as columns.

**Usage**

```
rowGrpNA(mat, grp)
```

**Arguments**

`mat` (matrix of data.frame) data to count the number of NAs  
`grp` (character or factor) defining which columns should be grouped (considered as replicates)

**Value**

matrix with number of NAs per group

**See Also**[rowGrpMeans](#), [rowSds](#), [colSums](#)**Examples**

```
mat2 <- c(22.2, 22.5, 22.2, 22.2, 21.5, 22.0, 22.1, 21.7, 21.5, 22, 22.2, 22.7,
         NA, NA, NA, NA, NA, NA, NA, 21.2, NA, NA, NA, NA,
         NA, 22.6, 23.2, 23.2, 22.4, 22.8, 22.8, NA, 23.3, 23.2, NA, 23.7,
         NA, 23.0, 23.1, 23.0, 23.2, 23.2, NA, 23.3, NA, NA, 23.3, 23.8)
mat2 <- matrix(mat2, ncol=12, byrow=TRUE)
gr4 <- gl(3, 4, labels=LETTERS[1:3])
# overall number of NAs per row
rowSums(is.na(mat2))
# number of NAs per row and group
rowGrpNA(mat2, gr4)
```

---

|           |   |
|-----------|---|
| rowGrpSds | <i>Per line and per group sd-values</i> |
|-----------|---|

---

### Description

rowGrpSds calculate Sd (standard-deviation) for matrix with multiple groups of data, ie one sd for each group of data. Groups are specified as columns of 'x' in 'grp' (so length of grp should match number of columns of 'x', NAs are allowed).

### Usage

```
rowGrpSds(x, grp)
```

### Arguments

|     |   |
|-----|---|
| x   | matrix where replicates are organized into seprate columns                                |
| grp | (character or factor) defining which columns should be grouped (considered as replicates) |

### Value

This function returns a matrix of sd values

### See Also

[rowGrpMeans](#), [rowCVs](#), [rowSEMs](#), [sd](#)

### Examples

```
set.seed(2016); dat1 <- matrix(c(runif(200) +rep(1:10,20)), ncol=10)
head(rowGrpSds(dat1, gr=g1(4,3,labels=LETTERS[1:4])[2:11]))
```

---

|            |   |
|------------|---|
| rowGrpSums | <i>rowSums with destinction of groups (of columns, eg groups of replicates)</i> |
|------------|---|

---

### Description

This function calculates column-sums for matrix with multiple groups of data, ie similar to rowSums but one summed value for each line and group of data. Groups are specified as columns of 'x' in 'grp' (so length of grp should match number of columns of 'x', NAs are allowed).

### Usage

```
rowGrpSums(x, grp, na.rm = TRUE)
```

**Arguments**

|       |  |
|-------|--|
| x     | matrix or data.frame   |
| grp   | (character or factor) defining which columns should be grouped (considered as replicates)                  |
| na.rm | (logical) a logical value indicating whether NA-values should be stripped before the computation proceeds. |

**Value**

This function a matrix with sum values

**See Also**

[rowGrpMeans](#), [rowGrpSds](#), [rowSds](#), [colSums](#)

**Examples**

```
set.seed(2016); dat1 <- matrix(c(runif(200) + rep(1:10,20)), ncol=10)
head(rowGrpMeans(dat1, gr=gl(4, 3, labels=LETTERS[1:4])[2:11]))
```

---

|           |   |
|-----------|---|
| rowMedSds | <i>sd of median for each row by bootstrap</i> |
|-----------|---|

---

**Description**

rowMedSds determines the stand error (sd) of the median for each row by bootstrapping each row of 'dat'. Note: requires package [boot](#)

**Usage**

```
rowMedSds(dat, nBoot = 99)
```

**Arguments**

|       |  |
|-------|--|
| dat   | (numeric) matix, main input                  |
| nBoot | (integer) number if iterations for bootstrap |

**Value**

This functions returns a (numeric) vector with estimated standard errors

**See Also**

[boot](#)

**Examples**

```
set.seed(2016); dat1 <- matrix(c(runif(200)+rep(1:10,20)), ncol=10)
rowMedSds(dat1) ; plot(rowSds(dat1), rowMedSds(dat1))
```

---

|        |   |
|--------|---|
| rowSds | <i>sd for each row (fast execution)</i> |
|--------|---|

---

**Description**

rowSds is speed optimized sd (takes matrix or data.frame and treats each line as set of data for sd equiv to apply(dat,1,sd). NAs are ignored from data unless entire line NA). Speed improvements may be seen at more than 100 lines. Note: NaN instances will be transformed to NA

**Usage**

```
rowSds(dat)
```

**Arguments**

dat                   matrix (or data.frame) with numeric values (may contain NAs)

**Value**

numeric vector of sd values

**See Also**

[sd](#)

**Examples**

```
set.seed(2016); dat1 <- matrix(c(runif(200)+rep(1:10,20)),ncol=10)
rowSds(dat1)
```

---

|         |                         |
|---------|-------------------------|
| rowSEMs | <i>SEM for each row</i> |
|---------|-------------------------|

---

**Description**

rowSEMs speed optimized SEM (standard error of the mean) for each row. The function takes a matrix or data.frame and treats each row as set of data for SEM; NAs are ignored from data. Note: NaN instances will be transformed to NA

**Usage**

```
rowSEMs(dat)
```

**Arguments**

dat                   matrix or data.frame

**Value**

numeric vector with SEM values

**See Also**

[rowSds](#), [colSds](#), [colSums](#)

**Examples**

```
set.seed(2016); dat1 <- matrix(c(runif(200)+rep(1:10,20)),ncol=10)
head(rowSEMs(dat1))
```

---

|                  |   |
|------------------|---|
| sampNoDeMArrayLM | <i>Locate Sample Index From Index or Name Of Pair-Wise Comparisons in list or MArrayLM-Object</i> |
|------------------|---|

---

**Description**

When multiple series of data are tested simultaneously (eg using `moderTestXgrp`), multiple pairwise comparisons get performed. This function helps locating the samples, ie mean-columns, corresponding to a specific pairwise comparison.

**Usage**

```
sampNoDeMArrayLM(
  MArrayObj,
  useComp,
  groupSep = "-",
  lstMeans = "means",
  lstP = c("BH", "FDR", "p.value"),
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

**Arguments**

|           |   |
|-----------|---|
| MArrayObj | (list or MArray-object) main input  |
| useComp   | (character or integer) index or name of pairwise-comparison to be addressed   |
| groupSep  | (character, length=1) separator for pair of names   |
| lstMeans  | (character, length=1) the list element containing the individual sample names, typically the matrix containing the replicate-mean values for each type of sample, the column-names get used |
| lstP      | (character, length=1) the list element containing all pairwise comparisons performed, the column-names get used   |
| silent    | (logical) suppress messages   |
| debug     | (logical) additional messages for debugging   |
| callFrom  | (character) allow easier tracking of messages produced  |

**Details**

As main input one gives a list or MArrayLM-object containing testing results contain the pairwise comparisons and a specific comparison indicated by useComp to get located in the element of mean-columns (1stMeans) among all pairwise comparisons.

**Value**

This function returns a numeric vector (length=2) with index indicating the columns of (replicate) mean-values corresponding to the comparison specified in useComp

**See Also**

[moderTestXgrp](#), this function gets used eg in [MPlotW](#) or [VolcanoPlotW](#)

**Examples**

```
grp <- factor(rep(LETTERS[c(3,1,4)],c(2,3,3)))
set.seed(2017); t8 <- matrix(round(rnorm(208*8,10,0.4),2), ncol=8,
  dimnames=list(paste(letters[],rep(1:8,each=26),sep=""), paste(grp,c(1:2,1:3,1:3),sep="")))
test8 <- moderTestXgrp(t8, grp)
head(test8$p.value)          # all pairwise comparisons available
if(requireNamespace("limma", quietly=TRUE)) { # need limma installed...
  sampNoDeMArrayLM(test8,1)
  head(test8$means[,sampNoDeMArrayLM(test8,1)])
  head(test8$means[,sampNoDeMArrayLM(test8,"C-D")]) }
}
```

---

scaleXY

*Scale data to given minimum and maximum*

---

**Description**

This is a convenient way to scale data to given minimum and maximum without full standardization, ie without dividing by the sd.

**Usage**

```
scaleXY(x, min = 0, max = 1)
```

**Arguments**

|     |                                   |
|-----|-----------------------------------|
| x   | (numeric) vector to rescale       |
| min | (numeric) minimum value in output |
| max | (numeric) maximum value in output |

**Value**

vector of rescaled data (in dimensions as input)

**See Also**[scale](#)**Examples**

```

dat <- matrix(2*round(runif(100),2), ncol=4)
range(dat)
dat1 <- scaleXY(dat, 1,100)
range(dat1)
summary(dat1)
## scale for each column individually
dat2 <- apply(dat, 2, scaleXY, 1, 100)
range(dat2)
summary(dat2)

```

searchDataPairs

*Search duplicated data over multiple columns, ie pairs of data***Description**

searchDataPairs searches matrix for columns of similar data, ie 'duplicate' values in separate columns or very similar columns if realDupsOnly=FALSE. Initial distance measures will be normalized either to diagonale (normRange=TRUE) of 'window' or to the real max distance observed (equal or less than diagonale). Return data.frame with names for sample-pair, percent of identical values (100 for complete identical pair) and relative (Euclidean) distance (ie max dist observed =1.0). Note, that low distance values do not necessarily imply correlating data.

**Usage**

```

searchDataPairs(
  dat,
  disThr = 0.01,
  byColumn = TRUE,
  normRange = TRUE,
  altNa = NULL,
  realDupsOnly = TRUE,
  silent = FALSE,
  callFrom = NULL
)

```

**Arguments**

|        |  |
|--------|--|
| dat    | matrix or data.frame (main input)  |
| disThr | (numeric) threshold to decide when to report similar data (applied on normalized distances, low val fewer reported), applied on normalized distances (norm to diagonale of all data for best relative 'unbiased' view) |

|              |  |
|--------------|--|
| byColumn     | (logical) rotates main input by 90 degrees (using <code>t</code> ), thus allows to read by rows instead of by columns                      |
| normRange    | (logical) normalize each columns separately if TRUE  |
| altNa        | (character, default NULL) vector with alternative names (for display)  |
| realDupsOnly | (logical) if TRUE will consider equal values only, otherwise will also consider very close values (based on argument <code>disThr</code> ) |
| silent       | (logical) suppress messages  |
| callFrom     | (character) allows easier tracking of messages produced  |

**Value**

This function returns a data.frame with names of sample-pairs, percent of identical values (100 for complete identical pair) and rel (Euclidean) distance (ie max dist observed =1.0)

**See Also**

[duplicated](#)

**Examples**

```
mat <- round(matrix(c(11:40,runif(20)+12,11:19,17,runif(20)+18,11:20), nrow=10), 1)
colnames(mat) <- 1:9
searchDataPairs(mat,disThr=0.05)
```

---

searchLinesAtGivenSlope

*Search points forming lines at given slope*

---

**Description**

searchLinesAtGivenSlope searches among set of points (2-dim) those forming line(s) with user-defined slope ('coeff'), ie search optimal (slope-) offset parameter(s) for (regression) line(s) with given slope ('coef'). Note: larger data-sets : segment residuals to 'coeff' & select most homogenous

**Usage**

```
searchLinesAtGivenSlope(
  dat,
  coeff = 1.5,
  filtExtr = c(0, 1),
  minMaxDistThr = NULL,
  lmCompare = TRUE,
  indexPoints = TRUE,
  displHist = FALSE,
  displScat = FALSE,
  bestCluByDistRat = TRUE,
```

```

    neighbDiLim = NULL,
    silent = FALSE,
    debug = FALSE,
    callFrom = NULL
  )

```

### Arguments

|                  |  |
|------------------|--|
| dat              | matrix or data.frame   |
| coeff            | (numeric) slope to consider  |
| filtExtr         | (integer) lower & upper quantile values, remove points with extreme deviation to offset=0, (if single value: everything up to or after will be used) |
| minMaxDistThr    | (logical) optional minimum and maximum distance threshold  |
| lmCompare        | (logical) add'l fitting of linear regression to best results, return offset AND slope based on lm fit  |
| indexPoints      | (logical) return results as list with element 'index' specifying retained points   |
| displHist        | (logical) display histogram of residues  |
| displScat        | (logical) display (simple) scatter plot  |
| bestCluByDistRat | (logical) initial selection of decent clusters based on ratio overallDist/averNeighbDist (or by CV & cor)  |
| neighbDiLim      | (numeric) additional threshold for (trimmed mean) neighbour-distance   |
| silent           | (logical) suppress messages  |
| debug            | (logical) for bug-tracking: more/enhanced messages   |
| callFrom         | (character) allow easier tracking of messages produced   |

### Value

This function returns a matrix of line-characteristics (or if indexPoints is TRUE then list (line-characteristics & index & lm-results))

### Examples

```

set.seed(2016); ra1 <- runif(300)
dat1 <- cbind(x=round(c(1:100+ra1[1:100]/5, 4*ra1[1:50]), 1),
             y=round(c(1:100+ra1[101:200]/5, 4*ra1[101:150]), 1))
(li1 <- searchLinesAtGivenSlope(dat1, coeff=1))

```

---

|               |  |
|---------------|--|
| simpleFragFig | <i>Simple figure showing line from start- to end-sites of edges (or fragments) defined by their start- and end-sites simpleFragFig draws figure showing start- and end-sites of edges (or fragments)</i> |
|---------------|--|

---

### Description

Simple figure showing line from start- to end-sites of edges (or fragments) defined by their start- and end-sites

simpleFragFig draws figure showing start- and end-sites of edges (or fragments)

### Usage

```
simpleFragFig(
  frag,
  fullSize = NULL,
  sortByHead = TRUE,
  useTit = NULL,
  useCol = NULL,
  displNa = TRUE,
  useCex = 0.7
)
```

### Arguments

|            |   |
|------------|---|
| frag       | (matrix) 2 columns defining begin- and end-sites (as interger values)           |
| fullSize   | (integer) optional max size used for figure (x-axis)                            |
| sortByHead | (logical) sort by begin-sites (if TRUE) or sort by end-sites                    |
| useTit     | (character) custom title  |
| useCol     | (character) specify colors, if numeric vector will be onsidered as score values |
| displNa    | (character) display names of edges (figure may get crowded)                     |
| useCex     | (numeric) expansion factor, see also <a href="#">par</a>                        |

### Value

matrix with mean values

### See Also

[buildTree](#), [countSameStartEnd](#), [contribToContigPerFrag](#),

### Examples

```
frag2 <- cbind(beg=c(2,3,7,13,13,15,7,9,7, 3,7,5,7,3),end=c(6,12,8,18,20,20,19,12,12, 4,12,7,12,4))
rownames(frag2) <- c("A","E","B","C","D","F","H","G","I", "J","K","L","M","N")
simpleFragFig(frag2,fullSize=21,sortByHead=TRUE)
buildTree(frag2)
```

---

|                 |   |
|-----------------|---|
| singleLineAnova | <i>2-factorial Anova on single line of data</i> |
|-----------------|---|

---

**Description**

singleLineAnova runs 2-factorial Anova on a single line of data (using [aov](#) from package stats) using a model with two factors (without factor-interaction) and extracts the corresponding p-value.

**Usage**

```
singleLineAnova(dat, fac1, fac2, inclInteraction = TRUE)
```

**Arguments**

|                 |  |
|-----------------|--|
| dat             | numeric vector   |
| fac1            | (character or factor) vector describing grouping elements of dat for first factor, must be of same length as fac2  |
| fac2            | (character or factor) vector describing grouping elements of dat for second factor, must be of same length as fac1 |
| inclInteraction | (logical) decide if factor-interactions (eg synergy) should be included to model                                   |

**Value**

(uncorrected) p for factor 'Pr(>F)' (see [aov](#))

**See Also**

[aov](#), [anova](#); for repeated tests using the package [limma](#) including [lmFit](#) and [eBayes](#) see [test2factLimma](#)

**Examples**

```
set.seed(2012); dat <- round(runif(8),1)
singleLineAnova(dat, gl(2,4), rep(1:2,4))
```

---

|                          |
|--------------------------|
| sortBy2CategorAnd1IntCol |
|--------------------------|

*Sort matrix by two categorical and one integer columns*

---

**Description**

sortBy2CategorAnd1IntCol sorts matrix 'mat' subsequently by categorical and numerical columns of 'mat', ie lines with identical values for categor are sorted by numeric value.

**Usage**

```
sortBy2CategorAnd1IntCol(
  mat,
  categCol,
  numCol,
  findNeighb = TRUE,
  decreasing = FALSE,
  silent = FALSE,
  callFrom = NULL
)
```

**Arguments**

|            |   |
|------------|---|
| mat        | matrix (or data.frame) from which by 2 columns will be selected for sorting   |
| categCol   | (integer or character) which columns of 'mat' to be used as categorical columns   |
| numCol     | (integer or character) which column of 'mat' to be used as integer columns  |
| findNeighb | (logical) if 'findNeighb' neighbour cols according to 'numCol' will be identified as groups & marked in new col 'neiGr', orphans marked as NA |
| decreasing | (logical) order of sort   |
| silent     | (logical) suppress messages   |
| callFrom   | (character) allow easier tracking of message(s) produced  |

**Value**

sorted matrix (same dimensions as 'mat')

**Examples**

```
mat <- cbind(aa=letters[c(3,rep(7:8,3:4),4,4:6,7)],bb=LETTERS[rep(1:5,c(1,3,4,4,1))],
  nu=c(23:21,23,21,22,18:12))
mat[c(3:5,1:2,6:9,13:10),]
sortBy2CategorAnd1IntCol(mat,cate=c("bb","aa"),num="nu",findN=FALSE,decr=TRUE)
sortBy2CategorAnd1IntCol(mat,cate=c("bb","aa"),num="nu",findN=TRUE,decr=FALSE)
```

---

sortByNRepeated

*Make a list of common occurances sorted by number of repeats*

---

**Description**

The aim of this function is to count the number of occurances of words when comaring separate vectors (x, y and z) or from a list (given as x) and to give an output sorted by their frequency. The output lists the various values/words by their frequency, the names of the resulting list-elements indicate number of times the values/words were found repeated.

**Usage**

```
sortByNRepeated(  
  x,  
  y = NULL,  
  z = NULL,  
  filterIntraRep = TRUE,  
  silent = TRUE,  
  debug = FALSE,  
  callFrom = NULL  
)
```

**Arguments**

|                |  |
|----------------|--|
| x              | (list, character or integer) main input, if list, arguments y and z will not be used |
| y              | (character or integer) supplemental vector to compare with x                         |
| z              | (character or integer) supplemental vector to compare with x                         |
| filterIntraRep | (logical) allow making vectors x, y and z unique before comparing (defaults to TRUE) |
| silent         | (logical) suppress messages  |
| debug          | (logical) additional messages for debugging  |
| callFrom       | (character) allow easier tracking of messages produced                               |

**Details**

In order to compare the frequency of values/words between separate vectors or vectors within a list, it is necessary that these have been made unique before calling this function or using `filterIntraRep=TRUE`.

In case the input is given as list (in x), there is no restriction to the number of vectors to be compared. With very long lists, however, the computational effort increases (like it does when using `table`)

**Value**

This function returns a list sorted by number of occurrences. The names of the list indicate the number of repeats.

**See Also**

[table](#), [replicateStructure](#)

**Examples**

```
sortByNRepeated(x=LETTERS[1:11], y=LETTERS[3:13], z=LETTERS[6:12])  
sortByNRepeated(x=LETTERS[1:11], y=LETTERS[c(3:13,5:4)], z=LETTERS[6:12])
```

---

|            |  |
|------------|--|
| stableMode | <i>Estimate mode (most frequent value)</i> |
|------------|--|

---

### Description

Estimate mode, ie most frequent value. In case of continuous numeric data, the most frequent values may not be the most frequently repeated exact term. This function offers various approaches to estimate the mode of a numeric vector. Besides, it can also be used to identify the most frequent exact term (in this case also from character vectors).

### Usage

```
stableMode(
  x,
  method = "density",
  finiteOnly = TRUE,
  bandw = NULL,
  rangeSign = 1:6,
  nCl = NULL,
  histLike = NULL,
  silent = FALSE,
  callFrom = NULL,
  debug = FALSE
)
```

### Arguments

|            |   |
|------------|---|
| x          | (numeric, or character if 'method='mode') data to find/estimate most frequent value   |
| method     | (character) There are 3 options : BBmisc, binning and density (default). If "binning" the function will search context dependent, ie like most frequent class of histogram. Using "binning" mode the search will be refined if either 80 percent of values in single class or >50 percent in single class.                            |
| finiteOnly | (logical) suppress non-finite values; allows avoiding NULL as result in presence of some Inf values; NA will be ignored in any case   |
| bandw      | (integer) only used when method="binning" or method="density" : defines the number of points to look for density or number of classes used; very "critical" parameter, may change results in strong way. Note: with method="binning": At higher values for "bandw" you will finally loose advantage of histLike-type search of mode ! |
| rangeSign  | (integer) only used when method="binning": range of numbers used as number of significant values  |
| nCl        | (integer) depreciated argument, please use bandw instead  |
| histLike   | (logical) depreciated, please use argument method instead   |
| silent     | (logical) suppress messages   |

callFrom (character) allows easier tracking of messages produced  
 debug (logical) additional messages for debugging

### Details

The argument method allows to choose among (so far) 4 different methods available. If "density" is chosen, the most dense region of sqrt(n) values will be chosen; if "binning", the data will be binned (like in histograms) via rounding to a user-defined number of significant values ("rangeSign"). If method is set to "BBmisc", the function computeMode() from package **BBmisc** will be used. If "mode" is chosen, the first most frequently occurring (exact) value will be returned, if "allModes", all ties will be returned. This last mode also works with character input.

### Value

This function returns a numeric vector with value of mode, the name of the value indicates it's position

### See Also

computeMode() in package **BBmisc**

### Examples

```
set.seed(2012); dat <- round(c(rnorm(50), runif(100)),3)
stableMode(dat)
```

---

|           |                                 |
|-----------|---------------------------------|
| standardW | <i>Standardize (scale) data</i> |
|-----------|---------------------------------|

---

### Description

This functions work similar to [scale](#), however, it evaluates the entire input and not column-wise (and independently as scale does). With Standardizing we speak of transforming the data to end up with mean=0 and sd=1. Furthermore, in case of 3-dim arrays, this function returns also an object with the same dimensions as the input.

### Usage

```
standardW(mat, byColumn = FALSE, na.rm = TRUE)
```

### Arguments

mat (matrix, data.frame or array) data that need to get standardized.  
 byColumn (logical) if TRUE the function will be run independently over all columns such as `apply(mat, 2, standardW)`  
 na.rm (logical) if NAs in the data don't get ignored via this argument, the output will be all NA

**Value**

vector of rescaled data (in dimensions as input)

**See Also**

[scale](#)

**Examples**

```
dat <- matrix(2*round(runif(100),2), ncol=4)
mean(dat); sd(dat)
```

```
dat2 <- standardW(dat)
apply(dat2, 2, sd)
summary(dat2)
```

```
dat3 <- standardW(dat, byColumn=TRUE)
apply(dat2, 2, sd)
summary(dat2)
mean(dat2); sd(dat2)
```

---

stdErrMedBoot

*Standard error of median by boot-strap*

---

**Description**

stdErrMedBoot estimate standard error of median by boot-strap approach. Note: requires package [boot](#)

**Usage**

```
stdErrMedBoot(x, nBoot = 99)
```

**Arguments**

x (numeric) vector to estimate median and it's standard error  
nBoot (integer) number for iterations

**Value**

This function returns a (numeric) vector with estimated standard error

**See Also**

[boot](#)

**Examples**

```
set.seed(2014); ra1 <- c(rnorm(9,2,1),runif(8,1,2))
rat1 <- ratioAllComb(ra1[1:9],ra1[10:17])
median(rat1); stdErrMedBoot(rat1)
```

---

summarizeCols

*Summarize columns (as median,mean,min,last or other methods)*


---

**Description**

summarizeCols summarizes all columns of matrix (or data.frame). In case of text-columns the sorted middle (~median) will be given, unless 'maxLast', 'minLast', 'maxLast','maxAbsLast' or 'minLast' .. consider only last column of 'matr' : choose from all columns the line where (max of) last col is at min; 'medianComplete' or 'meanComplete' considers only lines/rows where no NA occur (NA have influence other columns !)

**Usage**

```
summarizeCols(
  matr,
  meth = "median",
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

**Arguments**

|          |   |
|----------|---|
| matr     | data.frame matrix of data to be summarized by comlumn (may do different method for text and numeric comlumnns)                  |
| meth     | (character) summarization method (eg 'maxLast','minLast','maxLast','maxAbsLast', 'minLast', 'medianComplete' or 'meanComplete') |
| silent   | (logical) suppress messages   |
| debug    | (logical) additional messages for debugging   |
| callFrom | (character) allow easier tracking of messages produced  |

**Value**

vector with summary for each column

**See Also**

rowMeans in [colSums](#)

**Examples**

```
t1 <- matrix(round(runif(30,1,9)), nc=3); rownames(t1) <- letters[c(1:5,3:4,6:4)]
summarizeCols(t1, me="median")
t(sapply(by(t1,rownames(t1), function(x) x), summarizeCols,me="maxLast"))
t3 <- data.frame(ref=rep(11:15,3), tx=letters[1:15],
  matrix(round(runif(30,-3,2),1), ncol=2), stringsAsFactors=FALSE)
by(t3,t3[,1], function(x) x)
t(sapply(by(t3,t3[,1], function(x) x), summarizeCols,me="maxAbsLast"))
```

---

sumNAperGroup

*Count number of NAs per sub-set of columns*


---

**Description**

This function will count the number of NAs per group (defined by argument `grp`) while summing over all lines of a matrix or data.frame. The row-position has no influence on the counting. Using the argument `asRelative=TRUE` the result will be given as (average) number of NAs per row and group.

**Usage**

```
sumNAperGroup(x, grp, asRelative = FALSE)
```

**Arguments**

|                         |  |
|-------------------------|--|
| <code>x</code>          | matrix or data.frame which may contain NAs                     |
| <code>grp</code>        | factor describing which column of 'dat' belongs to which group |
| <code>asRelative</code> | (logical) return as count of NAs per row and group             |

**Value**

integer vector with count of NAs per group

**See Also**

[NA](#), filter NAs by line [presenceFilt](#)

**Examples**

```
mat <- matrix(1:25, ncol=5)
mat[lower.tri(mat)] <- NA
sumNAperGroup(mat, rep(1:2,c(3,2)))
sumNAperGroup(mat, rep(1:2,c(3,2)), asRelative=TRUE)
```

---

|         |  |
|---------|--|
| sysDate | <i>System-date (compressed format)</i> |
|---------|--|

---

**Description**

This function returns current date (based on Sys.Date) in different format options.

**Usage**

```
sysDate(style = "univ1")
```

**Arguments**

style (character) choose style (default 'univ1' for very compact style)

**Details**

Multiple options for formatting exist : 'univ1' or 'wr' ... (default) compact style using day, first 3 letters of English name of month (lowercaps) and last 2 letters of year as ddmmmyy, eg 14jun21

'univ2' ... as ddMmmyy, eg 14Jun21

'univ3' ... as ddMonthyyyy, eg 14June2021

'univ4' ... as ddmonthyyyy, eg 14june2021

'univ5' ... as yyyy-mm-dd (output of Sys.Date()), eg 2021-06-14

'univ6' ... as yyyy-number of day (in year), eg 2021-165

'local1' ... compact style using day, first 3 letters of current locale name of month (not necessarily unique !) and last 2 letters of year as ddmmmyy, eg 14jui21

'local2' ... as ddMmmyy, month based on current locale (not necessarily unique !), eg 14Jui21

'local3' ... as ddMonthyyyy, month based on current locale , eg 14Juin2021

'local4' ... as ddmonthyyyy, month based on current locale , eg 14juin2021

'local5' ... as dd-month-yyyy, month based on current locale , eg 14-juin-2021

'local6' ... as yyymonthddd, month based on current locale , eg 2021juin14

**Value**

character vector with formatted date

**See Also**

[date](#), [Sys.Date](#) and [Sys.time](#),

**Examples**

```
sysDate()
```

---

tableToPlot

*Print matrix-content as plot*


---

### Description

tableToPlot prints all columns of matrix in plotting region for easier inclusion to reports (default values are set to work for output as A4-sized pdf). This function was made for integrating listings of text to graphical output to devices like png, jpeg or pdf. This function was initially designed for listings with small/medium 1st col (eg couner or index), 2nd & 3rd col small and long 3rd col (like file paths). Obviously, the final number of lines one can pack and still read correctly into the graphical output depends on the size of the device (on a pdf of size A4 one can pack up to apr. 110 lines). Of course, [Sweave](#), combined with LaTeX, provides a powerful alternative for wrapping text to pdf-output (and further combining text and graphics). Note: The final result on pdf devices may vary depending on screen-size (ie with of current device), the parameters 'colPos' and 'titOffS' may need some refinements. Note: In view of typical page/figure layouts like A4, the plotting region will be split to avoid too wide spacing between rows with less than 30 rows.

### Usage

```
tableToPlot(
  matr,
  colPos = c(0.05, 0.35, 0.41, 0.56),
  useCex = 0.7,
  useAdj = c(0, 1, 1, 0),
  titOffS = 0,
  useCol = 1,
  silent = FALSE,
  callFrom = NULL
)
```

### Arguments

|          |  |
|----------|--|
| matr     | (matrix) main (character) matrix to display  |
| colPos   | (numeric) position of columns on x-scale (from 0 to 1)                             |
| useCex   | (numeric) cex expansion factor for size of text (may be different for each column) |
| useAdj   | (numeric) left/center/right alignment for text (may be different for each column)  |
| titOffS  | (numeric) offset for title line (relative to 'colPos')                             |
| useCol   | color specification for text (may be different for each column)                    |
| silent   | (logical) suppress messages  |
| callFrom | (character) allow easier tracking of message(s) produced                           |

### Value

NULL (no R-object returned), print 'plot' in current device only

**See Also**

[Sweave](#) for more flexible framework

**Examples**

```
## as example let's make a listing of file-names and associated parameters in current directory
mat <- dir()
mat <- cbind(no=1:length(mat), fileName=mat, mode=file.mode(mat),
            si=round(file.size(mat)/1024), path=getwd())
## Now, we wrap all text into a figure (which could be saved as jpg, pdf etc)
tableToPlot(mat[, -1], colPos=c(0.01, 0.4, 0.46, 0.6), titOffs=c(0.05, -0.03, -0.01, 0.06))
tableToPlot(mat, colPos=c(0, 0.16, 0.36, 0.42, 0.75), useAdj=0.5, titOffs=c(-0.01, 0, -0.01, 0, -0.1))
```

---

test2factLimma

2-factorial limma-style t-test

---

**Description**

The aim of this function is to provide convenient access to two-factorial (linear) testing withing the framework of [makeMAList](#) including the empirical Bayes shrinkage. The input data 'datMatr' which should already be organized as limma-type MAList, eg using using [makeMAList](#). Note: This function uses the Bioconductor package [limma](#).

**Usage**

```
test2factLimma(
  datMatr,
  fac1,
  fac2,
  testSynerg = TRUE,
  testOrientation = "=",
  addResults = c("lfd", "FDR", "Mval", "means"),
  addGenes = NULL,
  silent = FALSE,
  callFrom = NULL,
  debug = FALSE
)
```

**Arguments**

|            |   |
|------------|---|
| datMatr    | matrix or data.frame with lines as independent series of measures (eg different genes)  |
| fac1       | (character or factor) vector describing grouping elements of each line of 'datMatr' for first factor, must be of same length as fac2  |
| fac2       | (character or factor) vector describing grouping elements of each line of 'datMatr' for second factor, must be of same length as fac1 |
| testSynerg | (logical) decide if factor-interactions (eg synergy) should be included to model  |

|                 |  |
|-----------------|--|
| testOrientation | (character) default (or any non-recognized input) '=', otherwise either '>', 'greater', 'sup', 'upper' or '<', 'inf', 'lower'  |
| addResults      | (character) vector defining which types of information should be included to output, may be 'lfdr', 'FDR' (for BY correction), 'Mval' (M values), 'means' (matrix with mean values for each group of replicates) |
| addGenes        | (matrix or data.frame) additional information to add to output   |
| silent          | (logical) suppress messages  |
| callFrom        | (character) allow easier tracking of messages produced   |
| debug           | (logical) additional messages for debugging  |

### Value

This function returns an object of class "MArrayLM" (from limma) containing/enriched by the testing results

### See Also

[makeMAList](#), single line testing [lmFit](#) and the eBayes-family of functions in package [limma](#)

### Examples

```
set.seed(2014)
dat0 <- rnorm(30) + rep(c(10,15,19,20),c(9,8,7,6))
fa <- factor(rep(letters[1:4],c(9,8,7,6)))
dat2 <- data.frame(facA=rep(c("-", "A", "-", "A"), c(9,8,7,6)),
  facB= rep(c("-", "-", "B", "B"), c(9,8,7,6)), dat1=dat0, dat2=runif(30))
grpNa <- sub("-", "", sub("\\.", "", apply(dat2[,1:2], 1, paste, collapse="")))
test2f <- test2factLimma(t(dat2[,3:4]), dat2$facA, dat2$facB, testS=FALSE)
test2f
# Now you can easily summarize results using topTable from limma
if(requireNamespace("limma", quietly=TRUE)) {
  library(limma)
  topTable(test2f, coef=1, n=5)
  topTable(test2f, coef=2, n=5) }
```

---

transpGraySca

*Make single vector gray-gradient*

---

### Description

This function helps making gray-gradients. Note : The resulting color gradient does not seem linear to the human eye, you may try [gray.colors](#) instead

### Usage

```
transpGraySca(startGray = 0.2, endGrey = 0.8, nSteps = 5, transp = 0.3)
```

**Arguments**

startGray      (numeric) gray shade at start  
endGrey        (numeric) gray shade at end  
nSteps         (integer) number of levels  
transp         (numeric) transparency alpha

**Value**

character vector (of same length as x) with color encoding

**See Also**

[gray.colors](#)

**Examples**

```
layout(1:2)
col1 <- transpGraySca(0.8,0.3,7,0.9)
pie(rep(1,length(col1)), col=col1, main="from transpGraySca")
col2 <- gray.colors(7,0.9,0.3,alph=0.9)
pie(rep(1,length(col2)), col=col2, main="from gray.colors")
```

---

treatTxtDuplicates      *Locate duplicates in text and make non-redundant*

---

**Description**

treatTxtDuplicates locates duplicates in character-vector 'x' and return list (length=3) : with \$init (initial), \$nRed .. non-redundant text by adding number at end or beginning, and \$nrLst .. list-version with indexes per unique entry. Note : NAs (if multiple) will be renamed to NA\_1, NA\_2

**Usage**

```
treatTxtDuplicates(  
  x,  
  atEnd = TRUE,  
  sep = "_",  
  onlyCorrectToUnique = FALSE,  
  silent = FALSE,  
  callFrom = NULL  
)
```

**Arguments**

|                     |   |
|---------------------|---|
| x                   | (character) vector with character-entries to identify (and remove) duplicates   |
| atEnd               | (logical) decide location of placing the counter (at end or at beginning of ID)<br>(see <a href="#">correctToUnique</a> ) |
| sep                 | (character) separator to add before counter when making non-redundant version   |
| onlyCorrectToUnique | (logical) if TRUE, return only vector of non-redundant  |
| silent              | (logical) suppress messages   |
| callFrom            | (character) allow easier tracking of message(s) produced  |

**Value**

list with \$init, \$nRed, \$nrLst

**See Also**

For simple correction use [correctToUnique](#)

**Examples**

```
treatTxtDuplicates(c("li0",NA,rep(c("li2","li3"),2)))
correctToUnique(c("li0",NA,rep(c("li2","li3"),2)))
```

---

|          |                                  |
|----------|----------------------------------|
| triCoord | <i>Pairwise x,y combinations</i> |
|----------|----------------------------------|

---

**Description**

triCoord gets pairwise combinations for 'n' elements; returns matrix with x & y coordinates to form all pairwise groups for 1:n elements

**Usage**

```
triCoord(n, side = "upper")
```

**Arguments**

|      |  |
|------|--|
| n    | (integer) number of elements for making all pair-wise combinations |
| side | (character) "upper" or "lower"                                     |

**Value**

2-column matrix with indexes for all pairwise combinations of 1:n

**See Also**

[lower.tri](#) or [upper.tri](#), simpler version [upperMaCoord](#)

## Examples

```
triCoord(4)
```

---

|                |                            |
|----------------|----------------------------|
| trimRedundText | <i>Trim redundant text</i> |
|----------------|----------------------------|

---

## Description

This function allows trimming/removing redundant text-fragments (redundant from head or tail) out of character vector 'txt'.

## Usage

```
trimRedundText(  
  txt,  
  minNchar = 1,  
  side = "both",  
  spaceElim = FALSE,  
  silent = TRUE,  
  callFrom = NULL,  
  debug = FALSE  
)
```

## Arguments

|           |  |
|-----------|--|
| txt       | character vector to be treated                                   |
| minNchar  | (integer) minimum number of characters that must remain          |
| side      | (character) may be either 'both', 'left' or 'right'              |
| spaceElim | (logical) optional removal of any heading or tailing white space |
| silent    | (logical) suppress messages                                      |
| callFrom  | (character) allow easier tracking of messages produced           |
| debug     | (logical) display additional messages for debugging              |

## Value

This function returns a modified character vector

## See Also

Inverse : Find/keep common text [keepCommonText](#); you may also look for related functions in package [stringr](#)

**Examples**

```
txt1 <- c("abcd_ccc", "bcd_ccc", "cde_ccc")
trimRedundText(txt1, side="right")      # trim from right

txt2 <- c("ddd_ab", "ddd_bcd", "ddd_cde")
trimRedundText(txt2, side="left")      # trim from left
```

---

|                          |   |
|--------------------------|---|
| <code>tTestAllVal</code> | <i>t.test on all individual values against all other values</i> |
|--------------------------|---|

---

**Description**

Run `t.test` on each indiv value of `x` against all its neighbours (=remaining values of same vector) in order to test if tis value is likely to belong to vector `x`. This represents a repeated leave-one-out testing. Mutiple choices for multiple testing correction are available.

**Usage**

```
tTestAllVal(x, alph = 0.05, alternative = "two.sided", p.adj = NULL)
```

**Arguments**

|                          |   |
|--------------------------|---|
| <code>x</code>           | matrix or data.frame  |
| <code>alph</code>        | (numeric) threshold alpha (passed to <code>t.test</code> )  |
| <code>alternative</code> | (character) will be passed to <code>t.test</code> as argument 'alternative', may be "two.sided", ..   |
| <code>p.adj</code>       | (character) multiple test correction : may be NULL (no correction), "BH", "BY", "holm", "hochberg" or "bonferroni" (but not 'fdr' since this may be confounded with local false discovery rate), see <a href="#">p.adjust</a> |

**Value**

numeric vector with p-values or FDR (depending on argument `p.adj`)

**See Also**

[t.test](#), [p.adjust](#)

**Examples**

```
set.seed(2016); x1 <- rnorm(100)
allTests1 <- tTestAllVal(x1)
hist(allTests1, breaks="FD")
```

---

|                 |   |
|-----------------|---|
| unIQCountReport | <i>Report number of unique and redundant elements (optional figure)</i> |
|-----------------|---|

---

### Description

Make report about number of unique and redundant elements of vector 'dat'. Note : fairly slow for long vectors !!

### Usage

```
unIQCountReport(
  dat,
  frL = NULL,
  plotDispl = FALSE,
  tit = NULL,
  col = NULL,
  radius = 0.9,
  sizeTo = NULL,
  clockwise = FALSE,
  silent = FALSE,
  callFrom = NULL
)
```

### Arguments

|           |   |
|-----------|---|
| dat       | (character or numeric vector) main input where number of unique (and redundant) should be determined          |
| frL       | (logical) optional (re-)introducing results from duplicated to shorten time of execution                      |
| plotDispl | (logical) decide if pie-type plot should be produced  |
| tit       | (character) optional title in plot  |
| col       | (character) custom colors in pie  |
| radius    | (numeric) radius passed to pie  |
| sizeTo    | (numeric or character) optional reference group for size-population relative adjusting overall surface of pie |
| clockwise | (logical) argument passed to pie  |
| silent    | (logical) suppress messages   |
| callFrom  | (character) allow easier tracking of message(s) produced  |

### Value

vector with counts of n (total), nUnique (wo any repeated), nHasRepeated (first of repeated), nRedundant), optional figure

**See Also**

[correctToUnique](#), [unique](#)

**Examples**

```
layout(1:2)
uniqCountReport(rep(1:7,1:7),plot=TRUE)
uniqCountReport(rep(1:3,1:3),plot=TRUE,sizeTo=rep(1:7,1:7))
```

---

|              |  |
|--------------|--|
| upperMaCoord | <i>(upper) pairwise x,y combinations</i> |
|--------------|--|

---

**Description**

upperMaCoord gets pairwise combinations for 'n' elements; return matrix with x & y coordinates to form all pairwise groups for n elements. But no distinction of 'upper' or 'lower' possible like in [triCoord](#)

**Usage**

```
upperMaCoord(n)
```

**Arguments**

n (integer) number of elements for making all pair-wise combinations

**Value**

2-column matrix with indexes for all pairwise combinations of 1:n

**See Also**

[lower.tri](#), more evolved version [triCoord](#)

**Examples**

```
upperMaCoord(4)
```

---

|                |   |
|----------------|---|
| withinRefRange | <i>Check for values within range of reference</i> |
|----------------|---|

---

### Description

withinRefRange checks which values of numeric vector 'x' are within range +/- 'fa' x 'ref' (ie within range of reference).

### Usage

```
withinRefRange(x, fa, ref = NULL, absRef = TRUE, asInd = FALSE)
```

### Arguments

|        |  |
|--------|--|
| x      | matrix or data.frame   |
| fa     | (numeric) absolute or relative tolerance value (numeric, length=1), interpreted according to 'absRef' as absolute or relative to 'x' (ie fa*ref) |
| ref    | (numeric) (center) reference value for comparison (numeric, length=1), if not given mean of 'x' (excluding NA or non-finite values) will be used |
| absRef | (logical) return result as absolute or relative to 'x' (ie fa*ref)   |
| asInd  | (logical) if TRUE return index of which values of 'x' are within range, otherwise return values if 'x' within range                              |

### Value

numeric vector (containing only the values within range of reference)

### Examples

```
## within 2.5 +/- 0.7
withinRefRange(-5:6, fa=0.7, ref=2.5)
## within 2.5 +/- (0.7*2.5)
withinRefRange(-5:6, fa=0.7, ref=2.5, absRef=FALSE)
```

---

|          |                                      |
|----------|--------------------------------------|
| writeCsv | <i>Write (and convert) csv files</i> |
|----------|--------------------------------------|

---

### Description

This functions is absed on write.csv allows for more options when writing data into csv-files. The main input may be given as R-object or read from file 'input'. Then, one can (re-)write using specified conversions. An optional filter to select columns (column-name specified via 'filterCol') is available. The output may be simultaneously written to multiple formats, as specified in 'expTy', tabulation characters may be converted to avoid accidentally split/shift text to multiple columns. Note: Mixing '.' and ',' as comma separators via text-columns or fused text&data may cause problems lateron, though.

**Usage**

```
writeCsv(
  input,
  inPutFi = NULL,
  expTy = c("Eur", "US"),
  imporTy = "Eur",
  filename = NULL,
  quote = FALSE,
  filterCol = NULL,
  replMatr = NULL,
  returnOut = FALSE,
  SYLKprevent = TRUE,
  digits = 22,
  silent = FALSE,
  debug = FALSE,
  callFrom = NULL
)
```

**Arguments**

|                          |   |
|--------------------------|---|
| <code>input</code>       | either matrix or data.frame   |
| <code>inPutFi</code>     | (character or NULL) file-name to be read (format as US or Euro-type may specified via argument <code>imporTy</code> )   |
| <code>expTy</code>       | (character) 'US' and/or 'Eur' for sparator and decimal type in output   |
| <code>imporTy</code>     | (character) default 'Eur' (otherwise set to 'US')   |
| <code>filename</code>    | (character) optional new file name(s)   |
| <code>quote</code>       | (logical) will be passed to function <code>write.csv</code>   |
| <code>filterCol</code>   | (integer or character) optionally, to export only the columns specified here  |
| <code>replMatr</code>    | optional, matrix (1st line:search, 2nd li:use for replacing) indicating which characters need to be replaced )  |
| <code>returnOut</code>   | (logical) return output as object   |
| <code>SYLKprevent</code> | (logical) prevent difficulty when opening file via Excel. In some cases Excel presumes (by error) the SYLK format and produces an error when trying to open files : To prevent this, if necessary, the 1st column-name will be changed from 'ID' to 'Id'. |
| <code>digits</code>      | (interger) limit number of signif digits in output (ie file)  |
| <code>silent</code>      | (logical) suppress messages   |
| <code>debug</code>       | (logical) for bug-tracking: more/enhanced messages  |
| <code>callFrom</code>    | (character) allow easier tracking of messages produced  |

**Value**

This function writes a file to disk and returns NULL unless `returnOut=TRUE`

**See Also**

write.csv in [write.table](#), batch reading using this package [readCsvBatch](#)

**Examples**

```
dat1 <- data.frame(ini=letters[1:5],x1=1:5,x2=11:15,t1=c("10,10","20.20","11,11","21,21","33.33"),
  t2=c("10,11","20.21","k1;k1","az,az","ze.ze"))
fiNa <- file.path(tempdir(), paste("test",1:2,".csv",sep=""))
writeCsv(dat1, filename=fiNa[1])
dir(path=tempdir(), pattern="cs")

(writeCsv(dat1, replM=rbind(bad=c(";",",",""), replBy="__"), expTy=c("Eur"),
  returnOut=TRUE, filename=fiNa[2]))
```

---

XYToDiffPpm

*Express difference as ppm*


---

**Description**

XYToDiffPpm transforms offset (pariwise-difference) between 'x' & 'y' to ppm (as normalized difference ppm, parts per million, ie  $(x-y)/y$ ). This type of expressing differences is used eg in mass-spectrometry.

**Usage**

```
XYToDiffPpm(x, y, nSign = NULL, silent = FALSE, callFrom = NULL)
```

**Arguments**

|          |   |
|----------|---|
| x        | (numeric) typically for measured variable   |
| y        | (numeric) typically for theoretical/expected value (vector must be of same length as 'x') |
| nSign    | (integer) number of significant digits in output  |
| silent   | (logical) suppress messages   |
| callFrom | (character) allow easier tracking of message(s) produced                                  |

**Value**

numeric vector of (ratio-) ppm values

**See Also**

[ratioToPpm](#) for classical ppm

**Examples**

```
set.seed(2017); aa <- runif(10,50,900)
cbind(x=aa,y=aa+1e-3,ppm=XYToDiffPpm(aa,aa+1e-3,nSign=4))
```

# Index

## \* character

- pasteC, 114
- addBeforFileExtension, 5
- adjBy2ptReg, 6, 107, 129, 130
- anova, 151
- aov, 151
- append, 7
- appendNR, 7
- arrayCV, 8, 136, 140
- asSepList, 8, 113
- boot, 21, 143, 156
- buildTree, 10, 33, 42, 150
- cbind, 11, 59, 81, 83
- cbindNR, 11
- checkAvSd, 12
- checkGrpOrder, 13
- checkGrpOrderSEM, 13, 14
- checkSimValueInSer, 15, 20, 46, 62, 64, 86
- checkStrictOrder, 16
- checkVectLength, 16
- cleanReplicates, 17
- closeMatchMatrix, 18, 64
- coinPermTest, 20
- colMedSds, 21
- colorAccording2, 22
- colSds, 23, 145
- colSums, 77, 139, 141, 143, 145, 157
- combinatIntTable, 24
- combineAsN, 25
- combineByEitherFactor, 26
- combineOverlapInfo, 27
- combineRedBasedOnCol, 29, 105, 106
- combineReplFromListToMatr, 30
- combineSingleT, 31
- combn, 24, 132
- completeArrLst, 31
- confInt, 32
- confint, 33
- contribToContigPerFrag, 10, 33, 42, 150
- conv01toColNa, 34
- convColorToTransp, 34
- convMatr2df, 35
- convToNum, 36, 88
- coordOfFilt, 38
- correctToUnique, 39, 57, 61, 72, 105, 106, 164, 168
- correctWinPath, 40
- countCloseToLimits, 41, 62
- countSameStartEnd, 10, 42, 150
- cut, 22, 44
- cutArrayInCluLike, 43
- cutAtMultSites, 43, 101, 102
- cutToNgrp, 44
- date, 159
- diff, 45, 46
- diffCombin, 45
- diffPPM, 45
- dist, 94, 113
- duplicated, 57, 61, 66, 67, 104, 134, 148
- elimCloseCoord, 46
- equLenNumber, 47
- exclExtrValues, 48
- exponNormalize, 49, 107
- extr1chan, 30, 32, 51
- extractLast2numericParts, 52
- extrColsDeX, 52, 57
- extrNumericFromMatr, 53
- extrSpcText, 54
- fdrtool, 117
- file.path, 40
- filt3dimArr, 55
- filterLiColDeList, 56
- filterList, 53, 57
- filterNetw, 58, 112

- filtSizeUniq, 39, 60
- findCloseMatch, 18–20, 41, 47, 61, 63, 64
- findRepeated, 29, 62, 72, 106
- findSimilFrom2sets, 63
- findUsableGroupRange, 65
- firstLineOfDat, 65, 106
- firstOfRepeated, 46, 47, 66, 66, 67, 71, 104, 106
- firstOfRepLines, 11, 29, 49, 67, 67, 106
- fisher.test, 119
- fread, 123, 124
- fuseAnnotMatr, 68
- fuseCommonListElem, 69
- fusePairs, 70
  
- get1stOfRepeatedByCol, 49, 62, 63, 71, 104, 106
- getValuesByUnique, 72
- gitDataUrl, 73
- gray.colors, 162, 163
- grep, 52, 76, 80, 87, 98
  
- htmlSpecCharConv, 74
  
- justvsn, 106, 107
  
- keepCommonText, 74, 165
- kmeans, 132
  
- levIndex, 76
- linModelSelect, 77
- linRegrParamAndPVal, 79
- listBatchReplace, 80
- listGroupsByNames, 81
- lm, 80, 82, 119
- lmFit, 56, 96, 97, 151, 162
- lmSelClu, 81
- LocationTests, 21
- lower.tri, 164, 168
- lrbind, 7, 83
  
- makeMAList, 84, 161, 162
- makeNRedMatr, 85
- MPlotW, 146
- match, 86, 100
- matchNamesWithReverseParts, 86
- matchSampToPairw, 87
- matr2list, 88
- merge, 68, 89–93
- mergeSelCol, 89, 91
- mergeSelCol3, 89, 90
- mergeVectors, 91
- mergeW2, 92
- minDiff, 94
- moderTest2grp, 56, 77, 78, 95, 97
- moderTestXgrp, 77–79, 87, 96, 146
- multiCharReplace, 97
- multiMatch, 99
  
- NA, 158
- na.fail, 101, 136
- naOmit, 100, 136
- nchar, 103
- nFragments, 44, 101
- nFragments0, 44, 102
- nNonNumChar, 102
- Node, 10
- nonAmbiguousMat, 103
- nonAmbiguousNum, 11, 67, 71, 104
- nonredDataFrame, 105
- nonRedundLines, 106
- Normal, 138
- normalizeThis, 6, 50, 106
- normalizeWithinArrays, 84
- numeric, 36, 38
- numPairDeColNames, 108
  
- order, 16, 79
- organizeAsListOfRepl, 29, 30, 32, 51, 109
  
- p.adjust, 96, 117, 166
- packageDownloadStat, 110
- pairsAsPropensMatr, 111
- par, 35, 150
- partialDist, 112
- partUnlist, 8, 9, 113
- paste, 114
- pasteC, 114
- pie, 128
- presenceFilt, 115, 158
- protectSpecChar, 116
- pVal2lfd, 117
  
- randIndex, 118
- randIndFx, 118
- rankToContigTab, 119
- ratioAllComb, 120
- ratioToPpm, 121, 171
- read.delim, 124

read.table, [53](#), [123](#), [125](#), [126](#)  
 read\_excel, [127](#)  
 readCsvBatch, [122](#), [124](#), [171](#)  
 readTabulatedBatch, [123](#)  
 readVarColumns, [125](#)  
 readXlsxBatch, [123](#), [126](#)  
 reduceTable, [128](#)  
 regrBy1or2point, [129](#), [130](#)  
 regrMultBy1or2point, [129](#), [130](#)  
 renameColumns, [131](#)  
 reorgByCluNo, [131](#)  
 replicateStructure, [26](#), [133](#), [153](#)  
 replNAbyLow, [134](#)  
 replPlateCV, [8](#), [136](#), [140](#)  
 rgb, [35](#)  
 rmDupl2colMatr, [137](#)  
 rnormW, [137](#)  
 rowCVs, [8](#), [136](#), [139](#), [140](#), [142](#)  
 rowGrpCV, [8](#), [139](#), [139](#)  
 rowGrpMeans, [13](#), [140](#), [141–143](#)  
 rowGrpNA, [141](#)  
 rowGrpSds, [142](#), [143](#)  
 rowGrpSums, [142](#)  
 rowMedSds, [143](#)  
 rowSds, [77](#), [139](#), [141](#), [143](#), [144](#), [145](#)  
 rowSEMs, [142](#), [144](#)  
  
 sampNoDeMArrayLM, [145](#)  
 scale, [147](#), [155](#), [156](#)  
 scaleXY, [146](#)  
 sd, [23](#), [142](#), [144](#)  
 searchDataPairs, [147](#)  
 searchLinesAtGivenSlope, [148](#)  
 simpleFragFig, [10](#), [42](#), [150](#)  
 singleLineAnova, [151](#)  
 sortBy2CategorAnd1IntCol, [151](#)  
 sortByNRepeated, [152](#)  
 sprintf, [48](#)  
 stableMode, [154](#)  
 standardW, [155](#)  
 stdErrMedBoot, [156](#)  
 strsplit, [44](#), [87](#), [100](#), [109](#)  
 sub, [73](#)  
 substr, [55](#)  
 summarizeCols, [86](#), [157](#)  
 sumNAperGroup, [158](#)  
 Sweave, [160](#), [161](#)  
 Sys.time, [159](#)  
 sysDate, [159](#)  
  
 t, [148](#)  
 t.test, [166](#)  
 table, [26](#), [128](#), [153](#)  
 tableToPlot, [160](#)  
 TDist, [33](#)  
 tempfile, [40](#)  
 test2factLimma, [84](#), [151](#), [161](#)  
 transpGraySca, [162](#)  
 treatTxtDuplicates, [39](#), [72](#), [163](#)  
 triCoord, [164](#), [168](#)  
 trimRedundText, [76](#), [134](#), [165](#)  
 tTestAllVal, [166](#)  
  
 uniqCountReport, [167](#)  
 unique, [39](#), [57](#), [61](#), [66](#), [67](#), [72](#), [105](#), [168](#)  
 unlist, [9](#), [69](#), [113](#), [137](#)  
 upperMaCoord, [164](#), [168](#)  
  
 VolcanoPlotW, [146](#)  
  
 which, [38](#)  
 withinRefRange, [15](#), [169](#)  
 write.table, [171](#)  
 writeCsv, [123](#), [169](#)  
  
 XYToDiffPpm, [121](#), [171](#)